Nashville Chemical
Redefining Water Treatment Services

PRODUCT DATA SHEET

CWT 8334 - COMPLETE COOLING WATER TREATMENT

GENERAL DESCRIPTION:

CWT 8334 is a cooling water treatment used as a scale retardant, antifoulant, and corrosion inhibitor. CWT 8334 contains an efficient dispersant of common inorganic particulates found in cooling water systems. CWT 8334 is authorized by the United States Department of Agriculture for use in federally inspected facilities.

PRODUCT CHARACTERISTICS:

Form ..... Light Golden Liquid
pH ..... Approximately 12.0
Density ..... 8.73 lbs./gallon

FEEDING:

CWT 8334 may be pumped directly from the drum into a recirculating cooling water line or fed directly to the tower basin. A proportional feed and bleed system controlled by a conductivity controller is recommended.

PRECAUTIONS AND HANDLING:

Product is an alkaline material. Avoid contact with skin and eyes. Do not take internally. Protective gloves and chemical splash goggles are recommended. Wear impervious apron and boots to minimize potential contact. General ventilation is adequate; however, a NIOSH-approved respirator should be used when airborne exposure limits are exceeded. Consult material safety data sheet for more information.

PACKAGING:

55 GALLON DRUMS
30 GALLON DRUMS
5 GALLON PAILS

7001 WESTBELT DRIVE P.O. BOX 90246 NASHVILLE, TENNESSEE 37209 (615) 350 - 7070 FAX (615) 350 - 6331