

RESTROOM / SHOWER ROOM / SWIMMING POOL FLOOR CARE

A. FOR POROUS CONCRETE, UNGLAZED CERAMIC AND QUARRY TILE SURFACES

RESTORATION "SHOCK TREATMENT" – to restore slip resistance to floor surface.

1. After resting, apply SAF-T-STEP® full strength to floor surface; work in a small area at a time.
2. Allow SAF-T-STEP® to work for 5 minutes.
3. Scrub thoroughly with deck brush or use a floor scrubber equipped with a brush.
4. Rinse with clean water.
5. Squeegee to the floor drains.

NOTE: If floor was sealed with a sealer, then strip the floor seal from the surface using a floor seal/finish stripper prior to using SAF-T-STEP®.

Do not "shock treat" glazed tile walls.

REGULAR MAINTENANCE

OPTION 1: Once a week, heavy scrub with SAF-T-STEP®.

1. Dilute 12 ounces SAF-T-STEP® per gallon of water. Set your dispenser at a 10-to-1 (water to SAF-T-STEP®) dilution rate.
2. Apply to walls, floors and fixtures using swab, mop, sprayer or foamer.
3. Thoroughly scrub surfaces with a brush
4. Rinse with clean water.
5. Squeegee water to the drain.

For the remaining days of the week, use the regular germicidal/cleaner.

NOTE: SAF-T-STEP® is self-foaming and may be applied with a foamer set at a 12 ounce per gallon of water (10-to-1 water to SAF-T-STEP®) dilution rate.

OPTION 2: Daily clean with SAF-T-STEP®

1. Dilute 2-4 ounces SAF-T-STEP® per gallon of water, or set your dispenser at a 64 or 32 to 1 (water to SAF-T-STEP®) dilution rate.
2. Apply to walls, floors and fixtures using swab, mop, sprayer or foamer.
3. Swab or brush surfaces; or use a floor scrubber equipped with a brush.
4. Rinse with clean water.
5. Squeegee water to the drains.

NOTE: SAF-T-STEP® is self-foaming and may be applied with a foamer set at a 4 ounce per gallon of water (32-to-1 water to SAF-T-STEP®) dilution rate.

OPTION 3: Daily mop with N.A.C.™ Acid Free Slip Resistant Floor Treatment/Cleaner.

1. Dilute 2-4 ounces N.A.C.™ per gallon of hot water, or set your dispenser at a 6 or 32 to 1 (water to N.A.C.™) dilution rate.
2. Apply to surface with a mop, swab, sprayer (walls, floors, counters).
3. Allow to dry.

B. FOR SEALED FLOORS, PAINTED, OR EPOXY COATED FLOORS

1. Initial floor treatment.

- a. Dilute 10-12 ounces N.A.C.™ per gallon of water, or set your dispenser at a 10 to 1 (water to N.A.C.) dilution rate.
- b. Wet mop floor surface.
- c. Allow to dry.

2. Regular daily maintenance.

- a. Dilute 2-4 ounces N.A.C.™ per gallon of water; or set your dispenser at a 64 or 32 to 1 (water to N.A.C.™) dilution rate.
- b. Wet mop floor surface.
- c. Allow to dry.

NOTE: For large floor surface areas, N.A.C.™ may be applied with automatic floor scrubbing equipment.

NOTE: For grouted floors, scrub the floor surface with a brush at least once a week to keep the grout lines clean. Rinse with clean water and squeegee to the floor drain or pick up residue with mop and N.A.C. diluted at 4 ounces N.A.C. per gallon of water.