FLOOR FINISH

FINI À PLANCHER

Product #126100

www.stateindustrial.com

State® Since 1911

MIGHTY SPARKLE™ DIAMOND Pro 25

Floor Finish

Fini à plancher

- 25% solids for superior, “show-room” gloss
- Excellent for low and high maintenance programs
- Low odor

Care For Work Environments®

NET CONTENTS/CONTENU NET: 1 U.S. Gallon (3.78L)

FOR INDUSTRIAL AND INSTITUTIONAL USE ONLY.
SEULEMENT POUR UN USAGE INDUSTRIEL ET INSTITUTIONNEL.

MADE IN THE USA

DIRECTIONS FOR USE:
For indoor use only. Do not apply if floor temperature is less than 55°F. Strip floor using one of State’s strippers according to label directions. Apply 3-5 thin coats using a clean applicator. Allow 45-60 minutes drying time between coats. If a higher gloss is desired, wait 24 hours before applying additional coats.
Maintenance: 1. Dust mop or sweep floor. 2. Clean floor using one of State’s neutral floor cleaners according to label directions. 3. To enhance gloss and remove scuff marks, spray buff as needed with one of State’s floor restorer or spray buff products, according to label directions. Use conventional equipment and the appropriate pad. 4. To enhance or restore appearance of finish, high-speed burnishing equipment can be used in between scrub and recoats or between full strip outs.
Before Recoating: 1. Dust mop or sweep floor. 2. Deep scrub floor using State Ecolution Pro Cleaner Degreaser according to label directions. 3. Apply 1-2 coats of Diamond Pro 25 using a clean applicator.
Food Plants: Do not use on food contact surfaces. Avoid contamination of food during use and storage.
NOTE: DO NOT FREEZE.

MODE D’EMPLOI :
Uniquement pour les utilisations intérieures. Ne pas appliquer si la température du plancher est inférieure à 13 °C (55 °F). Décaper le plancher à l’aide de n’importe quel décapant de State pour plancher en suivant les directives sur l’étiquette. Appliquer 3 à 5 couches minces à l’aide d’un applicateur propre. Allouer 45 à 60 minutes de temps de séchage entre les couches. Pour un lustre plus élevé, attendre 24 heures avant d’appliquer des couches supplémentaires.
Entretien : 1. Nettoyer au moyen d’une vadrouille ou d’un balai. 2. Nettoyer le plancher à l’aide d’un des nettoyants neutres pour plancher de State en suivant les directives de l’étiquette. 3. Pour optimiser la brillance et éliminer les marques de frottement, polir au jet au besoin avec l’un des produits rénovateurs de plancher ou de polissage de State en suivant les directives sur l’étiquette. Utiliser de l’équipement traditionnel ainsi que les tampons appropriés. 4. Pour rehausser et restaurer l’apparence du fini, de l’équipement de polissage à haute vitesse peut être utilisé entre les récurages et les applications de nouvelles couches ou entre les décapages complets.
Avant d’appliquer une nouvelle couche: 1. Nettoyer au moyen d’une vadrouille ou d’un balai. 2. Nettoyer à fond à l’aide du nettoyant dégraissant Ecolution Pro Cleaner Degreaser de State en suivant les directives de l’étiquette. 3. Appliquer 1 à 2 couches de Diamond Pro 25 Floor Finish à l’aide d’un applicateur propre.
Usines d’aliments: Ne pas l’utiliser sur les surfaces en contact avec les aliments. Éviter la contamination de la nourriture lors de l’utilisation et de l’entreposage du produit.

INGREDIENTS/INGRÉDIENTS: Water (CAS# 7732-18-5), Acrylic Copolymer Emulsion (CAS# Proprietary), Ethoxydiglycol (CAS# 111-90-0), Tributoxyethyl Phosphate (CAS# 78-51-3), Olefin Acrylate Graft Polymer (CAS# Proprietary), Trimethyl Pentanyl Diisobutyrate (CAS# 6846-50-0), Fluorosurfactant (CAS# Proprietary), Silicone Emulsion Blend (CAS# Proprietary), Methylchloroisothiazolinone (CAS# 26172-55-4), Methylisothiazolinone (CAS# 2682-20-4). For more ingredient information, see www.stateindustrial.com

Seller shall not be liable for consequential, special, or indirect damages from use of their product and liability is expressly limited to the refund of purchase price or replacement of product.

WARNING Not a hazardous substance or mixture according to 29 CFR 1910.1200
PRECAUTIONS Use personal protective equipment as required. In case of inadequate ventilation wear respiratory protection. **FIRST AID** IF ON SKIN: Wash with plenty of soap and water. **DISPOSAL** Dispose of container in accordance with all Federal, State and Local Regulations regarding waste disposal.

Keep out of reach of children. Read label before use. SDS available at www.stateindustrial.com or 1-800-782-2436

AVERTISSEMENT
PRÉCAUTIONS Utiliser l’équipement de protection individuelle requis. Lorsque la ventilation du local est insuffisante, porter un équipement de protection respiratoire. **PREMIERS SOINS** EN CAS DE CONTACT AVEC LA PEAU: laver abondamment à l’eau et au savon. **ÉLIMINATION** Éliminer le contenant conformément à tous les règlements fédéraux, d’État et locales en matière d’élimination des déchets.

Garder hors de la portée des enfants. Lire l’étiquette avant utilisation. La fiche signalétique est disponible à www.stateindustrial.com ou en communiquant au 1-800-782-2436.

SDS AND PRODUCT INFORMATION

State Industrial Products
5915 Landerbrook Drive
Mayfield Heights, OH 44124
To Order Call: 1-866-747-2229

6935 Davand Drive
Mississauga, Ontario L5T 1L5
To Order Call: 1-800-668-6513

Royal Industrial Park, Bldg “M”
Local #5, Carr 869, km 1.5 Palmas
Cataño, PR. 00962
To Order Call: 787-275-3185

22R07 126100LBL

© State Ind Prodt Co. 2022