DRAIN MAINTAINER & GREASE REMOVER

PRODUIT D'ENTRETIEN DÉGRAISSAGE DE CANALISATIONS

Product #122619

State® Since 1911

GATOR

Drain Maintainer — PRODUIT D'ENTRETIEN

Grease Remover — DÉGRAISSAGE DE CANALISATIONS

- Maintains Drains, Noncaustic, Cuts Grease, Noncorrosive, High Flashpoint, Nonacid, Fragrance Free, Naturally Derived Soy Solvent

SOY BASED

WARNING

May be harmful if swallowed and enters airways.
Causes mild skin irritation. Causes eye irritation.
Keep out of reach of children.

AVERTISSEMENT

Peut être nocif en cas d'ingestion et de pénétration dans les voies. Provoque une légère irritation de la peau. Provoque une irritation des yeux/Lésions oculaires/ irritation des yeux graves.
Garder hors de la portée des enfants.

NET CONTENTS/CONTENU NET:
20 U.S. Gallons (75L)

Care For Work Environments®

www.statechemical.com

FOR INDUSTRIAL AND INSTITUTIONAL USE ONLY.
SEULEMENT POUR UN USAGE INDUSTRIEL ET INSTITUTIONNEL.

DIRECTIONS FOR USE:
For food plant use, avoid food contamination during use and storage.
Drain Cleaner To open drains stopped up by grease and slime buildup, pour in 8 ounces (½ pint) GATOR. Allow to stand for 1 hour. Flush with hot tap water. GATOR effectively dissolves grease, slime and soap scum deposits in drains, pipes and grease traps. In garbage disposals, allow to stand 5 to 10 minutes. Flush with hot tap water.
Drain & Grease Trap Maintenance Prevent grease and slime buildup in grease traps and drains! Pour in a solution of 8 ounces (½ pint) GATOR per gallon of water. Allow to stand for 1 hour. Flush with hot tap water.
General Cleaning & Degreasing Dilute 4 ounces of GATOR to one gallon of warm water. For effective results, apply generously to greasy equipment, floors, or walls with mop, sponge, or cloth. Allow to set approximately 5 minutes. Rinse with clean water. Not for use on synthetic or resilient tile floors.
As Asphalt Release Agent Apply liberally to asphalt truck beds and other paving equipment to help prevent asphalt build-up. Can be sprayed, foamed, mopped or wiped on surface. Gator can be diluted anywhere from 1:5 to 1:30. NOTE: Use caution around plastics and avoid prolonged contact with solvent-glued joints in PVC pipes. Avoid prolonged contact with paint. Concrete floors may be stained and/or pitted if prolonged contact occurs. Seller shall not be liable for consequential, special, or indirect damages from use of their product and liability is expressly limited to the refund of purchase price or replacement of product.

MODE D'EMPLOI :
Pour l'utilisation dans les usines d'aliments, éviter la contamination lors de l'application et de l'entreposage du produit.
Nettoyant pour drain Pour libérer les drains obstrués par l'accumulation de graisse, verser 8 oz (ou ½ pinte) de GATOR. Laisser reposer pendant 1 heure. Rincer à l'eau chaude du robinet. GATOR dissout efficacement la graisse et les dépôts de résidus de savon dans les drains, les tuyaux et les séparateurs de graisse. Dans les carburateurs à déchets, laisser agir de 5 à 10 minutes. Rincer à l'eau chaude du robinet.
L'entretien des drains et des séparateurs de graisse prévient l'accumulation de graisse dans les séparateurs de graisse et les drains! Verser une solution de 8 oz (ou ½ pinte) de GATOR par gallon d'eau. Laisser reposer pendant 1 heure. Rincer à l'eau chaude du robinet.
Nettoyage et dégraissage courants Diluer 4 oz de GATOR dans un gallon d'eau tiède. Pour un rendement efficace, appliquer généreusement sur l'équipement, les planchers ou les murs graisseux à l'aide d'une vadrouille, d'une éponge ou d'un linge. Laisser agir environ 5 minutes. Rincer avec de l'eau propre. Ne pas utiliser sur des revêtements de sol synthétiques ou de carreaux souples.
Comme Agent Antiadhésif Pour le Bitume Utiliser avec précaution avec les matières plastiques et éviter tout contact prolongé dans les joints de tuyaux en PVC assemblés avec de l'adhésif à base de solvant et les surfaces peintes. Un contact prolongé sur un plancher de béton peut tacher la surface et la piquer. Le vendeur ne peut être tenu responsable des dommages circonstanciels, particuliers ou indirects découlant de l'utilisation du produit. La responsabilité est formellement limitée au remboursement du cout d'achat ou au remplacement du produit.

TOP FIVE INGREDIENTS AND HAZARDOUS SUBSTANCES/CINQ INGRÉDIENTS PRINCIPAUX SUBSTANCES DANGEREUSES: Methyl Soyate (CAS# 67784-80-9), Linear Alcohol Ethoxylate (CAS# 68131-40-8), Proprietary Anionic/Non-ionic Surfactant Blend, BHT(CAS# 128-37-0).

Seller shall not be liable for consequential, special, or indirect damages from use of their product and liability is expressly limited to the refund of purchase price or replacement of product.

State Industrial Products
5915 Landerbrook Drive
Mayfield Heights, OH 44124
To Order Call: 1-866-747-2229

6935 Davand Drive
Mississauga, Ontario L5T 1L5
To Order Call: 1-800-668-6513

Royal Industrial Park, Bldg "M"
Local #5, Carr 869, km 1.5 Palmas
Cataño, P.R. 00962
To Order Call: 787-275-3185

MADE IN THE USA

81R04
122619LBL
©State Ind Prodt Co. 2018

PRECAUTIONS Wash hands thoroughly after handling.
FIRST AID If eye irritation persists: Get medical advice. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF SKIN irritation occurs: Get medical attention. IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
STORAGE Store locked up.
DISPOSAL Dispose of container in accordance with all Federal, State and Local Regulations regarding waste disposal.

Keep out of reach of children. Read label before use. SDS available at www.stateindustrial.com or 1-800-782-2436

PRÉCAUTIONS Se laver soigneusement la peau après manutention.
PREMIERS SOINS Si l'irritation oculaire persiste: consulter un médecin. EN CAS DE CONTACT AVEC LES YEUX: rincer avec précaution à l'eau pendant plusieurs minutes. Enlever les lentilles de contact si la victime en porte et si elles peuvent être facilement enlevées. Continuer à rincer. En cas d'irritation cutanée: consulter un médecin. EN CAS D'INGESTION : Rincer la bouche. NE PAS faire vomir.
STOCKAGE Entreposer dans un endroit verrouillé.
ÉLIMINATION Éliminer le contenant conformément à tous les règlements fédéraux, d'État et locales en matière d'élimination des déchets.

Garder hors de la portée des enfants. Lire l'étiquette avant utilisation. La fiche signalétique est disponible à www.stateindustrial.comou en communiquant au 1-800-782-2436.

⚠ WARNING

This product can expose you to chemicals including ethylene oxide and 1,4-Dioxane which are known to the state of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

NSF
Nonfood Compounds
Program Listed (A8)
Registration #131125

CFIA

USDA CERTIFIED BIOBASED PRODUCT
PRODUCT 94%