DRAIN MAINTAINER

ÉGOUTTER MAINTENEUR

Product #123173

www.stateindustrial.com

State® Since 1911

PrimeZyme

- Liquid enzymes quickly breakdown fats, oils and greases
- Contains bacteria for lasting power
- Mint fragrance, non-flammable, no VOC's

Care For Work Environments®

NET CONTENTS/CONTENU NET: 1 U.S. Gallon (3.78L)

FOR INDUSTRIAL AND INSTITUTIONAL USE ONLY.
SEULEMENT POUR UN USAGE INDUSTRIEL ET INSTITUTIONNEL.

DIRECTIONS FOR USE:
Dilution rates will vary based upon method and area to be treated.
For Food Plant Use: Not for use on food contact surfaces. Avoid contamination during application and storage.
Lift Stations: PrimeZyme should be metered in directly into a lift station at the end of a pump cycle. This can be done using a DR-2000™ pump. Depending on the amount of FOG's and organic load, the usage rates will vary according to the amount of raw influent in the lift station. Typically, one gallon of product will be sufficient in a lift station that handles up to 20,000 gallons of raw influent. The same amounts will be used if slug feeding, but during low flow periods. The product can also be fed in at the nearest up-stream manhole.
Mains/Manholes For mains/manholes, treatment should be started in the closest upstream manhole from the problem area. One gallon should be metered in for each 10,000 gallons of influent. This can be done using a DR-2000™ pump. For best results, meter product in during high flow rate periods. If slug feeding, slug at a rate of one gallon for each 5,000 gallons of influent to start, and continue with a maintenance dose of one gallon to every 20,000 gallons of influent on a weekly basis.

MODE D'EMPLOI :
Les taux de dilution varieront selon la méthode et la zone à traiter.
Utilisation dans les usines d'aliments : Ne pas utiliser sur les surfaces en contact avec les aliments. Éviter la contamination lors de l'application et de l'entreposage du produit.
Stations de relèvement: PrimeZyme devrait être dosé directement dans la station de relèvement à la fin d'un cycle de pompage. Cette opération peut être effectuée par l'utilisation d'une pompe DR-2000MC. En fonction de la quantité de corps gras, d'huile et de graisse, et de la charge organique, les taux d'usage varieront selon la quantité d'influent non traité dans la station de relèvement. Généralement, un gallon de produit sera suffisant dans une station de relèvement qui traite jusqu'à 20 000 gallons d'influent non traité. Les mêmes quantités seront utilisées si l'alimentation du produit est effectuée en une seule fois, mais seulement dans les périodes de faibles débits. Il est également possible d'introduire le produit par le trou d'homme en amont le plus près.
Conduites principales et trous d'homme Pour les conduites principales et les trous d'homme, le traitement devrait être appliqué au trou d'homme en amont le plus près de la zone problématique. Un gallon de produit devrait être dosé pour chaque volume de 10 000 gallons d'influent. Cette opération peut être effectuée au moyen d'une pompe DR-2000MC. Pour des résultats optimaux, alimenter le produit pendant les périodes de débits élevés. Si l'alimentation du produit est effectuée en une fois, l'alimenter à un taux de un gallon pour chaque volume de 5000 gallons d'influent pour commencer, et continuer avec une dose d'entretien de un gallon pour chaque volume de 20 000 gallons d'influent sur une base hebdomadaire.

TOP FIVE INGREDIENTS AND HAZARDOUS SUBSTANCES/CINQ INGRÉDIENTS PRINCIPAUX SUBSTANCES DANGEREUSES: Water (CAS# 7732-18-5), Stabilized Cultures (CAS# Proprietary), Ethoxylated Alcohols (CAS# 68439-46-3), Fragrance (Proprietary).

Seller shall not be liable for consequential, special, or indirect damages from use of their product and liability is expressly limited to the refund of purchase price or replacement of product.

SDS AND PRODUCT INFORMATION

State Industrial Products
5915 Landerbrook Drive
Mayfield Heights, OH 44124
To Order Call: 1-866-747-2229

6935 Davand Drive
Mississauga, Ontario L5T 1L5
To Order Call: 1-800-668-6513

Royal Industrial Park, Bldg "M"
Local #5, Carr 869, km 1.5 Palmas
Cataño, PR. 00962
To Order Call: 787-275-3185

22R03 123173LBL
© State Ind Prodt Co. 2022

MADE IN THE USA

WARNING Harmful if swallowed. Causes eye irritation. Causes mild skin irritation.
PRECAUTIONS Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product. **FIRST AID** IF SWALLOWED: call a POISON CENTER or physician if you feel unwell. IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF SKIN irritation occurs: Get medical attention. If eye irritation persists: Get medical advice. **STORAGE** Store in dry place. **DISPOSAL** Dispose of container in accordance with all Federal, State and Local Regulations regarding waste disposal.

Keep out of reach of children. Read label before use. SDS available at www.stateindustrial.com or 1-800-782-2436

AVERTISSEMENT Nocif en cas d'ingestion. Provoque une irritation des yeux/Lésions oculaires/irritation des yeux graves. Provoque une légère irritation de la peau.
PRÉCAUTIONS Se laver soigneusement la peau après manutention. Ne pas manger, boire ou fumer en manipulant ce produit. **PREMIERS SOINS** EN CAS D'INGESTION : Appeler un CENTRE ANTIPOISON ou un médecin en cas de malaise. EN CAS D'INGESTION : Rincer la bouche. NE PAS faire vomir. EN CAS DE CONTACT AVEC LES YEUX: rincer avec précaution à l'eau pendant plusieurs minutes. Enlever les lentilles de contact si la victime en porte et si elles peuvent être facilement enlevées. Continuer à rincer. En cas d'irritation cutanée: consulter un médecin. Si l'irritation oculaire persiste: consulter un médecin. **STOCKAGE** Stocker dans un endroit sec. **ÉLIMINATION** Éliminer le contenant conformément à tous les règlements fédéraux, d'État et locales en matière d'élimination des déchets.

Garder hors de la portée des enfants. Lire l'étiquette avant utilisation. La fiche signalétique est disponible à www.stateindustrial.comou en communiquant au 1-800-782-2436.

FORD TOXICITY NUMBER 195491

NSF Nonfood Compounds Program Listed (L2) Registration #140763