



SUPER PURGE

Floor Finish Solubilizer

DESCRIPTION

A unique floor finish re-emulsifier and extra heavy-duty stripper, designed for use in heavy build up areas that have been high speed burnished. Comprised of synergistic solubilizers in combination with emulsifiers, chelating and anti-redeposition agents, and a new type of penetrant in a pH controlled base, allows a speed and efficiency never before attainable.

PRODUCT FEATURES / BENEFITS

- Formulated with extra solubilizers / Liquified finish stays in stripped solution longer without evaporating too quickly.
- Fast multiple coat penetration / Minimizes stripping time to reduce labor costs
- Removes all build-ups due to repeated burnishing / Allows for reduced product inventory making it a one product process
- pH and odor controlled / Reduces hazardous vapors and reduces potential tile damage
- Allows stripping without the necessity of a scrubbing machine / Reduces equipment costs and allows the product to be used in small areas where machine scrubbing is impractical.

DIRECTIONS FOR USE

Wet-Vac/Mop stripping: Dilute with hot, cold, hard or soft water for use. The amount of the solubilizer for each stripping job will depend upon the amount of finish buildup on the floor.

Heavy Duty 1 part solubilizer to 4 parts water.

Light/ Medium Buildup: 1 part solubilizer to 8 parts water.

Apply floor finish solubilizer liberally to the floor, using an area small enough to complete in 20-30 minutes (to avoid drying). Allow the solubilizer to stand for 5 minutes, then pick up the liquified finish with a squeegee equipped wet vacuum. When applying solubilizer to a new section of floor, re-wet the previously stripped section. Repeat this procedure until the floor is

completely stripped. Rinse thoroughly with clear water and mop or vacuum dry. Floor Machine Stripping Systems:

Floor Machine Stripping:

Heavy Duty 1 part solubilizer to 6 parts water.

Light/ Medium Buildup: 1 part solubilizer to 16 parts water.

Follow the manual directions above, except agitate well with a floor machine equipped with a stripping pad and remove solubilized finish with a wet vacuum and rinse.

NOTE: As some asphalt tiles may be damaged by prolonged soaking in concentrated strippers, a spot test is recommended before general use.

SPECIFICATIONS

Color Blue
Odor Sassafras
pH 13.4 ± 0.2
Specific Gravity (g/cc) 1.04 ± 0.01
Density (lbs/gal) 8.7 ± 0.1
Viscosity (cps) <10
Flash Point (TOC) None

Solubility Complete
Upper Cloud $> 140^{\circ}\text{F}$
Lower Cloud $< 34^{\circ}\text{F}$
Finish Penetration Milky less than 20 seconds
Wax Removal Excellent
Shelf Life 1 year minimum in original unopened container

SAFETY INFORMATION

DANGER: CAUSES SEVERE SKIN BURNS AND EYE DAMAGE. KEEP OUT OF THE REACH OF CHILDREN.



Precautionary statement

Prevention: Do not breathe mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.

Response: If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a

poison center/doctor. Wash contaminated clothing before reuse.

Storage: Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Disposal: Dispose of contents/container in accordance with local/regional/national/international regulations.

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

Additional safety measures:

Read the entire label and SDS before using this product, and for additional first-aid measures. SDS for this product is available on the web at www.nclonline.com

For Commercial and Industrial Use Only



Stripper



401 N. 10th Street • Philadelphia, PA 19123
1-800-NAT-CHEM • 215-922-1200 • FAX: 215-922-5517
www.nclonline.com • e-mail: info@nclonline.com


SAFETY DATA SHEET

Section 1 - Identification

Product Identifier	SUPER PURGE Floor Finish Solubilizer
Other means of identification	1056
Recommended use	Floor stripper.
Recommended restrictions	For commercial and industrial use only.
Manufacturer / Importer / Supplier / Distributor Information	
Company Name	National Chemical Laboratories of PA, Inc.
Address	401 N. 10th Street - Philadelphia, PA 19123
Telephone	1 (215) 922-1200
Supplier Email	info@nclonline.com
Contact	CHEM-TEL
Emergency Phone	1 (800) 255-3924

Section 2 - Hazard(s) Identification

SDS Hazards and Warnings are based on the undiluted product. Refer to diluted SDS for Ready-To-Use Hazards and Warnings.

	Classification	Category
Physical Hazards	Not Classified	
Health Hazards	Serious eye damage/eye irritation	1
	Skin corrosion/irritation	1
OSHA defined hazards	Not Classified.	
Label Elements		
Hazard Symbol		
Signal Word	Danger	
Hazard Statement	Causes severe skin burns and eye damage.	
Precautionary statement		
Prevention	Do not breathe mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing/eye protection/face protection.	
Response	If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. Wash contaminated clothing before reuse.	
Storage	Store in a well-ventilated place. Keep container tightly closed. Store locked up.	
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.	
Hazard(s) not otherwise classified (HNOC)	None known.	

Section 3 - Composition/Information on ingredients

Mixture			
Hazardous Components	Ingredient Name	CAS #	%
	2-Butoxyethanol	111-76-2	5 - 10
	2-Amino Ethanol	141-43-5	1 - 5
	Sodium dimethylbenzenesulfonate	1300-72-7	1 - 5
	Sodium Hydroxide	1310-73-2	1 - 5

Section 4 - First-aid Measures

Inhalation	If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Call a physician if symptoms develop or persist.
Skin contact	Take off immediately all contaminated clothing. Rinse skin with water/shower. Call a physician or poison control center immediately. Chemical burns must be treated by a physician. Wash contaminated clothing before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician or poison control center immediately.

SAFETY DATA SHEET

Ingestion	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
Most Important symptoms /effects, acute and delayed	Burning pain and severe corrosive skin damage. Headache. Nausea, vomiting. Irritation of nose and throat. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. May cause respiratory irritation.
Indication of immediate medical attention and special treatment	Provide general supportive measures and treat symptomatically. Chemical burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.
General Information	If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

Section 5 - Fire-fighting measures

Suitable extinguishing media	Alcohol resistant foam. Water fog. Dry chemical powder. Carbon dioxide (CO ₂).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire-fighting equipment /instructions	Move containers from fire area if you can do it without risk.
General fire hazards	No unusual fire or explosion hazards noted.
Specific Methods	Use standard firefighting procedures and consider the hazards of other involved materials.

Section 6 - Accidental release measures

Personal precautions, protective equipment and emergency procedures.	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Do not breathe dust or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Large Spills: Stop the flow of material, if this is without risk. Use water spray to reduce vapors or divert vapor cloud drift. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.

Section 7 - Handling and storage

Precautions for safe handling	Do not breathe mist or vapor. Do not get in eyes, on skin, or on clothing. Avoid prolonged exposure. Provide adequate ventilation. When using, do not eat, drink or smoke. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Store locked up. Store in original tightly closed container. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

Section 8 - Exposure control/personal protection

Occupational exposure limits		
US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)		
Components	Type	Value
2-Amino Ethanol (CAS 141-43-5)	TWA	6 mg/m ³ , 3 ppm
2-Butoxyethanol (CAS 111-76-2)	TWA	240 mg/m ³ , 50 ppm
Sodium Hydroxide (CAS 1310-73-2)	TWA	2 mg/m ³
US. ACGIH Threshold Limit Values		
Component	Type	Value
2-Butoxyethanol (CAS 111-76-2)	TWA	20 ppm
2-Amino Ethanol (CAS 141-43-5)	STEL	6 ppm
2-Amino Ethanol (CAS 141-43-5)	TWA	3 ppm
Sodium Hydroxide (CAS 1310-73-2)	Ceiling	2 mg/m ³
US. NIOSH: Pocket Guide to Chemical Hazards		
Components	Type	Value
2-Amino Ethanol (CAS 141-43-5)	STEL	15 mg/m ³ , 6 ppm
2-Amino Ethanol (CAS 141-43-5)	TWA	8 mg/m ³ , 3 ppm
2-Butoxyethanol (CAS 111-76-2)	TWA	24 mg/m ³ , 5 ppm
Sodium Hydroxide (CAS 1310-73-2)	Ceiling	2 mg/m ³
US. ACGIH. BEIs. Biological Exposure Indices		

Sampling

SAFETY DATA SHEET

Components	Value	Determinate	Specimen	Time
2-Butoxyethanol (CAS 111-76-2)	200 mg/g	Butoxyacetic acid (BAA), with hydrolysis	Creatinine in urine	*
* - For sampling details, please see the source document.				
Exposure guidelines	Use personal protective equipment as required. Keep working clothes separately.			
US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants				
Components	Exposure			
2-Butoxyethanol (CAS 111-76-2)	Can be absorbed though the skin.			
US.Minnesota Hazardous Substances List (Minn. Rules 5206.0400).				
Components	Exposure			
2-Butoxyethanol (CAS 111-76-2)	Skin designation applies.			
US.NIOSH: Pocket Guide to Chemical Hazards				
Component	Exposure			
2-Butoxyethanol (CAS 111-76-2)	Can be absorbed though the skin.			
US.OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.100)				
Components	Exposure			
2-Butoxyethanol (CAS 111-76-2)	Can be absorbed though the skin.			
US.OSHA Table Z-1-A (29 CFR 1910.100)				
Components	Exposure			
2-Butoxyethanol (CAS 111-76-2)	Can be absorbed though the skin.			
US.Tennessee. OELs Occupational Exposure Limkits, Table Z1A				
Components	Exposure			
2-Butoxyethanol (CAS 111-76-2)	Can be absorbed though the skin.			
Appropriate engineering controls	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.			
Individual protection measures, such as personal protective equipment				
Eye/face protection	Wear safety glasses with side shields (or goggles) and a face shield.			
Skin protection				
Hand protection	Wear appropriate chemical resistant gloves.			
Other	Wear appropriate chemical resistant clothing.			
Respiratory protection	In case of insufficient ventilation, wear suitable respiratory equipment.			
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.			
General hygiene considerations	Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.			

Section 9 - Physical and chemical properties

Appearance	
Physical state	Liquid.
Form	Clear, thin liquid.
Color	Blue.
Odor	Sassafras.
Odor threshold	Not available.
pH	13.4
Melting point/freezing point	Not available.
Initial boiling point and boiling range	212 °F (100 °C)
Flash point	> 212.0 °F (> 100.0 °C)
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Similar to water.
Vapor density	Similar to water.
Relative density	1.03 ± 0.01

SAFETY DATA SHEET

Relative density temperature	75 °F (23.89 °C)
Solubilities	Not available.
Partition Coefficient n-octanol/water	Not available.
Auto-ignition temperature	Not Available.
Decomposition temperature	Not Available.
Viscosity	< 10 cP
Viscosity Temperature	75 °F (23.89 °C)

Section 10 - Stability and reactivity

Reactivity	Reacts violently with strong acids. This product may react with oxidizing agents.
Chemical stability	Material is stable under normal conditions. Can form peroxides on prolonged exposure to air and light.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to Avoid	Do not mix with other chemicals. Contact with incompatible materials.
Incompatible materials	Strong acids. Acids. Strong oxidizing agents. Oxidizing agents.
Hazardous Decomposition Products	No hazardous decomposition products are known.

Section 11 - Toxicological information

Information on likely routes of exposure

Ingestion	Causes digestive tract burns. Harmful if swallowed.
Inhalation	May cause irritation to the respiratory system. Prolonged inhalation may be harmful.
Skin contact	Causes severe skin burns. 2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged. These effects have not been observed in humans. Prolonged or repeated exposure may cause liver and kidney damage. These effects have not been observed in humans.
Eye contact	Causes serious eye damage.
Symptoms related to the physical, chemical and toxicological characteristics	Burning pain and severe corrosive skin damage. Headache. Nausea, vomiting. Irritation of nose and throat. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. May cause respiratory irritation.

Information on toxicological effects.

Acute toxicity Not expected to be acutely toxic.

Components	Level	Type	Code	Species	Results
2-Butoxyethanol (CAS 111-76-2)	Acute	Dermal	LD50	Rabbit	400 mg/kg
	Acute	Inhalation	LC50	Rat	450 mg/l, 4 hrs
	Acute	Oral	LD50	Rat	560 mg/kg
2-Amino Ethanol (CAS 141-43-5)	Acute	Dermal	LD50	Rabbit	1025 mg/kg
	Acute	Oral	LD50	Rat	1715 mg/kg
Sodium dimethylbenzenesulfonate (CAS 1300-72-7)	Acute	Dermal	LD50	Rabbit	>2000 mg/kg
	Acute	Oral	LD50	Rat	7200 mg/kg
Sodium Hydroxide (CAS 1310-73-2)	Acute	Oral	LD50	Rabbit	500 mg/kg

Skin corrosion/irritation Causes severe skin burns and eye damage.

Serious eye damage/ eye irritation Causes serious eye damage.

Respiratory sensitization This product is not expected to cause respiratory sensitization.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

IARC Monographs. Overall Evaluation of Carcinogenicity

Component	Result	Comment
2-Butoxyethanol (CAS 111-76-2)	3	Not classifiable as to carcinogenicity to humans.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity - single exposure May cause respiratory irritation.

Specific target organ toxicity - repeated exposure Not classified.

Aspiration hazard Not classified.

Chronic effects May be harmful if absorbed through skin. Prolonged inhalation may be harmful.
2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged. These effects have not been observed in humans.
Prolonged or repeated exposure may cause liver and kidney damage. These effects have not been observed in humans.

SAFETY DATA SHEET

Section 12 - Ecological Information

Ecotoxicity		The product contains a substance which is toxic to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.		
Component(s)				
2-Amino Ethanol, 141-43-5				
Aquatic				
Acute	Algae	EC50	Selenastrum capricornutum (new name Pseudokirchnerella subca	2.5 mg/l, 48 hours
	Crustacea	EC50	Daphnia magna	65 mg/l, 48 hours
	Fish	LC50	Goldfish (Carassius auratus)	170 mg/l, 96 hours
	Fish	LC50	Cyprinus carpio	349 mg/l, 96 hours
Persistence and degradability		No data is available on the degradability of this product.		
Bioaccumulative potential		No data available.		
Partition coefficient n-octanol / water log (Kow)				
Components		Results		
2-Butoxyethanol (CAS 111-76-2)		0.83		
2-Amino Ethanol (CAS 141-43-5)		-1.31		
Mobility in soil		No data available.		
Mobility in general		No data available.		
Other adverse effects		No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.		

Section 13 - Disposal considerations

Disposal instructions	Dispose in accordance with applicable federal, state, and local regulations.
Local disposal regulations	Dispose of in accordance with local regulations.
Hazardous waste code	Waste codes should be assigned by the user based on the application for which the product was used.
Waste from residues / unused products	Dispose in accordance with all applicable regulations.
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied.

Section 14 - Transport information

DOT

UN number	UN1824
Proper shipping name	SODIUM HYDROXIDE SOLUTION
Transport hazard class(es)	8
Packing group	II
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	B2, IB2, N34, T7, TP2
Packaging exemption	154
Packaging non bulk	202
Packaging bulk	242

IATA

UN number	UN1824
UN proper shipping name	SODIUM HYDROXIDE SOLUTION
Transport hazard class(es)	8
Packaging group	II
Environmental hazards	No.
ERG Code	8L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Other Information	

IMDG

UN number	UN1824
UN proper shipping name	SODIUM HYDROXIDE SOLUTION
Transport hazard class(es)	8
Packaging group	II
Environmental hazards	No.
Marine pollutant	
EmS	F-A, S-B
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

SAFETY DATA SHEET

Transportation in bulk
according to Annex II of
MARPOL 73/78 and IBC Code

This substance/mixture is not intended to be transported in bulk.

Section 15 - Regulatory Information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR707, Subpt. D) Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) Not listed.

CERCLA Hazardous Substance List (40 CFR 302.4)

Components	Result
Sodium Hydroxide (CAS 1310-73-2)	LISTED
2-Butoxyethanol (CAS 111-76-2)	LISTED

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard Categories	Immediate Hazard	Yes
	Delayed Hazard	No
	Fire Hazard	Yes
	Pressure Hazard	No
	Reactivity Hazard	No

SARA 302 Extremely hazardous substance Not listed.

SARA 311/312 Hazardous chemical Yes

SARA 313 (TRI reporting)

Chemical name	CAS #	% by wt.
2-Butoxyethanol	111-76-2	5 - 10

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HSPs) List Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130) Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

Food and Drug Administration (FDA) Not regulated.

US state regulations

US.Massachusetts RTK - Substance List

Components
2-Butoxyethanol (CAS 111-76-2)
2-Amino Ethanol (CAS 141-43-5)
Sodium Hydroxide (CAS 1310-73-2)

US.New Jersey Worker and Community Right-to-Know Act

Components
2-Butoxyethanol (CAS 111-76-2)
2-Amino Ethanol (CAS 141-43-5)
Sodium Hydroxide (CAS 1310-73-2)

US.Pennsylvania RTK - Hazardous Substances

Components
2-Butoxyethanol (CAS 111-76-2)
2-Amino Ethanol (CAS 141-43-5)
Sodium Hydroxide (CAS 1310-73-2)

US.Rhode Island RTK

Components
2-Butoxyethanol (CAS 111-76-2)
2-Amino Ethanol (CAS 141-43-5)
Sodium Hydroxide (CAS 1310-73-2)

US - California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

International Inventories

Country(s) or region	Inventory Name	On Inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances	Yes
Unites States Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

SAFETY DATA SHEET

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

*A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

Section 16 - Other information, including date of preparation or last version

Issue date 2/11/2015

Version # 01

Disclaimer The information contained herein was obtained from current and reliable sources. However, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions for use, handling, storage and disposal of this product are beyond the manufacturer's control, it is the user's responsibility both to determine safe conditions for use of this product and to assume liability for loss, injury, damage or expense arising from the product's improper use. No warranty, expressed or implied, regarding the product described herein shall be created by or inferred from any statement or omission in this SDS. Various government agencies may have specific regulations concerning the transportation, handling, storage, use or disposal of this product which may not be reflected in this SDS. The user should review these regulations to ensure full compliance.

A unique floor finish re-emulsifier/heavy duty stripper, especially designed for removing heavily built-up finish!

Directions:

Mop/Wet Vacuum Stripping System:

Dilute SUPER PURGE™ with cold, hard or soft water for use. The amount of SUPER PURGE™ for each stripping job will depend upon the amount of finish build up on the floor.

Heavy Duty Buildup: 1 part solubilizer to 4 parts water.

Light / Medium Duty Buildup: 1 part solubilizer to 8 parts water.

Apply diluted solution of SUPER PURGE™ liberally to the floor, using an area small enough to complete in 20-30 minutes (to avoid drying). Allow SUPER PURGE™ to stand for 5 minutes, then pick up the liquified finish with a squeegee equipped wet vacuum. Repeat this procedure until the floor is completely stripped. Rinse thoroughly with clear water and mop or vacuum dry.

Floor Machine Stripping System:

Heavy Duty Buildup: 1 part solubilizer to 6 parts water.

Light / Medium Duty Buildup: 1 part solubilizer to 16 parts water.

Follow the manual directions above, except agitate well with a floor machine equipped with a stripping pad and remove solubilized finish with a wet vacuum and rinse.

Note: Asphalt tile, Linoleum, and other sensitive floor surfaces may be damaged by contact with stripping solution. We recommend that a spot test be conducted before general use.

Instrucciones para Uso

Aljofife/Sistema Que pela Mojado De Vacío:

SUPER PURGE™ diluida con frío, difícilmente o agua suave para el uso. La cantidad de SUPER PURGE para cada trabajo que pela dependerá de la cantidad de acumulación del final del piso.

Acumulación Resistente: 1 porción de solubilizer a 4 porciones de agua.

Acumulación Ligera/Media Del Deber: 1 porción de solubilizer a 8 porciones de agua.

Aplique la solución diluida de la SUPER PURGE™ liberalmente al piso, usando un área bastante pequeña para terminar en 20-30 minutos (evitar de secarse). Permita que la SUPER PURGE™ esté parada por 5 minutos, después tome el final licuefecho con un vacío mojado equipado enjugador. Repita este procedimiento hasta que el piso se pela totalmente. Aclare a fondo con agua clara y aljofife o limpie seco con la aspiradora.

Sistema Que pela De la Máquina Del Piso:

Acumulación Resistente: 1 porción de solubilizer a 6 porciones de agua.

Acumulación Ligera/Media Del Deber: 1 porción de solubilizer a 16 porciones de agua.

Siga las direcciones manuales arriba, a menos que agite bien con una máquina del piso equipada de un cojín que pela y quite el final solubilizado con un vacío mojado y aclárelo.

Nota: Las baldosas de asfalto, el linóleo y otras superficies sensibles del piso pueden resultar dañadas por contacto con la solución de decapado. Recomendamos que se realice una prueba puntual antes del uso general.

★★ MADE IN USA ★★

LG-0001-1056-05




FOR COMMERCIAL AND
INDUSTRIAL USE ONLY
QUESTIONS?
Call (800) 628-2436



To learn more
about this
product, scan
this QR code to
visit our website.



World Class Cleaning Solutions®



Strippers

Super Purge™

Floor Finish Solubilizer

DANGER: CAUSES SEVERE SKIN BURNS AND EYE DAMAGE.

See side panel for additional precautionary statements.

PELIGRO: CAUSAS DE LA PIEL Y QUEMADURAS GRAVES DAÑOS A LOS OJOS.

Ver panel lateral para las medidas preventivas adicionales.

NET CONTENTS: 1 GALLON / 3.79 LITERS

National Chemical Laboratories, Inc.
Philadelphia, PA 19123 USA • www.nclonline.com

Product No.: 1056



DANGER: CAUSES SEVERE SKIN BURNS AND EYE DAMAGE. KEEP OUT OF THE REACH OF CHILDREN.

Precautionary statement

Prevention: Do not breathe mist or vapor.

Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing/eye protection/face protection.

Response: If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. Wash contaminated clothing before reuse.

Storage: Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Disposal: Dispose of contents/container in accordance with local/regional/national/international regulations.

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. All components are on the U.S. EPA TSCA Inventory List.

Additional safety measures:

Read the entire label and SDS before using this product, and for additional first aid measures. SDS for this product is available on the web at www.nclonline.com

CONTAINS: 2-Butoxyethanol CAS# 111-76-2, 2-Amino Ethanol CAS# 141-43-5, Sodium dimethylbenzenesulfonate CAS# 1300-72-7, Sodium Hydroxide CAS# 1310-73-2



World Class Cleaning Solutions®

PELIGRO: CAUSA QUEMADURAS GRAVES EN LA PIEL Y DAÑO A LOS OJOS. MANTENER FUERA DEL ALCANCE DE LOS NIÑOS.

Consejos de prudencia

Prevención: No respirar vapores o niebla. Lávese cuidadosamente después de la manipulación. No comer, beber o fumar cuando se utiliza este producto. Usar guantes protectores y ropa de protección/protección para los ojos/la cara.

Respuesta: En caso de ingestión: Enjuagar la boca. No se debe inducir el vómito. Si en la piel (o el pelo): quitarse inmediatamente la ropa contaminada. Enjuagar con abundante agua y ducha. Si se inhala: Llevar a la persona a mantener aire fresco y cómodo para la respiración. Si en los ojos: Enjuague con cuidado con agua durante varios minutos. Quite los lentes de contacto, si los hay, y muy fácil de hacer. Continúe enjuagando. Inmediatamente llame a un centro de envenenamientos/médico. Lavar la ropa contaminada antes de volver a utilizarlo.

Almacenamiento: Almacenar en un lugar bien ventilado. Mantener el recipiente herméticamente cerrado. Store está bloqueado.

Eliminación: Disponer de contenidos/contenedor de conformidad con local/regional/nacional/internacional.

Este producto es una "sustancia química peligrosa" que se define por la OSHA Hazard Communication Standard, 29 CFR 1910.1200. Todos los componentes son de la EPA de EE.UU. Lista de inventario TSCA.

Medidas adicional de primeros auxilios:

Lea toda la etiqueta y SDS antes de usar este producto, así como medidas adicionales de primeros auxilios. SDS para el artículo está disponible en la web en www.nclonline.com

401 N. 10th Street • Philadelphia, PA 19123
1-800-NAT-CHEM • 215-922-1200 • FAX: 215-922-5517
www.nclonline.com • e-mail: info@nclonline.com