



TRELLIS[®] SYSTEM

PRICE LIST

December 17, 2014

Updated June 7, 2023

800.424.2432



Trellis®		
General Information		3
Product Color Options		4
Trellis® Power and Data Chase		
Laminate Inserts		5
Steel Inserts		6
Trellis® Connections and End Caps		
		7
Electrical		
Receptacles, Jumpers and Infeeds		9
Receptacles and Jumpers		11
Activ8® System		
Single Circuit Electrical		12

SPECIFICATIONS

Chase
Trellis ships knockdown with chase, feet components and chase-to-chase connection hardware. Preconfigured chases are 3.63" thick and are available in the follow dimensions:

- Widths: 24", 30", 36", 42", 48", 54", 60", 66" and 72"
- Heights: 24" and 30"

Trellis allows for distribution of power and data at the top of the chase. Trellis is capable of carrying 100 Cat 6 cables or (1) 2.5" diameter bundle of cables.

Trellis Construction
Adjoining chases share common feet, therefore chases are secured at the bottom. A locking clip is provided to align and secure the top of the chases. Chases can also be screwed together at the top if floor conditions require so (screws are included). Chases consist of the following:

- Top horizontal beam - formed of 22-gauge steel, 3.63" x 6", overall length 24" to 72"
- Vertical channels - formed of 20-gauge steel x .75" x 3.63", to allow for fit-up with feet
- Insert panel (Inserts provide lateral stability)

Laminate - formed of 5/8" thick, 45 lb. density particle board with high pressure laminate and a 2mm 73P edge.

Steel - (2) piece formed 22 ga. panels riveted together.

Corner Connector Construction
90° and 120° - formed of powdercoated 22-gauge steel, includes fasteners.

Top Cap
All preconfigured Trellis systems include a top cap of appropriate size. Top caps are formed of powdercoated 22-gauge cold rolled steel. Installation of top cap is a snap fit and requires no tools.

- Top cap dimensions: 0.4" x 3.62" x width of chase

End-of-Run Trim
All exposed ends of a chase are covered with an end-of-run trim formed from powdercoated 20-gauge steel. Installation of end-of-run trim is a slide fit. Chase end trim lengths correspond to Trellis height.

ELECTRICAL (10-Wire)

Power Options
The US standard electrical system supplied for Trellis is a 10-wire electrical system, UL183 listed. Rigid wireway is factory mounted to chase beam.

10 wire power system is 6-2-2 configuration:
6-2-2

- (6) hot wires
- (2) shared, oversized neutral wires
- (2) ground wires - one isolated ground, one building ground

Rigid Wireways
Each powered chase includes the rigid wireways to pass power to receptacles. Wireways are mounted within the horizontal beam. Wireways are specified by chase length. The wireway design allows for snap connection of one chase wireway to another through the use of common chase jumpers. All chases 30" and wider accept electrical receptacles.

There are two receptacle locations on each side of every rigid wireway (see planning guide for spacing locations).

Base Infeeds
The electrical system permits power infeed at either end of the chase. Base infeeds are constructed of an 8' long, 3/4" dia. liquid-tight, flexible medal conduit. The metal conduit contains ten wires with a snap fit design allowing for quick installation and removal. The ten wires must be connected to building electrical by a licensed electrician.

Top Infeeds (Data and/or Power)
Power and data may be brought into Trellis through the use of a top infeed. Top infeed assembly consists of a 10' extruded aluminum data and/or power pole, top cap and ceiling trim. The interior of the power pole features a septum for power and data cable management. Flexible metal conduits containing ten wires with a snap fit attachment for connection to the rigid wireway cable are included. Refer to the Planning Guide for additional tips on specifying top infeeds. The ten wires must be connected to building electrical by a licensed electrician.

Power Pass-Through
The electrical system provides a method of passing power from one powered chase through a non-powered 24" chase to the powered rigid wireway of the next chase. Chase-to-chase jumpers are required to connect adjacent wireways.

Chase-to-Chase Jumpers
18.5" chase-to-chase jumpers feature steel casing and are used for inline and corner connections.

Receptacles
The receptacles for the modular electrical system feature injection molded components which snap fit into the rigid wireways of the chase. The rated capacity of the duplex receptacles is 15 amp, 6-2-2 (6 circuits) configurations.

Bezels/Filler Plates
Bezels and filler plates are molded in nylon and are available in a variety of colors.

Electrical System Test Requirements
The modular US electrical components used within Trellis meet applicable UL183 standards and requirements as identified by Underwriters Laboratories, Inc

Electrical (Single-Circuit)

Activ8 Overview
The Activ8 electrical system is a UL 962 recognized component that allows up to eight duplex power modules to be connected to one standard 15-amp power cord. This system uses patented

technology that allows the power modules to be connected in any order, without the need for sequential keying. The number of power modules connected is limited to the maximum allowed under UL standard 962. If more than eight modules are connected, the Activ8 control box disconnects all power to the system and illuminates a red LED. Power is resumed automatically to the system once the additional power module or modules are disconnected, which is indicated by a green LED. The fuse on the power entry box can be reset as it is used to limit the number of devices on the chain.

Technical Applications
Activ8 is available as a standard power accessory on KI's Trellis Power Distribution solutions. To reduce the risk of electric shock, use only indoors.

Activ8 Components
Power Infeed: Series includes a standard NEMA 5-15P 15-amp plug on one end of the 108" cord and a non-sequentially keyed connector at the opposite end of the cord. Control box is located 12 inches from the table connection. Will not work with GFI/GCFI building outlets. Must specify the Trellis infeed cover separately to route cord out from beam area.

Built-in diagnostics LED shows system status:

- Green=power is on and system is working properly
- Red=power has been stopped because too many modules are connected or beyond 40'
- LED off=input power is not available; check that power cord is plugged into an outlet, and that power is available to that outlet

RPT power module and spacer plate for Trellis: Duplex power module provides two outlets per module. A connector with three ports is located at the opposite end of the 12" cord.

Jumper: Each jumper is equipped with a connector on each end that plugs into any connector on a given power module. Jumpers are non-sequential and are interchangeable to the extent that the jumper length is sufficient to reach the next module. Jumpers are available in four standard lengths - 29", 53", 77" and 101".

- UL962 Requirements
- Single-circuit power
 - 12-amp total system rating
 - 15-amp power infeed cord (9' minimum length, 15' maximum)
 - Over-current protection
 - 40' maximum length (not including power infeed cord)
 - Up to eight duplex power modules
 - Locking clip between chases is required

Complete requirements for meeting UL Standard 962 are described in that Standard.

Hardwire Overview
The Hardwire option consists of a slightly modified chase manufactured of standard materials.

A single bezel trimmed opening per side is on 24" and 30" troughs (3-1/2" off center). There are two openings per side on 36" through 72" troughs (6" and 13" from their respected ends), with the other

side being just the opposite.

KI provides a UL listed single gang metal outlet box, mounting bracket and screws per opening.

The same bezel and filler plates (standard KI colors) that are standard on our 10-wire troughs are standard here as well, with the top opening available for data. (1.38" x 2.70" standard opening).

The electrician is responsible for the décor receptacles, wiring, flexible conduit and fittings.



Paint Color - Unit, Connections, End Caps, Infeeds		Island	LID	Blue Grey	EGR	Light Tone	LG
		Italian Silver Ash	LIT	Brighton Walnut	EBW	Misty Brown	MY
Black	BL	Kensington Maple	LKM	Castle Oak	ECO	Sand	SA
Blue Grey	GR	Lapis Blue	LLB	Cayenne	ECY	Warm Grey	WG
Bronze Metallic	ZM	Markerboard White	LMK	Cherry Storm	ECX		
Cayenne	CY	Misted Zephyr	LMR	Cocobala	ECC		
Champagne Metallic	CM	Monticello Maple	LMT	Cool Grey	ECG		
Cool Grey	CG	Nickel Evolv	LVN	Earthen Clay	EEY		
Cottonwood	CO	North Sea	LNA	Everglade Shade	EEV		
Earthen Clay	EY	Ocean	LON	Flannel	EFN		
Espresso Metallic	EX	Pearl Bisque	LPB	Florence Walnut	EFC		
Everglade Shade	EV	Pearl Silver	LPS	Friston Ash	EFH		
Flannel	FN	Pressed Linen	LPR	Frosty White	EFW		
Glitz Metallic	GZ	River Cherry	LRY	Hazy Jade	EHJ		
Hazy Jade	HJ	Satin Stainless	LSS	Honey Bee	EHY		
Honey Bee	HY	Shadow Zephyr	LSR	Italian Silver Ash	EIT		
Light Tone	LG	Silicon evolv	LSV	Kensington Maple	EKM		
Mardi Gras	MG	Sterling Ash	LAZ	Light Tone	ELG		
Misty Brown	MY	Tailored Linen	LTL	Mardi Gras	EMG		
Nemo	NE	Titanium evolv	LTV	Misty Brown	EMY		
Nordic	ND	White Nebula	LWL	Monticello Maple	EMT		
Poppy Red	PR	White Sand	LWN	Nemo	ENE		
Purple Haze	PH	Windsor Mahogany	LWY	Nordic	END		
Rubber Ducky	RK			Poppy Red	EPR		
Sand	SA	Insert Color--Steel		Purple Haze	EPH		
Sky Blue	SK	Black	IBL	River Cherry	ERY		
Starlight Silver Metallic	SX	Blue Grey	IGR	Rubber Ducky	ERK		
Surf's Up	SP	Bronze Metallic	IZM	Sand	ESA		
Twilight Shadow	TI	Cayenne	ICY	Sky Blue	ESK		
Ultra Blue	UB	Champagne Metallic	ICM	Sterling Ash	EAZ		
Warm Grey	WG	Cool Grey	ICG	Surf's Up	ESP		
Zesty Lime	ZL	Cottonwood	ICO	Twilight Shadow	ETI		
		Earthen Clay	IEY	Ultra Blue	EUB		
		Espresso Metallic	IEX	Warm Grey	EWG		
		Everglade Shade	IEV	Windsor Mahogany	EWY		
		Flannel	IFN	Zesty Lime	EZL		
		Glitz Metallic	IGZ				
		Hazy Jade	IHJ	Bezel Color			
		Honey Bee	IHY	Black	BBL		
		Light Tone	ILG	Blue Grey	BGR		
		Mardi Gras	IMG	Cool Grey	BCG		
		Misty Brown	IMY	Light Tone	BLG		
		Nemo	INE	Misty Brown	BMY		
		Nordic	IND	Sand	BSA		
		Purple Haze	IPH	Warm Grey	BWG		
		Rubber Ducky	IRK				
		Sand	ISA	Conduit Color			
		Starlight Silver Metallic	ISX	Black	CBL		
		Surf's Up	ISP	Blue Grey	CGR		
		Twilight Shadow	ITI	Cottonwood	CCO		
		Ultra Blue	IUB	Light Tone	CLG		
		Warm Grey	IWG	Sand	CSA		
		Zesty Lime	IZL	Warm Grey	CWG		
				Receptacle Color			
			EBQ	Black	BL		
			EBT	Blue Grey	GR		
			EBL	Cool Grey	CG		



Finish Cards

View color swatches for items listed within this document.

- | | | | |
|----------------------|--------------------|---------------------|----------------------|
| <u>Paints</u> | <u>Wood/Veneer</u> | <u>Molded Edges</u> | <u>Hard Plastics</u> |
| <u>Plastics/Poly</u> | <u>Laminates</u> | <u>Edge Styles</u> | <u>Glass</u> |

Certain options referenced may not be available on GSA Schedule.



			MODEL NUMBER												
			Basic Model	Power Option	Data Separator	Bezel Color	Unit Color	Insert Color	Edge Color						
MODEL		W x H x D								Approx. Packaged Weight	Delivered Pricing	AC8 add to list price	HW add to list price	T6 add to list price	DS add to list price
 TRLI	Laminate Insert 24”H	24x24x3-5/8”	TRLI2424	<input type="checkbox"/>	NS		<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	19.0#	\$ 534	\$ 35	N/A	N/A	N/A
	• 24” high with laminate insert option	30x24x3-5/8”	TRLI3024	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	22.0#	553	35	72	122	23
	• 24” length not available with T6 power	36x24x3-5/8”	TRLI3624	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	26.0#	573	35	129	125	24
	• T6 option includes rigid wireway.	42x24x3-5/8”	TRLI4224	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	30.0#	606	35	129	129	26
	Receptacles to be specified separately	48x24x3-5/8”	TRLI4824	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	33.0#	626	35	129	129	27
	• Optional data separator keeps data wires above the rigid wireway	54x24x3-5/8”	TRLI5424	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	36.0#	664	35	129	133	36
	• T6 option must be selected to order the DS option	60x24x3-5/8”	TRLI6024	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	38.0#	707	97	129	142	37
	• Includes the inline connecting clamp	66x24x3-5/8”	TRLI6624	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	42.0#	730	97	129	163	37
	• T6 & NP chases 30” and wider have two bezels per side	72x24x3-5/8”	TRLI7224	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	45.0#	747	97	129	190	37
	• A8 chases 60” and wider have two holes per side; black filler covers included														
	• Activ8 RPT receptacles to be specified separately														
	• HW chase 36” and wider have two bezels per side														
 TRLI	Laminate Insert 30”H	24x30x3-5/8”	TRLI2430	<input type="checkbox"/>	NS		<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	23.0#	\$ 573	\$ 35	N/A	N/A	N/A
	• 30” high with laminate insert option	30x30x3-5/8”	TRLI3030	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	27.0#	600	35	72	122	23
	• 24” length not available with T6 power	36x30x3-5/8”	TRLI3630	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	32.0#	625	35	129	125	24
	• T6 option includes rigid wireway.	42x30x3-5/8”	TRLI4230	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	35.0#	667	35	129	129	26
	Receptacles to be specified separately	48x30x3-5/8”	TRLI4830	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	39.0#	684	35	129	129	27
	• Optional data separator keeps data wires above the rigid wireway	54x30x3-5/8”	TRLI5430	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	43.0#	730	35	129	133	36
	• T6 option must be selected to order the DS option	60x30x3-5/8”	TRLI6030	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	47.0#	775	97	129	142	37
	• Includes the inline connecting clamp	66x30x3-5/8”	TRLI6630	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	50.0#	745	97	129	163	37
	• T6 & NP chases 30” and wider have two bezels per side	72x30x3-5/8”	TRLI7230	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	53.0#	758	97	129	190	37
	• A8 chases 60” and wider have two holes per side; black filler covers included														
	• Activ8 RPT receptacles to be specified separately														
	• HW chase 36” and wider have two bezels per side														
			A	B	C	D	E	F	G						

HOW TO ORDER

Indicate the following information on order form:

- Quantity of each item.
- Model number, including options. See “How To Build a Model Number”.
- Any special service required.

Note:

- The ☐ indicates that a choice is required.
- The absence of the ☐ indicates that no choice is required.
- Alpha-numeric characters in place of ☐ indicate that no other alternatives are available.

HOW TO BUILD A MODEL NUMBER

ASelect basic model.

BSelect power option

Add upcharge to unit price for A8, HW or T6 option.

NP	- No power
A8	- Activ8 power
HW	- Hardwire power
T6	- T6 power

T6 and HW are not available on 24” wide models.

CSelect data separator.

Add upcharge to unit price for DS option.

NS	- No data separator
DS	- Data separator

If NP, A8 or HW is selected then only NS. If T6 is selected then either NS or DS.

DSelect bezel color

Refer to the **Product Color Options** page in this price list.

Bezel color selection is not available on A8

option or 24” wide models.

ESelect unit color.

Refer to the **Product Color Options** page in this price list.

FSelect insert color.

Refer to the **Product Color Options** page in this price list.

GSelect edge color.

Refer to the **Product Color Options** page in this price list.

SPECIAL SERVICES



Special Carton Marking

With specially marked information N/C

Shipping
Ships **knocked down, FOB Manitowoc, WI 54220, freight prepaid.** Freight class 70.

Specifications and prices are subject to change without prior notice.



			MODEL NUMBER															
MODEL			W x H x D	Basic Model	Power Option	Data Separator	Bezel Color	Unit Color	Insert Color	Approx. Packaged Weight	Delivered Pricing	AC8 add to list price		HW add to list price	T6 add to list price	DS add to list price		
 TRSI	Steel Insert 24”H		24x24x3-5/8”	TRSI2424	<input type="checkbox"/> <input type="checkbox"/>	NS		<input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	19.0#	\$ 600	\$	35	N/A	N/A	N/A		
	• 24” high with solid steel insert option		30x24x3-5/8”	TRSI3024	<input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	22.0#	617		35	72	122	23			
	• 24” length not available with T6 power		36x24x3-5/8”	TRSI3624	<input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	24.0#	625		35	129	125	24			
	• T6 option includes rigid wireway.		42x24x3-5/8”	TRSI4224	<input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	29.0#	652		35	129	129	26			
	Receptacles to be specified separately		48x24x3-5/8”	TRSI4824	<input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	33.0#	673		35	129	129	27			
	• Optional data separator keeps data wires above the rigid wireway		54x24x3-5/8”	TRSI5424	<input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	35.0#	697		35	129	133	36			
	• T6 option must be selected to order the DS option		60x24x3-5/8”	TRSI6024	<input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	38.0#	794		97	129	142	37			
	• Includes the inline connecting clamp		66x24x3-5/8”	TRSI6624	<input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	41.0#	807		97	129	163	37			
	• T6 & NP chases 30” and wider have two bezels per side		72x24x3-5/8”	TRSI7224	<input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	44.0#	901		97	129	190	37			
	• A8 chases 60” and wider have two holes per side; black filler covers included																	
	• Activ8 RPT receptacles to be specified separately																	
	• HW chase 36” and wider have two bezels per side																	
	 TRSI	Steel Insert 30”H		24x30x3-5/8”	TRSI2430	<input type="checkbox"/> <input type="checkbox"/>	NS		<input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	22.0#	\$ 627	\$	35	N/A	N/A	N/A	
• 30” high with solid steel insert option		30x30x3-5/8”	TRSI3030	<input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	26.0#	647		35	72	122	23				
• 24” length not available with T6 power		36x30x3-5/8”	TRSI3630	<input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	31.0#	664		35	129	125	24				
• T6 option includes rigid wireway.		42x30x3-5/8”	TRSI4230	<input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	34.0#	697		35	129	129	26				
Receptacles to be specified separately		48x30x3-5/8”	TRSI4830	<input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	37.0#	718		35	129	129	27				
• Optional data separator keeps data wires above the rigid wireway		54x30x3-5/8”	TRSI5430	<input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	41.0#	745		35	129	133	36				
• T6 option must be selected to order the DS option		60x30x3-5/8”	TRSI6030	<input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	45.0#	852		97	129	142	37				
• Includes the inline connecting clamp		66x30x3-5/8”	TRSI6630	<input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	49.0#	863		97	129	163	37				
• T6 & NP chases 30” and wider have two bezels per side		72x30x3-5/8”	TRSI7230	<input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	52.0#	948		97	129	190	37				
• A8 chases 60” and wider have two holes per side; black filler covers included																		
• Activ8 RPT receptacles to be specified separately																		
• HW chase 36” and wider have two bezels per side																		

A

B

C

D

E

F

HOW TO ORDER

Indicate the following information on order form:

- Quantity of each item.
- Model number, including options. See “How To Build a Model Number”.
- Any special service required.

Note:

- The ☐ indicates that a choice is required.
- The absence of the ☐ indicates that no choice is required.
- Alpha-numeric characters in place of ☐ indicate that no other alternatives are available.

HOW TO BUILD A MODEL NUMBER

ASelect basic model.

BSelect power option

Add upcharge to unit price for A8, HW or T6 option.

NP	- No power
A8	- Activ8 power
HW	- Hardwire power
T6	- T6 power

T6 and HW are not available on 24” wide models.

CSelect data separator.

Add upcharge to unit price for DS option.

NS	- No data separator
DS	- Data separator

If NP, A8 or HW is selected then only NS. If T6 is selected then either NS or DS.

DSelect bezel color

Refer to the **Product Color Options** page in this price list.

Bezel color selection is not available on A8

option or 24” wide models.

ESelect unit color.

Refer to the **Product Color Options** page in this price list.

FSelect insert color.

Refer to the **Product Color Options** page in this price list.

SPECIAL SERVICES





Special Carton Marking

With specially marked information N/C

Shipping
Ships **knocked down, FOB Manitowoc, WI 54220, freight prepaid.** Freight class 70.

Specifications and prices are subject to change without prior notice.



		MODEL NUMBER		Approx. Packaged Weight		Delivered Pricing	
		Basic Model	Unit Color				
	MODEL End-of-run Cover <ul style="list-style-type: none">• TRER24 for 24" high Trellis• TRER30 for 30" high Trellis	24"	TRER24	<input type="checkbox"/> <input type="checkbox"/>	3.0#	\$	54
		30"	TRER30	<input type="checkbox"/> <input type="checkbox"/>	4.0#		62
TRER							
	Trellis Inline Foot <ul style="list-style-type: none">• Used to connect two chases inline or at end of the run• Shared foot• Used for end of run and infeeds		TRFTINL	<input type="checkbox"/> <input type="checkbox"/>	4.0#	\$	112
TRFT							
	Trellis Corner Connector 120° 2-Way <ul style="list-style-type: none">• Used to connect two chases at 120 degrees• Includes one end-of-run cover• Height is determined by corresponding chase height	24"	TRFT2W12024	<input type="checkbox"/> <input type="checkbox"/>	6.0#	\$	198
		30"	TRFT2W12030	<input type="checkbox"/> <input type="checkbox"/>	7.0#		198
TRFT							
	Trellis Corner Connector 120° 3-Way <ul style="list-style-type: none">• Used to connect three chases at 120 degrees• Works for both heights of Trellis		TRFT3W120	<input type="checkbox"/> <input type="checkbox"/>	4.0#	\$	182
TRFT							

A

B

HOW TO ORDER

Indicate the following information on order form:

1. Quantity of each item.
2. Model number, including options. See “How To Build a Model Number”.
3. Any special service required.

Note:

- The ☐ indicates that a choice is required.
- The absence of the ☐ indicates that no choice is required.
- Alpha-numeric characters in place of ☐ indicate that no other alternatives are available.

HOW TO BUILD A MODEL NUMBER

- A** Select basic model.
- B** Select unit color.
Refer to the **Product Color Options** page in this price list.

SPECIAL SERVICES




Special Carton Marking

With specially marked information N/C

Shipping
Ships **knocked down, FOB Manitowoc, WI 54220, freight prepaid.** Freight class 70.

Specifications and prices are subject to change without prior notice.



		MODEL NUMBER				
		Basic Model	Unit Color			
MODEL	H			Approx. Packaged Weight	Delivered Pricing	
	Trellis Corner Connector 90° 2-Way <ul style="list-style-type: none">Used to connect two chases at 90 degreesHeight is determined by corresponding chase height	24"	TRFT2W9024	<input type="checkbox"/> <input type="checkbox"/>	8.0#	\$ 238
		30"	TRFT2W9030	<input type="checkbox"/> <input type="checkbox"/>	9.0#	238
TRFT						
	Trellis Corner Connector 90° 3-Way <ul style="list-style-type: none">Used to connect three chases in 90 degree t-configurationsHeight is determined by corresponding chase height	24"	TRFT3W9024	<input type="checkbox"/> <input type="checkbox"/>	7.0#	\$ 225
		30"	TRFT3W9030	<input type="checkbox"/> <input type="checkbox"/>	8.0#	225
TRFT						
	Trellis Corner Connector 90° 4-Way <ul style="list-style-type: none">Used to connect four chases at 90 degreesWorks for both heights of Trellis		TRFT4W90	<input type="checkbox"/> <input type="checkbox"/>	5.0#	\$ 205
TRFT						
		A	B			

HOW TO ORDER

Indicate the following information on order form:

- Quantity of each item.
- Model number, including options. See “How To Build a Model Number”.
- Any special service required.

Note:

- The ☐ indicates that a choice is required.
- The absence of the ☐ indicates that no choice is required.
- Alpha-numeric characters in place of ☐ indicate that no other alternatives are available.

HOW TO BUILD A MODEL NUMBER

- A** Select basic model.
- B** Select unit color.
Refer to the **Product Color Options** page in this price list.

SPECIAL SERVICES





Special Carton Marking

With specially marked information N/C

Shipping
Ships **knocked down, FOB Manitowoc, WI 54220, freight prepaid.** Freight class 70.

Specifications and prices are subject to change without prior notice.



			MODEL NUMBER				
			Basic Model	Unit Color	Conduit Color		
MODEL	Features	L				Approx. Packaged Weight	Delivered Pricing
 HRDPT	15-Amp Duplex Receptacle for Raceway Use; 10-wire/6 Circuit <ul style="list-style-type: none">• Snaps to rigid wireway• Receptacle color is orange with white lettering for circuits 4I, 5I and 6I	Circuit 1	TRRECP.1	<input type="checkbox"/> <input type="checkbox"/>		1.0#	\$ 29
		Circuit 2	TRRECP.2	<input type="checkbox"/> <input type="checkbox"/>		1.0#	29
		Circuit 3	TRRECP.3	<input type="checkbox"/> <input type="checkbox"/>		1.0#	29
		Circuit 4	TRRECP.4I			1.0#	29
		Circuit 5	TRRECP.5I			1.0#	29
		Circuit 6	TRRECP.6I			1.0#	29
 HRDPT	Electrical Chase-to-Chase Jumpers; 10-wire/6 Circuit <ul style="list-style-type: none">• Flexible metal conduit jumper• 49.0245.TJ for all chase-to-chase connections• 49.0245.30 to use as power pass through for 24” Trellis	18-1/2”	TRJP.TJ			3.0#	\$ 113
		48-1/2”	TRJP.30			3.5#	158
 TRIB	Base Infeed; 10-wire/6 Circuit <ul style="list-style-type: none">• Base feed includes 96” liquid colored conduit• Height must be specified• Height is determined by corresponding chase height		TRIB24	<input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	10.0#	\$ 364
			TRIB30	<input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	11.0#	380
 TRIT	Top Infeed; 10-wire/6 Circuit <ul style="list-style-type: none">• Provides power from ceiling to power chase distribution system• Includes 10’ long aluminum pole with separate channel for electrical and data entry, trim plate and 144” prewired harness• Height must be specified• Height is determined by corresponding chase height		TRIT24	<input type="checkbox"/> <input type="checkbox"/>		22.0#	\$ 614
			TRIT30	<input type="checkbox"/> <input type="checkbox"/>		23.0#	626
			A	B	C		

HOW TO ORDER

Indicate the following information on order form:

1. Quantity of each item.
2. Model number, including options. See “How To Build a Model Number”.
3. Any special service required.

Note:

- The ☐ indicates that a choice is required.
- The absence of the ☐ indicates that no choice is required.
- Alpha-numeric characters in place of ☐ indicate that no other alternatives are available.

HOW TO BUILD A MODEL NUMBER

- A** Select basic model.
- B** Select unit color.
Refer to the **Product Color Options** page in this price list.
- C** Select conduit color.
Refer to the **Product Color Options** page in this price list.

SPECIAL SERVICES



Special Carton Marking

With specially marked information N/C

Shipping
Ships **knocked down, FOB Manitowoc, WI 54220, freight prepaid.** Freight class 70.

Specifications and prices are subject to change without prior notice.



		MODEL NUMBER				
		Basic Model	Unit Color	Conduit Color		
	Middle Base Infeed; 10-wire/6 Circuit <ul style="list-style-type: none">• Base feed includes 96" liquid colored conduit• Height must be specified• Height is determined by corresponding chase height	L				
TRIB	Middle Top Infeed; 10-wire/6 Circuit <ul style="list-style-type: none">• Provides power from ceiling to power chase distribution system• Includes 10' long aluminum pole with separate channel for electrical and data entry, trim plate and 144" prewired harness• Height must be specified• Height is determined by corresponding chase height					
TRIT						
		A	B	C		

HOW TO ORDER

Indicate the following information on order form:

1. Quantity of each item.
2. Model number, including options. See “How To Build a Model Number”.
3. Any special service required.

Note:

- The ☐ indicates that a choice is required.
- The absence of the ☐ indicates that no choice is required.
- Alpha-numeric characters in place of ☐ indicate that no other alternatives are available.

HOW TO BUILD A MODEL NUMBER

- A** Select basic model.
- B** Select unit color.
Refer to the **Product Color Options** page in this price list.
- C** Select conduit color.
Refer to the **Product Color Options** page in this price list.




SPECIAL SERVICES

Special Carton Marking

With specially marked information N/C

Shipping
Ships **knocked down, FOB Manitowoc, WI 54220, freight prepaid.** Freight class 70.

Specifications and prices are subject to change without prior notice.

		MODEL NUMBER			
		Basic Model	Unit Color		
MODEL		L		Approx. Packaged Weight	Delivered Pricing
	Top Data Infeeds; Hardwire				
	• Provides data from ceiling to power chase distribution system	TRDIT24	<input type="checkbox"/>	22.0#	\$ 421
	• Includes 10' long aluminum pole with separate channel for electrical and data entry and trim plate	TRDIT30	<input type="checkbox"/>	23.0#	489
	• Height must be specified				
	• Height is determined by corresponding chase height				
	• Provides access for hardwire				
TRIT					
	Middle Data Base Infeeds; Hardwire	TRDBM24	<input type="checkbox"/>	22.0#	\$ 331
	• Height must be specified	TRDBM30	<input type="checkbox"/>	23.0#	340
	• Height is determined by corresponding chase height				
	• Cover and foot only				
	• For use as a data cover, Activ8 or hardwire				
TRIB					
	Middle Data; Hardwire Top Infeeds	TRDTM24	<input type="checkbox"/>	22.0#	\$ 661
	• Height must be specified	TRDTM30	<input type="checkbox"/>	23.0#	668
	• Height is determined by corresponding chase height				
	• Provides access for top data and hardwire				
TRIT					
		A	B		

HOW TO ORDER

Indicate the following information on order form:

- Quantity of each item.
- Model number, including options. See “How To Build a Model Number”.
- Any special service required.

Note:

- The ☐ indicates that a choice is required.
- The absence of the ☐ indicates that no choice is required.
- Alpha-numeric characters in place of ☐ indicate that no other alternatives are available.

HOW TO BUILD A MODEL NUMBER

- A** Select basic model.
- B** Select unit color.
Refer to the **Product Color Options** page in this price list.

SPECIAL SERVICES





Special Carton Marking

With specially marked information N/C

Shipping
Ships **knocked down, FOB Manitowoc, WI 54220, freight prepaid.** Freight class 70.

Specifications and prices are subject to change without prior notice.



		MODEL NUMBER			
		Basic Model	Paint Color		
MODEL	L			Approx. Packaged Weight	Delivered Pricing
 HRDPT	Activ8® Infeed <ul style="list-style-type: none">• 108” cord plugs into standard 15 amp outlet• Control module is located 6” from table connection• Diagnostic LED indicator shows power status (see details below)• Controller automatically limits number of connections to 8• 40 Ft maximum string, not including infeed cord• Will not work with GFI/GCFI outlets or backup systems such as uninterrupted power supplies	AC8IF.108		2.0#	\$ 281
 HRDPT	Trellis Infeed Cover <ul style="list-style-type: none">• Cover only (infeed sold separately)• For use with Activ8 infeed• For use as a data infeed cover	24” 30” 48.6032.24 48.6032.30	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	1.0# 1.0#	\$ 123 134
 HRDPT	Activ8® Module and Attachment Bracket <ul style="list-style-type: none">• Duplex receptacles provide 2 outlets• Power module provides 15 amp power• Up to 8 modules may be used per infeed per UL Standard 962• Modules may be connected (reconnected in any order without sequential keying)• Jumpers ordered separately• Attached cord is approximately 9”	AC8RPTTR.12		1.0#	\$ 177
 HRDPT	Activ8® Jumper <ul style="list-style-type: none">• For Connection Zone and Trellis, refer to their Planning Guides for size recommendations	29” 53” 77” 101” AC8JP.29 AC8JP.53 AC8JP.77 AC8JP.101		1.0# 1.0# 1.0# 1.0#	\$ 88 104 120 125

A

B

HOW TO ORDER

Indicate the following information on order form:

1. Quantity of each item.
2. Model number, including options. See “How To Build a Model Number”.
3. Any special service required.

Note:

- The ☐ indicates that a choice is required.
- The absence of the ☐ indicates that no choice is required.
- Alpha-numeric characters in place of ☐ indicate that no other alternatives are available.

HOW TO BUILD A MODEL NUMBER

- A**Select basic model.
- B**Select paint color.
Refer to the **Product Color Options** page in this price list.

SPECIAL SERVICES

Special Carton Marking

With specially marked information N/C

Shipping
Shipped **k.d. FOB Bonduel, WI 54107, freight prepaid.** Freight class #85.

Covers shipped **k.d. FOB Manitowoc, WI 54220, freight prepaid.** Freight class #85.

Specifications and prices are subject to change without prior notice.

1330 Bellevue Street
P.O. Box 8100
Green Bay, WI 54308-8100
800.424.2432
ki.com

KI and Furnishing Knowledge are registered
trademarks of Krueger International, Inc.

© 2020 Krueger International, Inc.
All Rights Reserved.
Code KI-PLW-000259/KI/PDF



Furnishing Knowledge®