

Trellis® System Price List ■

December 17, 2014

Updated July 2, 2018

800-424-2432



Furnishing Knowledge®



Contents

Refer to KI Terms & Conditions document or visit ki.com.

Trellis®	General Information	2
Trellis® Power and Data Chase		
	Laminate Inserts	4
	Steel Inserts	6
Trellis® Connections and Endcaps		8
Electrical		
	Receptacles, Jumpers and Infeeds	12
	Receptacles and Jumpers	16
Activ8® System	Single Circuit Electrical	18
Index		20

Trellis™

General Information

SPECIFICATIONS

Chase

Trellis ships knockdown with chase, feet components and chase-to-chase connection hardware. Preconfigured chases are 3.63" thick and are available in the follow dimensions:

- Widths: 24", 30", 36", 42", 48", 54", 60", 66" and 72"
- Heights: 24" and 30"

Trellis allows for distribution of power and data at the top of the chase. Trellis is capable of carrying 100 Cat 6 cables or (1) 2.5" diameter bundle of cables.

Trellis Construction

Adjoining chases share common feet, therefore chases are secured at the bottom. A locking clip is provided to align and secure the top of the chases. Chases can also be screwed together at the top if floor conditions require so (screws are included). Chases consist of the following:

- Top horizontal beam - formed of 22-gauge steel, 3.63" x 6", overall length 24" to 72"
- Vertical channels - formed of 20-gauge steel x .75" x 3.63", to allow for fit-up with feet
- Insert panel (Inserts provide lateral stability)

Laminate - formed of 5/8" thick, 45 lb. density particle board with high pressure laminate and a 2mm 73P edge.

Steel - (2) piece formed 22 ga. panels riveted together.

Corner Connector Construction

90° and 120° - formed of powdercoated 22-gauge steel, includes fasteners.

Top Cap

All preconfigured Trellis systems include a top cap of appropriate size. Top caps are formed of powdercoated 22-gauge cold rolled steel. Installation of top cap is a snap fit and requires no tools.

- Top cap dimensions: 0.4" x 3.62" x width of chase

End-of-Run Trim

All exposed ends of a chase are covered with an end-of-run trim formed from powdercoated 20-gauge steel. Installation of end-of-run trim is a slide fit. Chase end trim lengths correspond to Trellis height.

ELECTRICAL (10-Wire)

Power Options

The US standard electrical system supplied for Trellis is a 10-wire electrical system, UL183 listed. Rigid wireway is factory mounted to chase beam.

10 wire power system is 6-2-2 configuration:
6-2-2

- (6) hot wires
- (2) shared, oversized neutral wires
- (2) ground wires - one isolated ground, one building ground

Rigid Wireways

Each powered chase includes the rigid wireways to pass power to receptacles. Wireways are mounted within the horizontal beam. Wireways are specified by chase length. The wireway design allows for snap connection of one chase wireway to another through the use of common chase jumpers. All chases 30" and wider accept electrical receptacles.

There are two receptacle locations on each side of every rigid wireway (see planning guide for spacing locations).

Base Infeeds

The electrical system permits power infeed at either end of the chase. Base infeeds are constructed of an 8' long, 3/4" dia. liquid-tight, flexible medal conduit. The metal conduit contains ten wires with a snap fit design allowing for quick installation and removal. The ten wires must be connected to building electrical by a licensed electrician.

Top Infeeds (Data and/or Power)

Power and data may be brought into Trellis through the use of a top infeed. Top infeed assembly consists of a 10' extruded aluminum data and/or power pole, top cap and ceiling trim. The interior of the power pole features a septum for power and data cable management. Flexible metal conduits containing ten wires with a snap fit attachment for connection to the rigid wireway cable are included. Refer to the Planning Guide for additional tips on specifying top infeeds. The ten wires must be connected to building electrical by a licensed electrician.

Power Pass-Through

The electrical system provides a method of passing power from one powered chase through a non-powered 24" chase to the powered rigid wireway of the next chase. Chase-to-chase jumpers are required to connect adjacent wireways.

Chase-to-Chase Jumpers

18.5" chase-to-chase jumpers feature steel casing and are used for inline and corner connections.

Receptacles

The receptacles for the modular electrical system feature injection molded components which snap fit into the rigid wireways of the chase. The rated capacity of the duplex receptacles is 15 amp, 6-2-2 (6 circuits) configurations.

Bezels/Filler Plates

Bezels and filler plates are molded in nylon and are available in a variety of colors.

Electrical System Test Requirements

The modular US electrical components used within Trellis meet applicable UL183 standards and requirements as identified by Underwriters Laboratories, Inc

Electrical (Single-Circuit)

Activ8 Overview

The Activ8 electrical system is a UL 962 recognized component that allows up to eight duplex power modules to be connected to one standard 15-amp power cord. This system uses patented technology that allows the power modules to be connected in any order, without the need for sequential keying. The number of power modules

connected is limited to the maximum allowed under UL standard 962. If more than eight modules are connected, the Activ8 control box disconnects all power to the system and illuminates a red LED. Power is resumed automatically to the system once the additional power module or modules are disconnected, which is indicated by a green LED. The fuse on the power entry box can be reset as it is used to limit the number of devices on the chain.

Technical Applications

Activ8 is available as a standard power accessory on KI's Trellis Power Distribution solutions. To reduce the risk of electric shock, use only indoors.

Activ8 Components

Power Infeed: Series includes a standard NEMA 5-15P 15-amp plug on one end of the 108" cord and a non-sequentially keyed connector at the opposite end of the cord. Control box is located 12 inches from the table connection. Will not work with GFI/GCFI building outlets. Must specify the Trellis infeed cover separately to route cord out from beam area.

Built-in diagnostics LED shows system status:

- Green=power is on and system is working properly
- Red=power has been stopped because too many modules are connected or beyond 40'
- LED off=input power is not available; check that power cord is plugged into an outlet, and that power is available to that outlet

RPT power module and spacer plate for Trellis: Duplex power module provides two outlets per module. A connector with three ports is located at the opposite end of the 12" cord.

Jumper: Each jumper is equipped with a connector on each end that plugs into any connector on a given power module. Jumpers are non-sequential and are interchangeable to the extent that the jumper length is sufficient to reach the next module. Jumpers are available in four standard lengths - 29", 53", 77" and 101".

UL962 Requirements

- Single-circuit power
- 12-amp total system rating
- 15-amp power infeed cord (9' minimum length, 15' maximum)
- Over-current protection
- 40' maximum length (not including power infeed cord)
- Up to eight duplex power modules
- Locking clip between chases is required

Complete requirements for meeting UL Standard 962 are described in that Standard.

Hardwire Overview

The Hardwire option consists of a slightly modified chase manufactured of standard materials.

A single bezel trimmed opening per side is on 24" and 30" troughs (3-1/2" off center). There are two openings per side on 36" through 72" troughs (6" and 13" from their respected ends), with the other side being just the opposite.

KI provides a UL listed single gang metal outlet box, mounting bracket and screws

per opening.



The same bezel and filler plates (standard KI colors) that are standard on our 10-wire troughs are standard here as well, with the top opening available for data. (1.38" x 2.70" standard opening).

The electrician is responsible for the décor receptacles, wiring, flexible conduit and fittings.



Trellis® Power and Data Chase

Laminate Inserts

	MODEL	W x H x D	MODEL NUMBER							Approx. Packaged Weight
			Basic Model	Power Option	Data Separator	Bezel Color	Unit Color	Insert Color	Edge Color	
 <p>TRLI</p>	Laminate Insert 24"H	24x24x3-5/8"	TRLI2424	<input type="checkbox"/>	NS		<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	19.0#
	• 24" high with laminate insert option	30x24x3-5/8"	TRLI3024	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	22.0#
	• 24" length not available with T6 power	36x24x3-5/8"	TRLI3624	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	26.0#
	• T6 option includes rigid wireway.	42x24x3-5/8"	TRLI4224	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	30.0#
	• Receptacles to be specified separately	48x24x3-5/8"	TRLI4824	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	33.0#
	• Optional data separator keeps data wires above the rigid wireway	54x24x3-5/8"	TRLI5424	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	36.0#
	• T6 option must be selected to order the DS option	60x24x3-5/8"	TRLI6024	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	38.0#
	• Includes the inline connecting clamp	66x24x3-5/8"	TRLI6624	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	42.0#
	• T6 & NP chases 30" and wider have two bezels per side	72x24x3-5/8"	TRLI7224	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	45.0#
	• A8 chases 60" and wider have two holes per side; black filler covers included									
 <p>TRLI</p>	Laminate Insert 30"H	24x30x3-5/8"	TRLI2430	<input type="checkbox"/>	NS		<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	23.0#
	• 30" high with laminate insert option	30x30x3-5/8"	TRLI3030	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	27.0#
	• 24" length not available with T6 power	36x30x3-5/8"	TRLI3630	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	32.0#
	• T6 option includes rigid wireway.	42x30x3-5/8"	TRLI4230	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	35.0#
	• Receptacles to be specified separately	48x30x3-5/8"	TRLI4830	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	39.0#
	• Optional data separator keeps data wires above the rigid wireway	54x30x3-5/8"	TRLI5430	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	43.0#
	• T6 option must be selected to order the DS option	60x30x3-5/8"	TRLI6030	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	47.0#
	• Includes the inline connecting clamp	66x30x3-5/8"	TRLI6630	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	50.0#
	• T6 & NP chases 30" and wider have two bezels per side	72x30x3-5/8"	TRLI7230	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	53.0#
	• A8 chases 60" and wider have two holes per side; black filler covers included									

A

B

C

D

E

F

G

HOW TO ORDER

Indicate the following information on order form:

1. Quantity of each item.
2. Model number, including options. See "How To Build a Model Number".
3. Any special service required.

Note: • The ☐ indicates that a choice is required.

- The absence of the ☐ indicates that no choice is required.

• Alpha-numeric characters in place of ☐ indicate that no other alternatives are available.

HOW TO BUILD A MODEL NUMBER

A Select basic model.

B Select power option

Add upcharge to unit price for A8, HW or T6 option.

NP - No power

A8 - Activ8 power

HW - Hardwire power

T6 - T6 power

T6 and HW are not available on 24" wide models.

C Select data separator.

Add upcharge to unit price for DS option.

NS - No data separator

DS - Data separator

If NP, A8 or HW is selected then only NS.

If T6 is selected then either NS or DS.

D Select bezel color

Refer to the **KI Color Addendum** or **KI**

Fabrics & Finishes binder.

Bezel color selection is not available on A8

option or 24" wide models.

E Select unit color.

Refer to the **KI Color Addendum** or **KI**

Fabrics & Finishes binder.

F Select insert color.

Refer to the **KI Color Addendum** or **KI**

Fabrics & Finishes binder.

G Select edge color.

Refer to the **KI Color Addendum** or **KI**

Fabrics & Finishes binder.



Trellis® Power and Data Chase

Laminate Inserts

Delivered Pricing	AC8 add to list price	HW add to list price	T6 add to list price	DS add to list price
\$ 397	\$ 26	N/A	N/A	N/A
412	26	54	90	16
426	26	96	93	17
451	26	96	96	19
465	26	96	96	20
493	26	96	99	27
526	72	96	106	28
543	72	96	121	28
555	72	96	141	28
\$ 426	\$ 26	N/A	N/A	N/A
446	26	54	90	16
464	26	96	93	17
495	26	96	96	19
509	26	96	96	20
543	26	96	99	27
576	72	96	106	28
554	72	96	121	28
564	72	96	141	28

SPECIAL SERVICES

Special Carton Marking

With specially marked information N/C



Shipping

Ships **knocked down, FOB Manitowoc, WI 54220, freight prepaid.** Freight class 70.

Specifications and prices are subject to change without prior notice.

Trellis® Power and Data Chase

Steel Inserts

	MODEL	W x H x D	MODEL NUMBER						Approx. Packaged Weight
			Basic Model	Power Option	Data Separator	Bezel Color	Unit Color	Insert Color	
 <p>TRSI</p>	Steel Insert 24"H	24x24x3-5/8"	TRSI2424	<input type="checkbox"/>	NS		<input type="checkbox"/>	<input type="checkbox"/>	19.0#
	• 24" high with solid steel insert option	30x24x3-5/8"	TRSI3024	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	22.0#
	• 24" length not available with T6 power	36x24x3-5/8"	TRSI3624	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	24.0#
	• T6 option includes rigid wireway.	42x24x3-5/8"	TRSI4224	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	29.0#
	• Receptacles to be specified separately	48x24x3-5/8"	TRSI4824	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	33.0#
	• Optional data separator keeps data wires above the rigid wireway	54x24x3-5/8"	TRSI5424	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	35.0#
	• T6 option must be selected to order the DS option	60x24x3-5/8"	TRSI6024	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	38.0#
	• Includes the inline connecting clamp	66x24x3-5/8"	TRSI6624	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	41.0#
	• T6 & NP chases 30" and wider have two bezels per side	72x24x3-5/8"	TRSI7224	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	44.0#
	• A8 chases 60" and wider have two holes per side; black filler covers included								
 <p>TRSI</p>	Steel Insert 30"H	24x30x3-5/8"	TRSI2430	<input type="checkbox"/>	NS		<input type="checkbox"/>	<input type="checkbox"/>	22.0#
	• 30" high with solid steel insert option	30x30x3-5/8"	TRSI3030	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	26.0#
	• 24" length not available with T6 power	36x30x3-5/8"	TRSI3630	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	31.0#
	• T6 option includes rigid wireway.	42x30x3-5/8"	TRSI4230	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	34.0#
	• Receptacles to be specified separately	48x30x3-5/8"	TRSI4830	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	37.0#
	• Optional data separator keeps data wires above the rigid wireway	54x30x3-5/8"	TRSI5430	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	41.0#
	• T6 option must be selected to order the DS option	60x30x3-5/8"	TRSI6030	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	45.0#
	• Includes the inline connecting clamp	66x30x3-5/8"	TRSI6630	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	49.0#
	• T6 & NP chases 30" and wider have two bezels per side	72x30x3-5/8"	TRSI7230	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	52.0#
	• A8 chases 60" and wider have two holes per side; black filler covers included								
			A	B	C	D	E	F	

HOW TO ORDER

Indicate the following information on order form:

- Quantity of each item.
- Model number, including options. See "How To Build a Model Number".
- Any special service required.

Note: • The ☐ indicates that a choice is required.

- The absence of the ☐ indicates that no choice is required.

- Alpha-numeric characters in place of ☐ indicate that no other alternatives are available.

HOW TO BUILD A MODEL NUMBER

A Select basic model.

B Select power option

Add upcharge to unit price for A8, HW or T6 option.

NP	- No power
A8	- Activ8 power
HW	- Hardwire power
T6	- T6 power

T6 and HW are not available on 24" wide models.

C Select data separator.

Add upcharge to unit price for DS option.

NS	- No data separator
DS	- Data separator

If NP, A8 or HW is selected then only NS.

If T6 is selected then either NS or DS.

D Select bezel color

Refer to the **KI Color Addendum** or **KI Fabrics & Finishes binder**.

Bezel color selection is not available on A8

option or 24" wide models.

E Select unit color.

Refer to the **KI Color Addendum** or **KI Fabrics & Finishes binder**.

F Select insert color.

Refer to the **KI Color Addendum** or **KI Fabrics & Finishes binder**.



Trellis® Power and Data Chase

Steel Inserts

Delivered Pricing	AC8 add to list price	HW add to list price	T6 add to list price	DS add to list price
\$ 446	\$ 26	N/A	N/A	N/A
459	26	54	90	16
464	26	96	93	17
485	26	96	96	19
501	26	96	96	20
518	26	96	99	27
590	72	96	106	28
600	72	96	121	28
669	72	96	141	28

\$ 466	\$ 26	N/A	N/A	N/A
482	26	54	90	16
493	26	96	93	17
518	26	96	96	19
534	26	96	96	20
554	26	96	99	27
634	72	96	106	28
642	72	96	121	28
705	72	96	141	28

SPECIAL SERVICES

Special Carton Marking





With specially marked information N/C

Shipping

Ships **knocked down, FOB Manitowoc, WI 54220, freight prepaid.** Freight class 70.

Specifications and prices are subject to change without prior notice.

Trellis® Connections and Endcaps

	MODEL	H	MODEL NUMBER		Approx. Packaged Weight
			Basic Model	Unit Color	
 TRER	End-of-run Cover <ul style="list-style-type: none">• TRER24 for 24" high Trellis• TRER30 for 30" high Trellis	24"	TRER24	<input type="checkbox"/>	3.0#
		30"	TRER30	<input type="checkbox"/>	4.0#
 TRFT	Trellis Inline Foot <ul style="list-style-type: none">• Used to connect two chases inline or at end of the run• Shared foot• Used for end of run and infeeds		TRFTINL	<input type="checkbox"/>	4.0#
 TRFT	Trellis Corner Connector 120° 2-Way <ul style="list-style-type: none">• Used to connect two chases at 120 degrees• Includes one end-of-run cover• Height is determined by corresponding chase height	24"	TRFT2W12024	<input type="checkbox"/>	6.0#
		30"	TRFT2W12030	<input type="checkbox"/>	7.0#
 TRFT	Trellis Corner Connector 120° 3-Way <ul style="list-style-type: none">• Used to connect three chases at 120 degrees• Works for both heights of Trellis		TRFT3W120	<input type="checkbox"/>	4.0#

A

B

HOW TO ORDER

Indicate the following information on order form:

1. Quantity of each item.
2. Model number, including options. See "How To Build a Model Number".
3. Any special service required.

Note:

- The ☐ indicates that a choice is required.
- The absence of the ☐ indicates that no choice is required.
- Alpha-numeric characters in place of ☐ indicate that no other alternatives are available.

HOW TO BUILD A MODEL NUMBER

- A** Select basic model.
- B** Select unit color.
Refer to the **KI Color Addendum** or **KI Fabrics & Finishes binder**



Trellis® Connections and Endcaps

Delivered
Pricing

\$ 40
46

\$ 84

\$ 147
147

\$ 136

SPECIAL SERVICES

Special Carton Marking




With specially marked information N/C

Shipping

Ships **knocked down, FOB Manitowoc, WI 54220, freight prepaid.** Freight class 70.

Specifications and prices are subject to change without prior notice.

Trellis® Connections and Endcaps

		MODEL NUMBER		Approx. Packaged Weight
		Basic Model	Unit Color	
	Trellis Corner Connector 90° 2-way <ul style="list-style-type: none">Used to connect two chases at 90 degreesHeight is determined by corresponding chase height	24" TRFT2W9024	<input type="checkbox"/>	8.0#
		30" TRFT2W9030	<input type="checkbox"/>	9.0#
TRFT				
	Trellis Corner Connector 90° 3-Way <ul style="list-style-type: none">Used to connect three chases in 90 degree t-configurationsHeight is determined by corresponding chase height	24" TRFT3W9024	<input type="checkbox"/>	7.0#
		30" TRFT3W9030	<input type="checkbox"/>	8.0#
TRFT				
	Trellis Corner Connector 90° 4-Way <ul style="list-style-type: none">Used to connect four chases at 90 degreesWorks for both heights of Trellis	TRFT4W90	<input type="checkbox"/>	5.0#
TRFT				
		A	B	

HOW TO ORDER

Indicate the following information on order form:

- Quantity of each item.
- Model number, including options. See "How To Build a Model Number".
- Any special service required.

Note:

- The ☐ indicates that a choice is required.
- The absence of the ☐ indicates that no choice is required.
- Alpha-numeric characters in place of ☐ indicate that no other alternatives are available.

HOW TO BUILD A MODEL NUMBER

- A** Select basic model.
- B** Select unit color.
Refer to the **KI Color Addendum** or **KI Fabrics & Finishes binder**



Trellis® Connections and Endcaps

Delivered Pricing	
\$	178
	178
\$	167
	167
\$	152

SPECIAL SERVICES

Special Carton Marking

With specially marked information N/C





Shipping

Ships **knocked down, FOB Manitowoc, WI 54220, freight prepaid.** Freight class 70.

Specifications and prices are subject to change without prior notice.

Electrical

Receptacles and Jumpers

				MODEL NUMBER			Approx. Packaged Weight
MODEL	Features	L	Basic Model	Unit Color	Conduit Color		
 HRDPT	15-Amp Duplex Receptacle for Raceway Use; 10-wire/6 Circuit <ul style="list-style-type: none">• Snaps to rigid wireway• Receptacle color is orange with white lettering for circuits 4I, 5I and 6I	Circuit 1	TRRECP.1	<input type="checkbox"/>		1.0#	
		Circuit 2	TRRECP.2	<input type="checkbox"/>		1.0#	
		Circuit 3	TRRECP.3	<input type="checkbox"/>		1.0#	
		Circuit 4	TRRECP.4I			1.0#	
		Circuit 5	TRRECP.5I			1.0#	
		Circuit 6	TRRECP.6I			1.0#	
 HRDPT	Electrical Chase-to-Chase Jumpers; 10-wire/6 Circuit <ul style="list-style-type: none">• Flexible metal conduit jumper• 49.0245.TJ for all chase to chase connections• 49.0245.24 to use as power pass through for 24" Trellis	18-1/2"	TRJP.TJ			3.0#	
		42-1/2"	TRJP.24			3.5#	
 TRIB	Base Infeed; 10-wire/6 Circuit <ul style="list-style-type: none">• Base feed includes 96" liquid colored conduit• Height must be specified• Height is determined by corresponding chase height		TRIB24	<input type="checkbox"/>	<input type="checkbox"/>	10.0#	
			TRIB30	<input type="checkbox"/>	<input type="checkbox"/>	11.0#	
 TRIT	Top Infeed; 10-wire/6 Circuit <ul style="list-style-type: none">• Provides power from ceiling to power chase distribution system• Includes 10' long aluminum pole with separate channel for electrical and data entry, trim plate and 144" prewired harness• Height must be specified• Height is determined by corresponding chase height		TRIT24	<input type="checkbox"/>		22.0#	
			TRIT30	<input type="checkbox"/>		23.0#	
				A	B	C	

HOW TO ORDER

Indicate the following information on order form:

1. Quantity of each item.
2. Model number, including options. See "How To Build a Model Number".
3. Any special service required.

Note:

- The ☐ indicates that a choice is required.
- The absence of the ☐ indicates that no choice is required.
- Alpha-numeric characters in place of ☐ indicate that no other alternatives are available.

HOW TO BUILD A MODEL NUMBER

- A** Select basic model.
- B** Select unit color.
Refer to the **KI Color Addendum** or **KI Fabrics & Finishes binder**.
- C** Select conduit color.
Refer to the **KI Color Addendum** or **KI Fabrics & Finishes binder**.



Delivered Pricing	
\$	22
	22
	22
	22
	22
	22
\$	85
	117
\$	270
	282
\$	456
	465

SPECIAL SERVICES

Special Carton Marking

With specially marked information N/C



Shipping

Ships **knocked down, FOB Manitowoc, WI 54220, freight prepaid.** Freight class 70.

Specifications and prices are subject to change without prior notice.

Electrical

Receptacles and Jumpers

		MODEL NUMBER			Approx. Packaged Weight	
		Basic Model	Unit Color	Conduit Color		
 TRIB	MODEL	L				
	Middle Base Infeed; 10-wire/6 Circuit					
	• Base feed includes 96" liquid colored conduit		TRIBM24	<input type="checkbox"/>	<input type="checkbox"/>	10.0#
	• Height must be specified		TRIBM30	<input type="checkbox"/>	<input type="checkbox"/>	11.0#
	• Height is determined by corresponding chase height					
 TRIT	Middle Top Infeed; 10-wire/6 Circuit		TRITM24	<input type="checkbox"/>	<input type="checkbox"/>	10.0#
	• Provides power from ceiling to power chase distribution system		TRITM30	<input type="checkbox"/>	<input type="checkbox"/>	11.0#
	• Includes 10' long aluminum pole with separate channel for electrical and data entry, trim plate and 144" prewired harness					
	• Height must be specified					
	• Height is determined by corresponding chase height					
		A	B	C		

HOW TO ORDER

Indicate the following information on order form:

1. Quantity of each item.
2. Model number, including options. See "How To Build a Model Number".
3. Any special service required.

Note:

- The ☐ indicates that a choice is required.
- The absence of the ☐ indicates that no choice is required.
- Alpha-numeric characters in place of ☐ indicate that no other alternatives are available.

HOW TO BUILD A MODEL NUMBER

- A** Select basic model.
- B** Select unit color.
Refer to the **KI Color Addendum** or **KI Fabrics & Finishes binder**.
- C** Select conduit color.
Refer to the **KI Color Addendum** or **KI Fabrics & Finishes binder**.



Delivered Pricing	
\$	493
	499
\$	758
	763

SPECIAL SERVICES

Special Carton Marking

With specially marked information N/C




Shipping

Ships **knocked down, FOB Manitowoc, WI 54220, freight prepaid.** Freight class 70.

Specifications and prices are subject to change without prior notice.

Electrical

Receptacles and Jumpers

MODEL	L	MODEL NUMBER		Approx. Packaged Weight
		Basic Model	Unit Color	
		TRDIT24	<input type="checkbox"/>	22.0#
		TRDIT30	<input type="checkbox"/>	23.0#
TRIT				
		TRDBM24	<input type="checkbox"/>	22.0#
		TRDBM30	<input type="checkbox"/>	23.0#
TRIB				
		TRDTM24	<input type="checkbox"/>	22.0#
		TRDTM30	<input type="checkbox"/>	23.0#
TRIT				

A

B

HOW TO ORDER

Indicate the following information on order form:

- Quantity of each item.
- Model number, including options. See "How To Build a Model Number".
- Any special service required.

Note:

- The ☐ indicates that a choice is required.
- The absence of the ☐ indicates that no choice is required.
- Alpha-numeric characters in place of ☐ indicate that no other alternatives are available.

HOW TO BUILD A MODEL NUMBER

- A** Select basic model.
- B** Select unit color.
Refer to the **KI Color Addendum** or **KI Fabrics & Finishes binder**.



Delivered Pricing	
\$	313
	363
\$	246
	253
\$	491
	496

SPECIAL SERVICES

Special Carton Marking

With specially marked information N/C





Shipping

Ships **knocked down, FOB Manitowoc, WI 54220, freight prepaid.** Freight class 70.

Specifications and prices are subject to change without prior notice.

Activ8® System

Single Circuit Electrical

	MODEL	L	MODEL NUMBER		Approx. Packaged Weight
			Basic Model	Paint Color	
 HRDPT	Activ8® Infeed <ul style="list-style-type: none"> Infeed only (cover sold separately) 108" cord plugs into standard 15 amp outlet Control module is located 12" from table connection Diagnostic LED indicator shows power status (see details below) Controller automatically limits number of connections to 8 40 Ft maximum string, not including infeed cord Will not work with GFI/GCFI outlets 		AC8IF.108		2.0#
 HRDPT	Trellis Infeed Cover <ul style="list-style-type: none"> Cover only (infeed sold separately) For use with Activ8 infeed For use as a data infeed cover 	24"	48.6032.24	<input type="checkbox"/>	1.0#
		30"	48.6032.30	<input type="checkbox"/>	1.0#
 HRDPT	Activ8® Module and Attachment Bracket <ul style="list-style-type: none"> Duplex receptacles provide 2 outlets Power module provides 15 amp power Up to 8 modules may be used per infeed per UL Standard 962 Modules may be connected (reconnected in any order without sequential keying) Jumpers ordered separately Attached cord is approximately 9" 		AC8RPTTR.12		1.0#
 HRDPT	Activ8® Jumper <ul style="list-style-type: none"> Refer to Trellis Planning Guide for size recommendations Jumpers are all keyed alike 	29"	AC8JP.29		1.0#
		53"	AC8JP.53		1.0#
		77"	AC8JP.77		1.0#
		101"	AC8JP.101		1.0#

A

B

HOW TO ORDER

Indicate the following information on order form:

- Quantity of each item.
- Model number, including options. See "How To Build a Model Number".
- Any special service required.

Note: • The ☐ indicates that a choice is required.

- The absence of the ☐ indicates that no choice is required.

- Alpha-numeric characters in place of ☐ indicate that no other alternatives are available.

HOW TO BUILD A MODEL NUMBER

A Select basic model.

B Select paint color.
Refer to the **KI Color Addendum** or **KI Fabrics & Finishes binder**



Delivered Pricing	
\$	209
\$	91
	100
\$	132
\$	66
	77
	88
	93

SPECIAL SERVICES

Special Carton Marking

With specially marked information N/C

Shipping

Shipped **k.d. FOB Bonduel, WI 54107, freight prepaid.** Freight class #85.

Covers shipped **k.d. FOB Manitowoc, WI 54220, freight prepaid.** Freight class #85.

Specifications and prices are subject to change without prior notice.

Index

Model No.	Description	Page
48.6032.24	Single Circuit Electrical: Trellis Infeed Cover	18
AC8IF.108	Single Circuit Electrical: Activ8® Infeed	18
AC8JP.29	Single Circuit Electrical: Activ8® Jumper	18
AC8RPTTR.12	Single Circuit Electrical: Activ8® Module and Attachment Bracket	18
TRDBM24	Receptacles and Jumpers: Middle Data Base Infeeds; Hardwire	16
TRDIT24	Receptacles and Jumpers: Top Data Infeeds; Hardwire	16
TRDTM24	Receptacles and Jumpers: Middle Data; Hardwire Top Infeeds	16
TRER24	End-of-run Cover	8
TRFT2W12024	Trellis Corner Connector 120° 2-Way	8
TRFT2W9024	Trellis Corner Connector 90° 2-way	10
TRFT3W120	Trellis Corner Connector 120° 3-Way	8
TRFT3W9024	Trellis Corner Connector 90° 3-Way	10
TRFT4W90	Trellis Corner Connector 90° 4-Way	10
TRFTINL	Trellis Inline Foot	8
TRIB24	Receptacles, Jumpers and Infeeds: Base Infeed; 10-wire/6 Circuit	12
TRIBM24	Receptacles, Jumpers and Infeeds: Middle Base Infeed; 10-wire/6 Circuit	14
TRIT24	Receptacles, Jumpers and Infeeds: Top Infeed; 10-wire/6 Circuit	12
TRITM24	Receptacles, Jumpers and Infeeds: Middle Top Infeed; 10-wire/6 Circuit	14
TRJP.TJ	Receptacles, Jumpers and Infeeds: Electrical Chase-to-Chase Jumpers; 10-wire/6 Circuit	12
TRLI2424	Laminate Inserts: Laminate Insert 24"H	4
TRLI2430	Laminate Inserts: Laminate Insert 30"H	4
TRRECP.1	Receptacles, Jumpers and Infeeds: 15-Amp Duplex Receptacle for Raceway Use; 10-wire/6 Circuit	12
TRSI2424	Steel Inserts: Steel Insert 24"H	6
TRSI2430	Steel Inserts: Steel Insert 30"H	6



A series of horizontal lines of varying lengths, creating a striped effect on the left side of the page.

KI
1330 Bellevue Street
P.O. Box 8100
Green Bay, Wisconsin 54308-8100
1-800-424-2432
www.ki.com

KI and Furnishing Knowledge
are registered trademarks
of Krueger International, Inc.

© 2014 Krueger International, Inc.
All Rights Reserved.
Code KI-11610/KI/PDF/1114