

#### PRODUCT DESCRIPTION

SAF-T-STEP Slip-Resistant Cleaner Treatment is formulated for quarry, ceramic, and concrete floors. It is used full strength or diluted to remove both the grease deposits and silica stains restoring the stone floor surface to its original slip-resistant condition. Excellent for use on floors in restaurants, fast food and foodservice operations, industrial plants, school shower rooms and anywhere else that slips and falls are a problem. Follow all directions carefully.

#### PRECAUTIONS:

Contains anionic and nonionic surfactants, citric acid, hydroxyacetic acid, propylene series glycol ether and unique chelators and sequestrants. **HARMFUL IF SWALLOWED. CONCENTRATE MAY IRRITATE EYES AND SKIN. KEEP OUT OF REACH OF CHILDREN.** Avoid contact with eyes and skin. Do not take internally. Never use or mix with other cleaners or chemicals such as chlorine bleaches or ammonia. See Material Safety Data Sheet (MSDS) for specific information.

#### FIRST AID:

**EYES:** Rinse immediately with water. Remove contact lenses, then flush eyes with water for 10-15 minutes. **SKIN:** Flush with water for 10-15 minutes. **SWALLOWED:** Rinse mouth. Drink glass of milk or water. Do not induce vomiting. **CALL PHYSICIAN IMMEDIATELY.** Give physician information from MSDS.

**CAUTION:** The use of SAF-T-STEP full strength is not recommended on glazed or highly polished stone floors unless a duller surface is acceptable. Since floor compositions differ greatly among manufacturers it is always a good idea to test on a small inconspicuous area for appearance **PRIOR** to full applications. Light discoloration or dulling is rare, but can occur. Do not allow to remain on aluminum, marble or painted surfaces.



U.S. Coating Specialties & Supplies

# SAF-T-STEP

## Slip-Resistant Cleaner & Treatment

Contains Kalisite®

*Solely for Industrial Use*

Keep Out Of Reach Of Children

MANUFACTURED FOR  
U.S.COATING SPECIALTIES & SUPPLIES  
JACKSON, MS 39283-1809  
(601) 981-8986

NET 5 U.S. GALLONS

#### SHOCK AND SLIP TREATMENT PROCEDURES:

Use SAF-T-STEP full strength whenever floor surface is out of control with heavy stains or grease build-ups. One (1) gallon will effectively shock clean and slip treat approximately 400-500 sq. ft. of floor surface. This procedure is only necessary when extreme conditions exist. Newly installed floor surfaces or lightly soiled surfaces should **NOT** be shock treated.

#### DAILY SLIP TREATMENT AND CLEANING PROCEDURES

Add sixteen (16) ounces of SAF-T-STEP to a mop bucket with four gallons of warm water to adequately clean, degrease and slip treat approximately 1200 sq. ft. of floor area daily. For extreme conditions when mineral and silica stains form follow the SHOCK AND SLIP TREATMENT PROCEDURES.

**NOTE:** If a regular degreaser is used for daily cleaning of floors instead of SAF-T-STEP then follow the same four (4) step procedure below and increase frequency of the SHOCK AND SLIP TREATMENT to about once or twice monthly to remove mineral and silica stains.

#### GENERAL APPLICATION

1. **APPLY** evenly onto floor from container, mop bucket or foam sprayer after sweeping & removing debris from floor. Use stiff bristle brush to spread evenly. Leave on floor five minutes.
2. **SCRUB** floor vigorously with stiff bristle brush paying special attention to grout lines and heavy grease or stain area. Squeegee residues into drain or proceed to rinse step.
3. **RINSE** or hose down floor thoroughly with clean water after scrubbing and removing residues. Hose toward drains.
4. **SQUEEGEE** the remaining water and residue into floor drains and allow floor to dry. When floor drains not available, then mop up or wet vacuum water from floor and properly discard.

Apply



Scrub



Rinse



Squeegee

