Product Safety Data Sheet

SDS # : 21-00720
2021-07-09
Revision 2

Xerox EC8036

Product Description / Product Identifier	Multifunction Equipment J-A330 J-B330
Speed (PPM)	35
Mono / Color	Color

ELECTRICAL INPUT INFORMATION

Voltage (Volts)	**110V-127V**	**220V-240V**
Rated Current (Amperes)	12/16	8/10
Frequency (Hertz)	50/60	50/60
Phase Connection	single	single

POWER AND HEAT

	Power (Watts)	**Heat Output (BTU/Hr)**	**Power (Watts)**	**Heat Output (BTU/Hr)**
Active [1]	610	2081.3	620	2115.4
Ready[1]	55	187.7	55	187.7
Sleep[1]	40	136.5	40	136.5
Sleep (2)[1]	1.1	3.75	1.3	4.4
Standby[1] (Off/FEMP) [2]	0.1	0.341	0.4	1.365

[1] Power states defined per ENERGY STAR Program requirements for Imaging Equipment
[2] FEMP - Federal Energy Management Program
Note: The electrical power information provided should not be used to define the electrical support required for this product. Consult your Xerox representative if you require detailed information.

OPERATING ENVIRONMENT

Relative Humidity %	15-85%		
Ambient Temperature	50-90 °F	/	10-32 °C

PRODUCT SIZE

Depth	28.9 in.	73.4 cm
Width	43.6 in.	110.7 cm
Height	45.2 in.	114.8 cm
Weight	275.5 lbs	125 kg

SPACE REQUIREMENTS

Refer to Installation Planning Guide
For additional information regarding different configurations please contact your local sales representative.

LIGHT SOURCE

LED

Chemical Emission Test Method RAL-UZ171
The machine was tested under the conditions as specified in the standard inside a room of 57.5 m^3 with 2 air changes per hour.

PARAMETER	**Color Emission Rate**	**Monochrome Emission Rate**
TVOC	2.97 mg/h	1.4 mg/h
Dust	0.142 mg/h	0.194 mg/h
Ozone	0.167 mg/h	0.132 mg/h
Styrene	0.0413 mg/h	0.028 mg/h
Benzene	0.014 mg/h	0.009 mg/h

Product Safety Data Sheet

ACOUSTICAL NOISE

Tested in accordance to ISO 7779 and declared per ISO 9296

	Sound Power Level LwAd (B)	Sound Pressure Level LpAd (dBA)
Standby	3.32	15.3
Run	6.42	47.2

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

Inquiries U.S. Only: 1-800-275-9376
Contact U.S. Only: askxerox@xerox.com
Contact Non-U.S. Only: ehs-europe@xerox.com