Product Safety Data Sheet

SDS # : 21-00722
2021-07-14
Revision 2.01

Xerox® B225 Multifunction Printer

Product Description	Multifunction Equipment 3400-4e1
Speed (PPM)	36
Mono / Color	Monochrome

ELECTRICAL INPUT INFORMATION

Voltage (Volts)	**110V-127V**	**220V-240V**
Rated Current (Amperes)	7.0	3.5
Frequency (Hertz)	50/60	50/60
Phase Connection	single	single

POWER AND HEAT

	Power (Watts)	**Heat Output (BTU/Hr)**	**Power (Watts)**	**Heat Output (BTU/Hr)**
Active [1]	454	1549	454	1549
Ready[1]	5.2	17.7	5.1	17.4
Sleep[1]	1.19	4.06	1.23	4.20
Standby[1] (Off/FEMP) [2]	0.03	0.10	0.6	0.20

[1] Power states defined per ENERGY STAR Program requirements for Imaging Equipment
[2] FEMP - Federal Energy Management Program
Note: The electrical power information provided should not be used to define the electrical support required for this product. Consult your Xerox representative if you require detailed information.

OPERATING ENVIRONMENT

Relative Humidity %	10-85%		
Ambient Temperature	50-90 °F	/	10-32 °C

PRODUCT SIZE

Depth	16.5 in.	42.0 cm
Width	14.7 in.	37.3 cm
Height	13.5 in.	34.3 cm
Weight	25.6 lbs	11.6 kg

SPACE REQUIREMENTS

Refer to Users Guide
For additional information regarding different configurations please contact your local sales representative.

LIGHT SOURCE

Class 1 Laser Product

Chemical Emission Test Method RAL - UZ205
The machine was tested under the conditions as specified in the standard inside a room of 2.0 m^3 with 4.0 air changes per hour.

PARAMETER	**Emission Rate**
TVOC	5.6 mg/h
Dust	0.84 mg/h
Ozone	<0.23 mg/h
Styrene	0.06 mg/h
Benzene	0.02 mg/h

Product Safety Data Sheet

ACOUSTICAL NOISE

Tested in accordance to ISO 7779 and declared per ISO 9296

	Sound Power Level LwAd (dBA)	Sound Pressure Level LpAd (dBA)
Run	67.0	--

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

Inquiries U.S. Only: 1-800-275-9376
Contact U.S. Only: askxerox@xerox.com
Contact Non-U.S. Only: ehs-europe@xerox.com