


## Glass Tiles

1-High

Pricing

GSA SIN 711-1



| <i>W</i>             | <i>H</i>                          | <b>Clear or Frosted</b><br><i>Model</i> | <i>Price</i> | <b>Linear-Vertical</b><br><i>Model</i> | <i>Price</i> |
|----------------------|-----------------------------------|-----------------------------------------|--------------|----------------------------------------|--------------|
| <b>Painted Frame</b> |                                   |                                         |              |                                        |              |
| 18"                  | 11 <sup>7</sup> / <sub>16</sub> " | <b>36P181ITGAP</b>                      | \$337        | <b>36P181ITGBP</b>                     | \$386        |
| 24"                  |                                   | <b>36P241ITGAP</b>                      | 367          | <b>36P241ITGBP</b>                     | 439          |
| 30"                  |                                   | <b>36P301ITGAP</b>                      | 393          | <b>36P301ITGBP</b>                     | 489          |
| 33"                  |                                   | <b>36P331ITGAP</b>                      | 406          | <b>36P331ITGBP</b>                     | 512          |
| 36"                  |                                   | <b>36P361ITGAP</b>                      | 419          | <b>36P361ITGBP</b>                     | 534          |
| 39"                  |                                   | <b>36P391ITGAP</b>                      | 444          | <b>36P391ITGBP</b>                     | 570          |
| 42"                  |                                   | <b>36P421ITGAP</b>                      | 467          | <b>36P421ITGBP</b>                     | 607          |
| 48"                  |                                   | <b>36P481ITGAP</b>                      | 504          | <b>36P481ITGBP</b>                     | 660          |
| <b>Wood Frame</b>    |                                   |                                         |              |                                        |              |
| 18"                  | 11 <sup>7</sup> / <sub>16</sub> " | <b>36P181ITGAW</b>                      | \$847        | <b>36P181ITGBW</b>                     | \$967        |
| 24"                  |                                   | <b>36P241ITGAW</b>                      | 909          | <b>36P241ITGBW</b>                     | 1088         |
| 30"                  |                                   | <b>36P301ITGAW</b>                      | 971          | <b>36P301ITGBW</b>                     | 1207         |
| 33"                  |                                   | <b>36P331ITGAW</b>                      | 1004         | <b>36P331ITGBW</b>                     | 1266         |
| 36"                  |                                   | <b>36P361ITGAW</b>                      | 1037         | <b>36P361ITGBW</b>                     | 1322         |
| 39"                  |                                   | <b>36P391ITGAW</b>                      | 1098         | <b>36P391ITGBW</b>                     | 1411         |
| 42"                  |                                   | <b>36P421ITGAW</b>                      | 1158         | <b>36P421ITGBW</b>                     | 1499         |
| 48"                  |                                   | <b>36P481ITGAW</b>                      | 1247         | <b>36P481ITGBW</b>                     | 1631         |

Specify one glass tile to complete both sides of frame.

Power and data cables cannot be routed through glass tiles.

Specify a 33"W tile for use about a 36"W hinged door or a 39"W tile for use about a 42"W hinged door.

|                          |                |
|--------------------------|----------------|
| Overview                 | ➤ See page 116 |
| Traxx and Tiles Overview | 137            |
| Product Information      | 142            |
| Traxx Pricing            | 198            |

### Standard Includes

- One frame with glass
- One frame without glass
- Locking clip

### How to Specify


- ① Model
- ② Glass type:
  - 3** = Clear
  - 9** = Frosted
  - 8** = Linear-Vertical
- ③ Finish type:
  - STD** = Group 1
  - STD<sub>M</sub>** = Group M (+10%)
  - STD<sub>2</sub>** = Group 2 (+20%)
- ④ Finish designator

## Glass Tiles

1.5-High

Pricing

GSA SIN 711-1



| <i>W</i>             | <i>H</i>                         | <b>Clear or Frosted</b><br><i>Model</i> | <i>Price</i> | <b>Linear-Vertical</b><br><i>Model</i> | <i>Price</i> |
|----------------------|----------------------------------|-----------------------------------------|--------------|----------------------------------------|--------------|
| <b>Painted Frame</b> |                                  |                                         |              |                                        |              |
| 18"                  | 18 <sup>3</sup> / <sub>8</sub> " | <b>36P18H18ITGAP</b>                    | \$358        | <b>36P18H18ITGBP</b>                   | \$446        |
| 24"                  |                                  | <b>36P24H18ITGAP</b>                    | 383          | <b>36P24H18ITGBP</b>                   | 519          |
| 30"                  |                                  | <b>36P30H18ITGAP</b>                    | 404          | <b>36P30H18ITGBP</b>                   | 580          |
| 36"                  |                                  | <b>36P36H18ITGAP</b>                    | 436          | <b>36P36H18ITGBP</b>                   | 648          |
| 42"                  |                                  | <b>36P42H18ITGAP</b>                    | 496          | <b>36P42H18ITGBP</b>                   | 745          |
| 48"                  |                                  | <b>36P48H18ITGAP</b>                    | 528          | <b>36P48H18ITGBP</b>                   | 817          |
| <b>Wood Frame</b>    |                                  |                                         |              |                                        |              |
| 18"                  | 18 <sup>3</sup> / <sub>8</sub> " | <b>36P18H18ITGAW</b>                    | \$892        | <b>36P18H18ITGBW</b>                   | \$1115       |
| 24"                  |                                  | <b>36P24H18ITGAW</b>                    | 948          | <b>36P24H18ITGBW</b>                   | 1290         |
| 30"                  |                                  | <b>36P30H18ITGAW</b>                    | 1005         | <b>36P30H18ITGBW</b>                   | 1437         |
| 36"                  |                                  | <b>36P36H18ITGAW</b>                    | 1083         | <b>36P36H18ITGBW</b>                   | 1603         |
| 42"                  |                                  | <b>36P42H18ITGAW</b>                    | 1227         | <b>36P42H18ITGBW</b>                   | 1847         |
| 48"                  |                                  | <b>36P48H18ITGAW</b>                    | 1307         | <b>36P48H18ITGBW</b>                   | 2019         |

IMPORTANT 1.5-high tile is only for use with 3.5-high frame. 1.5-high tile must be installed above worksurface height (top position).

➤ See page 138 for specific location.

Specify one glass tile to complete both sides of frame.

Power and data cables cannot be routed through glass tiles.

|                          |                |
|--------------------------|----------------|
| Overview                 | ➤ See page 116 |
| Traxx and Tiles Overview | 137            |
| Product Information      | 142            |
| Traxx Pricing            | 198            |

### Standard Includes

- One frame with glass
- One frame without glass
- Locking clip

### How to Specify


- ① Model
- ② Glass type:
  - 3** = Clear
  - 9** = Frosted
  - 8** = Linear-Vertical
- ③ Finish type:
  - STD** = Group 1
  - STD M** = Group M (+10%)
  - STD2** = Group 2 (+20%)
- ④ Finish designator

## Glass Tiles

2-High

Pricing

GSA SIN 711-1



| <i>W</i>             | <i>H</i> | <b>Clear or Frosted</b><br><i>Model</i> | <i>Price</i> | <b>Linear-Vertical</b><br><i>Model</i> | <i>Price</i> |
|----------------------|----------|-----------------------------------------|--------------|----------------------------------------|--------------|
| <b>Painted Frame</b> |          |                                         |              |                                        |              |
| 18"                  | 24 1/16" | <b>36P182ITGAP</b>                      | \$420        | <b>36P182ITGBP</b>                     | \$525        |
| 24"                  |          | <b>36P242ITGAP</b>                      | 450          | <b>36P242ITGBP</b>                     | 612          |
| 30"                  |          | <b>36P302ITGAP</b>                      | 477          | <b>36P302ITGBP</b>                     | 681          |
| 36"                  |          | <b>36P362ITGAP</b>                      | 514          | <b>36P362ITGBP</b>                     | 763          |
| 42"                  |          | <b>36P422ITGAP</b>                      | 583          | <b>36P422ITGBP</b>                     | 877          |
| 48"                  |          | <b>36P482ITGAP</b>                      | 620          | <b>36P482ITGBP</b>                     | 960          |
| <b>Wood Frame</b>    |          |                                         |              |                                        |              |
| 18"                  | 24 1/16" | <b>36P182ITGAW</b>                      | \$1049       | <b>36P182ITGBW</b>                     | \$1311       |
| 24"                  |          | <b>36P242ITGAW</b>                      | 1115         | <b>36P242ITGBW</b>                     | 1516         |
| 30"                  |          | <b>36P302ITGAW</b>                      | 1180         | <b>36P302ITGBW</b>                     | 1689         |
| 36"                  |          | <b>36P362ITGAW</b>                      | 1275         | <b>36P362ITGBW</b>                     | 1888         |
| 42"                  |          | <b>36P422ITGAW</b>                      | 1442         | <b>36P422ITGBW</b>                     | 2171         |
| 48"                  |          | <b>36P482ITGAW</b>                      | 1538         | <b>36P482ITGBW</b>                     | 2374         |

Specify one glass tile to complete both sides of frame.

Power and data cables cannot be routed through glass tiles.

|                          |                |
|--------------------------|----------------|
| Overview                 | ➤ See page 116 |
| Traxx and Tiles Overview | 137            |
| Product Information      | 142            |
| Traxx Pricing            | 198            |

### Standard Includes

- One frame with glass
- One frame without glass
- Locking clip

### How to Specify


- ① Model
- ② Glass type:
  - 3** = Clear
  - 9** = Frosted
  - 8** = Linear-Vertical
- ③ Finish type:
  - STD** = Group 1
  - STD M** = Group M (+10%)
  - STD2** = Group 2 (+20%)
- ④ Finish designator

## Glass Tiles

Pricing

3-High

GSA SIN 711-1



| <i>W</i>             | <i>H</i>                         | <b>Clear or Frosted</b><br><i>Model</i> | <i>Price</i> | <b>Linear-Vertical</b><br><i>Model</i> | <i>Price</i> |
|----------------------|----------------------------------|-----------------------------------------|--------------|----------------------------------------|--------------|
| <b>Painted Frame</b> |                                  |                                         |              |                                        |              |
| 18"                  | 36 <sup>5</sup> / <sub>8</sub> " | <b>36P183ITGAP</b>                      | \$505        | <b>36P183ITGBP</b>                     | \$705        |
| 24"                  |                                  | <b>36P243ITGAP</b>                      | 534          | <b>36P243ITGBP</b>                     | 784          |
| 30"                  |                                  | <b>36P303ITGAP</b>                      | 557          | <b>36P303ITGBP</b>                     | 872          |
| 36"                  |                                  | <b>36P363ITGAP</b>                      | 607          | <b>36P363ITGBP</b>                     | 984          |
| <b>Wood Frame</b>    |                                  |                                         |              |                                        |              |
| 18"                  | 36 <sup>5</sup> / <sub>8</sub> " | <b>36P183ITGAW</b>                      | \$1263       | <b>36P183ITGBW</b>                     | \$1760       |
| 24"                  |                                  | <b>36P243ITGAW</b>                      | 1322         | <b>36P243ITGBW</b>                     | 1937         |
| 30"                  |                                  | <b>36P303ITGAW</b>                      | 1381         | <b>36P303ITGBW</b>                     | 2159         |
| 36"                  |                                  | <b>36P363ITGAW</b>                      | 1499         | <b>36P363ITGBW</b>                     | 2441         |

|                          |                |
|--------------------------|----------------|
| Overview                 | ➤ See page 116 |
| Traxx and Tiles Overview | 137            |
| Product Information      | 142            |
| Traxx Pricing            | 198            |

### Standard Includes

- One frame with glass
- One frame without glass
- Locking clip

### How to Specify

- ① Model
- ② Glass type:
  - 3** = Clear
  - 9** = Frosted
  - 8** = Linear-Vertical
- ③ Finish type:
  - STD** = Group 1
  - STD<sub>M</sub>** = Group M (+10%)
  - STD<sub>2</sub>** = Group 2 (+20%)
- ④ Finish designator

Specify one glass tile to complete both sides of frame.



Power and data cables cannot be routed through glass tiles.

## Pass-Thru Tiles

Pricing

GSA SIN 711-1

| <i>W</i>            | <i>H</i>                          | <i>Segment</i> | <i>Model</i>     | <i>Price</i> |
|---------------------|-----------------------------------|----------------|------------------|--------------|
| <b>2-High Tiles</b> |                                   |                |                  |              |
| 30"                 | 24 <sup>1</sup> / <sub>16</sub> " | 2 H            | <b>36P302ITT</b> | \$345        |
| 36"                 |                                   | 2 H            | <b>36P362ITT</b> | 371          |
| 42"                 |                                   | 2 H            | <b>36P422ITT</b> | 419          |
| 48"                 |                                   | 2 H            | <b>36P482ITT</b> | 448          |
| <b>3-High Tiles</b> |                                   |                |                  |              |
| 30"                 | 36 <sup>5</sup> / <sub>8</sub> "  | 3 H            | <b>36P303ITT</b> | \$403        |
| 36"                 |                                   | 3 H            | <b>36P363ITT</b> | 434          |



Specify one pass-thru tile to complete both sides of frame.

Power and data cables cannot be routed through pass-thru tiles.

|                          |                |
|--------------------------|----------------|
| Overview                 | ➤ See page 116 |
| Traxx and Tiles Overview | 137            |
| Product Information      | 142            |
| Traxx Pricing            | 198            |

### Standard Includes

- Two frames
- Locking clip

### How to Specify


- ① Model
- ② Finish type:  
**STD** = Group 1  
**STD M** = Group M (+10%)
- ③ Finish designator

## Metal Tiles


## Pricing

.5-High and 1-High

GSA SIN 711-1



Embossed shown



| <i>W</i>             | <i>H</i>                          | <i>Model</i>       | <i>Price</i> |
|----------------------|-----------------------------------|--------------------|--------------|
| <b>.5-High Tiles</b> |                                   |                    |              |
| 18"                  | 5 <sup>3</sup> / <sub>4</sub> "   | <b>36P18H06ITM</b> | \$42         |
| 24"                  |                                   | <b>36P24H06ITM</b> | 57           |
| 30"                  |                                   | <b>36P30H06ITM</b> | 71           |
| 36"                  |                                   | <b>36P36H06ITM</b> | 86           |
| 42"                  |                                   | <b>36P42H06ITM</b> | 98           |
| 48"                  |                                   | <b>36P48H06ITM</b> | 115          |
| 54"                  |                                   | <b>36P54H06ITM</b> | 127          |
| 60"                  |                                   | <b>36P60H06ITM</b> | 141          |
| 72"                  |                                   | <b>36P72H06ITM</b> | 171          |
| <b>1-High Tiles</b>  |                                   |                    |              |
| 18"                  | 11 <sup>7</sup> / <sub>16</sub> " | <b>36P181ITM</b>   | \$50         |
| 24"                  |                                   | <b>36P241ITM</b>   | 63           |
| 30"                  |                                   | <b>36P301ITM</b>   | 82           |
| 36"                  |                                   | <b>36P361ITM</b>   | 96           |
| 42"                  |                                   | <b>36P421ITM</b>   | 110          |
| 48"                  |                                   | <b>36P481ITM</b>   | 128          |
| 54"                  |                                   | <b>36P541ITM</b>   | 142          |
| 60"                  |                                   | <b>36P601ITM</b>   | 158          |
| 72"                  |                                   | <b>36P721ITM</b>   | 191          |

IMPORTANT .5-high tile is only for use with 3.5-high frame.

➤ See page 138 for specific locations.

Specify tiles for both sides of frame.

|                          |                |
|--------------------------|----------------|
| Overview                 | ➤ See page 116 |
| Traxx and Tiles Overview | 137            |
| Product Information      | 143            |
| Traxx Pricing            | 198            |

### Standard Includes

- Tile: metal

### How to Specify

- ① Model
- ② Metal pattern:  
**A** = Perforated  
**B** = Embossed
- ③ Finish type:  
**STD** = Group 1  
**STD M** = Group M (+10%)
- ④ Finish designator


## Metal Tiles

1.5-High and 2-High


Pricing

GSA SIN 711-1

| <i>W</i>              | <i>H</i>                          | <i>Model</i>       | <i>Price</i> |
|-----------------------|-----------------------------------|--------------------|--------------|
| <b>1.5-High Tiles</b> |                                   |                    |              |
| 18"                   | 18 <sup>3</sup> / <sub>8</sub> "  | <b>36P18H18ITM</b> | \$88         |
| 24"                   |                                   | <b>36P24H18ITM</b> | 108          |
| 30"                   |                                   | <b>36P30H18ITM</b> | 135          |
| 36"                   |                                   | <b>36P36H18ITM</b> | 164          |
| 42"                   |                                   | <b>36P42H18ITM</b> | 190          |
| 48"                   |                                   | <b>36P48H18ITM</b> | 218          |
| 54"                   |                                   | <b>36P54H18ITM</b> | 242          |
| 60"                   |                                   | <b>36P60H18ITM</b> | 270          |
| 72"                   |                                   | <b>36P72H18ITM</b> | 325          |
| <b>2-High Tiles</b>   |                                   |                    |              |
| 18"                   | 24 <sup>1</sup> / <sub>16</sub> " | <b>36P182ITM</b>   | \$101        |
| 24"                   |                                   | <b>36P242ITM</b>   | 128          |
| 30"                   |                                   | <b>36P302ITM</b>   | 158          |
| 36"                   |                                   | <b>36P362ITM</b>   | 191          |
| 42"                   |                                   | <b>36P422ITM</b>   | 224          |
| 48"                   |                                   | <b>36P482ITM</b>   | 257          |
| 54"                   |                                   | <b>36P542ITM</b>   | 288          |
| 60"                   |                                   | <b>36P602ITM</b>   | 319          |
| 72"                   |                                   | <b>36P722ITM</b>   | 382          |



Embossed shown



IMPORTANT 1.5-high tile is only for use with 3.5-high frame.  
➤ See page 138 for specific locations.

Specify tiles for both sides of frame.

|                          |                |
|--------------------------|----------------|
| Overview                 | ➤ See page 116 |
| Traxx and Tiles Overview | 137            |
| Product Information      | 143            |
| Traxx Pricing            | 198            |

### Standard Includes

- Tile: metal

### How to Specify




- ① Model
- ② Metal pattern:  
**A** = Perforated  
**B** = Embossed
- ③ Finish type:  
**STD** = Group 1  
**STD M** = Group M (+10%)
- ④ Finish designator

## Marker Board Tiles

Pricing

.5-High, 1-High, and 1.5-High

GSA SIN 711-1



| <i>W</i>              | <i>H</i> | <i>Model</i>      | <i>Metal †</i> | <i>Laminate</i> |
|-----------------------|----------|-------------------|----------------|-----------------|
| <b>.5-High Tiles</b>  |          |                   |                |                 |
| 30"                   | 5¾"      | <b>36P30H06IT</b> | —              | \$104           |
| 36"                   |          | <b>36P36H06IT</b> | —              | 127             |
| 42"                   |          | <b>36P42H06IT</b> | —              | 149             |
| 48"                   |          | <b>36P48H06IT</b> | —              | 169             |
| <b>1-High Tiles</b>   |          |                   |                |                 |
| 30"                   | 11⅞"     | <b>36P301IT</b>   | \$116          | \$118           |
| 36"                   |          | <b>36P361IT</b>   | 140            | 142             |
| 42"                   |          | <b>36P421IT</b>   | 165            | 167             |
| 48"                   |          | <b>36P481IT</b>   | 187            | 189             |
| <b>1.5-High Tiles</b> |          |                   |                |                 |
| 30"                   | 18⅜"     | <b>36P30H18IT</b> | \$200          | \$202           |
| 36"                   |          | <b>36P36H18IT</b> | 240            | 242             |
| 42"                   |          | <b>36P42H18IT</b> | 278            | 280             |
| 48"                   |          | <b>36P48H18IT</b> | 322            | 324             |
| 54"                   |          | <b>36P54H18IT</b> | 359            | 361             |
| 60"                   |          | <b>36P60H18IT</b> | 400            | 402             |

**IMPORTANT** .5-high and 1.5-high tiles are only for use with 3.5-high frame.

➤ See page 138 for specific locations.

Specify tiles for both sides of frame.

Marker board tiles should not be used on unsupported runs due to panel movement when writing on the surface.

Expo or Expo2 dry erase markers are recommended for use on marker boards. Low-odor dry erase markers are not recommended, as they may leave undesirable results when erased.

|                          |                |
|--------------------------|----------------|
| Overview                 | ➤ See page 116 |
| Traxx and Tiles Overview | 137            |
| Product Information      | 144            |
| Traxx Pricing            | 198            |

### Standard Includes

- Tile: painted metal or laminate

### How to Specify

#### Metal Marker Board Tile

- ① Model
- ② Tile material:  
**MP** = Metal
- ③ Finish designator:  
**405M** = Designer White

#### Laminate Marker Board Tile



- ① Model
- ② Tile material:  
**K** = Laminate
- ③ Finish designator:  
**409M** = Icy White  
**483M** = Off White

## Marker Board Tiles

Pricing

2-High and 3-High

GSA SIN 711-1



| <i>W</i>            | <i>H</i>                          | <i>Model</i>    | <i>Metal †</i> | <i>Laminate</i> |
|---------------------|-----------------------------------|-----------------|----------------|-----------------|
| <b>2-High Tiles</b> |                                   |                 |                |                 |
| 30"                 | 24 <sup>1</sup> / <sub>16</sub> " | <b>36P302IT</b> | \$236          | \$238           |
| 36"                 |                                   | <b>36P362IT</b> | 280            | 283             |
| 42"                 |                                   | <b>36P422IT</b> | 325            | 329             |
| 48"                 |                                   | <b>36P482IT</b> | 362            | 380             |
| 54"                 |                                   | <b>36P542IT</b> | 423            | 425             |
| 60"                 |                                   | <b>36P602IT</b> | 469            | 472             |
| <b>3-High Tiles</b> |                                   |                 |                |                 |
| 30"                 | 36 <sup>5</sup> / <sub>8</sub> "  | <b>36P303IT</b> | \$351          | \$356           |
| 36"                 |                                   | <b>36P363IT</b> | 416            | 425             |
| 42"                 |                                   | <b>36P423IT</b> | —              | 495             |
| 48"                 |                                   | <b>36P483IT</b> | —              | 569             |
| 54"                 |                                   | <b>36P543IT</b> | —              | 636             |
| 60"                 |                                   | <b>36P603IT</b> | —              | 707             |

Specify tiles for both sides of frame.

Marker board tiles should not be used on unsupported runs due to panel movement when writing on the surface.

Expo or Expo2 dry erase markers are recommended for use on marker boards. Low-odor dry erase markers are not recommended, as they may leave undesirable results when erased.

|                          |                |
|--------------------------|----------------|
| Overview                 | ➤ See page 116 |
| Traxx and Tiles Overview | 137            |
| Product Information      | 144            |
| Traxx Pricing            | 198            |

### Standard Includes

- Tile: painted metal or laminate

### How to Specify

#### Metal Marker Board Tile

- ① Model
- ② Tile material:  
**MP** = Metal
- ③ Finish designator:  
**405M** = Designer White

#### Laminate Marker Board Tile




- ① Model
- ② Tile material:  
**K** = Laminate
- ③ Finish designator:  
**409M** = Ikey White  
**483M** = Off White

## Slat Tiles

## Pricing

.5-High, 1-High, and 1.5-High

GSA SIN 711-1



IMPORTANT .5 and 1.5-high tiles are for only use with 3.5-high frame.  
➤ See page 138 for specific locations.

Specify tiles for both sides of frame.

Monitor arms can be used on 18", 24", and 30"W 1-high and 2-high slat tiles. 2-high tiles require an additional mid-frame support for stability, specified separately. One single monitor arm per slat tile can be accommodated.

Work tools and monitor arms  
➤ See the Perks Price List.

| W                     | H                                 | Model              | Price |
|-----------------------|-----------------------------------|--------------------|-------|
| <b>.5-High Tiles</b>  |                                   |                    |       |
| 18"                   | 5 <sup>3</sup> / <sub>4</sub> "   | <b>36P18H06ITS</b> | \$191 |
| 24"                   |                                   | <b>36P24H06ITS</b> | 242   |
| 30"                   |                                   | <b>36P30H06ITS</b> | 302   |
| 36"                   |                                   | <b>36P36H06ITS</b> | 363   |
| 42"                   |                                   | <b>36P42H06ITS</b> | 424   |
| 48"                   |                                   | <b>36P48H06ITS</b> | 484   |
| <b>1-High Tiles</b>   |                                   |                    |       |
| 18"                   | 11 <sup>7</sup> / <sub>16</sub> " | <b>36P181ITS</b>   | \$215 |
| 24"                   |                                   | <b>36P241ITS</b>   | 272   |
| 30"                   |                                   | <b>36P301ITS</b>   | 341   |
| 36"                   |                                   | <b>36P361ITS</b>   | 409   |
| 42"                   |                                   | <b>36P421ITS</b>   | 477   |
| 48"                   |                                   | <b>36P481ITS</b>   | 545   |
| <b>1.5-High Tiles</b> |                                   |                    |       |
| 18"                   | 18 <sup>3</sup> / <sub>8</sub> "  | <b>36P18H18ITS</b> | \$351 |
| 24"                   |                                   | <b>36P24H18ITS</b> | 463   |
| 30"                   | 18 <sup>3</sup> / <sub>8</sub> "  | <b>36P30H18ITS</b> | 579   |
| 36"                   |                                   | <b>36P36H18ITS</b> | 696   |
| 42"                   |                                   | <b>36P42H18ITS</b> | 810   |
| 48"                   |                                   | <b>36P48H18ITS</b> | 926   |

|                          |                |
|--------------------------|----------------|
| Overview                 | ➤ See page 116 |
| Traxx and Tiles Overview | 137            |
| Product Information      | 144            |
| Traxx Pricing            | 198            |

### Standard Includes

- Slat tile
- Two trim channels

### How to Specify

- ① Model
- ② Finish type:  
**STD** = Group 1  
**STDM** = Group M (+10%)
- ③ Finish designator



## Slat Tiles

2-High and 3-High

Pricing

GSA SIN 711-1

| <i>W</i>            | <i>H</i>                          | <i>Model</i>     | <i>Price</i> |
|---------------------|-----------------------------------|------------------|--------------|
| <b>2-High Tiles</b> |                                   |                  |              |
| 18"                 | 24 <sup>1</sup> / <sub>16</sub> " | <b>36P182ITS</b> | \$413        |
| 24"                 |                                   | <b>36P242ITS</b> | 545          |
| 30"                 |                                   | <b>36P302ITS</b> | 680          |
| 36"                 |                                   | <b>36P362ITS</b> | 819          |
| 42"                 |                                   | <b>36P422ITS</b> | 953          |
| 48"                 |                                   | <b>36P482ITS</b> | 1090         |
| <b>3-High Tiles</b> |                                   |                  |              |
| 18"                 | 36 <sup>5</sup> / <sub>8</sub> "  | <b>36P183ITS</b> | \$614        |
| 24"                 |                                   | <b>36P243ITS</b> | 819          |
| 30"                 |                                   | <b>36P303ITS</b> | 1021         |
| 36"                 |                                   | <b>36P363ITS</b> | 1227         |
| 42"                 |                                   | <b>36P423ITS</b> | 1430         |
| 48"                 |                                   | <b>36P483ITS</b> | 1633         |



Specify tiles for both sides of frame.

Monitor arms can be used on 18", 24", and 30"W 1-high and 2-high slat tiles. 2-high tiles require an additional mid-frame support for stability, specified separately. One single monitor arm per slat tile can be accommodated.

Work tools and monitor arms  
➤ See the Perks Price List.

|                          |                |
|--------------------------|----------------|
| Overview                 | ➤ See page 116 |
| Traxx and Tiles Overview | 137            |
| Product Information      | 144            |
| Traxx Pricing            | 198            |

### Standard Includes

- Slat tile
- Two trim channels


### How to Specify

- ① Model
- ② Finish type:  
**STD** = Group 1  
**STD M** = Group M (+10%)
- ③ Finish designator


## Storage and Fold-Down Tiles

Pricing

GSA SIN 711-1



| <i>W</i>                    | <i>H</i>                          | <i>Model</i>     | <i>Price</i> |
|-----------------------------|-----------------------------------|------------------|--------------|
| <b>1-High Storage Tiles</b> |                                   |                  |              |
| 18"                         | 11 <sup>7</sup> / <sub>16</sub> " | <b>36P181ITR</b> | \$208        |
| 24"                         |                                   | <b>36P241ITR</b> | 249          |
| 30"                         |                                   | <b>36P301ITR</b> | 293          |
| 36"                         |                                   | <b>36P361ITR</b> | 336          |



|                               |                                   |                  |       |
|-------------------------------|-----------------------------------|------------------|-------|
| <b>1-High Fold-Down Tiles</b> |                                   |                  |       |
| 18"                           | 11 <sup>7</sup> / <sub>16</sub> " | <b>36P181ITF</b> | \$654 |
| 24"                           |                                   | <b>36P241ITF</b> | 732   |
| 30"                           |                                   | <b>36P301ITF</b> | 864   |
| 36"                           |                                   | <b>36P361ITF</b> | 938   |

Specify tiles for both sides of frame.

Storage tiles cannot be placed back to back, or back to back with a technology tile or power/data tile.

Can only be installed in the 2nd segment or above.

Storage Tile Accessories  
► See page 223.

|                          |                |
|--------------------------|----------------|
| Overview                 | ► See page 116 |
| Traxx and Tiles Overview | 137            |
| Product Information      | 144            |
| Traxx Pricing            | 198            |

### Standard Includes

- Storage or fold-down tile



### How to Specify

- ① Model
- ② Finish type:  
**STD** = Group 1  
**STD M** = Group M (+10%)
- ③ Finish designator

## Storage Tile Accessories

Pricing

GSA SIN 711-1



| <i>D</i>                        | <i>W</i> | <i>H</i> | <i>Model</i>     | <i>Description</i>                                                                             | <i>Price</i> |
|---------------------------------|----------|----------|------------------|------------------------------------------------------------------------------------------------|--------------|
| <b>Web Kit</b>                  |          |          |                  |                                                                                                |              |
|                                 |          |          | <b>36AFTW</b>    | For use in storage tile only. Fits 24", 30" and 36" W storage tiles to hold and display items. | \$50         |
| <b>Fold-Down Accessory Kits</b> |          |          |                  |                                                                                                |              |
| 24"                             | 12"      |          | <b>36A241FDK</b> | For use in existing 24"W storage tile only to provide a fold-down surface.                     | \$499        |
| 30"                             |          |          | <b>36A301FDK</b> | For use in existing 30"W storage tile only                                                     | 545          |
| 36"                             |          |          | <b>36A361FDK</b> | For use in existing 36"W storage tile only                                                     | 592          |

|                          |                |
|--------------------------|----------------|
| Overview                 | ➤ See page 116 |
| Traxx and Tiles Overview | 137            |
| Product Information      | 144            |
| Traxx Pricing            | 198            |

### Standard Includes

- Web kit or accessory kit

### How to Specify

#### Web Kit

- ① Model

#### Fold-Down Accessory Kit

- ① Model
- ② Finish type:  
**STD** = Group 1  
**STD M** = Group M (+10%)
- ③ Finish designator

Storage tiles are specified separately.  
➤ See page 222.




All accessories are field installed.  
➤ See page 145 for planning information.

# Technology Tiles

with Cutouts

Pricing

GSA SIN 711-1



Specify tiles to match the full width of the frame.

Electrical components for technology tiles must be specified separately. Components for Xsite base wireway or power/data tiles are not applicable to technology tiles. Specify hole cover plates for cut-outs that will not be used.

Work tools and monitor arms  
►Perks Price List.

| W                        | H                                 | Cutouts | Model      | Fabric Price Grade |       |       |       |       |
|--------------------------|-----------------------------------|---------|------------|--------------------|-------|-------|-------|-------|
|                          |                                   |         |            | A or COM           | B     | C     | D     | E     |
| 1-High Fabric Tile       |                                   |         |            |                    |       |       |       |       |
| 24"                      | 11 <sup>7</sup> / <sub>16</sub> " | 2       | 36P241ITBA | \$195              | \$200 | \$202 | \$207 | \$214 |
| 30"                      | 11 <sup>7</sup> / <sub>16</sub> " | 3       | 36P301ITBA | 213                | 219   | 222   | 228   | 237   |
| 36"                      | 11 <sup>7</sup> / <sub>16</sub> " | 4       | 36P361ITBA | 224                | 231   | 235   | 242   | 252   |
| 42"                      | 11 <sup>7</sup> / <sub>16</sub> " | 5       | 36P421ITBA | 240                | 248   | 253   | 261   | 273   |
| 48"                      | 11 <sup>7</sup> / <sub>16</sub> " | 6       | 36P481ITBA | 260                | 269   | 275   | 284   | 297   |
|                          |                                   |         |            |                    |       |       |       |       |
| W                        | H                                 | Cutouts | Model      | Price              |       |       |       |       |
| 1-High Marker Board Tile |                                   |         |            |                    |       |       |       |       |
| 24"                      | 11 <sup>7</sup> / <sub>16</sub> " | 2       | 36P241ITBK |                    |       |       |       | \$251 |
| 30"                      | 11 <sup>7</sup> / <sub>16</sub> " | 3       | 36P301ITBK |                    |       |       |       | 276   |
| 36"                      | 11 <sup>7</sup> / <sub>16</sub> " | 4       | 36P361ITBK |                    |       |       |       | 299   |
| 42"                      | 11 <sup>7</sup> / <sub>16</sub> " | 5       | 36P421ITBK |                    |       |       |       | 332   |
| 48"                      | 11 <sup>7</sup> / <sub>16</sub> " | 6       | 36P481ITBK |                    |       |       |       | 373   |
|                          |                                   |         |            |                    |       |       |       |       |
| 1-High Slat Tile         |                                   |         |            |                    |       |       |       |       |
| 24"                      | 11 <sup>7</sup> / <sub>16</sub> " | 2       | 36P241ITBS |                    |       |       |       | \$313 |
| 30"                      | 11 <sup>7</sup> / <sub>16</sub> " | 3       | 36P301ITBS |                    |       |       |       | 366   |
| 36"                      | 11 <sup>7</sup> / <sub>16</sub> " | 4       | 36P361ITBS |                    |       |       |       | 429   |
| 42"                      | 11 <sup>7</sup> / <sub>16</sub> " | 5       | 36P421ITBS |                    |       |       |       | 500   |
| 48"                      | 11 <sup>7</sup> / <sub>16</sub> " | 6       | 36P481ITBS |                    |       |       |       | 565   |

►See chart on page 158 for configuration options.



|                        |               |
|------------------------|---------------|
| Features               | ►See page 116 |
| Product Information    | 156           |
| Circuit Configurations | 160           |
| Electrical Components  | 226           |

## Standard Includes

- Technology Tile

## How to Specify

### Fabric Tile

- ① Model
- ② Finish type:  
STD = Group 1  
STDM = Group M (+10%)
- ③ Finish designator
- ④ Fabric grade
- ⑤ Fabric number

### Slat or Markerboard Tile


- ① Model
- ② Finish type:  
STD = Group 1  
STDM = Group M (+10%)
- ③ Finish designator
- ④ Marker board designator (omit for slat tile):  
409M = Icy White  
483M = Off White

## Technology Tiles


Pricing

Without Cutouts


GSA SIN 711-1



| W                  | H                                 | Model        | Fabric Price Grade |       |       |       |       |
|--------------------|-----------------------------------|--------------|--------------------|-------|-------|-------|-------|
|                    |                                   |              | A or COM           | B     | C     | D     | E     |
| 1-High Fabric Tile |                                   |              |                    |       |       |       |       |
| 24"                | 11 <sup>7</sup> / <sub>16</sub> " | 36P241ITBANC | \$195              | \$200 | \$202 | \$207 | \$214 |
| 30"                | 11 <sup>7</sup> / <sub>16</sub> " | 36P301ITBANC | 213                | 219   | 222   | 228   | 237   |
| 36"                | 11 <sup>7</sup> / <sub>16</sub> " | 36P361ITBANC | 224                | 231   | 235   | 242   | 252   |
| 42"                | 11 <sup>7</sup> / <sub>16</sub> " | 36P421ITBANC | 240                | 248   | 253   | 261   | 273   |
| 48"                | 11 <sup>7</sup> / <sub>16</sub> " | 36P481ITBANC | 260                | 269   | 275   | 284   | 297   |



| W                               | H                                 | Model               | Price |
|---------------------------------|-----------------------------------|---------------------|-------|
| <b>1-High Marker Board Tile</b> |                                   |                     |       |
| 24"                             | 11 <sup>7</sup> / <sub>16</sub> " | <b>36P241ITBKNC</b> | \$251 |
| 30"                             | 11 <sup>7</sup> / <sub>16</sub> " | <b>36P301ITBKNC</b> | 276   |
| 36"                             | 11 <sup>7</sup> / <sub>16</sub> " | <b>36P361ITBKNC</b> | 299   |
| 42"                             | 11 <sup>7</sup> / <sub>16</sub> " | <b>36P421ITBKNC</b> | 332   |
| 48"                             | 11 <sup>7</sup> / <sub>16</sub> " | <b>36P481ITBKNC</b> | 373   |



|                         |                                   |                     |       |
|-------------------------|-----------------------------------|---------------------|-------|
| <b>1-High Slat Tile</b> |                                   |                     |       |
| 24"                     | 11 <sup>7</sup> / <sub>16</sub> " | <b>36P241ITBSNC</b> | \$313 |
| 30"                     | 11 <sup>7</sup> / <sub>16</sub> " | <b>36P301ITBSNC</b> | 366   |
| 36"                     | 11 <sup>7</sup> / <sub>16</sub> " | <b>36P361ITBSNC</b> | 429   |
| 42"                     | 11 <sup>7</sup> / <sub>16</sub> " | <b>36P421ITBSNC</b> | 500   |
| 48"                     | 11 <sup>7</sup> / <sub>16</sub> " | <b>36P481ITBSNC</b> | 565   |

Use these tiles in conjunction with technology tiles with cutouts for a seamless look where power and data are not required.

Specify tiles to match the full width of the frame when pass-thru jumper will be used behind the tile.

Pass-thru jumpers  
➤ See page 230.

Work tools and monitor arms  
➤ Perks Price List.

|                        |                |
|------------------------|----------------|
| Features               | ➤ See page 116 |
| Product Information    | 156            |
| Circuit Configurations | 160            |
| Electrical Components  | 226            |

### Standard Includes

- Technology tile

### How to Specify

#### Fabric Tile

- ① Model
- ② Finish type:  
STD = Group 1  
STDM = Group M (+10%)
- ③ Finish designator
- ④ Fabric grade
- ⑤ Fabric number

#### Slat or Markerboard Tile

- ① Model
- ② Finish type:  
STD = Group 1  
STDM = Group M (+10%)
- ③ Finish designator
- ④ Marker board designator (omit for slat tile):  
409M = Icy White  
483M = Off White

## Technology Tile Electrical Components

Pricing


### Power Kits with Vertical Jumper

GSA SIN 711-1


| For Use<br>with<br>Tile<br>Width | No. of<br>Power<br>Blocks | Max.<br>No. of<br>Duplex<br>per Side | Available<br>No. of<br>Data<br>per Side | Configuration | Model            | Price |
|----------------------------------|---------------------------|--------------------------------------|-----------------------------------------|---------------|------------------|-------|
| <b>Single Power Blocks</b>       |                           |                                      |                                         |               |                  |       |
| 30"                              | 2 single                  | 2                                    | 1                                       |               | <b>36P30EHSV</b> | \$537 |
| 36"                              | 2 single                  | 2                                    | 2                                       |               | <b>36P36EHSV</b> | 569   |
| 42"                              | 2 single                  | 2                                    | 3                                       |               | <b>36P42EHSV</b> | 596   |
| 48"                              | 2 single                  | 2                                    | 4                                       |               | <b>36P48EHSV</b> | 629   |
| <b>Double Power Blocks</b>       |                           |                                      |                                         |               |                  |       |
| 36"                              | 2 double                  | 4                                    | 0                                       |               | <b>36P36EHDV</b> | \$683 |
| 42"                              | 2 double                  | 4                                    | 1                                       |               | <b>36P42EHDV</b> | 712   |
| 48"                              | 2 double                  | 4                                    | 2                                       |               | <b>36P48EHDV</b> | 744   |

**Legend:**

■ = Duplex  
□ = Data



Single-Block Kit



Double-Block Kit

Cover plates can be specified for cut-outs not in use.

Data plates can be specified for any cut-out where there is no power block.

To transition power from base to 4H or 5H, select power kit without a vertical jumper and specify a vertical jumper separately.

Receptacles, data plates, and cover plates

➤ See page 231.

|                        |                |
|------------------------|----------------|
| Features               | ➤ See page 116 |
| Product Information    | 156            |
| Circuit Configurations | 160            |
| Receptacles            | 231            |

### Standard Includes

#### Single-Block Kit:

- Single power block assembly:
  - Two single power blocks: injection-molded, PVC-free plastic
  - Power harness
- Vertical base-to-tile jumper (base to 2H or 3H)
- Mounting brackets and hardware

#### Double-Block Kit:

- Two double power blocks: injection-molded, PVC-free plastic
- Block-to-block jumpers: PVC-free plastic
  - Male-to-male jumper in 36"W kit
  - 8" jumper in 42"W kit
  - 14" jumper in 48"W kit
- Vertical base-to-tile jumper (base to 2H or 3H)
- Mounting brackets and hardware

### How to Specify

- 1 Model

## Technology Tile Electrical Components


Pricing

### Power Kits with Vertical and Horizontal Jumpers


GSA SIN 711-1

| For Use<br>with<br>Tile<br>Width | No. of<br>Power<br>Blocks | Max.<br>No. of<br>Duplex<br>per Side | Available,<br>No. of<br>Data<br>per Side | Configuration | Model             | Price |
|----------------------------------|---------------------------|--------------------------------------|------------------------------------------|---------------|-------------------|-------|
| <b>Single Power Blocks</b>       |                           |                                      |                                          |               |                   |       |
| 30"                              | 2 single                  | 2                                    | 1                                        |               | <b>36P30EHSVH</b> | \$651 |
| 36"                              | 2 single                  | 2                                    | 2                                        |               | <b>36P36EHSVH</b> | 680   |
| 42"                              | 2 single                  | 2                                    | 3                                        |               | <b>36P42EHSVH</b> | 703   |
| 48"                              | 2 single                  | 2                                    | 4                                        |               | <b>36P48EHSVH</b> | 739   |
| <b>Double Power Blocks</b>       |                           |                                      |                                          |               |                   |       |
| 36"                              | 2 double                  | 4                                    | 0                                        |               | <b>36P36EHDVH</b> | \$791 |
| 42"                              | 2 double                  | 4                                    | 1                                        |               | <b>36P42EHDVH</b> | 821   |
| 48"                              | 2 double                  | 4                                    | 2                                        |               | <b>36P48EHDVH</b> | 849   |

**Legend:**  
■ = Duplex  
□ = Data



Single-Block Kit



Double-Block Kit



Cover plates can be specified for cut-outs not in use.

Data plates can be specified for any cut-out where there is no power block.

To transition power from base to 4H or 5H, select power kit without a vertical jumper and specify a vertical jumper separately.

Receptacles, data plates, and cover plates  
➤ See page 231.

|                        |                |
|------------------------|----------------|
| Features               | ➤ See page 116 |
| Product Information    | 156            |
| Circuit Configurations | 160            |
| Receptacles            | 231            |

### Standard Includes

#### Single-Block Kit:

- Single power block assembly:
  - Two single power blocks: injection-molded, PVC-free plastic
  - Power harness
- Horizontal tile-to-tile jumper: PVC-free plastic
- Vertical base-to-tile jumper (base to 2H or 3H)
- Mounting brackets and hardware

#### Double-Block Kit:

- Two double power blocks: injection-molded, PVC-free plastic
- Block-to-block jumpers: PVC-free plastic
  - Male-to-male jumper in 36"W kit
  - 8" jumper in 42"W kit
  - 14" jumper in 48"W kit
- Horizontal tile-to-tile jumper: PVC-free plastic
- Vertical base-to-tile jumper (base to 2H or 3H)
- Mounting brackets and hardware

### How to Specify

- 1 Model

## Technology Tile Electrical Components


Pricing

### Power Kits with Horizontal Jumpers

GSA SIN 711-1

| For Use<br>with<br>Tile<br>Width | No. of<br>Power<br>Blocks | Max.<br>No. of<br>Duplex<br>per Side | Available<br>No. of<br>Data<br>per Side | Configuration | Model           | Price |
|----------------------------------|---------------------------|--------------------------------------|-----------------------------------------|---------------|-----------------|-------|
| <b>Single Power Blocks</b>       |                           |                                      |                                         |               |                 |       |
| 30"                              | 2 single                  | 2                                    | 1                                       |               | <b>36P30EHS</b> | \$305 |
| 36"                              | 2 single                  | 2                                    | 2                                       |               | <b>36P36EHS</b> | 318   |
| 42"                              | 2 single                  | 2                                    | 3                                       |               | <b>36P42EHS</b> | 329   |
| 48"                              | 2 single                  | 2                                    | 4                                       |               | <b>36P48EHS</b> | 341   |
| <b>Double Power Blocks</b>       |                           |                                      |                                         |               |                 |       |
| 24"                              | 1 double                  | 2                                    | 0                                       |               | <b>36P24EDH</b> | 303   |
| 36"                              | 2 double                  | 4                                    | 0                                       |               | <b>36P36EDH</b> | 434   |
| 42"                              | 2 double                  | 4                                    | 1                                       |               | <b>36P42EDH</b> | 476   |
| 48"                              | 2 double                  | 4                                    | 2                                       |               | <b>36P48EDH</b> | 503   |


**Legend:**  
■ = Duplex  
□ = Data



Single-Block Kit



Double-Block Kit



Kits on this page can be used:

- In the middle of a ganged run to jump power to the next tile
- With a ceiling power entry
- With a vertical jumper, specified separately, to transition power from base to 4H or 5H (not applicable to 36P24EDH)
- For hardwire applications

Cover plates can be specified for cut-outs not in use.

Data plates can be specified for any cut-out where there is no power block.

➤ See page 231.

|                        |                |
|------------------------|----------------|
| Features               | ➤ See page 116 |
| Product Information    | 156            |
| Circuit Configurations | 160            |
| Receptacles            | 231            |

### Standard Includes

#### Single-Block Kit:

- Single power block assembly:
  - Two single power blocks: injection-molded, PVC-free plastic
  - Power harness
- Horizontal tile-to-tile jumper: PVC-free plastic
- Mounting brackets and hardware

#### Double-Block Kit:

- One or two double power blocks: injection-molded, PVC-free plastic
- Block-to-block jumpers: PVC-free plastic
  - Male-to-male jumper in 36"W kit
  - 8" jumper in 42"W kit
  - 14" jumper in 48"W kit
- Horizontal tile-to-tile jumper: PVC-free plastic
- Mounting brackets and hardware

### How to Specify

- 1 Model

## Technology Tile Electrical Components

Pricing


Power Kits with Blocks and Harness or Jumper Only

GSA SIN 711-1


| For Use<br>with<br>Tile<br>Width | No. of<br>Power<br>Blocks | Max.<br>No. of<br>Duplex<br>per Side | Available<br>No. of<br>Data<br>per Side | Configuration | Model           | Price |
|----------------------------------|---------------------------|--------------------------------------|-----------------------------------------|---------------|-----------------|-------|
| <b>Single Power Blocks</b>       |                           |                                      |                                         |               |                 |       |
| 30"                              | 2 single                  | 2                                    | 1                                       |               | <b>36P30EHS</b> | \$193 |
| 36"                              | 2 single                  | 2                                    | 2                                       |               | <b>36P36EHS</b> | 204   |
| 42"                              | 2 single                  | 2                                    | 3                                       |               | <b>36P42EHS</b> | 216   |
| 48"                              | 2 single                  | 2                                    | 4                                       |               | <b>36P48EHS</b> | 227   |
| <b>Double Power Blocks</b>       |                           |                                      |                                         |               |                 |       |
| 24"                              | 1 double                  | 2                                    | 0                                       |               | <b>36P24ED</b>  | \$188 |
| 36"                              | 2 double                  | 4                                    | 0                                       |               | <b>36P36EHD</b> | 323   |
| 42"                              | 2 double                  | 4                                    | 1                                       |               | <b>36P42EHD</b> | 374   |
| 48"                              | 2 double                  | 4                                    | 2                                       |               | <b>36P48EHD</b> | 426   |

**Legend:**


■ = Duplex  
□ = Data



Single-Block Kit



Double-Block Kit



Kits on this page can be used:

- At the end of a ganged run
- With a vertical jumper, specified separately, to transition power from base to 4H or 5H in a single-station application (not applicable to 36P24ED)
- With a ceiling power entry in a single-station application
- For hardwire applications

Receptacles, data plates, and cover plates

➤ See page 231.

|                        |                |
|------------------------|----------------|
| Features               | ➤ See page 116 |
| Product Information    | 156            |
| Circuit Configurations | 160            |
| Receptacles            | 231            |

### Standard Includes

#### Single-Block Kit:

- Single power block assembly:
  - Two single power blocks: injection-molded, PVC-free plastic
  - Power harness
- Mounting brackets and hardware

#### Double-Block Kit:

- One or two double power blocks: injection-molded, PVC-free plastic
- Block-to-block jumpers: PVC-free plastic
  - Male-to-male jumper in 36"W kit
  - 8" jumper in 42"W kit
  - 14" jumper in 48"W kit
- Mounting brackets and hardware

### How to Specify

- ① Model

## Technology Tile Electrical Components

Pricing

Jumpers and Power Entries

GSA SIN 711-1

| Width                    | Model              | Price |
|--------------------------|--------------------|-------|
| <b>Pass-Thru Jumpers</b> |                    |       |
| 24"                      | <b>36P24EPT84B</b> | \$201 |
| 30"                      | <b>36P30EPT84B</b> | 201   |
| 36"                      | <b>36P36EPT84B</b> | 201   |
| 42"                      | <b>36P42EPT84B</b> | 201   |
| 48"                      | <b>36P48EPT84B</b> | 201   |

### Vertical Base-to-Tile Jumpers for 4H and 5H Frames

#### For Use with:

- 30" Single-Block Kit (36P30EHS, 36P30EHSB)
- 42" Double-Block Kit (36P42EHD, 36P42EHDH)
- 48" Double-Block Kit (36P48EHD, 36P48EHDH)

|                    |       |
|--------------------|-------|
| <b>36PEBT84J72</b> | \$384 |
|--------------------|-------|

#### For Use with:

- 36" Single- or Double-Block Kit (36P36EHS, 36P36EHD, 36P36EHSB, 36P36EHDH)
- 42" Single-Block Kit (36P42EHS, 36P42EHSB)
- 48" Single-Block Kit (36P48EHS, 36P48EHSB)

|                    |       |
|--------------------|-------|
| <b>36PEBT84J94</b> | \$402 |
|--------------------|-------|

### Ceiling Power Entry




|            |                   |       |
|------------|-------------------|-------|
| 12' length | <b>36PEPEC84B</b> | \$284 |
|------------|-------------------|-------|

### New York City Power Entry

|                      |       |
|----------------------|-------|
| <b>36PEPEBNYC84B</b> | \$377 |
|----------------------|-------|

### Hardwire Box

|                 |       |
|-----------------|-------|
| <b>36PEHBB2</b> | \$124 |
|-----------------|-------|



|                        |                |
|------------------------|----------------|
| Features               | ➤ See page 116 |
| Product Information    | 156            |
| Circuit Configurations | 160            |
| Power/Data Pole        | 241            |

Specify a technology tile without cuts for a panel with a pass-thru jumpers. They cannot be placed behind other tiles.

### Standard Includes

- Pass-thru jumpers: PVC-free plastic

### How to Specify

#### Jumpers and Power Entries

- ① Model

#### Hardwire Box


- ① Model
- ② Finish designator:  
**462** = Cinder  
**405** = Designer White

# Technology Tile Electrical Components

Pricing

Receptacles, Data Plates, and Cover Plates

GSA SIN 711-1



| For Use<br>With                             | Available Colors |                   |                | Standard             |              | With Controlled Circuit<br>Stamp |       |
|---------------------------------------------|------------------|-------------------|----------------|----------------------|--------------|----------------------------------|-------|
|                                             | Cinder           | Designer<br>White | Dark<br>Orange | Model                | Price        | Model                            | Price |
| <b>15-Amp Duplex Receptacles</b>            |                  |                   |                |                      |              |                                  |       |
| Circuit 1                                   | •                | •                 |                | <b>36PER184SB15</b>  | \$29         | <b>36PER184SB15C</b>             | \$32  |
| Circuit 2                                   | •                | •                 |                | <b>36PER284SB15</b>  | 29           | <b>36PER284SB15C</b>             | 32    |
| Circuit 3                                   | •                | •                 |                | <b>36PER384SB15</b>  | 29           | <b>36PER384SB15C</b>             | 32    |
| <b>For Dedicated or Designated Circuits</b> |                  |                   |                |                      |              |                                  |       |
| Circuit 3                                   | •                | •                 | •              | <b>36PER3D84SB15</b> | \$29         | <b>36PER3D84SB15C</b>            | \$32  |
| Circuit 4                                   | •                | •                 | •              | <b>36PER4D84SB15</b> | 29           | <b>36PER4D84SB15C</b>            | 32    |
| <b>20-Amp Duplex Receptacles</b>            |                  |                   |                |                      |              |                                  |       |
| Circuit 1                                   | •                | •                 |                | <b>36PER184SB20</b>  | \$34         | <b>36PER184SB20C</b>             | \$37  |
| Circuit 2                                   | •                | •                 |                | <b>36PER284SB20</b>  | 34           | <b>36PER284SB20C</b>             | 37    |
| Circuit 3                                   | •                | •                 |                | <b>36PER384SB20</b>  | 34           | <b>36PER384SB20C</b>             | 37    |
| <b>For Dedicated or Designated Circuits</b> |                  |                   |                |                      |              |                                  |       |
| Circuit 3                                   | •                | •                 | •              | <b>36PER3D84SB20</b> | \$34         | <b>36PER3D84SB20C</b>            | \$37  |
| Circuit 4                                   | •                | •                 | •              | <b>36PER4D84SB20</b> | 34           | <b>36PER4D84SB20C</b>            | 37    |
|                                             |                  |                   |                | <i>Model</i>         | <i>Price</i> |                                  |       |
| <b>Data Plate</b>                           |                  |                   |                | <b>36PETTDP02</b>    | \$25         |                                  |       |
| <b>Hole Cover Plates (set of 10)</b>        |                  |                   |                | <b>36PETTRCP10</b>   | \$52         |                                  |       |

|                        |                |
|------------------------|----------------|
| Features               | ▶ See page 116 |
| Product Information    | 156            |
| Circuit Configurations | 160            |

## Standard Includes

### Duplex Receptacles

- One duplex receptacle: injection-molded, PVC-free plastic
- Trim plate: black with Cinder or Dark Orange receptacles; white with Designer White receptacles

### Data Plate

- One plate with two openings
- Voice/data adapter kit with two of each style: black with Cinder plate or white with Designer White plate (PVC-free plastic)

### Cover Plates

- Set of 10 plates: paint

## How to Specify

### Duplex Receptacles and Data Plates

- ① Model
- ② Finish designator:  
**462** = Cinder  
**405** = Designer White  
**698** = Dark Orange (available on noted receptacles only)

### Hole Cover Plates

- ① Model
- ② Finish type:  
**STD** = Group 1  
**STD M** = Group M (+10%)
- ③ Finish designator


IMPORTANT: California Title 24 requires all controlled circuits to be identifiable with a permanent marking.

Models on this page are not applicable to base wireway or power/data tiles.

## Power/Data Tiles

## Pricing

GSA SIN 711-1



| <i>W</i>            | <i>H</i>                          | <i>Model</i>     | <i>Price</i> |
|---------------------|-----------------------------------|------------------|--------------|
| <b>1-High Tiles</b> |                                   |                  |              |
| 30"                 | 11 <sup>7</sup> / <sub>16</sub> " | <b>36P301ITE</b> | \$132        |
| 36"                 |                                   | <b>36P361ITE</b> | 176          |

Specify tiles for both sides of frame.

Power/data tile cannot be placed back to back with storage tiles

Mid-distribution block, distribution block bracket, mid-block jumper, and base-to-power/data tile jumper must be specified separately for power/data tile when planning to access power.

One base receptacle is used for power/data tile.

Power/data tiles cannot be connected to a technology tile.

Power/data tile electrical components  
➤ See page 233.

|                        |                |
|------------------------|----------------|
| Features               | ➤ See page 116 |
| Power & Data Overview  | 146            |
| Product Information    | 163            |
| Application Guidelines | 152            |

### Standard Includes

- Four trim plates
- Four blank cover plates, cinder





### How to Specify

- ① Model
- ② Finish type:
  - STD** = Group 1
  - STD M** = Group M (+10%)
- ② Finish designator

## Power/Data Tile Electrical

Pricing

GSA SIN 711-1



| Model                                  | Description                                                             | Price |
|----------------------------------------|-------------------------------------------------------------------------|-------|
| <b>Mid-Distribution Block</b>          |                                                                         |       |
| 36PEDM                                 |                                                                         | \$151 |
| <b>Distribution Block Bracket</b>      |                                                                         |       |
| 36PEDBB                                |                                                                         | \$42  |
| <b>Mid-Block Jumper</b>                |                                                                         |       |
| 36PEJM                                 | Used to connect power between adjacent or back-to-back power/data tiles | \$74  |
| <b>Base-to-Power/Data Tile Jumpers</b> |                                                                         |       |
| 36PEBTJ3                               | To jump from base to 2-high                                             | \$132 |
| 36PEBTJ5                               | To jump from base to 3-, 4- or 5-high                                   | 146   |

|                        |                |
|------------------------|----------------|
| Features               | ➤ See page 116 |
| Power & Data Overview  | 146            |
| Product Information    | 163            |
| Application Guidelines | 152            |

Power/data tile electrical components must be specified separately. All electrical components must be the same power type (10S or 10D).

Specify one mid-distribution block for each receptacle required.

Base-to-power/data tile jumper cannot cross frames or connectors.

### How to Specify

#### Mid-Distribution Block and Jumpers

- ① Model
- ② Power type:
  - 10S** = Shared neutral
  - 10D** = Independent neutral

#### Distribution Block Bracket


- ① Model

## Electrical Components

Pricing

### Base Wireway Harnesses

GSA SIN 711-1



| <i>Model</i>                  | <i>Description</i> | <i>Function</i>              | <i>Price</i> |
|-------------------------------|--------------------|------------------------------|--------------|
| <b>Base Wireway Harnesses</b> |                    |                              |              |
| <b>36P24EDB</b>               | For 24"W frames    | Carries power to receptacles | \$151        |
| <b>36P30EDB</b>               | For 30"W frames    | Carries power to receptacles | 151          |
| <b>36P36EDB</b>               | For 36"W frames    | Carries power to receptacles | 151          |
| <b>36P42EDB</b>               | For 42"W frames    | Carries power to receptacles | 151          |
| <b>36P48EDB</b>               | For 48"W frames    | Carries power to receptacles | 151          |

|                       |                |
|-----------------------|----------------|
| Features              | ➤ See page 116 |
| Power & Data Overview | 146            |
| Product Information   | 163            |
| Electrical Guidelines | 152            |

### How to Specify

- ① Model
- ② Power type:
  - 10S** = Shared neutral
  - 10D** = Independent neutral

IMPORTANT: All electrical components must be the same power type (10S or 10D).


Base wireway harnesses accommodate up to four receptacles.

## Electrical Components

Pricing

### Base Wireway Jumpers

GSA SIN 711-1



| <i>Model</i>                                 | <i>Description</i>                                  | <i>Function</i>                                                      | <i>Price</i> |
|----------------------------------------------|-----------------------------------------------------|----------------------------------------------------------------------|--------------|
| <b>For Use in Straight-Line Applications</b> |                                                     |                                                                      |              |
| <b>36PEJB1</b>                               | From panel to panel                                 | Routes power panel to panel                                          | \$74         |
| <b>36PEJB5</b>                               | Thru connector OR 3" extender                       | Routes power panel to panel through connector or 3" extender         | 74           |
| <b>36PEJB8</b>                               | Thru connector AND 3" extender                      | Routes power panel to panel through connector and 3" extender        | 74           |
| <b>36PEJB9</b>                               | Thru 3" extender, connector AND another 3" extender | Routes power panel to panel through connector AND two 3" extenders   | 74           |
| <b>For Use in 90° Applications</b>           |                                                     |                                                                      |              |
| <b>36PEJB2</b>                               | Thru connector                                      | Routes power panel to panel through 90° corner                       | \$74         |
| <b>36PEJB5</b>                               | Thru connector AND 3" extender                      | Routes power panel to panel through 90° corner and 3" extender       | 74           |
| <b>36PEJB8</b>                               | Thru 3" extender, connector AND another 3" extender | Routes power panel to panel through 90° corner AND two 3" extenders  | 74           |
| <b>For Use in 120° Applications</b>          |                                                     |                                                                      |              |
| <b>36PEJB5</b>                               | Thru connector                                      | Routes power panel to panel through 120° corner                      | \$74         |
| <b>36PEJB8</b>                               | Thru connector AND 3" extender                      | Routes power panel to panel through 120° corner and 3" extender      | 74           |
| <b>36PEJB9</b>                               | Thru 3" extender, connector AND another 3" extender | Routes power panel to panel through 120° corner AND two 3" extenders | 74           |

Base wireway jumpers are specified according to application.  
 ➤See page 148 for application guidelines and illustrations.

IMPORTANT: All electrical components must be the same power type (10S or 10D).

Base wireway pass-thru jumpers  
 ➤See page 236.

|                       |               |
|-----------------------|---------------|
| Features              | ➤See page 116 |
| Power & Data Overview | 146           |
| Product Information   | 148           |
| Electrical Guidelines | 152           |

### How to Specify


- ① Model
- ② Power type:
  - 10S** = Shared neutral
  - 10D** = Independent neutral

## Electrical Components


Pricing

Base Wireway Pass-Thru Jumpers

GSA SIN 711-1



Straightline Connection  
(Thru panel shown)



90° Connection  
(Thru connector and panel shown)

Model

Price

### Pass-Thru Jumpers

|                 |       |
|-----------------|-------|
| <b>36P18EPT</b> | \$196 |
| <b>36P24EPT</b> | 196   |
| <b>36P30EPT</b> | 196   |
| <b>36P36EPT</b> | 196   |
| <b>36P42EPT</b> | 196   |
| <b>36P48EPT</b> | 196   |
| <b>36P53EPT</b> | 196   |
| <b>36P58EPT</b> | 196   |

Pass-Thru Jumper Selection:

| Frame Width to be Passed Thru | Straightline Connections |                        |                          |                                      |                                      | 90° and 120° Connections |                                      |                                      |
|-------------------------------|--------------------------|------------------------|--------------------------|--------------------------------------|--------------------------------------|--------------------------|--------------------------------------|--------------------------------------|
|                               | Thru Panel               | Thru Connector & Panel | Thru 3" Extender & Panel | Thru Connector, 3" Extender, & Panel | Thru 3" Extender, Connector, & Panel | Thru Connector & Panel   | Thru Connector, 3" Extender, & Panel | Thru 3" Extender, Connector, & Panel |
| 18"                           | 36P18EPT                 | 36P24EPT               | 36P24EPT                 | 36P24EPT                             | 36P30EPT                             | 36P24EPT                 | 36P24EPT                             | 36P30EPT                             |
| 24"                           | 36P24EPT                 | 36P30EPT               | 36P30EPT                 | 36P30EPT                             | 36P36EPT                             | 36P30EPT                 | 36P30EPT                             | 36P36EPT                             |
| 30"                           | 36P30EPT                 | 36P36EPT               | 36P36EPT                 | 36P36EPT                             | 36P42EPT                             | 36P36EPT                 | 36P36EPT                             | 36P42EPT                             |
| 36"                           | 36P36EPT                 | 36P42EPT               | 36P42EPT                 | 36P42EPT                             | 36P48EPT                             | 36P42EPT                 | 36P42EPT                             | 36P48EPT                             |
| 42"                           | 36P42EPT                 | 36P48EPT               | 36P48EPT                 | 36P48EPT                             | 36P53EPT                             | 36P48EPT                 | 36P48EPT                             | 36P53EPT**                           |
| 48"                           | 36P48EPT                 | 36P53EPT               | 36P53EPT                 | 36P53EPT                             | 36P58EPT                             | 36P53EPT                 | 36P53EPT                             | 36P58EPT                             |

\*\* For this configuration at a 120° connection, specify 36P58EPT.

Base wireway pass-through jumpers are specified according to application.  
➤ See chart at left.

IMPORTANT: All electrical components must be the same power type (10S or 10D).

Base wireway jumpers  
➤ See page 235.

|                       |                |
|-----------------------|----------------|
| Features              | ➤ See page 116 |
| Power & Data Overview | 146            |
| Product Information   | 148            |
| Electrical Guidelines | 152            |

### Standard Includes

- Jumper

### How to Specify

- 1 Model
- 2 Power type:  
**10S** = Shared neutral  
**10D** = Independent neutral

# Electrical Components

Pricing

## Base Wireway 15-Amp Duplex Receptacles

GSA SIN 711-1



IMPORTANT: California Title 24 requires all controlled circuits to be identifiable with a permanent marking.

Select receptacle models based on the wiring configuration  
➤See pages 152–155 for circuit configurations and wiring diagrams.

IMPORTANT: All electrical components must be the same power type (10S or 10D). Models on this page are not applicable to technology tiles.

Mid-distribution block  
➤See page 233.

Base wireway harness  
➤See page 234.

| For Use<br>With                                     | Available Colors |                   |                | Standard   | Price | With Controlled Circuit<br>Stamp | Price |
|-----------------------------------------------------|------------------|-------------------|----------------|------------|-------|----------------------------------|-------|
|                                                     | Cinder           | Designer<br>White | Dark<br>Orange | Model      |       | Model                            |       |
| Shared Neutral (10S) configured as 10-Wire, 3 and 3 |                  |                   |                |            |       |                                  |       |
| Circuit 1                                           | •                | •                 |                | 36PER110S  | \$29  | 36PER110SC                       | \$32  |
| Circuit 2                                           | •                | •                 |                | 36PER210S  | 29    | 36PER210SC                       | 32    |
| Circuit 3                                           | •                | •                 |                | 36PER310S  | 29    | 36PER310SC                       | 32    |
| Circuit 4                                           | •                | •                 | •              | 36PER4D10S | 29    | 36PER4D10SC                      | 32    |
| Circuit 5                                           | •                | •                 | •              | 36PER5D10S | 29    | 36PER5D10SC                      | 32    |
| Circuit 6                                           | •                | •                 | •              | 36PER6D10S | 29    | 36PER6D10SC                      | 32    |
| Shared Neutral (10S) configured as 8-Wire, 3 and 1  |                  |                   |                |            |       |                                  |       |
| Circuit 1                                           | •                | •                 |                | 36PER110S  | \$29  | 36PER110SC                       | \$32  |
| Circuit 2                                           | •                | •                 |                | 36PER210S  | 29    | 36PER210SC                       | 32    |
| Circuit 3                                           | •                | •                 |                | 36PER310S  | 29    | 36PER310SC                       | 32    |
| Circuit 4                                           | •                | •                 | •              | 36PER4D10S | 29    | 36PER4D10SC                      | 32    |
| Shared Neutral (10S) configured as 8-Wire, 2 and 2  |                  |                   |                |            |       |                                  |       |
| Circuit 1                                           | •                | •                 |                | 36PER110S  | \$29  | 36PER110SC                       | \$32  |
| Circuit 2                                           | •                | •                 |                | 36PER210S  | 29    | 36PER210SC                       | 32    |
| Circuit 3                                           | •                | •                 | •              | 36PER3D10S | 29    | 36PER3D10SC                      | 32    |
| Circuit 4                                           | •                | •                 | •              | 36PER4D10S | 29    | 36PER4D10SC                      | 32    |
| Independent Neutral (10D)                           |                  |                   |                |            |       |                                  |       |
| Circuit 1                                           | •                | •                 | •              | 36PER110D  | \$29  | 36PER110DC                       | \$32  |
| Circuit 2                                           | •                | •                 | •              | 36PER210D  | 29    | 36PER210DC                       | 32    |
| Circuit 3                                           | •                | •                 | •              | 36PER310D  | 29    | 36PER310DC                       | 32    |
| Circuit 4                                           | •                | •                 | •              | 36PER410D  | 29    | 36PER410DC                       | 32    |

|                       |               |
|-----------------------|---------------|
| Features              | ➤See page 116 |
| Power & Data Overview | 146           |
| Product Information   | 147           |
| Electrical Guidelines | 152           |

### Standard Includes

- Duplex receptacle

### How to Specify

- 1 Model
- 2 Finish designator (omit for Cinder):  
**439** = Nebulous White  
**498** = Orange (available on noted receptacles only)

## Electrical Components

Pricing

### Base Wireway 20-Amp Duplex Receptacles

GSA SIN 711-1



IMPORTANT: California Title 24 requires all controlled circuits to be identifiable with a permanent marking.

Select receptacle models based on the wiring configuration. Model 36PER3D10S20 is for use only in an 8-wire, 2 + 2 configuration.

➤See pages 152–155 for circuit configurations and wiring diagrams.

20-amp receptacles protrude 1/8" more than 15-amp receptacles.

IMPORTANT: All electrical components must be the same power type (10S or 10D). Models on this page are not applicable to technology tiles, nor to independent neutral configurations.

Mid-distribution block  
➤See page 233.

Base wireway harness  
➤See page 234.

| For Use With                                               | Available Colors                                                              |                |             | Standard     |       | With Controlled Circuit Stamp |       |
|------------------------------------------------------------|-------------------------------------------------------------------------------|----------------|-------------|--------------|-------|-------------------------------|-------|
|                                                            | Cinder                                                                        | Designer White | Dark Orange | Model        | Price | Model                         | Price |
| <b>Shared Neutral (10S) configured as 10-Wire, 3 and 3</b> |                                                                               |                |             |              |       |                               |       |
| Circuit 1                                                  | •                                                                             | •              |             | 36PER110S20  | \$34  | 36PER110S20C                  | \$37  |
| Circuit 2                                                  | •                                                                             | •              |             | 36PER210S20  | 34    | 36PER210S20C                  | 37    |
| Circuit 3                                                  | •                                                                             | •              |             | 36PER310S20  | 34    | 36PER310S20C                  | 37    |
| Circuit 4                                                  | •                                                                             | •              | •           | 36PER4D10S20 | 34    | 36PER4D10S20C                 | 37    |
| Circuit 5                                                  | •                                                                             | •              | •           | 36PER5D10S20 | 34    | 36PER5D10S20C                 | 37    |
| Circuit 6                                                  | •                                                                             | •              | •           | 36PER6D10S20 | 34    | 36PER6D10S20C                 | 37    |
| <b>Shared Neutral (10S) configured as 8-Wire, 3 and 1</b>  |                                                                               |                |             |              |       |                               |       |
| Circuit 1                                                  | •                                                                             | •              |             | 36PER110S20  | \$34  | 36PER110S20C                  | \$37  |
| Circuit 2                                                  | •                                                                             | •              |             | 36PER210S20  | 34    | 36PER210S20C                  | 37    |
| Circuit 3                                                  | •                                                                             | •              |             | 36PER310S20  | 34    | 36PER310S20C                  | 37    |
| Circuit 4                                                  | •                                                                             | •              | •           | 36PER4D10S20 | 34    | 36PER4D10S20C                 | 37    |
| <b>Shared Neutral (10S) configured as 8-Wire, 2 and 2</b>  |                                                                               |                |             |              |       |                               |       |
| Circuit 1                                                  | •                                                                             | •              |             | 36PER110S20  | \$34  | 36PER110S20C                  | 37    |
| Circuit 2                                                  | •                                                                             | •              |             | 36PER210S20  | 34    | 36PER210S20C                  | 37    |
| Circuit 3                                                  | •                                                                             | •              | •           | 36PER3D10S20 | 34    | 36PER3D10S20C                 | 37    |
| Circuit 4                                                  | •                                                                             | •              | •           | 36PER4D10S20 | 34    | 36PER4D10S20C                 | 37    |
| <b>Independent Neutral (10D)</b>                           |                                                                               |                |             |              |       |                               |       |
| Circuit 1                                                  | •                                                                             | •              | •           | 36PER110D20  | \$34  | 36PER110D20C                  | \$37  |
| Circuit 2                                                  | •                                                                             | •              | •           | 36PER210D20  | 34    | 36PER210D20C                  | 37    |
| Circuit 3                                                  | Not available in 20-amp; use 15-amp receptacle model 36PER310D or 36PER310DC. |                |             |              |       |                               |       |
| Circuit 4                                                  | •                                                                             | •              | •           | 36PER410D20  | 34    | 36PER410D20C                  | 37    |

|                       |               |
|-----------------------|---------------|
| Features              | ➤See page 116 |
| Power & Data Overview | 146           |
| Product Information   | 147           |
| Electrical Guidelines | 152           |

#### Standard Includes

- Duplex receptacle

#### How to Specify

- 1 Model
- 2 Finish designator (omit for Cinder):  
439 = Nebulous White  
498 = Orange (available on noted receptacles only)

## Electrical Components

Pricing

Base Wireway USB Receptacles

GSA SIN 711-1



| For Use<br>With                                     | Available Colors                               |                   | Model     | Price |
|-----------------------------------------------------|------------------------------------------------|-------------------|-----------|-------|
|                                                     | Cinder                                         | Nebulous<br>White |           |       |
| Shared Neutral (10S) configured as 10-Wire, 3 and 3 |                                                |                   |           |       |
| Circuit 1                                           | •                                              | •                 | 36PERUP1S | \$155 |
| Circuit 2                                           | •                                              | •                 | 36PERUP2S | 155   |
| Circuit 3                                           | •                                              | •                 | 36PERUP3S | 155   |
| Circuit 4                                           | •                                              | •                 | 36PERUP4S | 155   |
| Circuit 5                                           | •                                              | •                 | 36PERUP5S | 155   |
| Circuit 6                                           | •                                              | •                 | 36PERUP6S | 155   |
| Shared Neutral (10S) configured as 8-Wire, 3 and 1  |                                                |                   |           |       |
| Circuit 1                                           | •                                              | •                 | 36PERUP1S | \$155 |
| Circuit 2                                           | •                                              | •                 | 36PERUP2S | 155   |
| Circuit 3                                           | •                                              | •                 | 36PERUP3S | 155   |
| Circuit 4                                           | •                                              | •                 | 36PERUP4S | 155   |
| Shared Neutral (10S) configured as 8-Wire, 2 and 2  |                                                |                   |           |       |
| Circuit 1                                           | •                                              | •                 | 36PERUP1S | \$155 |
| Circuit 2                                           | •                                              | •                 | 36PERUP2S | 155   |
| Circuit 3                                           | Not available for use in 2 and 2 applications. |                   |           | —     |
| Circuit 4                                           | •                                              | •                 | 36PERUP4S | 155   |

IMPORTANT: All electrical components must be the same power type (10S or 10D). Models on this page are not applicable to technology tiles, nor to independent neutral configurations.

Base wireway harness  
➤ See page 234.

|                       |                |
|-----------------------|----------------|
| Features              | ➤ See page 116 |
| Power & Data Overview | 146            |
| Product Information   | 147            |
| Electrical Guidelines | 152            |

### Standard Includes

- USB receptacle

### How to Specify



- 1 Model
- 2 Finish designator (omit for Cinder):  
**439** = Nebulous White

## Electrical Components

Pricing

### Power Entries

GSA SIN 711-1



**IMPORTANT:** All electrical components must be the same power type (10S or 10D). Power entries use one receptacle location.

Access to ceiling source is regulated by National Electric Code to 12' maximum conduit for standard includes construction. Lengths up to 24' are available with custom quote for alternate construction.

Ceiling power entry must plug into right-hand block of base wireway harness. It does not include junction box or related connectors.

Power/data pole must be specified separately for ceiling power entry.  
➤ See page 241.

Ceiling power entry for use with technology tiles  
➤ See page 230.

*Model*

*Price*

#### Base Power Entry (Non-Handed)

|           | Model          | Price |
|-----------|----------------|-------|
| 6' Length | <b>36PEPEB</b> | \$231 |

#### New York City Floor/Wall Power Entry

*Note: Approval number E44747.*

|  | Model             | Price |
|--|-------------------|-------|
|  | <b>36PEPEBNYC</b> | \$377 |

#### Ceiling Power Entry

|            | Model          | Price |
|------------|----------------|-------|
| 12' Length | <b>36PEPEC</b> | \$284 |

|                       |                |
|-----------------------|----------------|
| Features              | ➤ See page 116 |
| Power & Data Overview | 146            |
| Product Information   | 149            |
| Electrical Guidelines | 152            |

### Standard Includes

- Power entry assembly

### How to Specify

- ① Model
- ② Power type:
  - 10S** = Shared neutral
  - 10D** = Independent neutral


## Electrical Components

Pricing

Power/Data Poles

GSA SIN 711-1

| Top Cap<br>Width         | Pole<br>Length | Model      | Flat Profile |       | Curved Profile |       |
|--------------------------|----------------|------------|--------------|-------|----------------|-------|
|                          |                |            | Wood         | Paint | Wood           | Paint |
|                          |                |            | (W)          | (P)   | (W)            | (P)   |
| Ceiling Power/Data Poles |                |            |              |       |                |       |
| 24"                      | 82"            | 36P24CPDPK | \$778        | \$591 | \$594          | \$464 |
| 30"                      |                | 36P30CPDPK | 778          | 591   | 594            | 464   |
| 36"                      |                | 36P36CPDPK | 778          | 591   | 594            | 464   |
| 42"                      |                | 36P42CPDPK | 778          | 591   | 594            | 464   |
| 48"                      |                | 36P48CPDPK | 778          | 591   | 594            | 464   |



Ceiling power entry for use with  
technology tiles  
➤ See page 230.

|                       |                |
|-----------------------|----------------|
| Features              | ➤ See page 116 |
| Power & Data Overview | 146            |
| Product Information   | 151            |
| Electrical Guidelines | 152            |

### Standard Includes

- Pole: paint
- Notched structure top caps: wood or paint
- Power pole trim plate: paint

### How to Specify

- 1 Model
- 2 Top cap material:  
**W** = Wood  
**P** = Paint
- 3 Top cap profile:  
**C** = Curved  
**F** = Flat
- 4 Top cap finish type:  
**STD** = Group 1  
**STD M** = Group M (+10%)
- 5 Top cap finish designator
- 6 Power pole and trim plate:  
**STD** = Group 1  
**STD M** = Group M (+10%\*)  
\*Applies once per model.
- 7 Power pole and trim plate designator


**Electrical Components**

Pricing


Hardwire

GSA SIN 711-1


| <i>D</i>            | <i>W</i> | <i>H</i> | <i>Model</i>   | <i>Price</i> |
|---------------------|----------|----------|----------------|--------------|
| <b>Hardwire Box</b> |          |          |                |              |
| 27/8"               | 611/16"  | 31/16"   | <b>36PEHBB</b> | \$119        |



|                             |  |  |                |      |
|-----------------------------|--|--|----------------|------|
| <b>Hardwire Cover Plate</b> |  |  |                |      |
|                             |  |  | <b>36PEHBC</b> | \$53 |



|                                       |  |  |                 |      |
|---------------------------------------|--|--|-----------------|------|
| <b>Hardwire Cover Plate for Power</b> |  |  |                 |      |
|                                       |  |  | <b>36PEHBCP</b> | \$58 |



Use standard non-powered frames and appropriately punched wireway covers.

Consult local electrical codes prior to specification.

Receptacles, conduit, wiring, and other required components to be supplied by electrician.

|                       |                |
|-----------------------|----------------|
| Features              | ➤ See page 116 |
| Power & Data Overview | 146            |
| Product Information   | 150            |
| Electrical Guidelines | 152            |

- Standard Includes
- Box or cover plate: galvanized

How to Specify


❗ Model

## Cable Management


Pricing

GSA SIN 711-1

|                       |                |
|-----------------------|----------------|
| Features              | ▶ See page 116 |
| Power & Data Overview | 146            |
| Product Information   | 165            |



| <i>D</i>                                   | <i>W</i>                        | <i>H</i>                         | <i>Model</i>      | <i>Description</i>                                                                                                         | <i>Price</i> |
|--------------------------------------------|---------------------------------|----------------------------------|-------------------|----------------------------------------------------------------------------------------------------------------------------|--------------|
| <b>Vertical Cable Managers</b>             |                                 |                                  |                   |                                                                                                                            |              |
| 15 <sup>1</sup> / <sub>16</sub> "          | 7 <sup>7</sup> / <sub>8</sub> " | 19 <sup>1</sup> / <sub>4</sub> " | <b>36A1VCMN2</b>  | For use with standard includes-height (18 <sup>11</sup> / <sub>16</sub> "H) radius and square profile overheads.           | \$29         |
|                                            |                                 | 21 <sup>5</sup> / <sub>8</sub> " | <b>36A3VCMN2</b>  | For use with reduced-height (16 <sup>1</sup> / <sub>2</sub> "H) radius, square, bevel, flat, and curved profile overheads. | 31           |
|                                            |                                 | 23 <sup>5</sup> / <sub>8</sub> " | <b>36A5VCMN2</b>  | For use with lunar profile or flat profile sliding-door overheads.                                                         | 35           |
| <b>For Use with Center-Mount Overheads</b> |                                 |                                  |                   |                                                                                                                            |              |
| 15 <sup>1</sup> / <sub>16</sub> "          | 7 <sup>7</sup> / <sub>8</sub> " | 14 <sup>1</sup> / <sub>8</sub> " | <b>36A3HVCMN</b>  | For center-mount overheads on 3H Xsite panels                                                                              | \$36         |
|                                            |                                 | 21"                              | <b>36A50HVCMN</b> | For center-mount overheads on 3.5H Xsite panels                                                                            | 37           |
|                                            |                                 | 26 <sup>5</sup> / <sub>8</sub> " | <b>36A4HVCMN</b>  | For center-mount overheads on 4H Xsite panels                                                                              | 38           |



|                           |  |  |               |                                         |     |
|---------------------------|--|--|---------------|-----------------------------------------|-----|
| <b>Data Cable Manager</b> |  |  |               |                                         |     |
|                           |  |  | <b>36ADCM</b> | Holds 24, 1/4" diameter cables. Single. | \$8 |

### Standard Includes

- Cable manager

### How to Specify

#### Vertical Cable Manager

- ① Model
- ② Fabric grade
- ③ Fabric number

#### Data Cable Manager

- ① Model

Fabric is railroaded on vertical cable manager.

