DESCRIPTION

GREASE-OUT contains all natural d-limonene, which is derived from orange peel extracts. This product will remove heavy duty buildup from a variety of surfaces.

Keep away from heat, hot surfaces, open flames, sparks. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof ventilating, lighting, electrical equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Store in a well-ventilated place. Keep cool. Store locked up.

Avoid breathing gas, mist, spray, vapors. Wash thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. ear protective gloves, protective clothing, eye protection, face protection.

IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do NOT induce vomiting.
IF ON SKIN (OR HAIR): Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF SKIN IRRITATION OR RASH OCCURS: Get medical advice/attention.
Take off contaminated clothing and wash it before reuse.

IN CASE OF FIRE: Use carbon dioxide (CO2), dry extinguishing powder, foam to extinguish.

DISPOSAL

Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation*t.*

www.cannonindustrialproducts.com

CANNON
INDUSTRIAL PRODUCTS, INC.
Your Solutions Specialists

GREASE-OUT

Industrial Degreasing Agent
Naturally Powerful

Removes Grease, Tar, Oil and Gums
Cleans Drains and Grease Traps
Works as a "Shocker" for Grease Traps
Contains NO Petroleum Distillates

Professional Grade Shocker for Grease Traps

DANGER

Flammable liquid and vapor.
May be fatal if swallowed and enters airways.
Causes skin irritation.
May cause an allergic skin reaction.
KEEP OUT OF REACH OF CHILDREN

NET CONTENTS: 5 GALLONS

DIRECTIONS

Use **GREASE-OUT** undiluted in a parts washing unit as a cold solvent. On heavy tar and asphalt, allow to penetrate for several minutes then rinse.

To deodorize dumpsters and garbage cans: Dilute 6 ounces into 1 gallon of warm water and spray into receptacle.

NFPA® Ratings
Health: 1; Flammability: 2; Reactivity: 0

Contains/CAS Number:
d-limonene/5989-27-5;
Linear Alcohol Ethoxylates/34398-01-1;
1-Undecanol/112-42-5.

For industrial and commercial use only.
For additional information, see Safety Data Sheet.

Please Recycle.

SOLD BY:

CANNON
INDUSTRIAL PRODUCTS, INC.
MUSIC CITY U.S.A.
PO Box 291344 • Nashville, TN 37229 • (888) 879-6124

SPECIMEN LABEL