CERTIFIED

CHERRY MAT™

Drain and Lift Station Maintainer

FIRST AID
IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs, get medical attention. Take off contaminated clothing and wash before reuse.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists, get medical attention.
IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms, call a physician.
IF SWALLOWED: Rinse mouth. DO NOT induce vomiting. Call a physician if unwell.
See the Safety Data Sheet for more information.
For medical or environmental emergencies, call CHEMTREC® at 1-800-424-9300.
Not for Resale
MADE IN THE U.S.A.
0894CGSA
1M504

DISPOSAL
Dispose of contents and container in accordance with applicable regulations.

CERTIFIED LABORATORIES
A Division of NCH Corporation
P.O. Box 2493, Ft. Worth, Texas 76113-2493
www.certifiedlabs.com • ©2015 NCH Corporation

TO REORDER, Call TOLL-FREE:
1-800-527-9929
FAX: 1-800-456-0121

QUALITY ISO 9001 ASSURANCE

Si usted no entiende esta etiqueta, pida a alguien que sepa inglés que se la explique completamente antes de usar este producto. • Not intended for household use or resale. • Read the entire label before using this product.

SUPERIOR SOLVENCY PLUS MAXIMUM ODOR CONTROL

- **Removes grease, which reduces the risk of Sanitary Sewer Overflows (SSO's)**
- **Cleans and maintains lift stations**
- **Minimizes grease-related pump failure and replacement**
- **Cuts through grease buildup for free-flowing drains**
- **Ideal for sumps and ejector pits**
- **Controls odors**
- **Will not corrode floats or other pump station mechanics**
- **Safer to handle than conventional caustic lift station and drain products**

DANGER: COMBUSTIBLE LIQUID • CAUSES SKIN IRRITATION • MAY CAUSE AN ALLERGIC SKIN REACTION • CAUSES SERIOUS EYE IRRITATION • MAY CAUSE DROWSINESS OR DIZZINESS • MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS • MAY CAUSE DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED EXPOSURE

NET CONTENTS:32 fl oz (1 qt)/946 mL

Suitable for use in the drain lines of non-processing areas of U.S. Federally inspected meat and poultry plants.

DIRECTIONS FOR USE
NOTE: Use this product only with solvent-resistant equipment.
DRAINS
To open and/or deodorize slow-moving, grease-clogged drains, make sure there is NO standing water. Add 8 fluid ounces of product to the drain. Allow to work for 1 hour, then flush with hot water. Repeat if necessary.
MAINTENANCE: Add 4 to 8 fluid ounces per drain weekly (including commercial floor drains).
LIFT STATIONS
To control odor and grease in lift stations, add 1/2 gallon of product for every square foot of surface area of the lift station.
Maintenance: Add 10% of the initial dose every two to three weeks or as needed to control grease and odors. At this rate, the product should form a uniform surface across the top of the lift station.
STORAGE: Store in a well-ventilated place. Keep cool. Keep container tightly closed.
KEEP FROM FREEZING. If this product is stored in cold or freezing temperatures, it may separate or thicken. This will not harm the performance. Before using, warm to room temperature and stir thoroughly.
DANGER: INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE VAPORS CAN BE HARMFUL OR FATAL.
Contains 1-Tetradecene and Secondary ethoxylated alcohols.
Keep away from heat, sparks, open flames or hot surfaces. Wear protective gloves, protective clothing and eye protection. Wash face, hands and any exposed skin thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid breathing vapors or mist. Use in a well-ventilated area.
35 % of the mixture consists of ingredient(s) of unknown toxicity.

SPECIMEN