



Husky®

# 1020



## HIGH GLOSS PREMIUM FLOOR FINISH

A top-notch, work-horse floor finish combining excellent reparability with high initial gloss and good durability. Provides excellent reparability, re-coat, water detergent and black heel mark resistance.

### FORMULA FEATURES

- ▶ Excellent Leveling
- ▶ Dry-bright Gloss
- ▶ Reduced Mop Drag
- ▶ Exceptional Long Term Gloss
- ▶ Superb Reparability
- ▶ Exceeds Industry Standards For Slip Resistance

### APPLICATIONS \*READY TO USE

- ▶ For use on resilient tile, terrazzo and sealed wood floors to protect and provide long lasting gloss levels.
- ▶ Designed for use in 24 hour facilities.

### AREAS OF UTILIZATION

- ▶ Hospitals
- ▶ Universities
- ▶ Department Stores
- ▶ Nursing Homes
- ▶ Institutions
- ▶ Grocery Stores
- ▶ Schools
- ▶ Office Buildings

### OTHER LIQUID/AEROSOL FORMULA CATEGORIES

- ▶ Restroom Care
- ▶ Skin Care
- ▶ Odor Control
- ▶ Health Care
- ▶ Industrial Care
- ▶ Carpet Care
- ▶ Specialty Products

# Husky® 1020 HIGH GLOSS PREMIUM FLOOR FINISH

## DIRECTIONS

## PRODUCT DATA




1. Before applying floor finish, make sure that the floor surface is properly prepared. If the floor has been stripped, all residual stripper should be removed and the pH of the floor should be returned to neutral (6.5-7.5).
2. Always apply thin coats using a clean mop. It is important to pass the mop head in a figure 8 pattern to ensure that all areas are thoroughly covered.
3. Allow floor finish to dry sufficiently before walking on it or applying additional coats. For standard conditions, allow at least 30 minutes. For thorough drying in poor ventilation areas, dry times may be extended.
4. Repeat steps two and three for additional coats.

Styrenated Acrylic Polymer Base  
 Cross Link/Metal Interlock  
 Removes Easily  
 Slip Resistant  
 Superior Adhesion  
 DOT Regulated  
 VOC Compliant

YES	NO
X	
X	
X	
X	
X	X
X	

### Maintenance/Formula/Facility Recommendation Matrix

ZONE	Maintenance	Facility Recommendation	Formula
ZONE 1	<b>Low Maintenance</b> • Less than one buff or burnishing per week. • Customer typically wants a gloss level (7-9) to hold for extended period. Gloss Level: Initial: 7-8 • Post-Burnish: 8-9	Classrooms Budget/Staff Constrained Facility Restaurant Bars C-Stores	1018
ZONE 2	<b>Intermediate Maintenance</b> • One to five buff or burnishings per week. • Customer expects good initial gloss level with good reparability. Gloss Level: Initial: 6-8 • Post-Burnish: 8-10	Nursing Homes, Colleges Long Term Care Facilities Regional Medical Centers Urgent Care Facilities Government Offices, Grocery Stores Larger Restaurants, Drug Stores Retail Shops, Strip Malls	1020, 1022, 1030
ZONE 3	<b>High Maintenance</b> • Five or more buff or burnishings per week. • Customer demands reparability with critically high gloss levels. Gloss Levels: Initial: 9 • Post-Burnish: 9-10	Hospitals, Supermarkets Office Lobbies, Show Rooms Museums, Universities Shopping Malls, Mega/Super Stores	1025



### SECTION I - PRODUCT IDENTIFICATION

See reverse side for product identification.

### SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

Hazardous components	CAS#s	OSHA PEL	ACGIH TLV	Other Limits	% (Optional)
Water	7732-18-5	N/A	N/A	N/A	75-85
TBEP	78-51-3	N/A	N/A	N/A	1-5
*Glycol ether DE	111-90-0	N/A	N/A	N/A	1-5
Acrylate Polymer	25987-66-0	N/A	N/A	N/A	15-20
Ethylene Polymer	68441-17-8	N/A	N/A	N/A	1-5

\*This chemical is subject to the reporting requirements for section 313 of title III of the superfund amendments and reauthorization act of 1986 and 40 CFR part 372.

### SECTION III - PHYSICAL AND CHEMICAL CHARACTERISTICS

Boiling Point	≈212° F	Specific Gravity (H <sub>2</sub> O=1)	≈1.020
Vapor Pressure (mm Hg.)	N/E	Percent Volatile By Weight (%)	>80%
pH (conc.)	8.5	Evaporation Rate (H <sub>2</sub> O=1)	≈1
Solubility in Water	Complete		
Appearance and Odor	White Liquid/Mild Fragrance		

### SECTION IV - FIRE AND EXPLOSION HAZARD DATA

**Flash Point (Method Used):** None **Flammable Limits:** LEL: N/A UEL: N/A  
**Extinguishing Media:** Water, CO<sub>2</sub>, Foam or media suitable for surrounding fire  
**Special Fire Fighting Procedures:** Standard fire fighting procedures may be followed, including full protective gear, NIOSH approved self-contained breathing apparatus.  
**Unusual Fire and Explosion Hazards:** None Known

### SECTION V - PHYSICAL HAZARDS

**Stability**  Unstable **Conditions to Avoid:** None Known  
 Stable  
**Incompatibility (Materials to Avoid):** Do not mix with other chemicals.  
**Hazardous Decomposition Products or By-products:** Thermal decomposition generate toxic materials such as oxides of carbon.  
**Hazardous**  May Occur **Conditions to Avoid:** None Known  
**Polymerization**  Will Not Occur

N/A (Not applicable / Not available)  
 N/E (Not Established)

041813

### SECTION VI - HEALTH HAZARDS

**Route(s) of Entry:** Inhalation? Skin? **X** Ingestion? **X**  
**Health Hazards** (1. Acute and 2. Chronic) **1. Acute:** Harmful if swallowed. Eye irritant.  
**2. Chronic:** None Known  
**Chemical Listed as Carcinogen or Potential Carcinogen:**  
 National Toxicology Program:  No  
 I.A.R.C. Monographs:  No  
 OSHA:  No  
**Signs and Symptoms of Exposure:** Irritation or burning sensation.  
**Medical Conditions Generally Aggravated by Exposure:** May aggravate skin disorders or respiratory ailments. **Emergency and First Aid Procedures:** **Eye Contact:** Eye contact may cause irritation. **Skin Contact:** Extended skin contact may cause irritation of the skin. **Ingestion:** If swallowed, this product may cause irritation of mucosal linings of the mouth, throat, esophagus or stomach. May cause diarrhea.

### SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

**Steps To Be Taken In Case Material Is Released Or Spilled:** If spilled, floors may be slippery. Wear appropriate protective gear to avoid skin or eye contact. Dike and contain spill with inert material (sand, clay). transfer liquid and solids to separate containers for recovery or proper disposal. Keep spill out of storm sewers and open bodies of water. After removal, flush area with water. Follow good industrial hygiene practices. Wash thoroughly after clean up. If uncertain about proper disposal, contact your local waste disposal provider or the regional office of the Environmental Protection Agency for guidance.  
**Waste Disposal Method:** Empty containers should be triple rinsed and offered for recycling or reconditioning, or disposed of in a sanitary landfill or for small containers (1 gal. or less), may be wrapped and discarded in trash. **Precautions To Be Taken In Handling And Storing:** Avoid contact with skin and eyes. Use product only according to label directions. If unsure about safe use, contact your supervisor immediately. Store in original container in a cool, dry, well-ventilated area. Store away from food or feed. Containers should be kept tightly closed when not in use. Keep in an area inaccessible to small children. **Other Precautions:** Use only according to label directions. If unsure about safe use, contact your supervisor immediately.

### SECTION VIII - CONTROL MEASURES

**Respiratory Protection (Specify Type):** Not expected to be necessary under normal conditions of use.  
**Ventilation: Local Exhaust:** As Necessary **Mechanical (General):** Adequate  
**Special: N/A Other: N/A Protection Gloves:** Water Impervious (Latex, Neoprene)  
**Eye Protection:** Chemical Resistant Goggles  
**Other Protective Clothing Or Equipment:** Not Required. **Work/Hygiene Practices:** Follow OSHA mandated procedures. Never eat or smoke while working with chemicals. Good housekeeping practices apply.