



Husky®

1022

ULTRA VERSATILE PREMIUM FLOOR FINISH

Revolutionary multi-speed floor finish. Provides **wet-look** gloss levels with diamond-tough durability. Formulated with advanced acrylic polymers and top quality bonding agents to make application easy (less mop drag) and stand up to even the toughest scuffs, scratches, and heel marks. Covers a broad variety of facility type and maintenance application.

FORMULA FEATURES

- Non-yellowing
- Ultra-High-Speed Gloss
- May be Utilized with Equipment Ranging from 1000-2600 rpms
- Highly Durable

APPLICATIONS *READY TO USE

- For use on resilient tile, rubber and terrazzo floors to protect and provide long-lasting gloss levels. Designed for use in ultra-high-speed maintenance programs to provide high gloss levels.
- For facilities with one to seven burnishing per week average.

AREAS OF UTILIZATION

- | | | |
|----------------------------|---------------------|-----------------|
| ▸ Schools | ▸ Hospitals | ▸ Nursing Homes |
| ▸ Office Buildings | ▸ Universities | ▸ Institutions |
| ▸ Grocery Stores | ▸ Department Stores | ▸ Restaurants |
| ▸ Manufacturing Facilities | | |

OTHER LIQUID / AEROSOL FORMULA CATEGORIES

- | | | |
|---------------------|----------------|-------------------|
| ▸ Restroom Care | ▸ Odor Control | ▸ Industrial Care |
| ▸ Specialty Product | ▸ Skin Care | ▸ Health Care |
| ▸ Carpet Care | | |

CANBERRA CORPORATION

3610 N. Holland-Sylvania Rd. Toledo, OH 43615 • P 419-841-6616 • F 419-841-7597 • canberracorp.com

Husky® 1022 ULTRA VERSATILE PREMIUM FLOOR FINISH

DIRECTIONS

PRODUCT DATA



- Before applying floor finish, make sure that the floor surface is properly prepared. If the floor has been stripped, all residual stripper should be removed and the pH of the floor should be returned to neutral (6.5-7.5).

Acrylic Polymer Base
Metal Interlock
UHS Repairable
Removes Easily
Slip Resistant
Superior Adhesion
Superior Color
DOT Regulated
VOC Compliant



- Always apply thin coats using a clean mop.
- Allow floor finish to dry sufficiently before walking on it or applying additional coats. For standard conditions, allow at least 30 minutes. For thorough drying in poor ventilation areas, dry times may be extended.



- Repeat steps two and three for additional coats.

YES	NO
X	
X	
X	
X	
X	
X	
X	
X	X

Maintenance/Formula/Facility Recommendation Matrix

Zone	Maintenance	Facility Recommendation	Formula
ZONE 1	Low Maintenance • Less than one buff or burnishing per week. • Customer typically wants a gloss level (7-9) to hold for extended period. Gloss Level: Initial: 7-8 • Post-Burnish: 8-9	Classrooms Budget/Staff Constrained Facility Restaurant Bars C-Stores	1018
ZONE 2	Intermediate Maintenance • One to five buff or burnishings per week. • Customer expects good initial gloss level with good repairability. Gloss Level: Initial: 6-8 • Post-Burnish: 8-10	Nursing Homes, Colleges Long Term Care Facilities Regional Medical Centers Urgent Care Facilities Government Offices, Grocery Stores Larger Restaurants, Drug Stores Retail Shops, Strip Malls	1020, 1022
ZONE 3	High Maintenance • Five or more buff or burnishings per week. • Customer demands repairability with critically high gloss levels. Gloss Levels: Initial: 9 • Post-Burnish: 9-10	Hospitals, Supermarkets Office Lobbies, Show Rooms Museums, Universities Shopping Malls, Mega/Super Stores	1025

PHYSICAL AND CHEMICAL CHARACTERISTICS

PRECAUTIONS FOR SAFE HANDLING AND USE

Boiling Point	212° F
Specific Gravity (H ₂ O=1)	1.030
Vapor Pressure (mm Hg.)	N/E
Percent Volatile By Weight (%)	78%
pH (conc.)	8.6
Evaporation Rate (H ₂ O=1)	1
Solubility in Water	Complete
Color	White Liquid
Fragrance	Mild

Steps To Be Taken In Case Material Is Released Or Spilled:

Wear appropriate protective equipment. If possible, contain spill and collect in an approved container. Rinse affected area thoroughly with water. Keep product out of storm sewers or waterways. Hold for disposal.

Waste Disposal Method: Dispose of in accordance with local, state and federal regulations. If possible, triple rinse container and recycle.

Precautions To Be Taken In Handling And Storing: Avoid contact with skin or eyes. Avoid breathing vapor, spray or mist. Store in original container, in cool dry place with adequate ventilation. Keep container tightly closed when not in use.

Other Precautions: Use only according to label directions. If unsure about safe use, contact your supervisor immediately.

