JAWS® Just Add Water System

9030
Multi-Surface Bathroom Cleaner
Limpiador Para Azulejos, Lechada Y Baños

SAFER CHOICE
Meets U.S. EPA Safer Product Standards
epa.gov/dfesaferchoice

NSF
Nonfood Compounds Program Listed (C1, C2) (Registration 146450)

Powerful and fast acting... Acidulous detergent based cleaner instantly foams away heavy grease, soil, body oils, and mineral deposits from fiberglass, tile, chrome, and plastics. **Outstanding grout cleaner...**especially effective on greasy, dirty ceramic floors found in kitchens, shower rooms, and supermarket venues. Green. Dilutes automatically with cold water (1:128) when used with a JAWS® 9000 Series Chemical Dispensing System™.

Formula Features

- Cuts soap scum and dissolves mineral deposits
- Brightens grout lines
- Contains organic acid for enhanced cleaning
- Special grease releasing agent
- May be used on most restroom surfaces

Applications *Concentrated

- Dilute with cold water using JAWS® 9000 Series Chemical Dispensing Systems™
- Effective on shower walls, floors, and ceramic tile to remove soap film buildup and eradicate mineral deposits. Recommended for mopping, foaming or brushing on tile floors in kitchen and food service areas.

Areas Of Utilization

- Shower Walls/Floors
- Kitchen Floors
- Beach Houses
- Locker Rooms
- Quarry Tile Floors
- Air Conditioner Coils

JAWS INTERNATIONAL, LTD. • 3610 N. Holland-Sylvania Rd. • Toledo, Ohio 43615
(866) 664-JAWS • fax: (419) 841-7597 • Visit Our Website: www.jawsinternational.com

JAWS® 9030 Multi-Surface Bathroom Cleaner

DIRECTIONS

Step 1: Remove cap from super concentrate bottle.

Step 2: Dock super concentrate bottle into the underside of your JAWS® 9000 Series Dispenser.

Step 3: Begin proportioning by pressing the appropriate fill button (high or low flow).

DIRECCIONES

Paso 1: Retire la tapa para protección de la botella de super concentrado.

Paso 2: Coloque la botella de super concentrado dentro de la parte Inferior de su dispensador de la Serie JAWS® 9000.

Paso 3: Comience dándole la proporción pulsando el botón apropiado de llenado (flujo alto o bajo).