

**FOR TERRAZZO AND RESILIENT TILE!**

FORMULATED WITH DURAPLUS® Highly acclaimed, internationally accepted, patented polymer system.

MULTIPLE SUBSTRATE COMPATIBILITY! Seals terrazzo, vinyl, vinyl composition and other resilient tile. Excellent adhesion and compatibility with other finishes.

**CUTTING EDGE TECHNOLOGY**

Made with the most advanced floor sealer polymers available. A solid base coat for premium finishes, providing low color, high depth-of-gloss results on terrazzo, travertine, marble, asphalt tile, vinyl composition, linoleum and other resilient floors.

**DIRECTIONS FOR USE**

**Initial Application**

1. Remove all old finish from floor. For new floors, stripping of factory applied finish is necessary. Rinse well and allow to dry.
2. Using a clean mop, apply sealer in a thin, uniform coat. Allow to dry thoroughly, (30 to 40 minutes). For very porous floors and higher base gloss, a second uniform coat should be applied.
3. Allow floor to dry completely, then apply floor finish in thin, uniform coats.

NOTE: To avoid product contamination, do not return any unused material to original container.

**Day-To-Day Maintenance**

1. Keep floor clean and free from dust and grit for maximum durability.
2. Maintain finish with appropriate method. See finish label for direction.

**SAFETY DATA CAUTION:** Keep out of reach of children. Do not swallow. May cause nausea. See Material Safety Data Sheet for further information.

**FIRST AID:** For eye contact, flush eye well with water and call a physician. If swallowed, get immediate medical attention.

**NOTE:** Water or other foreign substances will cause any seal to become slippery. **ALWAYS** use a “Wet Floor” sign when moisture is present.

**SPECIAL INSTRUCTIONS**

Engineered for safety. Exceeds industry standards for static coefficient

Manufactured By:  
CANBERRA CORPORATION  
3610 N. Holland-Sylvania Rd.  
Toledo, OH 43615  
P 419-841-6616 • F 419-841-7597

of friction (ASTM2047/82).

**Contains:** Water CAS# 7732-18-5, Polyacrylate CAS# 25987-66-0, Glycol Ether CAS# 111-90-0, TBEP CAS# 78-51-3.

**HUSKY 1001 VERSATILE PREMIUM FLOOR SEALER**



Eye and skin irritant. Avoid contact with eyes and skin. Wear suitable protective clothing. Keep out of reach of children. If in contact with eyes, flush with water for 15 minutes. Call a doctor if irritation persists. If in contact with skin, flush with water. Call a doctor if irritation develops. If ingested, do not induce vomiting. Call a doctor immediately.

**READ MATERIAL SAFETY DATA SHEET BEFORE USING PRODUCT.**

Irritant pour les yeux et la peau. Eviter le contact avec les yeux et la peau. Porter un vêtement de protection approprié. Garder hors de la portée des enfants. En cas de contact avec les yeux, laver à grande eau durant 15 minutes. Appeler un médecin si l'irritation persiste. En cas de contact avec la peau, laver immédiatement à grande eau. Appeler un médecin en cas d'irritation. En cas d'ingestion, ne pas tenter de faire vomir, consulter un médecin immédiatement.

**LIRE LA FICHE SIGNALETIQUE AVANT D'UTILISER CE PRODUIT.**

CANBERRA CORPORATION

Made in U.S.A.

For Industrial and Institutional Use Only

Keep From Freezing



011703-01



Husky®

**1001**

**VERSATILE PREMIUM FLOOR SEALER**

A Multi-Substrate Premium Floor Sealer.

**KEEP OUT OF REACH OF CHILDREN**

**CAUTION**

See back panel for additional precautionary information.

**Net Contents: One Gallon (128 Fl. Oz.) 3.78 liters**