

SAVES APPLICATION COSTS!

REQUIRES FEWER COATS!

A high solids, high performance UHS premium floor finish.

LOWER AND FASTER MAINTENANCE!

Propane burnishable. Combines high NVS (non-volatile solids) and excellent wearability with WET-LOOK gloss to save labor costs.

CUTTING EDGE TECHNOLOGY

Made with the most advanced floor finish polymers available. Excellent re-coat, slip, water, detergent and black heel mark resistance. Repairs readily with high speed equipment. Product is non-yellowing. For all types of resilient tile.

DIRECTIONS FOR USE:

Initial Application

1. Remove all old wax and floor finish with appropriate stripper.
2. Rinse floor thoroughly and allow to dry.
3. Using a clean mop, apply a thin, uniform coat of finish. Allow to dry thoroughly (30 to 40 minutes). Apply additional coats in the same manner and let dry. For very porous floors, an initial coat of floor sealer is recommended.

NOTE: To avoid product contamination, do not return any unused material to original container. Dispose of unused floor finish according to local regulations.

Day-To-Day Maintenance

1. Sweep or dust mop as necessary.
2. Damp mop with proper cleaner, following label directions. For accumulated soil, lightly scrub as required.
3. To repair finish, burnish using proper pad and equipment or top coat following Step 3 above.

SAFETY DATA

CAUTION: KEEP OUT OF REACH OF CHILDREN.

FIRST AID For eye contact, rinse eye well with water for 10-15 minutes. Get medical attention if irritation persists. **If swallowed**, have person sip small amounts of water. Get immediate medical attention.

NOTE: Water or other foreign substances will cause any floor finish to become slippery. **ALWAYS** use a "Wet Floor" sign when moisture is present. Clean up spills or wet areas immediately.

CONTAINS: Water CAS# 7732-18-5, Styrenated-acrylic copolymers CAS# N/A, Ethylene polymer CAS# N/A, Tributoxylethyl phosphate CAS# 78-51-3, Glycol Ether CAS# 111-90-0.

Manufactured By:
CANBERRA CORPORATION
3610 N. Holland-Sylvania Rd.
Toledo, OH 43615
P 419-841-6616 • F 419-841-7597

**HUSKY 1025 HIGH PERFORMANCE UHS
PREMIUM FLOOR FINISH**



Eye and skin irritant. Avoid contact with eyes and skin.

Wear suitable protective clothing. Keep out of reach of children.

If in contact with eyes, flush with water for 15 minutes. Call a doctor if irritation persists. If in contact with skin, flush with water. Call a doctor if irritation develops. If ingested, do not induce vomiting. Call a doctor immediately.

READ MATERIAL SAFETY DATA SHEET BEFORE USING PRODUCT.

Irritant pour les yeux et la peau. Eviter le contact avec les yeux et la peau. Porter un vêtement de protection approprié. Garder hors de la portée des enfants. En cas de contact avec les yeux, laver à grande eau durant 15 minutes. Appeler un médecin si l'irritation persiste. En cas de contact avec la peau, laver à grande eau. Appeler un médecin en cas d'irritation. En cas d'ingestion, ne pas tenter de faire vomir, appeler un médecin immédiatement.

LIRE LA FICHE SIGNALETIQUE AVANT D'UTILISER CE PRODUIT.

CANBERRA CORPORATION

Made in U.S.A.

For Industrial and Institutional Use Only

Keep From Freezing

Engineered for safety... this floor finish exceeds industry standards for static coefficient of friction (ASTM2047).

VOC COMPLIANT (<1% w/w)



090910-01



Husky®

1025

**HIGH PERFORMANCE
UHS PREMIUM
FLOOR FINISH**

A High Solids, High Performance,
UHS Floor Finish.

KEEP OUT OF REACH OF CHILDREN

CAUTION

See back panel for additional precautionary information.

Net Contents: One Gallon (128 Fl. Oz.) 3.78 liters