

Semi-permanent resilient tile floor and concrete sealer. Excellent penetration, quickly fills pores and seals tile floors. Easy to use, diamond-tough. Levels beautifully, providing exceptional durability, protection, and adhesion properties. Can be removed using a special stripper at specified use dilution. Resists stains such as iodine, betadine, mustard, catsup, coffee, tea, chocolate, rust, kool-aid and other dyed products.

DIRECTIONS FOR USE

1. Remove all old finish from floor. For new floors, stripping of factory applied finish is necessary. Rinse well with clean water and allow to dry.
2. Using a clean dry mop, or lamb's wool applicator, apply sealer in a thin, uniform coat. Allow to dry thoroughly, (30 to 40 minutes). For very porous floors and higher base gloss, a second uniform coat should be applied.
3. Allow floor to dry completely, then apply floor finish in thin, uniform coats.

PERFORMANCE DATA

Approximate Coverage..... 2000-2500 sq. ft./gal.
Adhesion..... Excellent
Finish Compatibility..... Excellent
Water Resistance..... Excellent
Detergent Resistance..... Excellent
Permanent..... Yes, can only be removed with special strippers.
Application Resilient Tile Floors Quarry Terrazzo Floors Sealed Wood Floors
Many Kinds of Concrete Floors

WARNING: Water or other foreign substances will cause any seal to become slippery. **ALWAYS** use a "Wet Floor" sign when moisture is present. NOTE: To avoid product contamination, do not return any unused material to original container.

SPECIAL INSTRUCTIONS

Engineered for safety... Exceeds industry standards for static coefficient of friction (ASTM2047/82).

Contains:

Water CAS# 7732-18-5, Styrene Acrylic Copolymer CAS# N/A, Diethylene Glycol Ethyl Ether CAS# 111-90-0, Diethylene Glycol Methyl Ether CAS# 111-77-3, Tributoxyl Ethyl Phosphate CAS# 78-51-3.

Manufactured By:
CANBERRA CORPORATION
3610 N. Holland-Sylvania Rd.
Toledo, OH 43615
P 419-841-6616 • F 419-841-7597

HUSKY 1000 SEMI-PERMANENT RESILIENT FLOOR AND CONCRETE SEALER



Eye and skin irritant. Avoid contact with eyes and skin. Wear suitable protective clothing. Keep out of reach of children. If in contact with eyes, flush with water for 15 minutes. Call a doctor if irritation persists. If in contact with skin, flush with water. Call a doctor if irritation develops. If ingested, do not induce vomiting. Call a doctor immediately. **READ MATERIAL SAFETY DATA SHEET BEFORE USING PRODUCT.**

Irritant pour les yeux et la peau. Eviter le contact avec les yeux et la peau. Porter un vêtement de protection approprié. Garder hors de la portée des enfants. En cas de contact avec les yeux, laver à grande eau durant 15 minutes. Appeler un médecin si l'irritation persiste. En cas de contact avec la peau, laver immédiatement à grande eau. Appeler un médecin en cas d'irritation. En cas d'ingestion, ne pas tenter de faire vomir, consulter un médecin immédiatement. **LIRE LA FICHE SIGNALETIQUE AVANT D'UTILISER CE PRODUIT.**

CANBERRA CORPORATION

Made in U.S.A.
For Industrial and Institutional Use Only
Keep From Freezing



101514



Husky®
1000

**SEMI-PERMANENT
RESILIENT FLOOR &
CONCRETE SEALER**

A Semi-Permanent Floor Seal with
Exceptional Durability, Protection,
Leveling, and Adhesion Properties.

KEEP OUT OF REACH OF CHILDREN

CAUTION

See back panel for additional precautionary information.

Net Contents: One Gallon (128 Fl. Oz.) 3.78 liters