



## FEATURES

747cc V-TWIN OHV EFI  
ENGINE

COLOR OPTIONS: YELLOW,  
CAMO, RED OR GREEN

47.7 FT-LBS OF TORQUE  
@ 2,400 RPM

11" GROUND CLEARANCE

3" LADDER-STYLE  
STEEL FRAME

14.4 CUBIC FOOT  
STEEL BED

ADJUSTABLE COIL-OVER  
SHOCKS

1-YEAR LIMITED  
WARRANTY†

## POWERFUL UTILITY. EXTREME VERSATILITY.

No matter what the job demands, the Volunteer™ series of 4x4 EFI utility vehicles delivers. With its on-demand 4x4 system, you get four-wheel drive performance at the flick of a switch. And with dual A-arm, independent suspension and adjustable coil-over shocks, no matter where you're headed, you'll be traveling in comfort.



### Unrivalled Versatility

With more than 40 available attachments, no task or adventure will hold you back. It's designed to do it all while letting you enjoy the outdoors.



### Haul the Heaviest Loads

With a 1,400 pound payload capacity\*, even large jobs are no match. The Volunteer™ takes it with ease, meaning fewer trips for you to get the job done faster.



### Ready for Anything

The Volunteer™ 4x4 EFI is ready for any job. On campus, at work or in the yard, finish what needs to get done while having some fun.



**Your Independent Dealer — Expert Service. Locally Owned.**

The advice, selection and support you need to find the right fit is at your local Cub Cadet Dealer.





## Acrylic Windshield (A200)

Mounts directly to OPS to protect operator and passenger from the elements.



## Soft Roof And Rear Window (A201/B201)

The Cub Cadet soft roof is made from weather-resistant, UV-coated nylon for durable protection.



## Light Bar (A70022)

Low-profile light bar has four 35-watt adjustable driving lights for added visibility.



## Warn® 4,000 lb Winch And Mounting Plates (A70015)

4,000 lb winch with remote control and steel cable. 3,500 lb mile marker winch also available. (A205)



## Hood Rack (A206)

Steel hood rack with headlight guards provides extra storage.



## 72" Super-Duty Snow Blade With Manual Angle (A70024)

Angles up to 28 degrees with heavy-duty skid shoes and four adjustable springs. Not compatible with winches. Winch not required.



## 14" Aluminum Rims And 26" Off-Road Tires (B235)

Set of four 14" aluminum rims and 26" heavy-duty, radial Goodyear® MTR tires.



## Bench Seat (A70003)

Comfortably fits two people for maximum efficiency.



## Complete Deluxe Cab (A70025-A70028)

The contoured design and thick poly reduce noise levels and provide maximum coverage for both the driver and passenger.

| ENGINE                    |   | 4x4 EFI |
|---------------------------|---|---------|
| Engine                    | 31 HP* Kohler® Aegis® V-Twin EFI  |         |
| Displacement              | 747 cc  |         |
| Fuel                      | Gas   |         |
| Torque                    | 47.7 ft-lbs at 2,400 rpm  |         |
| Ignition                  | Transistor controlled   |         |
| Lubrication               | Full pressure with spin-on oil filter                                   |         |
| Engine Cooling            | Liquid  |         |
| Air Cleaner               | Heavy-duty, replaceable   |         |
| SUSPENSION                |   |         |
| Shocks                    | Adjustable coil-over  |         |
| Travel                    | 8"  |         |
| FRAME                     |   |         |
| Frame                     | 3" ladder construction  |         |
| Receiver                  | 2"-class 1  |         |
| Bumper                    | Steel   |         |
| TRANSMISSION              |   |         |
| Drive                     | Enclosed CVT  |         |
| Front Differential        | Hilliard® front differential  |         |
| Rear Differential         | Mechanical differential   |         |
| Speed                     | 0-25 mph  |         |
| Transaxle                 | Fully enclosed, oil bath  |         |
| Selector                  | Hurst® shifter (H-L-N-R)  |         |
| Rear Axle Housing         | Cast-iron   |         |
| ELECTRICAL SYSTEM         |   |         |
| Battery                   | 450 cold crank amp  |         |
| Alternator                | 12V-65 amp  |         |
| Headlights                | Halogen 37.5 watts  |         |
| Wiring                    | Automotive fused  |         |
| Power Port                | 12V in-dash   |         |
| CONTROLS                  |   |         |
| Brakes                    | 4-wheel, 8" hydraulic disc  |         |
| Brake Lines               | Stainless steel braided   |         |
| Parking Brake             | Mechanical  |         |
| Steering                  | Rack and pinion   |         |
| Indicators                | Fuel, battery, oil, parking brake and hour meter                        |         |
| CAPACITY                  |   |         |
| Towing/Payload            | 1,400 lbs (total payload includes operator, passenger and bed capacity) |         |
| Fuel Tank                 | 6 gal   |         |
| Cargo Box                 | Steel (1,000 lbs) L / W / H: 51.6" / 42" / 11.5"                        |         |
| Storage                   | Glove box, under-seat   |         |
| SEATS                     |   |         |
| Seats                     | Sport   |         |
| TIRES                     |   |         |
| Tires                     | Trail   |         |
| Front Tire Size           | 26"x9"-12"  |         |
| Rear Tire Size            | 26"x11"-12"   |         |
| Rims                      | 12" steel   |         |
| DIMENSIONS                |   |         |
| Length / Width / Height   | 119" / 63.55" / 73"   |         |
| Track Width               | 52"   |         |
| Wheelbase                 | 78"   |         |
| Ground Clearance          | 11" (under foot platform)   |         |
| Turning Radius (diameter) | 11'   |         |
| Weight                    | 1,650 lbs   |         |
| WARRANTY*                 |   |         |
|                           | 1-year limited residential  |         |

Cub Cadet Utility Vehicles are intended for off-road use by adults only. They are neither designed nor equipped to be registered as motor vehicles for use on public roadways. Always use extreme caution when operating utility vehicles, and carefully follow all operating, maintenance and safety instructions and warnings. Please see the operator's manual and the warning labels posted on the vehicle itself for more details. This brochure is for advertisement purposes only. The product depictions are not meant to be used or relied upon as a substitute for the safety and use information that is published in the respective operator's manual. Before operating the machine, read, understand and follow all instructions in the manual and on the machine. Specifications and programs are subject to change without notice. Images may not reflect dealer inventory and/or unit specifications.

\* As rated by Kohler, all power levels are rated at 3600 RPM per SAE J1940 gross.

† See your local Cub Cadet Independent Dealer for warranty details. †† Built using the highest quality components sourced locally and globally. † See specifications for warranty information.

\*\*Includes operator, passenger and bed capacity.

