

Let's face it. The golf course isn't the only place where you want the perfect drive. Fortunately, with features like a streamlined body and responsible turning radius, The Drive® doesn't just look like a dream, it handles like one too. So, go ahead: Take the kids to the pool. Hit the tennis courts. And, if you happen to turn a few heads along the way, well...it's also available in envy green.



#### Maximum Efficiency or Maximum Power

Our EFI car has the best fuel efficiency of any on the market, while our AC Electric has incredible horsepower. Either choice takes you to the top. Low emissions make them the most environmentally friendly cars in the industry, so every ride is a clean getaway.



#### Head and taillights

The Drive® PTV comes standard with halogen headlights and taillights for maximum visibility and safety for your family.



#### ClimaGuard™ Top with dual gutters

This top comes with a 360° double rain channel, clog-proof downspouts, and a wider, longer coverage area. You and your personal belongings stay dry.







#### Long battery life

Yamaha uses only top of the line Trojan batteries in its AC models, so you get extensive battery life. That helps guarantee you'll always make it to the 19th hole.



### Rear seat grab handle

This rugged, powdercoated steel handle provides additional security and comfort for rear seat passengers.



## Largest, most comfortable seat in the industry

Made of pure supple foam bonded to a seamless, durable, vinyl-backed cover. Its polypropylene seat base won't sag, rot, or warp despite daily abuse and repeated washings.



## Mid-body seat storage Conveniently located

under the front seat (gas car only), extra storage space is always within reach.



### Side reflectors

Reflex reflectors on the front and rear make The Drive® Concierge easily visible from any direction, maximizing safety for everyone on board.



#### EFI or AC

Choice is one of Yamaha's greatest options. Whether you choose EFI or the AC model, rest assured you'll be getting excellent power and reliability.



#### STANDARD FEATURES



lift kit This new addition to Yamaha's Tru Trak™ II automotive-style suspension not only looks sportier, but allows for mounting larger vheels, and improves ground clearance.



Front brush guard Made of 3/16" steel, " round tubing, and 1-1/2" round tubing. Powder-coated for protection.




## Utility dump bed With a 7.8 cubic foot,

300 lb. payload capacity, pneumatic-assist tilting, fold & lock tailgate, and rotomolded linear polyethylene construction, this is where the hard work



#### Headlights & taillights If the sun goes down before the work is done, no worries. The Adventurer Sport comes standard with halogen headlights and taillights.



# 20" tires

These tough tires not only look great on the road, but they're perfect for navigating rougher terra off the road.



These sleek and stylish fender flares not only look great, but protect you, your passengers, and your car from flying debris.





#### Four cup holders; center storage area for wallets, cell phones, and personal items; six ball holders; six tee holders; and big, easy-to-clean storage compartments on each side. You may accidentally drive it home.



## Seating for four

The rear seat has a safety bar and full ootrest for maximum safety and comfort of your passengers. The rear seat flips down for added cargo space.



#### Flip down seat

When you need to carry cargo instead of people, the seat flips down, creating a flat bed with a 200 lb capacity.



#### Head and taillights

The Drive® PTV comes standard with halogen headlights and taillights. One more way we shed light on family safety



These tough tires not only look great on the road, but they're perfect for navigating rougher terrain off the road.



#### front suspension We designed a maintenance-

free suspension using automotive-style, coil-overshock struts to minimize roll and deliver a smooth, comfortable ride.

WARRANTY

PTV **CONCIERGE 4** 2395 mm (94.3 in) OVERALL LENGTH 3250 mm (128 in) OVERALL WIDTH 1200 mm (47.2 in) 1200 mm (47.2 in) Electric: 1821 mm (71.7 in) Electric: 1910 mm (75.2 in) OVERALL HEIGHT (with suntop) Gas: 1789 mm (70.4 in) Gas: 1910 mm (75.2 in) Electric: 1222 mm (48.1 in) Electric: 1222 mm (48.1 in) OVERALL HEIGHT (without suntop) Gas: 1190 mm (46.9 in) Gas: 1190 mm (46.9 in) 2492 mm (98.1 in) WHEELBASE 1640 mm (64.6 in) FRONT WHEEL TREAD 870 mm (34.3 in) 870 mm (34.3 in) REAR WHEEL TREAD 980 mm (38.6 in 980 mm (38.6 in) Electric: 148 mm (5.8 in) Electric: 148 mm (5.8 in) MINIMUM GROUND CLEARANCE Gas: 112 mm (4.4 in) Gas: 110 mm (4.3 in) FLOOR BOARD HEIGHT 342 mm (13.5 in) 342 mm (13.5 in) Hitachi 48-volt high-efficiency, shunt wound motor with 48-volt AC internal solid state tachome **OUTPUT RATING** 5.0 kW (6.7 hp) for 60 minutes MOTOR CONTROL UNIT NEOS 350 amp AC by TOYOTA industrial Corporation Standard: Six 8-volt Trojan T-875 **BATTERIES** Standard: Six 8-volt Trojan T-875 Optional: Eight 6-volt T-105 Optional: Six 8-volt Trojan Traveler CHARGER YAMAHA-built automatic microprocessor-based high frequency switching regulated charges **ENGINE TYPE** Yamaha-built, low-emission single cylinder 60° incline OHV DISPLACEMENT 357 сс BORE x STROKE 85 x 63 mm HORSEPOWER 8.5 kW/3500 rpm (11.4 hp) COMPRESSION RATIO LUBRICATION SYSTEM Splash-style positive oil lubrication OIL CAPACITY 1 liter, 1000 cc (1 U.S. quart) AIR CLEANER Two-stage, urethane-foam pre-cleaner, and high-capacity pleated paper cartridge COOLING SYSTEM Forced air FUEL SYSTEM Electronic fuel injection IGNITION SYSTEM Transistor magneto ignition STARTING SYSTEM Starter / Generator MAXIMUM TOROUS 25.5 Nm / 2,500 rpm HybriCore™ Chassis features a robotically welded automotive ladder-style frame mated to a polypropylene structural floor. Frame components are protected with a multi-step phosphate treatment, electro-deposition epoxy-based coating, and an electrostatically applied polyester/urethane powder topcoat Custom-formulated thermoplastic olefin painted with a two-part top coat of high luster automotive grade polyurethane Fiber reinforced plastic with a two-part top coat of high-luster BODY (INTERMEDIATE) N/A automotive-grade polyurethane STEERING Self-compensating double reduction helical rack-and-pinion, permanently lubricated with sealed, greaseless tie-rod ends FRONT SUSPENSION SYSTEM Tru-Trak II™ fully independent automotive-style strut suspension REAR SUSPENSION SYSTEM Unit swing arm with coil springs over hydraulic shock absorbers Self-adjusting mechanical rear drum Seamless, fabric-backed vinyl bonded to pure, virgin foam contoured seat cushions and matted to a warp and moisture-resistant polypropylene bottom strengthened with plated steel inserts Front and rear 5 mph energy-absorbing bumpers BUMPERS MAX FORWARD SPEED 31 km/h (19 mph) 31 km/h (19 mph) MAX REVERSE SPEED Electric: 9.7 km/h (6.0 mph) Gas: 16 km/h (13 mph) Electric: 16.1 km/h (6.0 mph) Gas: 16 km/h (13 mph) MINIMUM TURNING RADIUS 3.2 m (10.5 ft 4.56 m (15 ft) Electric: 273 kg (602 lbs) w/ suntop Electric: 349 kg (767 lbs) w/o suntop and batteries 447 kg (985 lbs) w/ Trojan T-875 batteries **DRY WEIGHT** 519 kg (1144 (lbs) w/ Trojan T-875 batteries Gas: 388 kg (855.4 lbs) w/ suntop Gas: 324 kg (714.3 lbs) w/ suntop **FUEL TANK CAPACITY** 22 liters (5.8 U.S. gal) TIRE SIZE 205/65-10 DOT (4 ply rating) SEATING CAPACITY 4 persons 2 persons AVAILABLE MODEL COLORS Glacier, Emerald, Tanzanite, Sandstone Metallic, Moonstone Metallic, Onyx Metallic, Jasper Metallic AVAILABLE SEAT COLORS Standard: Stone Optional: Black (rear flip seat only) **AVAILABLE SUNTOP COLORS** Stone, Black Stone, White, Black

Standard 2-year limited vehicle warranty

METALLIC

SANDSTONE

METALLIC

AVAILABLE COLORS: (Some may be Model-specific. Please see your Representative for details).

Standard 4-year limited vehicle warranty

MOONSTONE

METALLIC

ONYX METALLIC

GLACIER EMERALD. TANZANITE TORTUGA

ADVENTURER SPORT ADVENTURER SPORT 2+2 Electric: 2726 mm (107.3 in) **OVERALL LENGTH** 2765 mm (108.9 in) Gas: 2660 mm(104.7 in) Electric: 1296 mm (51 in) OVERALL WIDTH 1294 mm (50.9 in) Gas: 1243 mm( 48.9 in) Electric: 1844 mm (72.6 in) OVERALL HEIGHT (with suntop) 844 mm (72.6 in) Gas: 1773 mm (68.3 in) Electric: 1245 mm (49 in) OVERALL HEIGHT (without suntop) 1245 mm (49 in) Gas: 1198 mm (47.2 in) Electric: 1642 mm (64.6 i WHEELBASE 1642 mm (64.6 in) Gas: 1637 mm (64.4 in) FRONT WHEEL TREAD 883 mm (34 7 in) 980 mm (38.6 in) REAR WHEEL TREAD 980 mm (38.6 in) 980 mm (38.6 in) Electric: 171 mm (6.7 in) MINIMUM GROUND CLEARANCE 171 mm (6.7 in) Gas: 112 mm (4.4 in) FLOOR BOARD HEIGHT 365 mm (14.4 in) 365 mm (14.4 in) MOTOR Hitachi 48-volt high-efficiency, shunt wound motor with internal solid state tachometer **OUTPUT RATING** 5.0 kW (6.7 hp) for 60 minutes MOTOR CONTROL UNIT NEOS 350 amp AC by TOYOTA Industrial Corporation BATTERIES Standard: Six 8-volt Trojan T-875 Optional: Six 8-volt Trojan Traveler CHARGER Yamaha-built automatic microprocessor-based high frequency switching regulated charger. **ENGINE TYPE** Yamaha-built, low-emission single cylinder 60° incline OHV DISPLACEMENT 357 сс BORE x STROKE 85 x 63 mm HORSEPOWER 8.5 kW/3500 rpm (11.4 hp)

Two-stage, urethane-foam pre-cleaner, and high-capacity pleated paper cartridge

electrostatically applied polyester/urethane powder topcoat

Tru-Trak II™ fully independent automotive-style strut suspension

Unit swing arm with coil springs over hydraulic shock absorbers

 $HybriCore^{\intercal M}\ Chassis\ features\ a\ robotically\ welded\ automotive\ ladder-style\ frame\ mated\ to\ a\ polypropylene\ structural\ floor.$ 

Frame components are protected with a multi-step phosphate treatment, electro-deposition epoxy-based coating, and an

Custom-formulated thermoplastic olefin and the front is painted with a two-part top coat of high-luster automotive-grade

Self-compensating double reduction helical rack-and-pinion, permanently lubricated with sealed, greaseless tie-rod ends

CHASSIS

匝

GAS

COMPRESSION RATIO

LUBRICATION SYSTEM

OIL CAPACITY

AIR CLEANER

FUEL SYSTEM

FRAME

BODY

**STEERING** 

BRAKES

COOLING SYSTEM

**IGNITION SYSTEM** 

STARTING SYSTEM

MAXIMUM TORQUE

FRONT SUSPENSION

**REAR SUSPENSION** 

8 1

Forced air

Splash-style positive oil lubrication

1 liter, 1000 cc (1 U.S. quart)

Electronic fuel injection

Starter / Generator

25.5 Nm / 2500 rpm

polyurethane

Transistor magneto ignition

Self-adjusting, mechanical rear drum

Standard 2-year limited vehicle warranty

Seamless, fabric-backed vinyl bonded to pure, virgin foam contoured seat cushions and matted to a warp and moisture-resistant SEATING polypropylene bottom strengthened with plated steel inserts BUMPERS Front and rear 5 mph energy-absorbing bumpers MAX FORWARD SPEED 24 km/h (15 mph) MAX REVERSE SPEED Electric: 16.1 kmh (6.0 mph) Gas: 16 km/h (10 mph) Electric: 16.1 kmh (6.0 mph) Gas: 16 km/h (13 mph) MINIMUM TURNING RADIUS Electric: 3.1 m (10.3 ft) Gas: 2.8 m (9.2 ft) Electric: 3.1 m (10.3 ft) Gas: 3.0 m (9.8 ft) Electric: 316 kg (697 lbs) w/o suntop and batteries Electric: 414 kg (913 lbs) w/o suntop and batteries **DRY WEIGHT** 490 kg (1080 lbs) w/ Trojan T-875 batteries 589 kg (1298 lbs) w/ Trojan T-875 batteries Gas: 346 kg (760.6 lbs) w/suntop Gas: 411 kg (906.1 lbs) w/suntop CARGO BED CAPACITY 136 kg (300 lbs) 91 kg (200 lbs) FUEL TANK CAPACITY 22 liters (5.8 U.S. gal) Electric: 20 x 10-8 (4-ply rating) TIRE SIZE 20 x 10 - 8 (4-ply rating) Gas: 215/60-8 DOT (6 ply rating) SEATING CAPACITY 2 persons 4 persons Standard: Tortuga Glacier, Sunstone, Emerald, Tanzanite, Sandstone Metallic, AVAILABLE MODEL COLORS Optional: Tanzanite, Jasper Metallic Moonstone Metallic, Jasper Metallic AVAILABLE SEAT COLOR Stone Standard: Stone Optional: Black AVAILABLE SUNTOP COLOR Stone, White, Black Black

WARRANTY

See all models and accessories at

# YAMAHAGOLFCAR.COM

1.866.747.4027



1000 Highway 34 East Newnan, Georgia 30265 1.866.747.4027 www.yamahagolfcar.com



