Safety Data Sheet: CHEM-AQUA 31155

Supercedes Date 04/07/2014 **Issuing Date** 12/29/2014

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name CHEM-AQUA 31155
Recommended use Water treatment chemical
Information on Manufacturer
CHEM-AQUA, INC
BOX 152170
IRVING, TEXAS 75015

Product Code C777
Chemical nature Aqueous solution
Emergency Telephone Number
CHEMTREC® 800-424-9300
Telephone inquiry
972-579-2477

2. HAZARD IDENTIFICATION

Color Dark Amber **Physical State** Liquid **Odor** Sweet

GHS
Classification
Physical Hazards
Substances/mixtures corrosive to metal Category 1

Health Hazard
Skin Corrosion/Irritation Category 1
Serious Eye Damage/Eye Irritation Category 1
Other hazards
None

Labeling
Signal Word
DANGER

Hazard Statements
H314 - Causes severe skin burns and eye damage
H290 - May be corrosive to metals

Precautionary Statements
P280 - Wear protective gloves, protective clothing and eye protection.
P264 - Wash face, hands and any exposed skin thoroughly after handling.
P260 - Do not breathe mist
P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower
P332 + P313 - If skin irritation occurs, get medical attention.
P363 - Wash contaminated clothing before reuse
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 - Immediately call a physician
P304 + P340 - IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing.
P342 + P311 - If experiencing respiratory symptoms, call a physician
P301+ P330 + P331 - IF SWALLOWED: Rinse mouth. DO NOT induce vomiting. Call a physician if unwell.
P406 - Store in a corrosion-resistant container.
P390 - Absorb spillage to prevent damage
P501 - Dispose of contents and container in accordance with applicable regulations.

14 % of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION / INFORMATION ON INGREDIENTS

Component	CAS-No	Weight %
2-Phosphonobutane-1,2,4-tricarboxylic acid, sodium salt	40372-66-5	5-10
Sodium tolyltriazole	64665-57-2	3-7
Sodium polyacrylate	9003-04-7	1-5
Polymaleic acid, sodium salt	70247-90-4	1-5

Sodium hydroxide	1310-73-2	1-5

***

4. FIRST AID MEASURES

General advice Do not get in eyes, on skin or on clothing. Do not breathe mist.

Eye Contact Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Get medical attention immediately.

Skin Contact Remove immediately all contaminated clothing. Wash off immediately with plenty of water for at least 15 minutes. Get medical attention immediately.

Inhalation Move to fresh air. In case of shortness of breath, give oxygen. If breathing has stopped, apply artificial respiration. Get medical attention immediately.

Ingestion Drink 1 or 2 glasses of water. Do NOT induce vomiting. Get medical attention immediately. Never give anything by mouth to an unconscious person.

Notes to physician The product causes burns of eyes, skin and mucous membranes. Control of circulatory system, shock therapy if needed.

5. FIRE-FIGHTING MEASURES

Flash Point Does not flash **Method** Seta closed cup

Flammability Limits in Air % Hydrogen, by reaction with metals. **Upper** 75 **Lower** 4

Suitable Extinguishing Media

Carbon dioxide (CO2). Foam. Dry chemical. Water spray. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Specific hazards arising from the chemical

Contact with metals may evolve flammable hydrogen gas. Material can create slippery conditions.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

NFPA **Health** 3 **Flammability** 1 **Instability** 0

HMIS **Health** 3 **Flammability** 1 **Instability** 0

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions Use personal protective equipment. Ensure adequate ventilation. Prevent further leakage or spillage if safe to do so. Material can create slippery conditions.

Environmental Precautions Do not flush into surface water or sanitary sewer system.

Methods for Containment Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

Methods for Cleaning Up Pick up and transfer to properly labeled containers.

Neutralizing Agent Acetic acid, diluted.

7. HANDLING AND STORAGE

Handling Do not get in eyes, on skin or on clothing. Do not breathe mist.

Storage Store in original container. Metal containers must be lined. Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from direct sunlight. Freezing will affect the physical condition but will not damage the material. Thaw and mix before using.

Storage Temperature **Minimum** 40 °F / 4 °C **Maximum** 115 °F / 46 °C

Storage Conditions **Indoor** X **Outdoor** **Heated** **Refrigerated**

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines ***

Component	ACGIH TLV	OSHA PEL	NIOSH
Sodium polyacrylate	3 mg/m^3 PNOS	5 mg/m^3 PNOR	No data available
Sodium hydroxide	Ceiling: 2 mg/m^3	TWA: 2 mg/m^3	10 mg/m^3 Ceiling: 2 mg/m^3

Engineering Measures Ensure adequate ventilation, especially in confined areas. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction.

Personal Protective Equipment

Eye/Face Protection Tightly fitting safety goggles. Face-shield.

Skin Protection Wear suitable protective clothing, Impervious gloves.

Respiratory Protection In case of inadequate ventilation wear respiratory protection. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

General Hygiene Considerations Wear protective gloves/clothing. Ensure that eyewash stations and safety showers are close to the workstation location.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State	Liquid	**Viscosity**	Non viscous
Color	Dark Amber	**Odor**	Sweet
Odor Threshold	Not applicable	**Appearance**	Transparent
pH	> 13.4	**Specific Gravity**	1.154
Evaporation Rate	0.5 (BuAc = 1)	**Percent Volatile (Volume)**	86.4
VOC Content (%)	0	**VOC Content (g/L)**	0
Vapor Pressure	14.8 mmHg @ 70°F	**Vapor Density**	0.6 (Air = 1.0)
Solubility	Completely soluble	**n-Octanol/Water Partition**	No data available
Melting Point/Range	No data available	**Decomposition Temperature**	No data available
Boiling Point/Range	> 212 °F / 100 °C	**Flammability (solid, gas)**	No data available
Flash Point	Does not flash	**Method**	Seta closed cup
Autoignition Temperature	No information available.		
Flammability Limits in Air %	Hydrogen, by reaction with metals.	**Upper** 75 **Lower** 4	

10. STABILITY AND REACTIVITY

Chemical Stability Stable. Hazardous polymerization does not occur.
Conditions to Avoid None known
Incompatible Products Strong oxidizing agents, Acids, Light and/or alkaline metals, Halogenated hydrocarbon, Reducing agents, Aldehydes.
Hazardous Decomposition Products Carbon oxides, Nitrogen oxides (NOx), Hydrocarbons, Hydrogen cyanide, Phosphorus compounds, Contact with metals liberates hydrogen gas.
Possibility of Hazardous Reactions None under normal processing

11. TOXICOLOGICAL INFORMATION

Product Information No information available.

The following values are calculated based on chapter 3.1 of the GHS document (Rev. 3, 2009):
Oral LD50 No information available
Dermal LD50 No information available
Inhalation LC50
- **Gas** No information available
- **Mist** No information available
- **Vapor** No information available

Principle Route of Exposure Skin contact, Eye contact, Inhalation.
Primary Routes of Entry None known
Acute Effects
- **Eyes** Corrosive to the eyes and may cause severe damage including blindness.
- **Skin** Causes skin burns.
- **Inhalation** Harmful by inhalation. Causes burns.
- **Ingestion** If ingested, severe burns of the mouth and throat, as well as a danger of perforation of the esophagus and the stomach.

Chronic Toxicity Inhaled corrosive substances can lead to a toxic edema of the lungs.
Target Organ Effects Skin, Eyes, Respiratory system.
Aggravated Medical Conditions Respiratory disorders, Skin disorders.

Component Information

Acute Toxicity

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation	Draize Test	Other
Sodium polyacrylate	5000 mg/kg	2000 mg/kg	no data available	no data available	no data available
Sodium hydroxide	no data available	= 1350 mg/kg (Rabbit)	no data available	no data available	no data available

Component	Mutagenicity	Sensitization	Developmental Toxicity	Reproductive Toxicity	Target Organ Effects
Sodium hydroxide	no data available	no data available	no data available	no data available	eyes, respiratory system, skin

Carcinogenicity There are no known carcinogenic chemicals in this product.

12. ECOLOGICAL INFORMATION

Product Information

Toxicity to fish	Daphnia magna (Water flea)
LC50 854 mg/l 96h 922 mg/l 48h Pimephales promelas (fathead minnow)	LC50 1,525 mg/L 48h Ceriodaphnia dubia (water flea)

Component Information

Component	Toxicity to Algae	Toxicity to Fish	Microtox	Water Flea	log Pow
Sodium hydroxide	no data available	LC50 = 45.4 mg/L Oncorhynchus mykiss 96 h	no data available	no data available	N/A

Persistence and Degradability No information available.
Bioaccumulation No information available.
Mobility No information available.

13. DISPOSAL CONSIDERATIONS

Product Disposal Dispose of in accordance with local regulations.
Container Disposal Empty containers should be taken for local recycling, recovery, or waste disposal.

14. TRANSPORT INFORMATION

DOT
Proper Shipping Name CAUSTIC ALKALI LIQUIDS, N.O.S., (SODIUM TOLYLTRIAZOLE, SODIUM HYDROXIDE)
Hazard Class 8
UN-No UN1719
Packing Group II
Description UN1719, CAUSTIC ALKALI LIQUIDS, N.O.S., (SODIUM TOLYLTRIAZOLE, SODIUM HYDROXIDE), 8, PG II

TDG
Hazard Class 8
UN-No UN1719
Packing Group II

ICAO
UN-No UN1719
Proper Shipping Name CAUSTIC ALKALI LIQUIDS, N.O.S., (SODIUM TOLYLTRIAZOLE, SODIUM HYDROXIDE)
Hazard Class 8
Packing Group II
Shipping Description UN1719, CAUSTIC ALKALI LIQUIDS, N.O.S., (SODIUM TOLYLTRIAZOLE, SODIUM HYDROXIDE), 8, PG II

IATA
UN-No UN1719
Proper Shipping Name CAUSTIC ALKALI LIQUIDS, N.O.S., (SODIUM TOLYLTRIAZOLE, SODIUM HYDROXIDE)
Hazard Class 8
Packing Group II
Shipping Description UN1719, CAUSTIC ALKALI LIQUIDS, N.O.S., (SODIUM TOLYLTRIAZOLE, SODIUM HYDROXIDE), 8, PG II

IMDG/IMO
Proper Shipping Name CAUSTIC ALKALI LIQUIDS, N.O.S., (SODIUM TOLYLTRIAZOLE, SODIUM HYDROXIDE)
Hazard Class 8
UN-No UN1719
Packing Group II
Shipping Description UN1719, CAUSTIC ALKALI LIQUIDS, N.O.S., (SODIUM TOLYLTRIAZOLE, SODIUM HYDROXIDE), 8, PG II

15. REGULATORY INFORMATION

Inventories
TSCA Complies
DSL Complies
U.S. Federal Regulations
SARA 313
Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazardous Categorization

Acute Health Hazard	Chronic Health Hazard	Fire Hazard	Sudden Release of	Reactive Hazard

Yes	No	No	**Pressure Hazard** No	No

CERCLA

Component	Hazardous Substances RQs	CERCLA EHS RQs
Sodium hydroxide	1000 lb	Not applicable

16. OTHER INFORMATION

Prepared By	Rachael Mohochi
Supercedes Date	04/07/2014
Issuing Date	12/29/2014
Reason for Revision	No information available.
Glossary	No information available.
List of References.	No information available.

CHEM-AQUA, INCassumes no responsibility for personal injury or property damage caused by the use, storage, or disposal of the product in a manner not recommended on the product label. Users assume all risks associated with such unrecommended use, storage or disposal of the product. The information provided on this document is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.