ASHTON AS-C-SA (shown)







Ashton	(see online price list for com	plete :	specs)						
CODE	ITEM	W	D	АН	ВН	SW	SD	SH	WT
AS-C-SA	Chair	31.5	33.5	26.5	33.5	22	22	19	95
AS-L-SA	Loveseat	53.5	33.5	26.5	33.5	22	22	19	125
AS-S-SA	Sofa	75.5	33.5	26.5	33.5	22	22	19	145
AS-O	Ottoman	28.5	22.5	-	-	-	-	18	35

W=Width D=Depth AH=Arm Height BH=Back Height SW=Seat Width SD=Seat Depth SH=Seat Height WT=Weight

ASHTON SPECIFICATIONS signature series **9**

BACK

The back frame is constructed with $^{7}/\!\!\! 8"$ engineered paneling with the support system constructed of 11-gauge sinuous wire linked together with a 12-gauge tie wire. The back support system is covered with woven versare fabric with one piece of high-density polymeric foam. The outside back of the frame is covered with woven typar and an additional piece of high-density polymeric foam. The back frame is secured to the base frame with patented metal brackets attached to the base frame with metal-to-metal connections.

RASE

The base frame is constructed completely of 7/8" engineered paneling. Patented metal brackets are attached to the base frame with 5/16" -18 x 1" button-head cap screws into steel receivers (t-nuts) creating a metal-to-metal connection. Legs are attached with steel bolts and feet have plastic or metal glides.

SEAT

Seat cushions are of high-density, polymeric foam. The top and bottom is covered with a laminated, polyurethane, moisture-barrier membrane. The cushion is secured to the base frame by a nylon security strap (steel cable optional). Uniform seating comfort is provided by a dual-leverage amplification Spring System.

ARWM

Arm frames are constructed completely of 7/8" engineered paneling and 80-point chipboard. The arm frames are covered with polymeric high-density urethane foam. The arm frame is attached to the base frame by sliding machined slots onto patented metal brackets on the base frame.

> AS-L-SA loveseat

UPHOLSTERY

All upholstery offerings conform to California Technical Bulletin 117 fire code standard. All estimated yardage quotes are based on 54" non-matched, solid color material unless otherwise specified. Additional yardage and matching fees may apply.

ASSEMBLY AND DISASSEMBLY

No tools are needed. All components can be disassembled and removed by loosening the thumbscrew and sliding the components out of the tamper-proof interlocking state. Assembly can be completed within minutes without the usage of tools, and all upholstery fastens with hook and loop tape, facilitating removal and replacement of covers.

This product is warranted against defects in materials and workmanship and against structural damage occurred through normal use for 35-years from date of purchase. Foam is also covered under the 35-year period while fabric is generally covered under the fabric company's warranty. Transformations does not warrant any materials beyond its

ADDITIONAL OPTIONS

CAL 133 fabric treatment may also be applied for an additional fee per yard.

This is an abbreviated specifications list. For complete specs, contact Customer Service.

AVAILABLE OPTIONS:

UPGRADE OPTIONS: CAL133

SEE PRICE LIST FOR MORE INFORMATION

FOOT OPTIONS:

SF09

STAIN CHOICES: Black, Hickory, Natural, Sable, Sienna, Umber

Visit our **Options**

web page for samples.







AS-0 ottoman



AS-C-SA chair



Transformations Furniture 310 Racquet Drive Fort Wayne IN 46825 www.trfurniture.com customerservice@trfurniture.com phone: 800.440.9337