



## PRODUCT DATA SHEET

### **BWT 6475 - MULTIPURPOSE LIQUID TREATMENT**

#### **GENERAL DESCRIPTION:**

BWT 6475 is a multipurpose liquid internal boiler treatment containing natural and polymeric sludge conditioners, oxygen scavenger, iron sequestrant, and alkalinity builder designed for low-hardness feedwater. BWT 6475 is authorized by the United States Department of Agriculture for use in federally inspected facilities.

#### **PRODUCT CHARACTERISTICS:**

Form.....Light Brown Liquid  
pH.....Approximately 9.0  
Density.....9.83 lbs./gallon

#### **FEEDING:**

BWT 6475 can be fed directly from the shipping container to the deaerator storage section, feedwater line or boiler. Automatic and continuous feed is recommended for best results.

#### **PRECAUTIONS AND HANDLING:**

Product is an alkaline material. Avoid contact with skin and eyes. Do not take internally. Protective gloves and chemical splash goggles are recommended. Wear impervious apron and boots to minimize potential contact. General ventilation is adequate, however, a NIOSH approved breathing apparatus should be used for exposures above OSHA threshold limit values. Consult material safety data sheet for more information.

#### **PACKAGING:**

55 GALLON DRUMS  
30 GALLON DRUMS  
5 GALLON PAILS