



## PRODUCT DATA SHEET

### **BWT 6321 - SLUDGE CONDITIONER**

#### **GENERAL DESCRIPTION:**

BWT 6321 contains a blend of synthetic polymers, an iron sequestrant, and natural organic dispersants for suspension of sludge in boiler systems. The suspended sludge is readily removed by means of continuous and/or bottom blowdown. BWT 6321 is especially effective in boiler systems which contain an appreciable amount of iron. BWT 6321 is authorized by the United States Department of Agriculture for use in federally inspected facilities.

#### **PRODUCT CHARACTERISTICS:**

Form.....Light Brown Liquid  
pH.....Approximately 9.50  
Density.....9.25 lbs./gallon

#### **FEEDING:**

BWT 6321 may be mixed with other boiler treatment compounds and there are no restrictions on this product relative to point of feed.

#### **PRECAUTIONS AND HANDLING:**

Product is an alkaline material. Avoid contact with skin and eyes. Do not take internally. Protective gloves and chemical splash goggles are recommended. Wear impervious apron and boots to minimize potential contact. General ventilation is adequate, however, a NIOSH approved breathing apparatus should be used for exposures above OSHA threshold limit values. Consult material safety data sheet for more information.

#### **PACKAGING:**

55 GALLON DRUMS  
30 GALLON DRUMS  
5 GALLON PAILS