



PRODUCT DATA SHEET

CWT 8562 - CLOSED SYSTEM TREATMENT

GENERAL DESCRIPTION:

CWT 8562 is a highly effective molybdate based corrosion inhibitor. CWT 8562 is buffered with borate, contains tolyltriazole for protection of multi-metal systems, and also contains a polymer to disperse iron in a closed system. CWT 8562 is designed for use in both hot and chilled water systems.

PRODUCT CHARACTERISTICS:

Form Golden Liquid
pH..... Approximately 13.0
Density..... 10.79 lbs./gallon

FEEDING:

CWT 8562 may be introduced to closed recirculating waters by use of a by-pass feeder or any other method of insuring complete system distribution. Consult your service representative for specific recommendations.

PRECAUTIONS AND HANDLING:

Product is an alkaline material. Avoid contact with skin and eyes. Do not take internally. Protective gloves and chemical splash goggles are recommended. Wear impervious apron and boots to minimize potential contact. General ventilation is adequate; however, a NIOSH-approved respirator should be used when airborne exposure limits are exceeded. Consult material safety data sheet for more information.

PACKAGING:

275 GALLON TOTES
55 GALLON DRUMS
30 GALLON DRUMS
15 GALLON DRUMS
5 GALLON PAILS