



PRODUCT DATA SHEET

CWT 8448 - MULTIPURPOSE SCALE AND CORROSION INHIBITOR

GENERAL DESCRIPTION:

CWT 8448 concentrated cooling water treatment is a combination scale retardant, antifoulant and corrosion inhibitors for protection of all cooling system metals. CWT 8448 is recommended for use in industrial process, air wash and other open recirculating cooling systems. CWT 8448 contains a unique tracer for ease and accuracy of testing.

PRODUCT CHARACTERISTICS:

Form.....Light Golden Liquid
pH.....Approximately 12.5
Density.....9.97 lbs./gallon

FEEDING:

CWT 8448 may be pumped directly from the shipping container to a point of rapid circulation within the cooling water system. Care should be taken to utilize corrosion resistant materials in the feed system. If CWT 8448 is to be diluted, softened or low hardness water should be used. Consult your service representative for specific recommendations.

PRECAUTIONS AND HANDLING:

Product is an alkaline material. Avoid contact with skin and eyes. Do not take internally. Protective gloves and chemical splash goggles are recommended. Wear impervious apron and boots to minimize potential contact. General ventilation is adequate, however, a NIOSH approved breathing apparatus should be used for exposures above OSHA threshold limit values. Consult material safety data sheet for more information.

PACKAGING:

55 GALLON DRUMS
30 GALLON DRUMS
5 GALLON PAILS