SPECIFICATION SHEET
INNO795™ & INNO790™

STRUCTURAL FIREFIGHTING GLOVE

OUTER SHELL
Lightweight yet tough Kangaroo shell delivers increased dexterity and cut resistance. Secure grip, wet or dry with minimal water absorption

MOISTURE BARRIER
PYRO-PRO™ glove inserts, **Exclusively at INNOTEX®**, offers outstanding dexterity with excellent breathability in the palm and added thermal protection on the back-of-the-hand

LINING
Nomex®/Kevlar® lining for superior heat and slash protection

FEATURES
- **TRU-3D™** glove style, **Exclusively at INNOTEX®** with **complete fourchettes** on all sides of every finger and thumb from cuff to cuff for improved fit and dexterity
- **PIVOT-THUMB™,** natural / anatomically correct thumb to finger movement for better grip
- Formed knuckle-guard for better flexibility and grip; less hand fatigue
- Exclusive liner retention system helps prevent liner shifting and pull-out
- Thumb seam welt for increased abrasion resistance in this critical area
- Kevlar® thread with lock stitching on the shell for added strength and heat resistance
- Nomex® thread with lock stitching on lining
- ½" Heavy duty elastic sewn around the entire wrist helps prevent the glove from falling off the hand by keeping a snug fit around the wrist
- Compliant to NFPA 1971:2013

REGULAR STYLE

INNO795™ Back

INNO795™ Palm

WRISTLET STYLE
Also available as INNO790™ using 2 layers of black Nomex® knit for additional protection

Sizes	• Regular: XXS to XXL • Cadet: L and XL
Packaging	12 pairs per case
Case	12" x 12" x 12" (30.5 cm x 30.5 cm x 30.5 cm)
Case weight*	8.3 lbs (3.7 Kg)

*Based on typical order

MANUFACTURED IN USA

275 Gouin, Richmond, Québec J0B 2H0
2397 Harts Ferry Road, Ohatchee, Alabama 36271
Tel.: 1-888-821-3121 / 819-826-5971 Fax: 819-826-5195
www.innotexprotection.com