

TERRAINKING™

Engineering Practical Solutions™

A Member of Alamo Group

Mississippi State Contract - Grounds Maintenance Equipment

Wholegoods Pricing

Effective March 1, 2015- February 2016



Full Line

Full Line Price Book

15% Off List

Section

Index

KB1800-2200 Booms

Terrain Master RH

Terrain Master DW

Flail King

KSM60 Mower

KSB6 Mower



KB1800-2200

Mid-Mount Boom Mowers

F.O.B Seguin, TX

STANDARD SPECIFICATIONS

- ◆ Bolt-On Undermount with Front and Rear Attached Rails
- ◆ Exclusive Slewing Ring Bearing is Featured for Boom Maneuverability
- ◆ Standard Boom Structure Made from Alloy Steel
- ◆ Main Pivot Features 2" Chrome Pins with Greaseable, Hardened Steel Bushings
- ◆ Self Contained Front Mounted Hydraulic System
- ◆ Oil-to-Air Cooler with Electric Fan
- ◆ Ability to Mow Horizontally within 6" of Rear Tire with Swivel Heads
- ◆ Boom Features Dipper and Lift
- ◆ Boom Reach Specs: **18' Models**= Up 17'-1", Out-18', Down 9'-8"
22' Models= Up-19' 7", Out-22', Down-12' 1"
- ◆ 180° Horizontal Boom Swing
- ◆ Axle-Mounted Boom Rest
- ◆ Mount Kit, all Wheel Weight, and Polycarbonate Window Included in Base Price
- ◆ Tractor Req: Min of 8,500 lbs and 90 HP. Min 90" Wheelbase and 18" Ground Clearance

HEAD SPECIFICATIONS

- ◆ 58" Cutting Diameter
- ◆ Alloy Deck Material with Double Wall Side Skirt
- ◆ 4-1/2"x9" Heat-Treated Alloy Spindle
- ◆ 152 HP Motor Direct-Coupled
- ◆ 2-1/2" x 5" Stacked Three-Leaf Blade Bar, Alloy Steel
- ◆ 5/8" x 5" High-Carbon Alloy Steel Blade, 360° Swing
- ◆ Standard (1) year limited parts and labor warranty.

PRODUCT ORDER CODE	DESCRIPTION	APPRX. WEIGHT		LIST PRICE
Boom Mower Base Unit (One Choice Required)				
30004831820	KB1800 Boom with Electronic Joystick Control	5,000		47,403
30004831821	KB1800 Boom with Cable/Lever Control	5,000		39,749
30004832220	KB2200 Boom with Electronic Joystick Control	5,200		48,750
30004832221	KB2200 Boom with Cable/Lever Control	5,200		41,736
Mower Head (One Choice Required)				
34802986190	5' Rotary w/ Center Hyd Door, Blade Bar & Head Swivel	1,115		15,736
34802986203	5' Rotary w/ Center Hyd Door, Blade Bar (No Head Swivel)	1,061		13,565
34802986251	4' Heavy Duty Flail w/ Center Hyd Door & Head Swivel	968		15,577
34802986253	4' Heavy Duty Flail w/ Center Hyd Door (No Head Swivel)	777		13,406
34802986252	4' Grass Flail w/ Head Swivel Equipped w/ Flail King Style Cuttershaft- 3 oz Knives	787		16,851
34802986235	90" Saw Head- 4 Blade (No Head Swivel)	968		16,709
34802988854	M22 Maintainer Head (Hitch Post Mounted)			13,786



1502 E. Walnut St., Seguin, TX 78155
 800-882-5756 800-882-5758 fax
 boom@terrainking.com
 oemparts@terrainking.com



KB1800-2200

Mid-Mount Boom Mowers

F.O.B Seguin, TX

PRODUCT ORDER CODE	DESCRIPTION	APPRX. WEIGHT		LIST PRICE
Options				
30002983328A	Additional Operators and Parts Manuals			56
33002989326	Quick Hitch Kit- Converts Boom & One Cutting Head			4,229
33002989327	Quick Hitch Aux.Kit- One Required for each Additional Head			560
30002975647	Jack Stand Kit- Heavy Duty Flail ***			355
30802990399	Jack Stand Kit- M22- Maintainer ***			700
30002988458	High Wear Kit- Rotary Head			1,186
30002988459	High Wear Kit- Heavy Duty Flail Head			1,849
30002990017	High Wear Kit- Grass Flail Head Equipped w/ Flail King Style Cuttershaft- 3 oz Knives			1,388
30002988460	High Wear Kit- Saw Head			2,511
30002985029	Mounting Labor, Calcium Chloride, and Oil			6,895
30000889809	Additional 12 Month Warranty			4,211
Mount Kit (One Choice Required)				
30002988674	KB 18000- M108S Series Cab 2 & 4wd w/ Cast Rear Wheels- Cable Controlled			N/C- In Base Price
30002988675	KB1800- M108S Series Cab 2 & 4wd w/ Pressed Steel Rear Wheels- Cable Controlled			N/C- In Base Price
30002988676	KB1800- M108S Series Cab 2 & 4wd w/ Cast Rear Wheels- Joystick Controlled			N/C- In Base Price
30002988677	KB1800- M108S Series Cab 2 & 4wd w/ Pressed Steel Rear Wheels- Joystick Controlled			N/C- In Base Price
30002987087	KB 22000- M108S Series Cab 2 & 4wd w/ Cast Rear Wheels- Cable Controlled			N/C- In Base Price
30002987085	KB2200- M108S Series Cab 2 & 4wd w/ Pressed Steel Rear Wheels- Cable Controlled			N/C- In Base Price
30002987084	KB2200- M108S Series Cab 2 & 4wd w/ Cast Rear Wheels- Joystick Controlled			N/C- In Base Price
30002987080	KB2200- M108S Series Cab 2 & 4wd w/ Pressed Steel Rear Wheels- Joystick Controlled			N/C- In Base Price
30002992224	KB2200- M100-110GX Series Cab 2 & 4wd w/ Cast Rear Wheels- Joystick Controlled			N/C- In Base Price
30002994117	KB2200- M108S- M100-110GX Series Cab 2 & 4wd w/ Pressed Steel Rear Wheels- Joystick Controlled			N/C- In Base Price

*** Required to level the head for Quick Hitch applications



1502 E. Walnut St., Seguin, TX 78155
 800-882-5756 800-882-5758 fax
 boom@terrainking.com
 oemparts@terrainking.com



Terrain Master RH 62, 74 and 88

Right-Hand Flail Mowers

F.O.B Seguin, TX

STANDARD SPECIFICATIONS

- ♦ Full-Length Welded Tubular Frame with Transport Lock
- ♦ 10-Gauge Unitized Cutter Housing
- ♦ 1/2" Inboard & 5/16" Outboard Side Plates
- ♦ Replaceable Skid Shoes
- ♦ 4-1/2" x 5/16" Wall Cuttershaft
- ♦ 1-5/16" Bore Greaseable, Self-aligning Cuttershaft Bearings
- ♦ Belt Drive from Gearbox to Cuttershaft with Automatic Spring Tension
- ♦ 6" Adjustable Rear Roller
- ♦ 1" - 6" Cutting Height Adjustment

- ♦ 74", or 88" Cutting Widths
- ♦ Piston Pump Rated @ 24 GPM @ 3800 PSI
- ♦ 2-Spool Valve with Float Detent Position
- ♦ Automatic Cut-Off Switch
- ♦ 60 HP Piston Motor
- ♦ 25-Gallon Reservoir with 10 Micron Filtration
- ♦ Front & Rear Deflectors

General Specs:

- ♦ Cutting Capacity: 1" diameter material
- ♦ Standard (1) year limited parts and labor warranty

PRODUCT ORDER CODE	DESCRIPTION	APPRX. WEIGHT		LIST PRICE
Base Unit (One Choice Required)				
348988001	62" RH Terrain Master, 3 oz Knives	1,200		21,104
348988004	62" RH Terrain Master, 4 oz Knives	1,205		21,253
348988005	74" RH Terrain Master, 3 oz Knives	1,200		22,017
348988008	74" RH Terrain Master, 4 oz Knives	1,205		22,167
348988009	88" RH Terrain Master, 3 oz Knives	1,200		22,259
348988012	88" RH Terrain Master, 4 oz Knives	1,205		22,405
Mount Kit (One Choice Required)				
30002985128 30002985084	M108S Series Cab 2 & 4wd (4wd models require clipped foot guards below)			9,553
30802990553 30002990554	M8560-9960 Series Cab 2 & 4wd (4wd models require clipped foot guards below)			9,553
Options				
348988058	96" Flail King, Centered, 3 oz. knives	1170		8,385
348988067	96" Flail King, Centered, 4 oz. knives	1185		8,668
300107532	62" RH Clipped Foot Guard (Required on 4wd Models)			384
300107519	74" RH Clipped Foot Guard (Required on 4wd Models)			422
300107524	88" RH Clipped Foot Guard (Required on 4wd Models)			460
37002990357A	Additional Operators and Parts Manuals			56
308701150	Lift Chain (2 Ea. Required on Centered Units)	7		106
30002987303	High Wear Kit- Right Wing Mowers			670
30002991274	High Wear Kit- Rear Flail Mower			664
300801022	Mounting Charges- Labor & Oil			4,777
30000889899	Additional 12 Month Warranty			4,251



1502 E. Walnut St., Seguin, TX 78155
 800-882-5756 800-882-5758 fax
 boom@terraining.com
 oemparts@terraining.com



Terrain Master 19'4" and 21'7"

Tri-Wing Flail Mowers

F.O.B Seguin, TX

STANDARD SPECIFICATIONS

Base Unit

- ♦ 19'4" and 21'7" Overall Cutting Widths
- ♦ Full-Length Welded Tubular Frame with Transport Lock
- ♦ 25-Gallon Reservoir with 10 Micron Filtration
- ♦ Tandem Piston Pumps Rated @ 24 GPM @ 3800 PSI
- ♦ 4-Spool Valve with Float Detent Position
- ♦ 1-15/16" Bore Greaseable, Self Aligning Cuttershaft Bearings

Wing Mower Specifications

- ♦ 74", or 88" Cutting Widths
- ♦ 1/2" Inboard & 5/16" Outboard Side Plates
- ♦ Replaceable Skid Shoes
- ♦ 4-1/2" x 5/16" Wall Cuttershaft
- ♦ 1-5/16" Bore Greaseable, Self-aligning Cuttershaft Bearings
- ♦ 53 HP Piston Motor
- ♦ Belt Drive from Gearbox to Cuttershaft with Automatic Spring Tension
- ♦ 6" Adjustable Rear Roller
- ♦ 1" - 6" Cutting Height Adjustment
- ♦ Front & Rear Deflectors

Wing Mower Specifications Continued

- ♦ Automatic Cut-Off Switch
- ♦ 10-Gauge Unitized Cutter Housing

Rear Mower Specifications

- ♦ 96" Cutting Width
- ♦ 10-Gauge Unitized Cutter Housing
- ♦ 5/16" Side Plates
- ♦ CAT I or CAT II Three-Point Hitch
- ♦ 4-1/2" x 5/16" Wall Cuttershaft
- ♦ 1-15/16" Bore Greaseable, Self Aligning Cuttershaft Bearings
- ♦ 60 HP Gearbox
- ♦ 6" Adjustable Rear Roller
- ♦ 1" - 6" Cutting Height Adjustment
- ♦ Front & Rear Deflectors
- ♦ CAT 4 Driveline
- ♦ Belt Drive from Gearbox to Cuttershaft with Automatic Spring Tension

General Specs:

- ♦ Cutting Capacity: 1" diameter material
- ♦ Standard (1) year limited parts and labor warranty

PRODUCT ORDER CODE	DESCRIPTION	APPRX. WEIGHT		LIST PRICE
Base Unit (One Choice Required)				
34802990743	19'4" Terrain Master, 3 oz Knives	4,570		46,692
34802990744	19'4" Terrain Master, 4 oz Knives	4,574		47,036
34802990745	21'7" Terrain Master, 3 oz Knives	4,620		47,428
34802990746	21'7" Terrain Master, 4 oz Knives	4,624		47,770
Mount Kit (One Choice Required)				
30002990742	M108S- Series Cab 2 & 4wd	1,170		14,845
30002994030	M8560-9960 Series Cab 2 & 4wd (4wd models require clipped foot guards below)	1,170		14,845
Options				
300107532	62" RH Clipped Foot Guard (Required on 4wd Models)			384
300107533	62" LH Clipped Foot Guard (Required on 4wd Models)			384
300107519	74" RH Clipped Foot Guard (Required on 4wd Models)			422
300107520	74" LH Clipped Foot Guard (Required on 4wd Models)			422
300107524	88" RH Clipped Foot Guard (Required on 4wd Models)			460
300107525	88" LH Clipped Foot Guard (Required on 4wd Models)			460



1502 E. Walnut St., Seguin, TX 78155

800-882-5756 800-882-5758 fax

boom@terraining.com

oemparts@terraining.com



Terrain Master 19'4" and 21'7"

Tri-Wing Flail Mowers

F.O.B Seguin, TX

PRODUCT ORDER CODE	DESCRIPTION	APPRX. WEIGHT		LIST PRICE
Options				
37002990357A	Additional Operators and Parts Manuals			56
308701150	Lift Chain (2 Ea. Required on Centered Units)	7		106
33002972480	Left-Wing Remote Positioning System			3,123
30002987303	High Wear Kit- Right & Left Wing Mowers (2 required)			670
30002991274	High Wear Kit- Rear Flail Mower			664
300803399	Mounting Charges- Labor & Oil			7,768
30000889899	Additional 12 Month Warranty			5,453



1502 E. Walnut St., Seguin, TX 78155
800-882-5756 800-882-5758 fax
boom@terraining.com
oemparts@terraining.com



FLAIL KING 74, 88, 96

3-Point Mount Flail Mowers

F.O.B Seguin, TX

STANDARD SPECIFICATIONS

- ♦ 74", 88", 96" Cutting Widths
- ♦ 10-Gauge Unitized Cutter Housing
- ♦ 5/16" Side Plates
- ♦ CAT I or CAT II Three-Point Hitch
- ♦ 4-1/2" x 5/16" Wall Cuttershaft
- ♦ 1-15/16" Bore Greaseable, Self Aligning Cuttershaft Bearings
- ♦ 60 HP Gearbox
- ♦ CAT 4 Driveline
- ♦ Belt Drive from Gearbox to Cuttershaft with Automatic Spring Tension
- ♦ 6" Adjustable Rear Roller
- ♦ 1" - 6" Cutting Height Adjustment
- ♦ Front & Rear Deflectors
- ♦ Factory Set-Up
- ♦ Cutting Capacity: 1" diameter material
- ♦ Standard (1) year limited parts and labor warranty

Tractor Requirements

- ♦ 74" Req: Min 35 HP
- ♦ 88" Req: Min 40 HP
- ♦ 96" Req: Min 50 HP

PRODUCT ORDER CODE	DESCRIPTION	APPRX. WEIGHT		LIST PRICE
Base Unit (One Choice Required)				
34802990739	74" Flail King , Center, 3 oz Knives	930		7,425
34802990740	74" Flail King, Center, 4 oz Knives	930		7,641
348988037	88" Flail King , Center, 3 oz Knives	1,035		7,529
348988040	88" Flail King, Center, 4 oz Knives	1,035		7,788
348988058	96" Flail King , Center, 3 oz Knives	1,170		8,385
348988067	96" Flail King, Center, 4 oz Knives	1,170		8,668
Options				
37002990357A	Additional Operators and Parts Manuals			56
308701150	Lift Chain (2 Ea. Required on Centered Units)	7		106
30002991274	High Wear Kit- Rear Flail Mower			664
30000889899	Additional 12 Month Warranty			1,815
30000888990	Dealer Mounting- Setup Fee			212



1502 E. Walnut St., Seguin, TX 78155
800-882-5756 800-882-5758 fax
boom@terrainking.com
oemparts@terrainking.com



KSM60

60" Mid-Mount Rotary

F.O.B Seguin, TX

STANDARD SPECIFICATIONS

- ♦ Welded Steel Plate Frame Braced to the Front Bolster & Rear Axle
- ♦ 53-Gallon Hydraulic Reservoir with 12-Micron Filtration
- ♦ Lift Frame Capable of Tilting the Head 180°
- ♦ Lift Frame is Capable of Lifting the Head 17" Above & 6" Below Grade Level
- ♦ Stacked Hydraulic Pump Rated @ 51 GPM @ 2500 PSI
- ♦ 2-Spool, Open Center, Tapered Positive Metering Valve
- ♦ Min Tractor Req: 60 PTO HP
- ♦ Cutting Capacity: 2" material
- ♦ Standard (1) year limited parts and labor warranty

HEAD SPECIFICATIONS

- ♦ 60" Rotary Head
- ♦ 1/4" Gauge Deck with 3/8" Side Skirts
- ♦ Channel Reinforcements on the Top Deck
- ♦ Spindle Mounting Plate is 1" at the Spindle
- ♦ 90 HP Gear Motor Directly Splined to the Spindle
- ♦ 4-1/2"x9" Hardened Spindle
- ♦ 1-1/4"x6" Blades, 360° Swing
- ♦ 360° Swinging Updraft Blades
- ♦ Full-Length Replaceable Skid Shoes
- ♦ Front & Rear Chain Guards

PRODUCT ORDER CODE	DESCRIPTION	APPRX. WEIGHT		LIST PRICE
Mower Base Unit (One Choice Required)				
31804950005	Rotary- Extreme Service Extension Arm-Cab	2,300		7,237
31804950009	Rotary- Breakaway Extension Arm-Cab	2,370		9,581
Mower Head (One Choice Required)				
34802964876	60" Rotary with Bar, Front & Rear Chain Guards	1,050		9,673
34802964878	60" Rotary with Pan, Front & Rear Chain Guards	1,100		10,575
34802964884	60" Breakaway Rotary with Bar, Front & Rear Chain Guards	1,050		10,416
34802964886	60" Breakaway Rotary with Pan, Front & Rear Chain Guards	1,100		11,411
Mount Kit (One Choice Required)				
30002989855	M108S Cab 2 & 4wd- Under Fender Tank			7,393
30002993586	M8560/9960 Cab 2 & 4wd- Under Fender Tank			7,393
Options				
348FK96185CC	96" Flail King- 18.5" Offset Rear Flail Unit- CC Knives			8,385
348FK96185ES	96" Flail King- 18.5" Offset Rear Flail Unit- ES Knives			8,668
30002972609	Wheel Weight Kit-500 lbs.			1,356
30002971789	Wheel Weight Kit-1300 lbs.			2,902
30002897300	Additional Operators and Parts Manuals			56
30002963045	Mounting Labor & Oil		NET	6,422
30000889899KBR	Additional 12 Month Warranty (00889899)		NET	4,251



1502 E. Walnut St., Seguin, TX 78155
800-882-5756 800-882-5758 fax
boom@terraining.com
oemparts@terraining.com



KSB6

6' Mid-Mount Sickle Bar

F.O.B Seguin, TX

STANDARD SPECIFICATIONS

- ♦ Full Hydraulic Drive of Cutter Knife
- ♦ Hydraulically Actuated Breakaway
- ♦ Hydraulic Lift and Tilt
- ♦ Knife Speed Governor
- ♦ 3" Heavy Duty Industrial Rock Guards
- ♦ Reversible Hydraulic Motor
- ♦ Safety Transport Locks
- ♦ Self-Contained Hydraulics
- ♦ Cutting Capacity: 1/2" diameter material
- ♦ Tractor Req: Min. 3,000 lbs. and a 25 HP rating

PRODUCT ORDER CODE	DESCRIPTION	APPRX. WEIGHT		LIST PRICE
Sickle Bar Mower Base Unit (One Choice Required)				
31804117207	KSB6 Single RH w/ Serrated Knives	723		13,038
Options				
370002993751A	Additional Operators and Parts Manuals (Hard Copy)			56
370002993751ACD	Additional Operators, Parts & Service Manuals (CD Format)			35
3080487100	Knife Holder Brackets (Order Quantity 2 per Unit)	9		134
30802988134	Kubota M5040/M6040/M7040 Pump Guard Kit			317
3000800000	Factory Mounting & Oil			1,984
30002991505	Additional 12 Month Warranty			1,982

Mount Kit (One Choice Required)				
PRODUCT ORDER CODE	TRACTOR DESCRIPTION	MAX. TIRE SIZE		LIST PRICE
		FRONT	REAR	
30802992899	Kubota L5740 Cab 4wd (Mid-Mount PTO Req'd)	9.5-16	14.9-26	5,192
30802992900	Kubota M5040/M6040/M7040 ROPS 2 & 4wd	12.5-18	16.9-28	5,192
30802992901	Kubota M5040/M6040/M7040 Cab 2 & 4wd	11.2-24	16.9-30	5,192
30802993749	Kubota M8560/9960 Cab 2 & 4wd	12.4-24	18.4-30	5,192



1502 E. Walnut St., Seguin, TX 78155
 800-882-5756 800-882-5758 fax
 boom@terrainking.com
 oemparts@terrainking.com

TERRAINKING™

Engineering Practical Solutions™

A Member of Alamo Group



Sold Exclusively By Kubota Dealers

**OEM PERFORMANCE
PARTS**
TERRAINKING™

Terrain King™ OEM Performance Parts offer the safety, durability and warranty protection you expect. OEM Parts are available through your local dealer. For a list of these authorized dealers in your area, visit www.terrainking.com and click the authorized dealer tab.

**the CuttingEdge
Safetyprogram™**

Ask your local dealer for information on upcoming OSHA certified safety training courses. Please visit www.terrainking.com/safety to learn more.