

- > 30 PPM
- > Copy, Print, Scan, Fax
- > Fully Erasable Toner
- > Energy Star 2 Compliant
- > Secure MFP



**e-STUDIO306LP Specifications**

Copying Process/Type	IEPM (Dry Process)/Laser Technology
Original Reading Method	CCD Line Sensor
Copy/Print Resolution	2400 x 600 dpi (with Smoothing)
Copy/Print Speed	30 PPM
Scanning	Color Scanning
Warm-Up Time	Approx. 65 Seconds
First Copy Time	4.9 Seconds
Duty Cycle	125K
Multiple Copying	Up to 999 Copies
Standard Paper Supply	2 x 550-Sheet, 100-Sheet Stack Feed Bypass
Maximum Paper Supply	Up to 2,300 Sheets
Acceptable Paper Size	Cassette: Statement-R to Ledger (17-28 lb.); Bypass: Statement-R to Ledger (17-110 lb.)
Special Paper	Bypass: Envelope, Tab Sheet
Memory	1GB RAM, 160 GB Self-Encrypting HDD
Reduction/Enlargement	25% to 400%
Bypass Tray	100-Sheet Stack Feed Bypass
Control Panel	9" Wide VGA Color Touch-Screen
Dimensions	Approx. 23" x 23" x 30" (W x D x H)
Weight	Approx. 132 lbs.
Power Supply	115 Volts; 15 Amps
Power Consumption	Maximum 1.5kW
PM Cycle	120K
Toner Yield	29.3K Impressions @ 6%
Drum Type/Yield	Organic Photoconductor; 120K
Developer Yield	120K

**Print (Standard)**

Print Speed	30 PPM
PDL Support	PCL6, PostScript3, XPS
Operating Systems	Windows 2000/XP/2003/Vista/2007/8; Mac X OS10.2.4/10.3.10.4/10.5; UNIX, Linux, CUPS
Protocol Support	IPX/SPX, TCP/IP (IPv4/IPv6), EtherTalk, AppleTalk PAP, LPR/LPD, IPP w/Authentication, SMB, Netware
Drivers	Windows 2000/XP/2003/Vista/2007/8; Mac X OS 10.2.4/10.3/10.4/10.5 (OS 10.4 PPD); UNIX, Linux, AS/400, SAP R/3
Connectivity	Ethernet 10/100/1000BaseT, USB 2.0, 802.11b/g Wireless LAN
Device Management	TopAccess
Certification	WHQL, Novell, HPOS (Dazell), Vista Premium

**Scan (Standard)**

Scan Speed	57spm LT-Size@300dpi (B&W)/43spm LT-Size@300dpi (Color)
Scan Resolution	100 dpi, 150 dpi, 200 dpi, 300 dpi, 400 dpi, 600 dpi
File Format	TIFF, PDF, Slim PDF, JPEG, XPS
	MS Word, MS Excel, Searchable PDF w/Adv. Scanning option

**E-Filing (Standard)**

Operation Method	Color Touch Screen Control Panel or Client PC
Number of Boxes	1 Public Box; 200 Private User Boxes
Capacity of Boxes	100 Folder per Box; 400 Documents per Folder; 1000 Pages per Documents

**Security (Standard)**

Data Encryption	256 Bit AES
HDD Overwrite	Meets Department of Defense (DoD) standard 5220.22M
Authentication	LDAP, SMTP, Windows Server Domain

**Facsimile Option**

Compatibility	Super G3, G3
Data Compression	MH / MR / MMR / JBIG
Transmission Speed	Approx. 3 Seconds per Page
Fax Modem Speed	33.6 Kbps
Fax Memory	Transmission and Reception 1GB (HDD); Backup Permanent (HDD)
Memory Transmission	100 Jobs, 2,000 Destinations Max; 400 Destinations/Job
Scan Speed	0.7 Seconds per Page; 50 Scans per Minute
Other Fax Functions	Internet Fax; Network Fax

**Accessories (Options)**
**Paper Reusing Device**

Erasing Unit	KH1020
--------------	--------

**Input Options**

100-Sheet RADF	MR3021
Platen Cover	KA1640PC

**Additional Paper Options**

550-Sheet Paper Feed Pedestal	KD1033
550-Sheet Paper Feed Unit	MY1042

**Finishing Options**

Job Separator	MJ5009
Work Tray	KK4550

**Connectivity/Security Options**

Fax Kit	GD1250NFX
2nd Line Fax	GD1260F
IPSec Enabler	GP1080
Wireless LAN Adapter	GN1060
Antenna	GN3010
Meta Scan Enabler	GS1010
Advanced Scanning	GB1280T

**e-STUDIO<sup>RD</sup>30 Specifications**

Erasing Method	Twin Heat Roller Duplex Heating Method
Scanning Method	Single-pass Duplexing Automatic Document Feeder
Warm-up Time	Approx. 40 seconds (Approx. 12 seconds from Energy Saving Mode)
Dimensions (W x D x H)	18.5" x 18.5" x 32.5"
Weight	Approx. 99.2 lbs
Power Requirements	110 V, 8 A (50/60 Hz); 1.5 kW or less
and Power Consumption	
Operating Environment	Temperature: 10 - 30 °C / 50 - 86°F Humidity: 20 - 85 % (No Condensation)

**Paper Feed Tray**

Loading Capacity	Max. Stack Height: 0.6 inches (Approx. 100 sheets; A4 / Letter, 20 lb)
Acceptable Paper Size	A4, A5, B5 or Letter, Statement-R
Acceptable Paper Weight	17 - 20 lb (Plain Paper)

**Erase (Standard)**

Erase Speed (A4/Letter)	Erase only: 30 sheets/minute Erase & Sort/Scan: 15 sheets/minute
-------------------------	---------------------------------------------------------------------

**Scan(Standard)**

Resolution	100, 150, 200, 300 dpi
Scan/Erasing speed	15/30 sheets/minute
Color Modes	Full Color, Grayscale, B&W, Blue Original
File Formats	TIFF, PDF, Slim PDF, JPEG
Scan Functions	Scan to USB, Scan to Network Shared Folder (SMB, WebDAV), Management Scan

**Device Management**

TopAccess for Remote Administration and Configuration (Incl. Reuse Count Settings)


**Corporate Office**

9740 Irvine Blvd., Irvine, CA 92618-1631

Tel: 949-462-6000

**East Coast**

959 Route 46 East, 5th Floor, Parsippany, NJ 07054

Tel: 973-316-2700

**Midwest**

8770 W. Bryn Mawr Ave., Suite 700, Chicago, IL 60631

Tel: 773-380-6000

**South**

2037 Bakers Mill Rd., Dacula, GA 30019

Tel: 678-546-9385

**West Coast**

9740 Irvine Blvd., Irvine, CA 92618-1631

Tel: 949-462-6000

**Web Site**

www.business.toshiba.com

Designs and Specifications subject to change without notice. For best results and reliable performance, always use supplies manufacturer or designated by Toshiba. Not all options and accessories may be available at the time of product launch. Please contact a local Authorized Toshiba Dealership for availability. Toner yields are estimates based on 6% coverage, letter-size page. Driver and connectivity feature support varies by client/network operating system.

© 2013 Toshiba America Business Solutions, Inc. Electronic Imaging Division  
 Inv. Code: 22212 306LP BRO 2.5M WDG 4/13

