

- > 25 PPM
- > Black & White MFP
- > Small Workgroup
- > Copy, Print, Scan, Fax*





- > Black and White MFP
- > 25 PPM
- > Small Workgroup
- > Copy, Print, Scan, Fax
- > Secure MFP

General Specifications

Copying/Printing process	Indirect electrostatic photographic method
Type	Desktop
Original scanning method	Contact Image Sensor (CIS)
Resolution	2400 x 600 dpi (with smoothing)
Gradation	256 steps
Original Platen Type	Fixed hard platen, ADF
Available Original Size	ST-R, LD
Available Paper Size	Drawer: LT only Stack Feed Bypass: ST-R, LD Envelope
Paper Supply	Drawer (250 sheets x 1) and Stack Feed Bypass (50 sheets)
Available Paper Weight	Drawer: 17-20 lb Stack Feed Bypass: 17-90 lb Auto Duplexing Unit: 17-20 lb
Paper Exit	Face down/Inner Tray
Warm-up Time	Approx. 20 seconds
Counter	Electronic counter (indication by LCD display)
Memory	512 MB
Power Supply	110 V
Power Consumption	Max. 1.5kW
Dimensions	15.3 x 21.25 x 20 (W x D x H)
Weight	Approx. 47.3 lbs.
Special Features	Energy Saver, Auto Sleep Mode, Department code
Max Duty Cycle	50K Copies

Copy Specifications

Copying Speed	25 PPM
Original Scan Speed	20 SPM (by using ADF)
Scan Resolution	600 x 600 dpi (for copying)
First Copy Time	7.1 seconds
Original/Copy Size	ST-R to LD
Original Mode	Photo, Text/Photo, Text, Background Erase
Image Density Control	Automatic/Manual (11 steps)
Reproduction Ratio	Zoom: 25 % to 400 % in 1 % increments
Multiple Copying	Up to 999 copies (Ten key input)
Special Features	Interrupt, APS/AMS, Auto job start, Automatic sort mode, ID card copy

Print Specifications (Standard)

Printing Speed	25 PPM
Printing Resolution	2400 x 600 dpi (with smoothing)
Interface	Standard: 10/100 Base-T, USB 2.0, Optional: 802.11 b/g/n
PDL	PCL 6 emulation
Support OS	Windows 7/8/XP/Vista/Server 2003/2008/2008R2

Scan Specifications (Standard)

Connection Type	Standard: 10/100 Base-T, Optional: 802.11 b/g/n
Scanning Resolution	100/150/200/300/400/600 dpi
Scanning Speed	20 SPM (BW), 5 SPM (Color)
Scan Agent	Scan to File, SMB, FTP, Scan to Email, Scan to USB

*e-STUDIO2505F only

Paper Handling Options

Standard Automatic Document Feeder (ADF)

Stack Capacity	50 sheets
Original Setting	Face up
Original Paper Size	ST-R, LD
Original Paper Weight	17-20 lb

*Walk-up FAX Specifications (e-STUDIO2505F only)

Compatibility	Super G3, G3
Image Format on PSTN	JBIG, MMR, MR, MH
Document Size	ST-R-LD
Modem Speed	33.6kbps to 2.4kbps (automatic fallback)
Transmission Speed	Approx. 3 seconds
Communication Protocols	ITU-T T.30
Memory Transmission	Max 256 Jobs, 220 Destinations/Job, 1000 Pages/File

Options

Wireless LAN Module (ETA Nov. 2013)	GN1080
Damp Heater (for Drum)	MF2505U
Harness for Coin Controller	GQ1131



Corporate Office

9740 Irvine Blvd., Irvine, CA 92618

Tel: 949-462-6000

East Coast

959 Route 46 East, 5th Floor, Parsippany, NJ 07054

Tel: 973-316-2700

Midwest

8770 W. Bryn Mawr Ave., Suite 700, Chicago, IL 60631

Tel: 773-380-6000

South

2037 Bakers Mill Rd., Dacula, GA 30019

Tel: 678-546-9385

West Coast

9740 Irvine Blvd., Irvine, CA 92618

Tel: 949-462-6000

Web Site

www.business.toshiba.com

Designs and Specifications subject to change without notice. For best results and reliable performance, always use supplies manufacturer or designated by Toshiba. Not all options and accessories may be available at the time of product launch. Please contact a local Authorized Toshiba Dealership for availability. Toner yields are estimates based on 6% coverage, letter-size page. Driver and connectivity feature support varies by client/network operating system.