

- > 23 PPM
- > Black & White MFP
- > Small Workgroup
- > Copy, Print, Scan
- > Secure MFP





- > **Black and White MFP**
- > **23 PPM**
- > **Small Workgroup**
- > **Copy, Print, Scan**
- > **Secure MFP**

General Specifications

Copy/Print Process Type	Indirect Electrostatic Photographic Method Desktop
Original Scanning Method	Contact Image Sensor (CIS)
Resolution	Scanning: 600 x 600 dpi Printing: 2400 x 600 dpi (with smoothing)
Gradation	256 Steps
Original Platen Type	Fixed Hard Platen (optional RADF)
Available Original Size	Maximum Ledger
Available Paper Size	Drawer: Statement-R to Ledger Bypass: Statement-R to Ledger
Paper Supply	Standard Drawer (250 sheets), Bypass (100 sheets) Optional Paper Feed Unit (250 sheets)
Available Paper Weight	Drawer: 17 lb - 21 lb Bond Bypass: 14 lb Bond - 90 lb Index (Single-feed), 17 lb - 21 lb Bond (Multi-feed) Auto Duplexing Unit: 17 lb - 21 lb Bond
Paper Exit	Face Down, Inner Tray
Memory	512 MB
Warm-up Time	Approx. 20 Seconds
Counter	Electronic Counter
Power Supply	110 Volts
Power Consumption	1.5kW
Reduction/Enlargement	25% to 400%
Dimensions	Standard: Approx. 22.6" x 21.2" x 16" (W x D x H) With PFU: Approx. 23" x 22.2 x 20" (W x D x H)
Weight	Approx. 56.2 lbs.
Special Features	Auto Sleep Mode, Auto Energy Saver, Department Codes

Copy Specifications

Copy Speed	14 PPM (LD), 16 PPM (LG), 23 PPM (LT)
Original Scan Speed	20 SPM (LT)
First Copy Time	7.0 Seconds
Original/Copy Size	ST-R to LD
Original Mode	Text/Photo, Photo, Text, Background Mode
Image Density Control	Automatic/Manual (9 steps)
Reproduction Ratio	Zoom: 25% to 400% in 1% increments
Multiple Copying	Up to 999 Copies (ten key input)
Special Features	APS/AMS*, Auto Job Start, Auto Drawer Change*, Automatic Electronic Sort Mode, Thick Paper Mode, ID Card Copy *Options are required.

Print Specifications

Maximum Print Speed	14 PPM (LD), 16 PPM (LG), 23 PPM (LT), ,
Printing Resolution	600 x 600 dpi, 2400 x 600 dpi (with smoothing)
Interface	USB 2.0 (high speed)
Support OS	Windows XP, Vista, 7, 8, Server 2003, 2008, 2008R2, 2012

Scan Specifications

Connection Type	USB 2.0 (high speed)
Scan Resolution	150 dpi, 300 dpi, 600 dpi
Scan Speed	20 SPM (BW), 5 SPM (Color)
Compatibility	TWAIN

Paper Handling Options

Reversing Automatic Document Feeder (RADF)	MR3027
Stack Capacity	50 sheets
Original Setting	Face up
Original Paper Size	Statement-R to Ledger
Original Paper Weight	16 lb - 28 lb

Paper Feed Unit (PFU)	MY1043
Paper Supply	Maximum 250 sheets
Paper Size	Statement-R to Ledger
Paper Weight	17 lb - 21 lb Bond

Automatic Duplexing Unit (ADU)	MD0106
Type	Stackless
Paper Size	Statement-R to Ledger
Paper Weight	17 lb - 21 lb Bond

Other Options

Harness Kit for Coin Controller	GQ1131
Cabinet Stand	STAND2507
Platen Cover	KA2507



Corporate Office	9740 Irvine Blvd., Irvine, CA 92618 Tel: 949-462-6000
East Coast	959 Route 46 East, 5th Floor, Parsippany, NJ 07054 Tel: 973-316-2700
Midwest	8770 W. Bryn Mawr Ave., Suite 700, Chicago, IL 60631 Tel: 773-380-6000
South	2037 Bakers Mill Rd., Dacula, GA 30019 Tel: 678-546-9385
West Coast	9740 Irvine Blvd., Irvine, CA 92618 Tel: 949-462-6000
Web Site	www.business.toshiba.com

Designs and Specifications subject to change without notice. For best results and reliable performance, always use supplies manufacturer or designated by Toshiba. Not all options and accessories may be available at the time of product launch. Please contact a local Authorized Toshiba Dealership for availability. Toner yields are estimates based on 6% coverage, letter-size page. Driver and connectivity feature support varies by client/network operating system.