



GENUINE. PROFESSIONAL.



POWERFUL, PRACTICAL AND PRODUCTIVE.

Snapper Pro® mowers are where innovation meets common sense practicality to keep you mowing season after season. With powerful engine choices, heavy-duty components and technology, like the iCD™ Cutting System, Snapper Pro mowers are the smart choice for your landscaping needs.

- iCD™ CUTTING SYSTEM3
- ZERO-TURN MOWERS
 - S800x.....5
 - S200xt.....7
 - S150xt9
 - S125xt11
 - S50xt.....13
- WALK-BEHIND MOWERS
 - SW3515
 - SW2517
- COLLECTION SYSTEMS19
- ACCESSORIES & ATTACHMENTS...23
- MODEL SELECTION CHART24
- SPECIFICATIONS25





IT'S ALL ABOUT THE CUT

The iCD™ Cutting System was engineered to produce the best possible cut in a multitude of conditions. Every component works together to achieve superior cut quality. The baffle design and deep deck allow for better airflow and the extra wide opening allows for a more even and greater dispersal of clippings. The shell features a sloped nose design which allows the blades of grass to rise in the chamber before making contact with the blades and also reduces the amount of clippings that are discharged from the front.

Slice through thick grass with ease and get the job done sooner than you expected.



Snapper Pro® uses two layers of steel, running across the full width of our deck, welded in opposing directions, for maximum strength. Then we lap-weld the corners for increased dent resistance.

1. Flexible recycled rubber discharge chute reduces contact damage
2. Extra wide discharge opening evenly disperses grass clippings
3. Reinforced leading edge provides protection where the deck needs it most
4. Multi-layer heavy-gauge steel construction for maximum strength
5. Debris shield on idler pulleys keeps moisture and debris away extending bearing life
6. Center point is offset, optimizing airflow for discharge
7. Slope nose design reduces the amount of clippings discharged from the front
8. Deck step allows for easy entry and exit from the operator's compartment



HERCULES™ II SPINDLES
Cast-iron 10" dia. greaseable spindles with industrial double row angular contact ball bearings with 1 3/16" dia. shaft.



CAST-IRON SPINDLES
Longer usable life, 1" shaft with top access grease fitting, six-bolt 8" flange design adds strength and greater dispersal of energy to deck assembly.



CAST-ALUMINUM SPINDLES
Feature 1" shaft with 2.5" x 1" dual ball bearings with top access grease fittings and pressure relief valve.



MARBAIN STEEL BLADES
Our exceptionally strong 1/4" thick blades generate greater lift for a precision cut and require less frequent sharpening.



PROFESSIONAL LAWN STRIPER
Standard equipment on all iCD™ Cutting System decks.

S800X PROFESSIONAL



The S800x zero-turn mower is the ideal machine for visibility and versatility. Its out-front design is perfect for trimming around trees, bushes and landscaped areas with ease. Be even more productive with a wide selection of accessory and attachment options.



Raise the deck with a flip-of-the-switch to make deck maintenance a snap.



Yanmar™ compact diesel engines are clean, quiet, fuel efficient, and reliable.



Optional 60" broom clear debris and snow right down to the pavement. (Cab enclosure available, not shown.)



The pivoting rear axle in conjunction with the floating front frame allows the S800x to follow the contours of the landscape for a precise, manicured finish.

MOWS UP TO
5.8 ACRES/HOUR
BASED ON 80% EFFICIENCY

MODEL
S800XY30D w/S800X/61
S800XBV31 w/S800X/61
S800XY30D w/S800X/72
S800XBV31 w/S800X/72

ENGINE
30 gross hp^ Yanmar™ Diesel
31 gross hp^ Vanguard™
30 gross hp^ Yanmar™ Diesel
31 gross hp^ Vanguard™

DECK
61"
61"
72"
72"

VISIBILITY & VERSATILITY

ENGINE

- Choose from 30 gross hp^ Yanmar™ diesel or 31 gross hp^ Vanguard™ gasoline engine options
- Two-stage industrial air cleaner extends engine service life
- Easy access oil drain

DRIVE SYSTEM

- Independent pumps and wheel motors, feature 7" cooling fans that assist with repelling debris
- Hydro fluid reservoir and hydro filter
- Rugged 5/8" hoses supply a constant flow of fluid cooling the hydro system
- Ground speed up to 10 mph

MOWER DECK

- Available in 61" or 72" cutting widths
- iCD™ Cutting System with professional lawn striper
- Cast-iron greaseable spindles for longer usable life, 1" shaft with top access grease fitting, 6-bolt 8" flange design adds strength and greater dispersal of energy to deck assembly
- Electric deck-lift makes for easy cut height adjustment; cutting height ranges from 1.5" - 5" in 0.25" increments
- Debris shields on idler pulleys extend bearing life

CHASSIS

- Heavy-duty C-channel, 7-gauge frame rails
- Premium mid-back seat with arm rests, adjustable fore and aft positioning
- Flip-up seat for easy access

FUEL SYSTEM

- Twin 6-gallon rugged, impact resistant fuel tanks with extra large filler necks
- Switch for fuel source (gasoline only)
- Top-mounted fuel pick-up with Viton® seals

OPERATOR CONVENIENCE

- Ergonomic control panels with cup-holder and storage compartment
- Adjustable solid steel padded control arms

ACCESSORIES

- Collection System (61"), Mulch Kit, Suspension Seat, Suspension Seat Insert, Flat-Free Caster Tires, Snowblower, Broom, Cab



* Rated in accordance with SAE J1940 at 3600 RPM.
^ Power levels rated by engine manufacturer.



S200xt PROFESSIONAL



Vanguard™ BIG BLOCK™ engine provides increased horsepower and more torque.



Dual, commercial Hydro-Gear® ZT-5400 Powertrain® transaxles deliver unmatched power and durability.



The easy-to-use deck-lift takes the effort out of adjusting cut height. Cutting height ranges from 1.5" - 6" in 0.25" increments.



Quick removal of the floor pan provides convenient access to the top of the deck for easy cleaning and service.

ENGINE

- Choose from 25.5 gross hp** Kawasaki® FX801V , 26 gross hp* Vanguard™ 810cc, 27 gross hp* Briggs & Stratton Commercial Turf Series™, 27 gross hp^ Kohler® Command Pro EFI ECV749, 28 gross hp* Vanguard™ 810cc EFI, or 28/36 gross hp* Vanguard™ BIG BLOCK™ engine options
- Patented advanced debris management system (Briggs & Stratton Commercial Turf Series™ models)
- Two-stage industrial air-cleaner (Vanguard™, Kohler® and Kawasaki® models)
- Easy access oil drain

DRIVE SYSTEM

- Independent, commercial Hydro-Gear® ZT-5400 Powertrain® transaxles feature 9" cooling fans that assist with repelling debris
- Dual hydro fluid reservoirs and hydro filters
- Ground speed up to 10 mph

MOWER DECK

- Available in 61" or 72" cutting widths
- iCD™ Cutting System with professional lawn striper
- Cast-iron greaseable spindles for longer usable life, 1" shaft with top access grease fitting, 6-bolt 8" flange design adds strength and greater dispersal of energy to deck assembly (61" models)
- Hercules™ II spindles; 10" dia. cast-iron with industrial double row angular contact ball bearings with 1 3/16" dia. shaft (72" model)
- Cut height: 1.5" – 6", adjust in 0.25" increments
- Debris shields on idler pulleys extend bearing life

CHASSIS

- Heavy-duty 2" x 2" 7-gauge frame rails
- Premium mid-back seat with arm rests, adjustable fore and aft positioning
- Flip-up seat for easy access
- Removable floor pan
- Five-bolt pattern wheels, 1/4" solid center wheels
- Flat-free caster tires (excludes S200XTB2761)
- Heavy-duty bumper protects engine compartment

FUEL SYSTEM

- Twin 5-gallon rugged, impact resistant fuel tanks with switch for fuel source (excludes S200XTB2761)
- Single 5-gallon rugged, impact resistant fuel tank (S200XTB2761)
- Extra large filler neck(s)
- Top-mounted fuel pick-up with Viton® seals

OPERATOR CONVENIENCE

- Ergonomic control panels with cup-holder and storage compartment
- Adjustable solid steel padded control arms

ACCESSORIES

- Collection System (61"), Mulch Kit, Trailer Hitch Kit, Suspension Seat, Flat-Free Caster Tires

PRODUCTIVITY REDEFINED

MOWS UP TO
5.8 ACRES/HOUR
BASED ON 80% EFFICIENCY

MODEL

S200XTKAV2661
S200XTBV2661
S200XTB2761
S200XTKOH2761
S200XTBVE2861
S200XTBV2861
S200XTBV3661
S200XTBV3672

ENGINE

25.5 gross hp** Kawasaki® FX801V
26 gross hp* Vanguard™ 810cc
27 gross hp* Briggs & Stratton Commercial Turf Series™
27 gross hp^ Kohler® Command Pro EFI ECV749
28 gross hp* Vanguard™ 810cc EFI
28 gross hp* Vanguard™ BIG BLOCK™
36 gross hp* Vanguard™ BIG BLOCK™
36 gross hp* Vanguard™ BIG BLOCK™

DECK

61"
61"
61"
61"
61"
61"
61"
72"

The S200xt is equipped to ride for a full day of work with impressive features and premium components. Available with our iCD™ Cutting System deck in 61" and 72" cutting widths, the S200xt will cut your big jobs down to size. This machine delivers maximum performance and productivity.



S150xt

PROFESSIONAL

This compact yet powerful performer is designed for the serious professional who demands the ultimate in performance and durability. Get in and out of your jobs fast with the S150xt zero-turn mower.

ENGINE

- Choose from 24 gross hp** Kawasaki® FX730V, 26 gross hp* Vanguard™ 810cc, or 28 gross hp* Vanguard™ 810cc EFI engine options
- Two-stage industrial air-cleaner
- Easy access oil drain

DRIVE SYSTEM

- Independent, commercial Hydro-Gear® ZT-5400 Powertrain® transaxles feature 9" cooling fans that assist with repelling debris
- Dual hydro fluid reservoirs and hydro filters
- Ground speed up to 10 mph

MOWER DECK

- Available in 48" or 52" cutting widths
- iCD™ Cutting System with professional lawn striper
- Cast-iron greaseable spindles for longer usable life, 1" shaft with top access grease fitting, 6-bolt 8" flange design adds strength and greater dispersal of energy to deck assembly
- Cut height: 1.5" - 5", adjusts in 0.25" increments
- Debris shields on idler pulleys extend bearing life

CHASSIS

- Heavy-duty 1.5" x 2" 11-gauge frame rails
- Premium mid-back seat with arm rests, adjustable fore and aft positioning
- Flip-up seat for easy access
- Removable floor pan
- Five-bolt pattern wheels
- Flat-free caster tires
- Heavy-duty bumper protects engine compartment

FUEL SYSTEM

- Twin 5-gallon rugged, impact resistant fuel tanks with switch for fuel source
- Extra large filler necks
- Top-mounted fuel pick-up with Viton® seals

OPERATOR CONVENIENCE

- Ergonomic control panels with cup-holder and storage compartment
- Adjustable solid steel padded control arms

ACCESSORIES

- Collection System, Mulch Kit, Trailer Hitch Kit, Light Kit, Suspension Seat



Dual, commercial Hydro-Gear® ZT-5400 Powertrain® transaxles deliver unmatched power and durability.



Vanguard™ 810cc engines deliver the optimum power, performance, and efficiency commercial zero-turn mowers need.



Cast-iron greaseable spindles maximize usable life.



Quick removal of the floor pan provides convenient access to the top of the deck for easy cleaning and service.



A POWERFUL CHOICE

MOWS UP TO
4.2 ACRES/HOUR
BASED ON 80% EFFICIENCY

MODEL

S150XTKAV2448
S150XTBV2648
S150XTKAV2452
S150XTBV2652
S150XTBVE2852

ENGINE

24 gross hp** Kawasaki® FX730V
26 gross hp* Vanguard™ 810cc
24 gross hp** Kawasaki® FX730V
26 gross hp* Vanguard™ 810cc
28 gross hp* Vanguard™ 810cc EFI

DECK

48"
48"
52"
52"
52"



S125xt PROFESSIONAL



The easy-to-use deck-lift takes the effort out of adjusting cut height. Cutting height ranges from 1.5" - 5" in 0.25" increments.



Hydro-Gear® ZT-3400® commercial engineered drive system is designed for high performance and is fully serviceable.



Quick removal of the floor pan provides convenient access to the top of the deck for easy cleaning and service.



The Briggs & Stratton Commercial Turf Series™ engine features a patented advanced debris management system which deflects dirt and debris from the engine, and any remaining debris is trapped in the high-capacity, dual-sealing air cleaner cartridge.

ENGINE

- Choose from 23/24 gross hp™ Kawasaki® FS or 25/27 gross hp* Briggs & Stratton Commercial Turf Series™ engine options
- Patented advanced debris management system (Briggs & Stratton Commercial Turf Series™ models)
- Easy-to-use oil drain

DRIVE SYSTEM

- Independent, commercial Hydro-Gear® ZT-3400® transaxles feature 7" cooling fans that assist with repelling debris
- Ground speed up to 10 mph

MOWER DECK

- Available in 52" or 61" cutting widths
- iCD™ Cutting System with professional lawn striper
- Features greaseable cast aluminum spindles with 2.5" diameter ball bearings
- Cut height: 1.5"- 5", adjusts in 0.25" increments
- Debris shields on idler pulleys extend bearing life

CHASSIS

- Heavy-duty 1.5" x 2" 11-gauge frame rails
- Removable floor pan
- Rugged, impact resistant 5.5-gallon fuel tank
- Adjustable contour seat with arm rests
- Flip-up seat for easy access
- Heavy-duty bumper protects engine compartment

OPERATOR CONVENIENCE

- Ergonomic control panels with cup-holder and storage compartment
- Adjustable solid steel padded control arms
- Control system provides smooth precise steering

ACCESSORIES

- Collection System, Mulch Kit, Trailer Hitch Kit, Light Kit, Premium Mid-Back Seat, Flat-Free Caster Tires

MOWS UP TO
4.9 ACRES/HOUR
BASED ON 80% EFFICIENCY

MODEL

S125XTKAV2352
S125XTB2552
S125XTKAV2461
S125XTB2761

ENGINE

23 gross hp** Kawasaki® FS691V
25 gross hp* Briggs & Stratton Commercial Turf Series™
24 gross hp** Kawasaki® FS730V
27 gross hp* Briggs & Stratton Commercial Turf Series™

DECK

52"
52"
61"
61"

* Rated in accordance with SAE J1940 at 3600 RPM.
** Rated in accordance with SAE J2723 at 3600 RPM.

VALUE & PERFORMANCE

With powerful engine choices, 52" or 61" iCD™ Cutting System options and speed up to 10 mph, the S125xt zero-turn mower will cut your job down to size. The heavy-duty components, including the commercial Hydro-Gear® ZT-3400® transaxles, will keep you mowing season after season.



S50xt

PROFESSIONAL



The compact, easy-to use S50xt zero-turn mower is designed specifically for the daily rigors of commercial mowing. This mower may be small in size, but it's big on features.

COMPACT & TOUGH

MOWS UP TO
3.1 ACRES/HOUR
BASED ON 80% EFFICIENCY

MODEL	ENGINE	DECK
S50XTKAV1936	19 gross hp** Kawasaki® FX600V	36"
S50XTB2536	25 gross hp* Briggs & Stratton Commercial Turf Series™	36"
S50XTKAV1948	19 gross hp** Kawasaki® FX600V	48"
S50XTB2548	25 gross hp* Briggs & Stratton Commercial Turf Series™	48"

* Rated in accordance with SAE J1940 at 3600 RPM.
** Rated in accordance with SAE J2723 at 3600 RPM.

ENGINE

- Choose from 19 gross hp** Kawasaki® FX600V or 25 gross hp* Briggs & Stratton Commercial Turf Series™ engine options
- Patented advanced debris management system (Briggs & Stratton Commercial Turf Series™ models).
- Two-stage industrial remote air-cleaner (Kawasaki® models)
- Easy access oil drain

DRIVE SYSTEM

- Independent, commercial Hydro-Gear® ZT-3100® transaxles feature 7" cooling fans that assist with repelling debris
- Dual hydro fluid reservoirs and hydro filters
- Ground speed up to 8 mph

MOWER DECK

- Available in 36" or 48" cutting widths
- iCD™ Cutting System with professional lawn striper on 48" models
- Fabricated 10-gauge with double top deck, overlap welded corners and double reinforced side skirts, steel reinforced leading edge on 36" models
- Cast-aluminum spindles feature 1" shaft with greaseable 2.5" x 1" dual ball bearings with top access grease fittings and pressure relief valve
- Durable, .25" Marbain® steel blades
- Cut height: 1.5" - 4.5", adjusts in 0.25" increments
- Debris shields on idler pulleys extend bearing life

CHASSIS

- Heavy-duty 1.5" x 2", 11-gauge frame rails
- Adjustable contour seat
- Flip-up seat for easy access
- Removable floor pan
- Heavy-duty bumper protects engine compartment

FUEL SYSTEM

- Twin 4-gallon rugged, impact resistant fuel tanks with switch for fuel source (excludes S50XTB2536)
- Single 4-gallon rugged, impact resistant fuel tank (S50XTB2536)
- Extra large filler neck(s)
- Top mounted fuel pick-up with Viton® seals

OPERATOR CONVENIENCE

- Ergonomic control panels
- Adjustable solid steel padded control arms

ACCESSORIES

- Collection System (48"), Grass Catcher (36"), Mulch Kit, Trailer Hitch Kit, Light Kit, Arm Rests, Flat-Free Caster Tires, Professional Lawn Striper (36")

* Rated in accordance with SAE J1940 at 3600 RPM.
** Rated in accordance with SAE J2723 at 3600 RPM.




The easy-to-use deck-lift takes the effort out of adjusting cut height. Cutting height ranges from 1.5" - 4.5" in 0.25" increments.



Features greaseable cast-aluminum spindles for longer usable life.



Quick removal of the floor pan provides convenient access to the top of the deck for easy cleaning and service.



Hydro-Gear® ZT-3100® drive system is designed for high performance and is fully serviceable.





SW35 shown with standard controls.

SW35

PROFESSIONAL

The SW35 delivers consistently accurate cutting performance in diverse conditions. Built to run sunrise to sundown, the walk-behind is a productive performer for any size mowing crew.



Thick 1/4" engine deck construction provides robust mounting area for sully attachments.



Deck drive belt system is designed to provide even belt tension which improves the life of the belt and reduces maintenance.



Reliably set your speed with the improved easy-to-reach cruise control bar featuring a speed indicator. Conveniently located brake handle.



Set cutting height in one easy step using the quick-adjust crank.

ENGINE

- Choose from 20.5/23.5 gross hp** Kawasaki® FX, 26 gross hp* Vanguard™ 810cc, or 28 gross hp* Vanguard™ 810cc EFI engine options
- Electric start standard
- Two-stage industrial remote air-cleaner
- Easy-to-use oil drain

DRIVE SYSTEM

- Independent, commercial Hydro-Gear® ZT-3100® transaxles feature 7" cooling fans that assist with repelling debris
- Dual hydro fluid reservoirs and hydro filters
- Narrow transmission guards reduce build up of debris to improve air flow and allow for access to the filter for maintenance
- Ground speed up to 7 mph

MOWER DECK

- Available in 48", 52", or 61" cutting widths
- Fabricated 10-gauge with double top deck, overlap welded corners and double reinforced side skirts, steel reinforced leading edge
- Cast-aluminum spindles feature 1" shaft with greaseable 2.5" x 1" dual ball bearings with top access grease fittings and pressure relief valve
- The mower deck mounting system provides easier deck leveling, improved flexibility over terrain, and more durable wear points for reduced maintenance
- Cut height: 1.5"- 4.75", with infinite positioning using the quick-adjust crank
- Debris shields on idler pulleys extend bearing life

CHASSIS

- Heavy-duty 1.5" x 2" 11-gauge frame rails
- Easy to access dump valves
- Flat-free caster tires
- Convenient built in tie-down points for securing equipment

FUEL SYSTEM

- Rugged 5-gallon fuel tank
- Top-mounted fuel pick-up with Viton® seals

OPERATOR CONVENIENCE

- Centralized foot control for neutral position
- Easy-to-reach cruise control bar
- Comfortable easy-to-use operator controls
- Momentary PTO switch allows the operator to stop the mower blades while the engine continues to run. Simply put the machine in neutral and release the controls.

ACCESSORIES

- Grass Catcher (48", 52"), Mulch Kit, Professional Lawn Striper

MOWS UP TO
3.5 ACRES/HOUR
BASED ON 80% EFFICIENCY

MODEL

- SW35KAV2148
- SW35KAV2152
- SW35BV2652
- SW35BVE2852
- SW35KAV2461
- SW35BV2661
- SW35BVE2861
- SW35CCKAV2148
- SW35CCKAV2152
- SW35CCBV2652
- SW35CCBVE2852
- SW35CCKAV2461
- SW35CCBV2661
- SW35CCBVE2861

ENGINE

- 20.5 gross hp** Kawasaki® FX651V
- 20.5 gross hp** Kawasaki® FX651V
- 26 gross hp* Vanguard™ 810cc
- 28 gross hp* Vanguard™ 810cc EFI
- 23.5 gross hp** Kawasaki® FX730V
- 26 gross hp* Vanguard™ 810cc
- 28 gross hp* Vanguard™ 810cc EFI
- 20.5 gross hp** Kawasaki® FX651V
- 20.5 gross hp** Kawasaki® FX651V
- 26 gross hp* Vanguard™ 810cc
- 28 gross hp* Vanguard™ 810cc EFI
- 23.5 gross hp** Kawasaki® FX730V
- 26 gross hp* Vanguard™ 810cc
- 28 gross hp* Vanguard™ 810cc EFI

CONTROLS DECK

Standard	48"
Standard	52"
Standard	52"
Standard	52"
Standard	61"
Standard	61"
Standard	61"
CC™	48"
CC™	52"
CC™	52"
CC™	52"
CC™	61"
CC™	61"
CC™	61"

* Rated in accordance with SAE J1940 at 3600 RPM.
** Rated in accordance with SAE J2723 at 3600 RPM.

SMOOTH OPERATORS

The design of the CC™ Centralized Controls places the operator's hands in the ideal position to access all in-demand controls. Ergonomic operator presence, steering and reverse levers on both handles operate with a light touch to reduce operator fatigue.





SW25

PROFESSIONAL

Snapper Pro walk-behind mowers will keep you mowing even under the most demanding conditions. Whether shuttling between jobs or maneuvering around obstacles, this walk behind is a heavy duty performer in an efficient package.

SW25 shown with CC™ controls.

COMPACT PERFORMANCE

MOWS UP TO
2.4 ACRES/HOUR
BASED ON 80% EFFICIENCY

MODEL	ENGINE	CONTROLS	DECK
SW25KAV1536	15 gross hp** Kawasaki FS541V Manual Start	Standard	36"
SW25KAV1548	15 gross hp** Kawasaki FS541V Manual Start	Standard	48"
SW25KAV1948	18.5 gross hp** Kawasaki FS600V Electric Start	Standard	48"
SW25CCKAV1936	18.5 gross hp** Kawasaki FS600V Electric Start	CC™	36"
SW25CCKAV1548	15 gross hp** Kawasaki FS541V Manual Start	CC™	48"
SW25CCKAV1948	18.5 gross hp** Kawasaki FS600V Electric Start	CC™	48"

** Rated in accordance with SAE J2723 at 3600 RPM.

ENGINE

- Powered by a 15/19 gross hp** Kawasaki® FS engine options
- Electric and manual start available

DRIVE SYSTEM

- Independent, commercial Hydro-Gear® ZT-3100® transaxles feature 7" cooling fans that assist with repelling debris
- Dual hydro fluid reservoirs and hydro filters
- Narrow transmission guards reduce build up of debris to improve air flow and allow for access to the filter for maintenance
- Ground speed up to 6 mph

MOWER DECK

- Available in 36" or 48" cutting widths
- Fabricated 10-gauge with double top deck, overlap welded corners and double reinforced side skirts, steel reinforced leading edge
- Cast-aluminum spindles
- Cut height: 1.5" - 4.5", finite adjustment using pin style height of cut
- Debris shields on idler pulleys extend bearing life

CHASSIS

- Heavy-duty 1.5" x 2" 11-gauge frame rails, one piece frame
- Flat-free caster tires, wheels have cage bearings
- Convenient built in tie-down points for securing equipment
- 20 x 7 -10 drive tires

FUEL SYSTEM

- Rugged 5-gallon fuel tank
- Top-mounted fuel pick-up with Viton® seals

OPERATOR CONVENIENCE

- Centralized foot control for neutral position
- Easy-to-reach cruise control bar
- Comfortable easy-to-use operator controls
- Momentary PTO switch allows the operator to stop the mower blades while the engine continues to run. Simply step on the foot pedal or pull the Cruise Control bar and release the controls.

ACCESSORIES

- Grass Catcher, Mulch Kit, Professional Lawn Striper (48")



Adjust the mower's speed without removing your hands from the control handles with the improved, ready-access cruise control bar. A convenient speed indicator is placed within direct view on the control panel.



Brake handle is conveniently located beside the control panel, providing instant access with minimal operator effort to engage.



New centralized foot pedal for neutral position provides the operator with more natural control. The neutral position is identified on the speed indicator on the dash.



Need to walk away from the mower to move an obstacle or debris? The new PTO switch allows the operator to stop the mower blades in a single step – simply put the machine in neutral and release the controls. The blades will disengage while the engine continues to run.



SW25 shown with CC™ controls.

** Rated in accordance with SAE J2723 at 3600 RPM.

COLLECTION SYSTEMS

TURBO-PRO™

The TURBO-Pro™ system vacuums the lawn for a clean finish in a wide variety of conditions. The TURBO-Pro is a light weight blower assembly and is ideal for use with compact models. **This blower can be used in conjunction with the double bag soft / hard top, triple bag soft / hard top and Electric DFS bagging options.**

- Performs best in normal-to-dry cutting conditions
 - Generous 6" diameter outlet hose
 - Light weight design built to withstand commercial use
 - Durable plastic impeller housing
 - Heavy-duty oversized drive and idler pulleys combined with long drive belt allow for cool running and maximum belt life
 - Curved steel blade impeller reduces noise
- After initial installation the quick attach design can be mounted or removed with no tools in a few minutes
 - Weight: 50 lbs. (44"/48") / 53 lbs. (52") / 55 lbs. (61")



Heavy-duty oversized drive and idler pulleys combined with a long drive belt allow for cool running and maximum belt life.



The curved blade impeller reduces impeller speed and noise while maximizing air velocity.



S125xt shown with a TURBO-Pro triple bag collection system.
TURBO-Pro Blower — Length: 31" Height: 16.5" Width 19"

TURBO-PRO™ MAX

The TURBO-Pro™ Max system acts as a lawn vacuum for a clean finish in a wide variety of conditions. This commercial grade system mounts to the deck with a fabricated heavy-duty steel plate and is ideal for use with larger models. **This blower can be used in conjunction with the triple bag soft / hard top, Electric DFS, EZ Dump™ or EZ Dump XL™ bagging options.**

- Performs best in normal-to-dry cutting conditions
 - Extra wide 7" diameter outlet hose
 - Twice the airflow vs. Turbo-Pro™ for increased capacity on larger decks cutting at higher speeds
 - Rugged steel impeller housing designed for extended life
- After initial installation the quick attach design can be mounted or removed with no tools in a few minutes
 - Weight: 72 lbs. (52") / 64 lbs. (61") (24 lbs. less than the FAST-Vac®)



Heavy-duty oversized drive and idler pulleys combined with a long drive belt allow for cool running and maximum belt life.



The curved blade impeller reduces impeller speed and noise while maximizing air velocity.



S200xt shown with a TURBO-Pro EZ Dump XL collection system.
TURBO-Pro Max Blower — Length: 36" Height: 18" Width 21"

COLLECTION SYSTEMS

FAST-VAC®

This FAST-Vac® system is built around a super tough, high-volume side panel air induction system that reduces clogging and produces significantly more air volume than conventional systems. The super rugged impeller, built using industrial grade bearings, generates a phenomenal airflow. Its spindle-driven vertical turbo is narrower, allowing you to get in and out of tight places. **This blower can be used in conjunction with the triple bag soft / hard top, Electric DFS, EZ Dump™ or EZ Dump XL™ bagging options.**

- Performs best in heavy and wet cutting conditions
- Extra wide 7" diameter outlet hose
- Commercial grade idler and pulleys drive the vertical, spindle drive turbo resulting in a very narrow profile for improved maneuverability
- Super rugged impeller rides on industrial grade bearings to generate a phenomenal airflow
- Weight: 88 lbs. (61")



Commercial-grade idlers and pulleys drive the vertical, spindle-drive turbo resulting in a very narrow profile.



Extremely rugged impeller rides on industrial-grade bearings to generate a phenomenal airflow.



S200xt shown with a FAST-Vac triple bag collection system. FAST-Vac Blower — Length: 36.8" Height: 20.2" Width 15.2"

S800X S200xt S150xt S125xt S50xt

	DOUBLE BAG SOFT TOP The double bag collection system is simple to install. Each heavy-duty mesh bag has a rugged polyethylene underside with integrated handle to assist with removal. Capacity: 8.5 cubic feet			TURBO-PRO™ 48/52" Deck	TURBO-PRO™ 52" Deck	TURBO-PRO™ 48" Deck
	DOUBLE BAG HARD TOP Innovative molded hard top design allows for increased capacity. Simple to install. Each heavy-duty mesh bag has an integrated handle to assist with removal. Capacity: 10 cubic feet			TURBO-PRO™ 48/52" Deck	TURBO-PRO™ 52" Deck	TURBO-PRO™ 48" Deck
	TRIPLE BAG SOFT TOP Simple to install. Each heavy-duty mesh bag has a rugged polyethylene underside with integrated handle to assist with removal. Capacity: 13 cubic feet		TURBO-PRO™ MAX 61" Deck FAST-VAC® 61" Deck	TURBO-PRO™ 52" Deck TURBO-PRO™ MAX 52" Deck FAST-VAC® 52" Deck	TURBO-PRO™ 52"/61" Deck FAST-VAC® 52"/61" Deck	
	TRIPLE BAG HARD TOP Innovative molded hard top design allows for increased capacity. Simple to install. Each heavy-duty mesh bag has an integrated handle to assist with removal. Capacity: 15 cubic feet		TURBO-PRO™ MAX 61" Deck FAST-VAC® 61" Deck	TURBO-PRO™ 52" Deck TURBO-PRO™ MAX 52" Deck FAST-VAC® 52" Deck	TURBO-PRO™ 52"/61" Deck FAST-VAC® 52"/61" Deck	
	ELECTRIC DFS (Dump From Seat) Simply flip the switch on the control panel to release the hopper right from your seat. Capacity: 13 cubic feet		TURBO-PRO™ MAX 61" Deck FAST-VAC® 61" Deck	TURBO-PRO™ 52" Deck TURBO-PRO™ MAX 52" Deck FAST-VAC® 52" Deck	TURBO-PRO™ 52"/61" Deck FAST-VAC® 52"/61" Deck	
	EZ DUMP™ (Dump From Seat) Simply squeeze the handle and pull up to release the hopper right from your seat. The hopper is specially lined to ensure that all material is dumped. Capacity: 12 cubic feet		TURBO-PRO™ MAX 61" Deck FAST-VAC® 61" Deck	TURBO-PRO™ MAX 52" Deck FAST-VAC® 52" Deck		
	EZ DUMP XL™ (Dump From Seat) Ideal for larger jobs. Simply squeeze the handle and pull up to release the hopper right from your seat. The hopper is specially lined to ensure that all material is dumped. Capacity: 14 cubic feet	TURBO-PRO™ MAX 61" Deck FAST-VAC® 61" Deck	TURBO-PRO™ MAX 61" Deck FAST-VAC® 61" Deck			

ACCESSORIES & ATTACHMENTS

	S800X	S200xt	S150xt	S125xt	S50xt	SW35	SW25
Mulch Kit	Optional	Optional	Optional	Optional	Optional	Optional	Optional
Trailer Hitch Kit	N/A	Optional	Optional	Optional	Optional	N/A	N/A
Light Kit	N/A	N/A	Optional	Optional	Optional	N/A	N/A
Arm Rests	Standard	Standard	Standard	Standard	Optional	N/A	N/A
Suspension Seat Insert	Optional	N/A	N/A	N/A	N/A	N/A	N/A
Suspension Seat	Optional	Optional	Optional	N/A	N/A	N/A	N/A
Premium Seat	Standard	Standard	Standard	Optional	N/A	N/A	N/A
Flat-Free Caster Tires	Optional	Standard/ Optional*	Standard	Optional	Optional	Standard	Standard
Professional Stripe Kit	Standard	Standard	Standard	Standard	Standard/ Optional**	Optional	Optional†/N/A
Snowblower/Cab	Optional	N/A	N/A	N/A	N/A	N/A	N/A
60" Broom/Cab	Optional	N/A	N/A	N/A	N/A	N/A	N/A
Grass Catcher	N/A	N/A	N/A	N/A	Optional**/N/A	Optional†/N/A	Optional

*Optional on S200XTB2761. **Optional on 36" models. †Optional on 48" and 52" models. ‡Optional on 48" models.



MULCH KIT
Select kits include dedicated mulching blades, baffles, hardware and instruction sheet.



TRAILER HITCH KIT
Will accept a 1/2" shank ball and comes complete with hardware.



LIGHT KIT
Select zero-turn models are pre-wired for simple installation.



ARM RESTS
Add these foldable arm rests for increased riding comfort on S50xt.



SUSPENSION SEAT INSERT
Add this to the premium seat on the S800x for increased comfort.



SUSPENSION SEAT
Suspension seat for optimal comfort available on S800x, S200xt, and S150xt.



PREMIUM SEAT
High quality adjustable seat features red trim with foldable arm rests for added comfort. Optional on S125xt.



FLAT-FREE CASTER TIRES
Run all day with no flats, eliminates downtime. Standard on select models.



PROFESSIONAL STRIPE KIT
Rubber flap system lays down grass to create patterns across the landscape. Standard on iCD™ Cutting System decks.



SNOWBLOWER/CAB
Two-stage 60" snowblower and cab available on S800x.



60" BROOM/CAB
Clear debris and snow right down to the pavement. Bidirectional operation can be changed from the seat. (Cab enclosure available, not shown.)



GRASS CATCHER
A lightweight durable 3.75 bushel, fabric bag with hard plastic bottom attaches quickly.

MODEL SELECTION CHART

ENGINE			CUTTING WIDTH				
Gross hp	Make	Fuel Type	36"	48"	52"	61"	72"
15**	Kawasaki® FS541V	Gasoline	SW25	SW25 / SW25CC			
18.5**	Kawasaki® FS600V	Gasoline	SW25CC	SW25/ SW25CC			
19**	Kawasaki® FX600V	Gasoline	S50xt	S50xt			
20.5**	Kawasaki® FX651V	Gasoline		SW35 / SW35CC	SW35 / SW35CC		
23**	Kawasaki® FS691V	Gasoline			S125xt		
23.5**	Kawasaki® FX730V	Gasoline		S150xt	S150xt	SW35 / SW35CC	
24**	Kawasaki® FS730V	Gasoline				S125xt	
25*	Briggs & Stratton Commercial Turf Series™	Gasoline	S50xt	S50xt	S125xt		
25.5**	Kawasaki® FX801V	Gasoline				S200xt	
26*	Vanguard™ 810cc	Gasoline		S150xt	SW35 / SW35CC S150xt	SW35 / SW35CC S200xt	
27*	Briggs & Stratton Commercial Turf Series™	Gasoline				S125xt S200xt	
27^	Kohler® Command Pro EFI ECV749	Gasoline				S200xt	
28*	Vanguard™ 810cc EFI	Gasoline			SW35 / SW35CC S150xt	SW35 / SW35CC S200xt	
28*	Vanguard™ BIG BLOCK™	Gasoline				S200xt	
30^	Yanmar™	Diesel				S800x	S800x
31*	Vanguard™	Gasoline				S800x	S800x
36*	Vanguard™ BIG BLOCK™	Gasoline				S200xt	S200xt

* Rated in accordance with SAE J1940 at 3600 RPM.
** Rated in accordance with SAE J2723 at 3600 RPM.
^ Power levels rated by engine manufacturer.



SPECIFICATIONS		S800X	S200xt	S150xt	S125xt	S50xt	SW35	SW25
ENGINE								
Make (Gross Horsepower)	Yanmar™ Diesel (30") , Vanguard™ (31')	Kawasaki® FX801V (25.5"), Vanguard™ 810cc (26"), Kohler® Command Pro EFI ECV749 (27'), Briggs & Stratton Commercial Turf Series™ (27'), Vanguard™ 810cc EFI (28'), Vanguard™ BIG BLOCK™ (28/36')	Kawasaki® FX730V (24"), Vanguard™ 810cc (26'), Vanguard™ 810cc EFI (28')	Kawasaki® FS691V (23"), Kawasaki® FS730V (24"), Briggs & Stratton Commercial Turf Series™ (25/27')	Kawasaki® FX600V (19"), Briggs & Stratton Commercial Turf Series™ (25')	Kawasaki® FX651V (20.5**), Kawasaki® FX730V (23.5**), Vanguard™ 810cc (26') Vanguard™ 810cc EFI (28'),	Kawasaki® FS541V (15") or Kawasaki® FS600V (18.5")	
PTO	Electric	Electric	Electric	Electric	Electric	Electric	Electric	
Cylinders	2, 3 (diesel)	2	2	2	2	2	2	
Starting	Electric	Electric	Electric	Electric	Electric	Electric	Manual/Electric	
Fuel Capacity (TOTAL)	12 gallons	10 gallons / 5 gallons (S200XTB2761)	10 gallons	5.5 gallons	8 gallons / 4 gallons (S50XTB2536)	5 gallons	5 gallons	
MOWER								
Cutting Width (In.)	61, 72	61, 72	48, 52	52, 61	36, 48	48, 52, 61	36, 48	
Cutting Height (In.)	1.5 - 5	1.5 - 6	1.5 - 5	1.5 - 5.0	1.5 - 4.5	1.5 - 4.75	1.5 - 4.5	
Deck Construction	iCD™ Cutting System with professional lawn striper	iCD™ Cutting System with professional lawn striper	iCD™ Cutting System with professional lawn striper	iCD™ Cutting System with professional lawn striper	10-gauge, fabricated (36"), iCD™ Cutting System with professional lawn striper (48")	10-gauge, fabricated, double top deck, double reinforced side skirts, overlap welded corners	10-gauge, fabricated, double top deck, double reinforced side skirts, overlap welded corners	
Spindles	Cast-iron, greaseable	Cast-iron, greaseable (61"), Hercules™ II, greaseable (72")	Cast-iron, greaseable	Cast-aluminum, greaseable	Cast-aluminum, greaseable	Cast-aluminum, greaseable	Cast-aluminum, greaseable	
Belts	Single B-section Kevlar™ corded belts	Custom 5V belt with Kevlar™ cords	Single 5V-section Kevlar™ corded belts	Single 5V-section Kevlar™ corded belts	Single B-section Kevlar™ corded belts	Single 5V-section Kevlar™ corded belts	Single B-section Kevlar™ corded belts	
CHASSIS								
Frame Rail	C-channel, 7-gauge	2" x 2", 7-gauge	1.5" x 2", 11-gauge	1.5" x 2", 11-gauge	1.5" x 2", 11-gauge	1.5" x 2", 11-gauge	1.5" x 2", 11-gauge	
Bearings	Greaseable tapered caster yoke bearings			Greaseable tapered caster yoke bearings				
Finish	Powdura® super durable powder coat, a high gloss powder coat with excellent impact resistance and outstanding salt and U.V. protection			Powdura® super durable powder coat, a high gloss powder coat with excellent impact resistance and outstanding salt and U.V. protection				
DRIVE SYSTEM								
Transmission	Dual pumps and wheel motors with 7" cooling fans	Commercial Hydro-Gear® ZT-5400 Powertrain® transaxles with 9" cooling fans	Commercial Hydro-Gear® ZT-5400 Powertrain® transaxles with 9" cooling fans	Commercial Hydro-Gear® ZT-3400® transaxles with 7" cooling fans	Commercial Hydro-Gear® ZT-3100® transaxles with 7" cooling fans	Commercial Hydro-Gear® ZT-3100® transaxles with 7" cooling fans	Commercial Hydro-Gear® ZT-3100® transaxles with 7" cooling fans	
Drive Axles	1.25" Tapered	1.375" Tapered	1.375" Tapered	1.125" Tapered	1" Tapered	1" Tapered	1" Tapered	
Drive Tires (in.)	24 x 12-12	24 x 12-12	23 x 9.5-12 (48"), 23 x 10.5-12 (52")	22 x 11-10	20 x 7-10 (36"), 20 x 10-10 (48")	20 x 7 - 10 (48"), 20 x 8 - 10 (52", 61")	20 x 7-10	
Caster Tires (in.)	13 x 6.5 (rear), 11 x 4 (front)	13 x 6.5-6 Flat-Free (excludes S200XTB2761)	13 x 6.5-6 Flat-Free	13 x 5-6	11 x 4-5	11 x 4 - 5 Flat-Free	9 x 3.5 - 4 Flat-Free	
GROUND SPEED								
Speeds-fwd. (mph)	0-10	0-10	0-10	0-10	0-8	0-7	0-6	
Speeds-rev. (mph)	0-5	0-5	0-5	0-5	0-4	0-3	0-3	
DIMENSIONS								
Overall Length	115.5"	79" (61"), 82" (72")	78"	81"	69"	Standard: 78.75, CC™ :75" (48",52") Standard: 80.5", CC™ :76.75" (61")	Standard: 77.5", CC™: 73" (36"), Standard: 75.5", CC™: 71" (48")	
Overall Width : deflector down / up	73" / 61.5" (61"), 88" / 74" (72")	76" / 63" (61"), 88" / 75" (72")	64" / 50" (48"), 68" / 54" (52")	67.5" / 54.5" (52"), 77" / 63.5" (61")	52" / 37" (36"), 64" / 49" (48")	62.5"/49.5" (48"), 67"/57" (52"), 76.5"/65" (61")	51.5"/36.5"	
Dry Weight (lbs.)	1514 (61"), 1677 (72")	1190 (61"), 1424 (72")	1107 (48"), 1141 (52")	1059 (52"), 1113 (61")	688 (36"), 724 (48")	809 (48"), 814 (52"), 888 (61")	632 (36"), 694 (48")	
OPERATOR CONTROL & COMFORT SYSTEMS								
Seat Package	Premium adjustable seat with arm rest	Premium adjustable seat with arm rest	Premium adjustable seat with arm rest	Contour seat with arm rests	Contour seat	N/A	N/A	
Certified ROPS with retractable seat belt	Standard, 90° Foldable	Standard, 165° Foldable	Standard, 180° Foldable	Standard, 180° Foldable	N/A	N/A	N/A	
Instrumentation	Hour meter	Hour meter, Fuel level gauge	Hour meter, Fuel level gauge	Hour meter, Fuel level gauge	Hour meter, Fuel level gauge	Hour meter, Speed Indicator	Hour meter, Speed Indicator	
Safety Group	Seat actuated engine kill, blade, clutch safety switch, parking brake, safety circuit	Seat actuated engine kill, blade, clutch safety switch, neutral and parking brake safety circuit	Seat actuated engine kill, blade, clutch safety switch, neutral and parking brake safety circuit	Seat actuated engine kill, blade, clutch safety switch, neutral and parking brake safety circuit	Seat actuated engine kill, blade, clutch safety switch, neutral and parking brake safety circuit	Operator presence, Centralized foot activated neutral pedals, Neutral Start safety circuit	Operator presence, Centralized foot activated neutral pedals, Neutral Start safety circuit	
Parking Brake	Disk type	Internal transaxle	Internal transaxle	Internal transaxle	Internal transaxle	Internal transaxle	Internal transaxle	
Accessories	Collection System (61"), Mulch Kit, Suspension Seat, Suspension Seat Insert, Flat-Free Caster Tires, Snowblower, Broom, Cab	Collection System (61"), Mulch Kit, Trailer Hitch Kit, Suspension Seat,, Flat-Free Caster Tires (standard on 10 gal. models)	Collection System, Mulch Kit, Trailer Hitch Kit, Light Kit, Suspension Seat	Collection System, Mulch Kit, Trailer Hitch Kit, Light Kit, Premium Adjustable Seat Upgrade, Flat-Free Caster Tires	Collection System (48"), Grass Catcher (36"), Mulch Kit, Trailer Hitch Kit, Light Kit, Arm Rests, Flat-Free Caster Tires, Professional Stripe Kit (36")	Grass Catcher (48", 52"), Mulch Kit, Professional Lawn Striper	Grass Catcher, Mulch Kit, Professional Lawn Striper (48")	
WARRANTY								
Engine	2-Year Limited Manufacturer's Warranty (Yanmar), 3-Year Limited Manufacturer's Warranty (Vanguard)	3-Year Limited Manufacturer's Warranty	3-Year Limited Manufacturer's Warranty	3-Year Limited Manufacturer's Warranty	3-Year Limited Manufacturer's Warranty	3-Year Limited Manufacturer's Warranty	3-Year Limited Manufacturer's Warranty	
Balance of Machine	4-Year Limited Warranty (48 months) or 500 hours, whichever occurs first. Unlimited hours during the first 2 years (24 months). Belts, Tires, Brake Pads, Battery, Blades: 90 days†			4-Year Limited Warranty (48 months) or 500 hours, whichever occurs first. Unlimited hours during the first 2 years (24 months). Belts, Tires, Brake Pads, Battery, Blades: 90 days†		2-Year Limited Warranty commercial use, front-to-rear, parts & labor. Belts, Tires, Brake Pads, Battery, Blades: 90 days†		



**WE CONTINUALLY DEMONSTRATE OUR
COMMITMENT TO PERFORMANCE,
PRODUCTIVITY AND DURABILITY.**

RIDE-ON 2+2 YEAR LIMITED WARRANTY*

We know that each customer has different needs, and now we've got you covered with one simple warranty on all Snapper Pro® ride-on mowers, the 2+2 Year Limited Warranty. Snapper Pro ride-on mowers, including all zero-turn series, and S800x models, are covered for 4 years (48 months) or 500 hours, whichever occurs first. During the first two-years (24 months), the mower is covered for unlimited hours. Belts, tires, brake pads, battery and blades are covered for 90 days. For engine warranty see engine operator's manual.

*See your dealer for warranty details

WALK-BEHIND 2 YEAR LIMITED WARRANTY*

Walk-behind mowers are covered for two-years (24 months) for unlimited hours. Belts, tires, brake pads, battery and blades are covered for 90 days. For engine warranty see engine operator's manual.



www.SnapperPro.com

Hydro-Gear® is a trademark of Hydro-Gear Inc., and is used under license

Kawasaki® is a registered trademark of Kawasaki Motors Corporation

Kohler® is a registered trademark of Kohler Company

Marbain® is a registered trademark of The Fisher-Barton Group

Viton® is a registered trademark of DuPont

Yanmar™ is a trademark of Yanmar

Briggs & Stratton®: All power levels are stated gross horsepower at 3600 rpm per SAE J1940

Kawasaki®: All power levels are stated gross horsepower at 3600 rpm per SAE J2723

Kawasaki®: All power levels are stated gross horsepower per SAE J2723

Kohler® and Yanmar™: All power levels are provided by manufacturer

Acres per hour rating shown at 80% efficiency to represent typical mowing conditions. MPH x width of cut / 124 = acres per hour.

Not all models available in California. Models subject to change without notice.

BRIGGS&STRATTON PRODUCTS GROUP

MUNNSVILLE, NY 13409 USA

800 933 6175

©2015 ALL RIGHTS RESERVED

PART # 2112_SPR_CAT_0914