

# Connecting the PAPER & DIGITAL World

HIGH-SPEED FAXING


SECURE DOCUMENTS

COLOR SCAN TO E-MAIL

DOCUMENT MANAGEMENT

COMPACT DESIGN

IMPRESSIVE PRINTING PERFORMANCE



MFX-3091



BUSINESS-CLASS DOCUMENT SOLUTIONS

**muratec**

# Introducing the MFX-309I from Muratec. An MFP geared to improve your document workflow.

- 50-sheet reversing automatic document feeder quickly captures two-sided originals
- Platen glass captures documents that are not suitable for the document feeder (multipart forms, ID cards, bound documents)
- Color scan to e-mail, FTP, PC folders and USB flash drives
- High-speed faxing from the MFX-309I or your PC
- Multitasking technology enables you to perform multiple copy, fax and scan features simultaneously

## Document Capture & Routing

## Powerful Printing

- Print at up to 35 pages-per-minute
- Standard PCL and PostScript 3 enables printing from a variety of Windows, Macintosh, Linux and UNIX print environments
- Protect sensitive documents using the secure print feature
- Print documents from USB flash drives
- Standard 250-sheet paper cassette and 100-sheet bypass tray support a variety of paper weights and stocks. An optional 530-sheet paper cassette can be added to boost capacity.

- Adjustable LCD screen reduces glare and enhances user accessibility
- QWERTY keypad is located under the quick dial keys to enable simple e-mail address entry, job programming and more
- One-touch buttons on the control panel provide instant access to e-mail addresses and fax locations
- "Help" button provides real-time assistance for the function you are using

## Intelligent User Interface

The MFX-309I was designed to enhance your workgroup's ability to print, scan, fax and distribute documents. Standard features such as a reversing automatic document feeder (RADF), high-resolution color scanner, PCL & PostScript3 printing, intelligent user interface and high-speed network connection provide the tools needed to quickly produce, capture and distribute documents.

## Environmentally Responsible

- Standard duplex printing reduces paper consumption
- Energy Star® compliance promotes responsible energy usage
- Separate toner and drum cartridges minimize waste by enabling supply replacement after the cartridge is completely empty
- Consolidate multiple office devices into a single, energy-efficient product
- Supports printing on recycled paper stocks

# Quickly Capture Documents & Execute Job Functions



## 1 Document Feeder

- 50-sheet reversing document feeder quickly captures two-sided color and monochrome documents.
- Scan documents at up to 2.2 seconds-per-page.



## 2 Platen Glass

- 8.5" x 11" platen glass enables you to scan and copy originals that cannot be fed through the document feeder; such as multipart forms, ID cards, bound documents, photos, etc.



## 3 Control Panel

- The MFX-309I puts the features you need right at your fingertips. Quickly navigate menu screens, access real-time help and send documents at the touch of a button.

### The MFX-309I Features:



- 35 page-per-minute printing
- 50-sheet reversing automatic document feeder
- 8.5" x 11" platen glass
- 600 x 600 dpi color scanner
- 1200 x 1200 dpi print resolution (ultra reliable LED print technology)
- Scan to e-mail, FTP and SMB
- 33.6 Kbps fax modem
- PC fax utility
- Backlit LCD screen w/QWERTY keypad

- 250-sheet paper cassette (supports 16 - 32 lb. paper)
- 100-sheet multipurpose bypass tray (supports 16 - 43 lb. paper)
- 150-sheet document output tray
- PC 5e / XL / PostScript 3 printing support
- USB host drive (print / scan support)
- Optional 530-sheet paper cassette can be added to increase paper capacity to 880-sheets

# MFX-309I Specifications

## GENERAL

|                                                   |                                                                                                                                                                 |
|---------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Recording Method</b>                           | LED                                                                                                                                                             |
| <b>Monochrome Print Speed</b>                     | 35 pages-per-minute                                                                                                                                             |
| <b>User Interface</b>                             | Backlit LCD w/QWERTY                                                                                                                                            |
| <b>Reversing Automatic Document Feeder (RADF)</b> | 50 sheets                                                                                                                                                       |
| <b>RADF Scan Position</b>                         | Face up                                                                                                                                                         |
| <b>Standard Paper Capacity</b>                    | 350 sheets (including 100-sheet bypass tray)                                                                                                                    |
| <b>Maximum Paper Capacity</b>                     | 880 sheets                                                                                                                                                      |
| <b>Envelope Capacity in Bypass Tray</b>           | 10 envelopes (24 - 28 lb.)                                                                                                                                      |
| <b>Cassette Paper Weight</b>                      | 16 - 32 lb.                                                                                                                                                     |
| <b>Bypass Paper Weight</b>                        | 16 - 43 lb.                                                                                                                                                     |
| <b>Duplex Printing</b>                            | Standard                                                                                                                                                        |
| <b>Duplex Scanning</b>                            | Standard                                                                                                                                                        |
| <b>Output Tray Capacity</b>                       | 150 sheets                                                                                                                                                      |
| <b>Duplex Printing</b>                            | 1:2, 2:2                                                                                                                                                        |
| <b>Dimensions (H x W x D)</b>                     | 17.9" x 16.8" x 16.7"                                                                                                                                           |
| <b>Weight</b>                                     | 44.09 lbs.                                                                                                                                                      |
| <b>Toner Yield</b>                                | 10,000 impressions*                                                                                                                                             |
| <b>Drum Yield</b>                                 | 30,000 impressions                                                                                                                                              |
| <b>Power Consumption (Operating Mode)</b>         | 580w                                                                                                                                                            |
| <b>Power Consumption (Power Save)</b>             | 14w maximum                                                                                                                                                     |
| <b>Power Consumption (Sleep Mode)</b>             | 3w maximum                                                                                                                                                      |
| <b>Noise Emissions (Operating Mode)</b>           | 55 dBA                                                                                                                                                          |
| <b>Noise Emissions (Standby)</b>                  | 30 dBA                                                                                                                                                          |
| <b>Ethernet Connection</b>                        | Standard 10/100 BaseT, RJ-45 Connection                                                                                                                         |
| <b>Supported Network</b>                          | TCP/IP v4, TCP/IP v6, SMTP, POP3, HTTP, SNMP v1 / v3, DHCP, DNS, LPR, BOOTP, ARP, FTP, CIFS, LDAP, Bonjour, Web Services Discovery, NetWare, EtherTalk, NetBEUI |
| <b>LDAP Support</b>                               | Standard                                                                                                                                                        |
| <b>Local Connection</b>                           | Standard USB 2.0                                                                                                                                                |
| <b>Memory</b>                                     | 256 MB (Std / Max)                                                                                                                                              |

## PRINT

|                                   |                                                                                                                                               |
|-----------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Processor Speed</b>            | 330 MHz                                                                                                                                       |
| <b>Print Resolution</b>           | 1200 x 1200 dpi                                                                                                                               |
| <b>Page Description Language</b>  | Standard PCL 5e, PCL 5e / XL / PostScript 3                                                                                                   |
| <b>Client OS Support</b>          | 32-/64-bit – Windows® 7, Windows 8, Vista®, XP, Server 2008 and Server 2003; 64-bit – Server 2008 R2; Win 2000; Mac Support – OS 10.5 to 10.7 |
| <b>First-Print-Out-Time</b>       | 5 seconds                                                                                                                                     |
| <b>Warm-up Time</b>               | 25 seconds                                                                                                                                    |
| <b>Secure Print</b>               | Yes                                                                                                                                           |
| <b>Print Alignment</b>            | Upper Left Corner                                                                                                                             |
| <b>Print from USB Flash Drive</b> | Standard                                                                                                                                      |

## COPY

|                               |                           |
|-------------------------------|---------------------------|
| <b>Copy Resolution</b>        | 600 x 600 dpi             |
| <b>Copy Speed</b>             | 35 copies-per-minute      |
| <b>Platen Glass</b>           | 8.5" x 11"                |
| <b>First-Copy-Out-Time</b>    | 11 seconds                |
| <b>Image Combination</b>      | 2:1, 4:1, ID Card Copy    |
| <b>Zoom Ratio</b>             | 25 - 400% (1% increments) |
| <b>Electronic Sorting</b>     | Standard                  |
| <b>Number of Copies</b>       | 1-99                      |
| <b>Mixed Original Support</b> | Yes                       |
| <b>Repeat Copy</b>            | 2-up, 4-up                |

## SCAN

|                                           |                                                                      |
|-------------------------------------------|----------------------------------------------------------------------|
| <b>Scanning Method</b>                    | CIS                                                                  |
| <b>Resolution</b>                         | Up to 600 dpi                                                        |
| <b>Color Scan Depth</b>                   | 48-bit color                                                         |
| <b>Gray Scale</b>                         | 256 levels                                                           |
| <b>Background Removal</b>                 | Standard                                                             |
| <b>Scan To E-mail</b>                     | Standard                                                             |
| <b>Supported Mail Server Applications</b> | Lotus Mail Server 5.0, MS Exchange Server 2000, RedHat 7.0 SendMails |
| <b>Job Build (Scanning)</b>               | Yes                                                                  |
| <b>E-mail Subject Line / Body Editing</b> | Yes                                                                  |

|                                                      |                                  |
|------------------------------------------------------|----------------------------------|
| <b>File Name Editing</b>                             | Yes                              |
| <b>Change "Reply To" E-Mail Address when Sending</b> | Yes                              |
| <b>Scan To PC</b>                                    | Standard                         |
| <b>Scan To FTP</b>                                   | Standard                         |
| <b>Scan to USB Flash Drive</b>                       | Standard                         |
| <b>E-mail Address Book</b>                           | 100 locations                    |
| <b>Scan File Formats</b>                             | PDF, TIFF, JPEG, XPS             |
| <b>Scan as Encrypted PDF</b>                         | Yes                              |
| <b>Monochrome Scan Speed</b>                         | 2.2 seconds per page (300 dpi)   |
| <b>Color Scan Speed</b>                              | 3 seconds per page (300 dpi)     |
| <b>TWAIN Compliant</b>                               | Standard                         |
| <b>WSD Compliant</b>                                 | Standard (local connection only) |

## FAX

|                             |                                     |
|-----------------------------|-------------------------------------|
| <b>Modem Speed</b>          | 33.6 Kbps                           |
| <b>Transmission Speed</b>   | Under 2 seconds                     |
| <b>Compression</b>          | MH, MR, MMR, JBIG                   |
| <b>Fax Memory</b>           | 4 MB (200 pages)                    |
| <b>One-Touch Locations</b>  | 16                                  |
| <b>Speed Dial Locations</b> | 100                                 |
| <b>Broadcasting</b>         | 100 locations                       |
| <b>Confirmation Report</b>  | Yes                                 |
| <b>Group Dialing</b>        | 20 groups / 100 locations per group |
| <b>Memory Back-Up</b>       | Stored in Flash Memory              |
| <b>Secure Fax Reception</b> | Yes                                 |
| <b>PC-based Faxing</b>      | Yes                                 |
| <b>Delayed Transmission</b> | Yes. Up to (20) jobs                |
| <b>Internet Faxing</b>      | Standard T.37                       |

## OPTIONS & ACCESSORIES

### ITEM NO

|                                 |         |
|---------------------------------|---------|
| <b>530-Sheet Paper Cassette</b> | 3091CAS |
| <b>MFX-309I Toner Cartridge</b> | TS309I  |
| <b>MFX-309I Drum Cartridge</b>  | DK309I  |

\*Yields based on ISO 19752 specification



As an ENERGY STAR® partner, Murata Machinery, Ltd. has determined that these products meet the ENERGY STAR® guidelines for energy efficiency. Muratec and the Muratec logo are trademarks and/or registered trademarks of Murata Machinery, Ltd. or its subsidiaries in the United States and other countries. Other names, such as those of products of other companies, are the trademarks or registered trademarks of their respective companies. All specifications subject to change without notice.



**Muratec America, Inc.**  
3301 East Plano Parkway, Suite 100, Plano, Texas 75074  
For more information on Muratec products or services, call (469) 429-3300 or visit our web site at [www.muratec.com](http://www.muratec.com)