# **TOSHIBA**

Leading Innovation >>>

- > Black & White MFP
- > Up to 55 PPM
- > Small/Med. Workgroup
- > Copy, Print, Scan, Fax
- > Secure MFP



## **E**:STUDIO:477sL/527s



- > Black & White MFP
- > Up to 55 PPM
- > Small/Med. Workgroup
- > Copy, Print, Scan, Fax
- > Secure MFP

#### **Specifications**

Indirect Electrostatic Photographic Copying Process

Transfer System with Internal Transfer Belt

LED Head Printing Copying Type

Copy/Print Resolution 600 x 600 dpi (1200 x 1200 dpi - PS3 only)

Copy/Print Speed 49/55 PPM B&W Warm-Up Time Approx. 60 Seconds First Copy Out Time 8 Seconds Multiple Copying Up to 999 Copies

Cassette: ST-R to LG (17lb Bond - 120lb Index) Acceptable Paper Size

Bypass: 3" x 5" to LG, and Weight

Banner 8.5" x 52" (17lb Bond - 138lb Index)

Memory (Max) Main Memory: 2GB

HD: 320GB FIPS 140-2 Validated SED

Document Feeder 100-Sheet Reduction/Enlargement 25% to 400%

100-Sheet "Smart" Bypass (17lb Bond - 138lb Index) Bypass

Control Panel Color 9" LCD Touch Panel Up to 3,160-Sheet Input Capacity Paper Supply Standard 1 x 530-Sheet Cassettes 100-Sheet Bypass

Optional 3 x 530-Sheet Cassette Optional 2,000-Sheet LCF

Std. Automatic Duplex Unit (17lb Bond - 120lb Index) Duplex Dimensions 477sL: Approx. 20.55" x 22.2" x 26.5" (W x D x H) 527s: Approx. 20.55" x 22.2" x 32" (W x D x H)

Weight Approx. 115lb 36K Toner Yield

Power Supply 120 V, 15 Amps Power Consumption Maximum 1.5 kW Max Duty Cycle 200K/225K Copies

#### e-BRIDGE Print Specifications

PCL6, PostScript 3, XPS PDL Support

Windows Server 2003, 2008, 2012, Vista SP2, 7, 8, Operating Systems

NetWare 6.5, Citrix, Macintosh 10.4-10.9,

Solaris v10, 11, HP-UX V11.iv3, AIX 7.x, Linux, SCO Protocol Support Windows Printing (SMB1.0/2.0), LPR/LPD, IPP (Ver.1.1) w/Authentication, NetWare P-SERVER w/NDS, Binary, Novell NDPS Gateway, or LPD w/iPrint, Apple Talk PAP or

EtherTalk, Port 9100 (bi-directional), WS Print, FTP

Windows Server 2003, 2008, 2012, Vista SP2, 7, 8, Drivers Macintosh OS 10.4-10.9

10/100/1000BaseTX Ethernet, Connectivity 802.11b/g/n, Wireless LAN, USB

Wireless Device AirPrint, e-BRIDGE Print & Capture Application on iOS and

Android (Available via Apple App Store or Google Play)

Top Access, eFMS 6.0 (e-BRIDGE Fleet Device Management

Management Software)

Windows 7, 8, 8.1,2008R2, 2012, 2012 R2, Certification

WHQL, Novell, Citrix

## **Scan Specifications**

Scan Resolution 100 dpi, 150 dpi, 200 dpi, 300 dpi, 400 dpi, 600 dpi Scan Speed 55 SPM B&W, 40 SPM Color (@ 300 dpi)

File Format TIFF, PDF, Secure PDF, JPEG, XPS (with HDD)

## **Facsimile Specifications**

Compatibility Super G3 MH/MR/MMR/JBIG Data Compression Transmission Speed Approx. 3 Seconds Per Page Fax Modem Speed 33.6 Kbps

.7 Seconds Per Page, Maximum 42 SPM Scan Speed

## E-Filing Specifications

Color Touch Screen Control Panel or Client PC Operation Method Number of Boxes 1 Public Box, 200 Private User Boxes

100 Folders Per Box, 400 Documents Per Folder, Capacity of Boxes

200 Pages Per Document

Security

Data Encryption 256 Bit AES (SED Hard Drive)

1-5 Time Overwrite (meets DOD standard) Disk Overwrite Authentication LDAP, SMTP, Windows Server Domain, Local

#### Accessories (Options)

#### Additional Paper Options, Spacers, Caster Base

Spacer: (For Adjusting Machine Height Replacing a Stand) GR1160 Caster Base: (Caster Base for PFU, LCF or Spacer) GR1170 Cassettes: 530-Sheet Pedestal, ST-R to LG MY1046 Large Capacity Feeder (LCF): 2,000-Sheet Drawer, LT, KD1040 Stand (Use in place of LCF) STAND407CS

### **Finishing Options**

Inner Finisher (For e-STUDIO527s Only): MJ1038

1 Tray: 500 Sheets

Damper Kits KK1003 Offline Stapler MJ1039

## Connectivity/Security Options

Fax Board GD1340 Meta Scan Enabler for e-CONNECT GS1010 IPsec Enabler GP1080 Advanced Scanning (Re-Rite) GB1280V8 SharePoint Connector GB1440 GB1450 Exchange Connector Google Docs Connector GB1540















TOSHIBA Leading Innovation >>>



**Corporate Office** 9740 Irvine Blvd., Irvine, CA 92618-1631

Tel: 949-462-6000

959 Route 46 East, 5th Floor, Parsippany, NJ 07054 Fast Coast

Tel: 973-316-2700

8770 W. Bryn Mawr Ave., Suite 700, Chicago, IL 60631 Midwest

Tel: 773-380-6000

South 2037 Bakers Mill Rd., Dacula, GA 30019

Tel: 678-546-9385

9740 Irvine Blvd., Irvine, CA 92618 West Coast

Tel: 949-462-6000

Web Site www.business.toshiba.com

Designs and specifications subject to change without notice. For best results and reliable performance, always use supplies manufactured or designated by Toshiba. Not all options and accessories may be available at the time of product launch. Please contact a local Authorized Toshiba Dealership for availability. Toner yields are estimates based on 6% coverage, letter-size page. Driver and connectivity feature support vary by client/network operating system.

© 2014 Toshiba America Business Solutions, Inc. Electronic Imaging Division Inv. Code: 22265 477sL/527s Short Series Spec Sheet 1.5K PG 7/14

