TASK FORCE TIPS
FIRE FIGHTING EQUIPMENT

LOGIN New User?

Products Quick Links to Products

Home | Online Catalog | Product Search | Customer Service | Library | Find Dealer | About Us

ME2-VPGI

METRO 2 W/GRIP 1.5" NH (38mm)

Part No: ME2-VPGI

zoom

Details

METRO 2 W/GRIP 1.5" NH (38mm) Fixed gallonage nozzle with 10 flow and pressure choices. The METRO 2 includes a flush without shutting down, ball valve shut-off and molded rubber teeth for full-fill "power fog" pattern. Lightweight hardcoat anodized aluminum for maximum resistance to corrosion and wear. Pistol grip is mounted below the valve. 1.5" NH (38mm) full-time swivel rocker lug coupling is standard.

Weight: 6.600 lbs (2.993 kg)

More details | Related Products

Flow Control Method	Fixed Flow at a pressure (constant gallonage, flow does not change with pattern)
Flow Rate	Metro II - User Selectable
Coupling Size (Nozzles)	1 1/2 inch (38mm)
Coupling Style (Nozzles)	Rocker
Coupling Swiveling/Rigid (Nozzles)	Swivel (full time, even after tightening)
Pressure	Metro - User Selectable
Nozzle Body Style	Nozzle with shutoff and pistol grip
Valve Design	Ball Valve (Delrin/Acetal)
Valve Actuation Method	Horseshoe (Injection Molded Nylon w/ Colored Handle)
Fog Pattern Method	Molded Rubber Teeth (fixed)
Nozzle Bumper Material	Rubber - bonded
Certifications	N/A
Foam Expansion Performance	N/A

Related Videos

- **Pistol Grip Replacement**
- **Metro Series Video**
- **Nozzle Field Maintenance**
- **Visual Nozzle Inspection**

Online Technical Support Material

Metro 1/Metro 2 NFPA 1964 (pdf)
Service Procedure: Mid-Matic, Mid-Force, Metro 1 (pdf)
Metro 1 & Metro 2 Instruction Manual (pdf)

Technical Specifications and Drawings

ME2-VPGI Item Specification (doc)
ME2-VPGI Finished Good Print (pdf)
ME2-VPGI Finished Good Print (dxf)

CLICK TO SAVE PAGE AS PDF

PRODUCT SERIES OVERVIEW

- The METRO series of fixed gallonage nozzles are the perfect choice to help simplify complex fireground hydraulic calculations. All METRO 1, excluding the ME1-TO and ME1-TOS, comes with a standard inlet debris screen, quick straight stream to fog pattern control, and reflective Scotchlite labeling.

- The METRO 1 series comes with flow choices of 95, 125, 150 or 185 gpm at 50 psi, 60, 125, 150, 175 or 200 gpm at 75 psi, and 60, 95, 125, 150 or 175 gpm at 100 psi.

- The METRO 2 with 185 and 250 gpm at 50 psi, 125, 185, 200, and 250 gpm at 75 psi, and 95, 175, 250 or 325 at 100 psi.

- Pistol grips and custom laser engraved handle covers are available in white, black, red, blue, yellow, green, orange, pink, purple, tan, and gray. The perfect tool to identify individual attack lines or apparatus.

- METRO 0 series of fixed gallonage nozzles with 7 flow and pressure choices. Delivered with the 95 gpm @ 100 psi (380 l/min @ 7 bar) calibrated flow disc installed.