TASK FORCE TIPS
FIRE FIGHTING EQUIPMENT

LOGIN New User? Products Quick Links to Products

Home Online Catalog Product Search Customer Service Library Find Dealer About Us

FQS125PS

QUADRAFOG W/GRIP 1.5" NH (38mm)

Part No:FQS125PS

zoom

Details

QUADRAFOG W/GRIP 1.5" NH (38mm) Selectable gallonage nozzle with four flow settings of 30, 60, 95, and 125 gpm @ 100 psi (110-230-360-470 l/min @ 7bar). All lightweight materials, hardcoat anodized aluminum. Flush without shutting down. Quick-change rear valve seat and stainless steel shut-off ball. Pistol grip is mounted below the valve. Rocker lug 1.5" NH swivel is standard.

Weight: 2.900 lbs (1.315 kg)

CLICK TO SAVE PAGE AS PDF

More details | Related Products

Flow Control Method	Selectable Flow at a pressure (constant gallonage, flow does not change with pattern)
Flow Rate	30 & 60 & 95 & 125 gpm (110 & 230 & 360 & 470 l/min)
Coupling Size (Nozzles)	1 1/2 inch (38mm)
Coupling Style (Nozzles)	Rocker
Coupling Swiveling/Rigid (Nozzles)	Swivel (non-full time, no swivel after tightening)
Pressure	100 psi (7bar)
Nozzle Body Style	Nozzle with shutoff and pistol grip
Valve Design	Ball Valve (Stainless)
Valve Actuation Method	Horseshoe (Injection Molded Nylon w/ Colored Handle)
Fog Pattern Method	stainless steel teeth (spinning)
Nozzle Bumper Material	Rubber - bonded
Certifications	NFPA/FM
Foam Expansion Performance	N/A

Related Videos

- **Pistol Grip Replacement**
- **Bail Handle and Valve Seat Ball Valve**
- **QuadraFog Series Video**

Online Technical Support Material

- **QuadraFog & ThunderFog Demo Sheet (pdf)**
- **1.5in QuadraFog/QuadraCup NFPA 1964 (pdf)**
- **QuadraFog FM Approval (pdf)**
- **Service Procedure: 1.5 QuadraFog & QuadraCup (pdf)**
- **Manual de Instruções ThunderFog & QuadraFog (pdf)**
- **QuadraFog & ThunderFog Instruction Manual (pdf)**

Technical Specifications and Drawings

- **FQS125PS Item Specification (doc)**
- **FQS125PS Finished Good Print - STEP (zip)**
- **FQS125PS Finished Good Print (pdf)**
- **FQS125PS Finished Good Print (dxf)**

PRODUCT SERIES OVERVIEW

- The Quadrafog Series of selectable gallonage 1 in and 1.5 in nozzles are designed for simple operation and rugged durability in wildland or structural firefighting operations. Available in tip only configurations or with a stainless steel ball shutoff and optional color coded nylon pistol grip, these series incorporate lightweight aluminum construction, reflective labeling, and stainless steel components with a protective front rubber bumper.

- The 1 in Quadrafog Series, with its fixed cut fog tooth pattern is ideal for wildfire operations or booster line operations. The 1.5in Quadrafog Series are available with either TFTs uniquely cut style of fixed fog teeth, or our popular stainless steel spinning teeth to provide a wide protective fog pattern. All models also accept either a low or multi-expansion foam aspiration attachment.

- All Quadrafog Series ball shutoff models offer TFTs unique quick change rear valve seat that requires no special tools or disassembly of the valve to change the rear seat assembly. The shut off handle can be color coded, laser engraved, and is produced from nylon to withstand harsh operating conditions without breaking or bending.

TFT ® is a registered trademark of Task Force Tips, Inc.
Task Force Tips ® is a registered trademark of Task Force Tips, Inc.
TFT ® is a registered trademark of Task Force Tips, Inc.

Task Force Tips © 2015 • 3701 Innovation Way Valparaiso IN 46383-9327 • Phone (800) 348-2686