# GERALDINE®

## Nonammoniated Wax and Finish Stripper

*This product quickly unlocks the molecular structure of all types of water-based floor waxes, finishes, and floor sealers. It removes floor waxes; petroleum and carnauba-based products. It removes floor finishes; acrylics, metal crosslinked polymers and copolymers. This product also is an excellent heavy duty cleaner. It's great for cutting wax build-up, grease, oil and dirt. The unique chemical elements penetrate, dissolve, and lift the wax to the surface to be picked up easily. This product is effective in hot, cold, hard or soft water. Safe for use on all floors not harmed by water.*

### Uses

**Floor Wax Stripping:**
- Asphalt tile
- Cork
- Rubber
- Terrazzo
- Vinyl asbestos

**Cleaning:**
- Concrete
- Floors
- Kitchens
- Machinery
- Walls

### Features

- Pleasant - No harsh ammonia or solvent odors. Perfect for small or large areas.
- Powerful stripping action quickly unlocks all synthetic polymer and molecular wax chains.
- Extended suspension of emulsified particles eliminates costly restripping.

### Properties

| | |
|---|---|
| Color | Pink |
| Detergency | Excellent |
| Emulsification | Excellent |
| Flash point | None |
| Foaming | Moderate |
| Fragrance | Pleasant |
| Metal interlock removal | Complete |
| pH | 13.0 - 13.9+ |
| Rinsability | Complete |
| Solubility in water | Complete |
| Specific gravity | 1.07 |
| Viscosity | 5 centipoise |
| Wax removal | Complete |
| Wetting | Excellent |
| Shelf life | 1 year |

### Directions For Use

**Read the entire label before using this product.**
Recommended for removing water-based acrylic and urethane fortified floor finishes from all types of resilient tile and hard surfaces. Pre-test in a small area; color bleeding or discoloration may occur on linoleum, rubber tile, or asphalt tile. *Not recommended for stripping linoleum or sheet vinyl floors.* Sweep or dust mop floor to remove any large debris. Dilute with hot water. For normal stripping dilute 13 oz./gal. or 100 mL/L (1:10) of water. For heavy stripping dilute 25 oz./gal. or 200 mL/L (1:5) of water. Apply solution liberally to floor surface. Allow 4 - 5 minutes contact time. Be sure to keep surface wet at all times. Agitate with a low speed rotary machine, automatic scrubber or stripping machine. Pick up solution with a wet vacuum, automatic scrubber or mop and bucket and thoroughly rinse the floor. Allow floor to dry completely before applying finish or sealer.

### Safety

Keep out of reach of children. For institutional and commercial use. **DANGER:** CORROSIVE. Contains Sodium Hydroxide, 2-Butoxyethanol, and Monoethanolamine. Avoid contact with skin and eyes. Wear chemical anti-splash goggles and suitable gloves and boots. Harmful if swallowed. **FIRST AID:** Remove contaminated clothing immediately. SKIN AND EYES: Flush skin and eyes immediately with large quantities of water for at least 15 minutes. Seek immediate medical attention. INGESTION: If swallowed, contact a poison control center immediately for treatment advice. Have conscious person take sips of water if able to swallow. Never give anything by mouth to an unconscious person. Do not induce vomiting unless instructed to do so by poison control center or doctor. INHALATION: Remove to fresh air. If not breathing, call 911 or ambulance, then administer artificial respiration.

### Available In

Case/4 - 1 Gallon (3.78 L): Item #10404-00
Pail/5 Gallon (18.9 L): #10405-00
Drum/55 Gallon (208 L): #10455-00



©Betco Corporation • All Rights Reserved. • 1001 Brown Avenue • Toledo, Ohio 43607-0127 • 888-GO BETCO (888-462-3826) • email@betco.com • www.betco.com