SURE™ CURE

Acrylic Urethane Sealer/Finish

This Water-Based Acrylic Urethane Sealer/Finish is the answer to your most challenging floors. Outstanding adhesion characteristics make this sealer an excellent choice for a variety of flooring substrates including: VCT, Terrazzo, Stone, Sheet Vinyl and laminate flooring. This sealer is widely used on new and old concrete as an alternative to permanent sealers because it has the flexibility to be recoated or removed with a high performance floor stripper.

Uses

- Resilient tile
- Brick
- Slate
- Terrazzo
- Quarry tile
- Marble
- Ceramic tile
- Concrete, new and old

Benefits

- Urethane formula provides a durable protective coating for the floor.
- Versatile - Adheres to a variety of floor types and is easily maintained.
- Clear Gloss - Uses non-yellowing polymers with excellent long-term color stability for high gloss.
- Strippable - Allows for application to resilient tile floors.
- Water-based - Pleasant to work with, low odor. Clean up is easy.
- Chemical Resistance - to All Purpose and Alkaline cleaners.

Properties

Color (dried film)	Clear
Color (liquid)	Milky-white
Coverage	1500 - 2000 sq. ft./gallon
Drying time	30 - 45 minutes under normal conditions
Durability	Excellent
Flash point	None
Fragrance	Mild
Freeze/thaw stability	Protect from freezing
Initial gloss	High
Leveling	Excellent
Solids	>20%
pH	8.4 - 8.9
Recoatability	Very good
Shelf life	1 year

Directions For Use

Read the entire label before using this product.
RESTORATIVE MAINTENANCE: Completely remove all old wax, finish and soil from the floor surface using a stripper or cleaner/degreaser. Floor surface must be clean, dry and free of residue before sealer is applied. Rinse with water if necessary. Apply sealer/finish in uniform, thin to medium coats using a clean synthetic finish mop or applicator system. Allow each coat to dry thoroughly before applying additional coats, usually 30 - 45 minutes. Four to five coats of sealer/finish are recommended. Elevated temperatures and humidity may extend dry time.
INTERIM MAINTENANCE: Simply deep scrub the floor and recoat as necessary. Floor surface must be clean, dry and free of residue before sealer/finish is applied. Rinse with water if necessary.
ROUTINE MAINTENANCE: Damp mop or automatic scrub with a pH neutral or nonbutyl cleaner at recommended dilutions.
CONCRETE APPLICATION: May be applied to new concrete after 30 days (fully cured) and a surface temperature above 50 °F. Prior to applying sealer to new concrete, use an acidic solution to neutralize excess alkalinity. All new concrete must be cleaned and rinsed. Not for use outdoors. Old concrete must be cleaned with a degreasing solution and rinsed for proper adhesion.
GLAZED TILE/POLISHED SURFACES: 1. Test in an inconspicuous area first, proper adhesion may be difficult due to lack of porosity.
NOTE: Slip resistance meets or exceeds (ASTM D 2047-04) James Machine 0.5 minimum.

Safety

Keep out of reach of children. For institutional and commercial use.
WARNING: SKIN AND EYE IRRITANT. Contains Glycol Ether. Vapor and spray mist harmful. May cause headache, dizziness or nausea. Harmful if absorbed through skin. Wear safety glasses and impervious gloves such as Butyl Rubber. Use with adequate ventilation. Do not breathe vapor, mist, or dust. Wearing an appropriate NIOSH approved respirator is recommended unless air monitoring demonstrates vapor levels are below applicable limits. Follow manufacturer's directions for respirator use. Avoid contact with eyes, skin, and clothing. **FIRST AID:** IF ON SKIN OR CLOTHING: Remove contaminated clothing, wash skin with soap and water. Seek medical attention if irritation persists. IF IN EYES: Rinse with gentle stream of water for 15 minutes. Seek medical attention. IF INHALED: Remove to fresh air. If not breathing, call 911 or ambulance, then administer artificial respiration. IF SWALLOWED: Contact a poison control center or doctor for treatment advice. Do NOT induce vomiting unless instructed to do so by poison control center or doctor.

Available In

Case/4 - 1 Gallon (3.78 L): Item #60904-00
Case/2 - 1.25 Gallon (4.73 L): Item #60959-00 (QUICKCOAT®)
Pail/5 Gallon (18.9 L): #60905-00
BIB/5 Gallons (18.9 L): Item #60739-00
Drum/55 Gallon (208 L): #60955-00

Literature Item #60992-92

©Betco Corporation • All Rights Reserved. • 1001 Brown Avenue • Toledo, Ohio 43607-0127 • 888-GO BETCO (888-462-3826) • email@betco.com • www.betco.com