GREEN EARTH®
FLOOR FINISH

This product was developed using highly advanced polymer technology to provide a premium environmentally preferred floor finish. This high solids finish offers a clear, deep gloss and requires fewer coats to achieve the desired results.*

This product is part of Betco's Green Earth® program. Betco's Green Earth® products are formulated and packaged to have a reduced environmental impact while still maintaining superior performance.

Uses

- Resilient tile

Performance Benefits

- High gloss.
- Extended wear formula.
- Holds gloss between burnishing.
- Self sealing.
- Excellent leveling.
- Available in QUICKCOAT® packaging.
- Reduces labor.

Environmental Benefits

- No zinc crosslinking agents.
- Less than 0.5% total phosphorous
- No ammonia.
- No flammable solvents.
- No 2-Butoxyethanol.
- No environmentally toxic preservatives.
- No alkyl phenol ethoxylate (APE).
- No bio-accumulative fluorocarbon surfactants.
- No added fragrance.
- VOC's do not exceed established limits for applicable category.
- Low environmental impact packaging.

Properties

Color (dried)	Crystal Clear
Color (liquid)	White
Coverage	2000 - 3000 square feet/gallon
Drying time	30 - 40 minutes per coat
Fragrance	Mild
Freeze/thaw stability	3 cycles
Gloss (ASTM D1455)	One Coat 80 - 85 Two Coats 90 - 95
Heel mark resistance	Very good
Leveling	Excellent
pH	7.0 - 8.5
Powdering resistance	Excellent
Specific Gravity	1.03
Free styrene content	0.0
Shelf life	1 year

Directions For Use

Read the entire label before using this product.
Recommended for use on all types of resilient tile flooring and properly prepared hard surfaces. RESTORATIVE MAINTENANCE: Completely remove all old wax, finish and soil from floor surface following strip procedure instructions on stripper label. Floor surface must be clean, dry and free of residue before finish is applied. Rinse with clean water if necessary. Apply finish in uniform, thin to medium coats using a clean synthetic finish mop or applicator system. Allow each coat to dry thoroughly before applying additional coats, usually 30 - 40 minutes. 4 - 5 coats of finish are recommended. ***Note: This product is a self sealing finish, however, if tile is old, worn or porous, initially applying 1 - 2 coats of a sealer will enhance gloss and long term performance.*** ROUTINE MAINTENANCE: Damp mop or automatic scrub using a neutral pH cleaner. Buff or burnish the floor as desired. The use of a cleaner/restorer is recommended to condition the floor and extend the time between top scrub and recoating. INTERIM MAINTENANCE: Top scrub the floor using a top scrub cleaner and recommended floor pad to remove the top soiled layers of finish. Floor surface must be clean, dry and free of residue before finish is applied. Apply 1 - 2 coats of finish as directed above. ***Note: Slip resistance meets or exceeds (ASTM D 2047-04) James Machine 0.5 minimum.***

Safety

Keep out of reach of children. For institutional and commercial use. **CAUTION:** Eye irritant. May cause skin irritation. May cause respiratory irritation. Wear safety glasses, and gloves. **FIRST AID:** If splashed on skin or in eyes, flush with large quantities of water. If swallowed, drink two glasses of water. Call a physician. If inhaled, remove to fresh air. If not breathing, call 911 or ambulance, then administer artificial respiration, preferably mouth-to-mouth.

Available In

Case/4 - 1 Gallon (3.78 L): Item #54204-00
Box/2-1.125 Gallon Bags (4.25 L): Item #54259-00 (QUICKCOAT®)
BIB/5 Gallons (18.9 L): Item #54239-00
Drum/55 Gallon (208 L): Item #54255-00

GREEN SEAL CERTIFIED

This product meets the Green Seal™ environmental standard for industrial and institutional floor care products based on its reduced human and aquatic toxicity and reduced smog production potential.

Literature Item #54292-92

BETCO®

©Betco Corporation • All Rights Reserved. • 1001 Brown Avenue • Toledo, Ohio 43607-0127 • 888-GO BETCO (888-462-3826) • email@betco.com • www.betco.com