


HC0627

## HEAVY-DUTY CLEANERS

*Technical  
information*

# KNOCK OUT

Tough-Purpose Soil and Graffiti Remover



### CLEANS WHAT ORDINARY CLEANERS CANNOT

Knock Out's powerful formula is made for the tough jobs - embedded soil, layered soap scum, and filthy scratched-on drawings. Spray on a penetrating coating of cleaning power and watch Knock Out go to work!

### CLINGS TO VERTICAL SURFACES

Knock Out's thickened formula holds fast until soil is dissolved - won't run off brick walls, shower stalls, or tires. The longer the cling, the more thorough the cleaning job!

### SAFE ON MOST METALS

Use Knock Out almost anywhere - in machine shops, on tools, parts, machinery and equipment. The formula will not harm metal - not even aluminum.

### EFFECTIVE ON POROUS SURFACES

Knock out with Penetrol is thick enough to stay where cleaning power is needed - strong enough to penetrate caked-in dirt. Knock Out is the perfect whitewall tire cleaner - whitewalls are returned to showroom white with little effort.

Renew your neglected chimneys, grimeiest fireplace walls and sooty kitchen brick too!

### RIDS DIRT FROM EVERY CREVICE

Use Knock Out with the flexible State Caterpillar Brush to get into the smallest crevice and corner - its potent formula won't allow dirt to stay behind.

Enables cleaning of ridges between bathroom tiles, grouting, rough textured brick walls, tire grooves and intricate machinery.



STATE

*Care for work environments*

1-800-782-2436

# KNOCK OUT

## DIRECTIONS FOR USE

1. Shake well before using.
2. Hold can 6 to 10 inches from surface to be sprayed. Cover surface with a thin, even coating.
3. Do not use on painted or varnished surfaces if paint removal is not desired. Immediately wipe off any overspray.
4. Wait 3 to 5 minutes to allow Knock Out to penetrate. Wipe surface with a damp rag or sponge. For tough stains, use a mild abrasive pad. On rough surfaces such as brick, use a brush.
5. Rinse surface with clean water.
6. To prevent clogging, turn can upside down and spray a short jet of gas after completing each job.

**NOTE:** Before using, always test on a small area of the surface to be cleaned to be sure there is no attack. Note any change in color or texture.

*Please review label and MSDS for all product directions, precautions and first aid information.*

## TECHNICAL DATA

**APPEARANCE:** Aerosol spray

**ODOR:** Fresh and clean

**pH:** 11.8 +/- 0.1

**SPECIFIC GRAVITY OF CONCENTRATE:** 1.002 +/- 0.001

**FLAMMABILITY:** No flame extension; concentrate has no flashpoint to boiling

**FORD CUP VISCOSITY:** 14-16 secs.

**SOIL REMOVAL:** Excellent

**PENETRATING AGENT:** Present

**AMMONIA CONTENT:** None

**WATER CONTENT:** Must contain less than 75% water

**DELETERIOUS EFFECT ON:** **Grouting:** None; **Ceramic Tile:** None; **Stainless Steel:** None; **Vinyl:** None; **Painted Surfaces:** May attack some paints - test small area before use; **Terrazzo:** None; **Aluminum:** None.

**ACTIVE INGREDIENTS:** Must contain not less than 25% active ingredients

**SHELF STABILITY:** Minimum one year

**RINSABILITY:** Excellent

**AUTHORIZATION:** USDA Authorized for use in Federally inspected meat and poultry plants.

