




# MIGHTY SPARKLE™

## Floor Stripper


**Mighty Sparkle™ Bathroom Cleaning System** is a complete line of cleaning products to keep your facility's restrooms shining and smelling great! The **Mighty Sparkle™** line includes specialty products for both hard-surface care and skin care.

*Mighty Sparkle™ brings back the shine!*



## MIGHTY SPARKLE™ Floor Stripper

- High-performance stripper
- Attacks tough stripping problems with ease
- Great for large areas and multiple layers of old, tough, or hardened finish
- Leaves a clean, bare surface - the perfect foundation for a deep, glossy shine
- Excellent for use with automatic floor machines for labor-saving efficiency
- Works without the harsh ammonia fumes found in most common strippers
- Safe on all floors, including asphalt tiles and asphalt plank (in post offices)
- Non-Butyl formula





# MIGHTY SPARKLE™ FLOOR STRIPPER



## Directions for Use:

This product must be diluted with water. For best results, do not use undiluted.

1. Dust mop or sweep.
2. Mop on - Dilute 1:5 with warm water  
Autoscrubber - dilute 1:10 with warm water
3. Apply stripper solution generously to floor and let stand for 5-10 minutes.  
If needed, reapply stripper to areas that dry back.
4. Scrub with a black pad and 175-350 rpm rotary or autoscrubber.
5. Pick up solution with a wet vacuum or mop.
6. Rinse floor with clean, cool water.
7. Damp mop any marks left by foot or machine before applying finish.

Please review label and MSDS for all product directions, precautions and first aid information.



## Technical Data:

**APPEARANCE:** Clear red liquid

**FRAGRANCE:** Morning Fresh™ fragrance

**SOLUBILITY IN WATER:** Soluble

**DENSITY:** 8.6 lbs./gal. (1.03 Kg/L)

**SPECIFIC GRAVITY:** 1.03

**pH:** 13.3±0.2

**PERSONAL PROTECTION:** We recommend you wear chemical goggles and gloves while using this product. We recommend that this product be stored in a sealed container in a well ventilated area away from sparks, fire and open flame. Avoid over treating. Avoid contact with eyes and prolonged contact with the skin.

**FREEZE-THAW STABILITY:** Passed standard test

**SHELF STABILITY:** Minimum one year

**SILICONE:** None present

**DIRT SUSPENSION PROPERTIES:** Excellent

**FLASH POINT:** > 200°F

**FREEZING POINTS:** Undiluted: -3°F

Diluted 1 to 1: 20°F

Diluted 1 to 5: 24°F



**State Industrial Products**  
5915 Landerbrook Drive  
Mayfield Heights, OH 44124  
To Order Call: 1-866-747-2229  
www.stateindustrial.com

**Canada**  
6935 Davand Drive  
Mississauga, Ontario L5T 1L5  
To Order Call: 1-800-668-6513

**Puerto Rico**  
Royal Industrial Park, Bldg "M"  
Local #5, Carr 869, km 1.5 Palmas  
Cataño, P.R. 00962  
To Order Call: 1-800-782-2436