



THE ALL CHALLENGE MASK



The Avon C50 protective mask is based on the U.S. M50/ JSGPM (Joint Services General Purpose Mask) and sharing key technologies, provides maximum operational flexibility to counter multiple threat scenarios, including chemical, biological, nuclear and radiological (CBRN) agents, Toxic Industrial Chemicals (TICs), and Toxic Industrial Materials (TIMs).

The C50 offers high protection, outstanding field of vision and superior comfort. The innovative design features optimize the user's time in the operational area.

IDEAL FOR:

Battlefield CBRN protection
First Responders
Corrections Officers
Specialist law enforcement
Counter terrorism operations

CE

C50 single & twin filter port masks are CE certified for use in a CBRN environment (Article 10 certificate number C11-6401-1)

NIOSH

The C50 twin port mask is NIOSH CBRN Cap 1 approved with the CBRNF12B filter (TC-14G-0285) and NIOSH 42 CFR 84 riot control CS/CN/P100 approved with the CTF12 filter (TC-14G-0278)

The C50 meets the latest NATO military requirements

UNIQUE VISOR TECHNOLOGY

- Polyurethane visor is highly flexible plus scratch and impact resistant and will not yellow over time
- Optically correct across the whole field of view
- Panoramic visor design gives excellent field of vision and wearer recognition while enhancing compatibility with weapon sights
- The Vision Correction System allows prescription lenses to be mounted inside the mask
- Clear outserts for extreme environments
- Sunlight outserts for high intensity light situations
- BlueBlocker outsert delivers sharper images by filtering out specific light wavelengths



AIR FLOW MANAGEMENT

- Heat build up minimized
- Low inhalation resistance
- Excellent de-mist properties
- Common valves for simplicity and lower through-life cost

THE ALL CHALLENGE MASK

USER BENEFITS

- The unique chlorobutyl/silicone blend face piece material ensures the mask is not only high in protection but also provides a better seal and is more comfortable to wear for extended periods
- Compatibility with helmets, CBRN protective clothing and NFPA Class 3 Suits due to the low profile, close contour brow, flat buckles and extended chin flap
- Quick donning due to the pre-adjusted buckles
- 3 sizes providing secure and comfortable fit for all facial shapes and sizes

HYDRATION

 High flow fail safe drinking device allows connection to either a canteen or bladder type hydration system

COMMUNICATIONS

- Front mounted exhale valve allows clear direct communication
- For enhanced communication, an optional Voice Projection Unit (VPU) with internal microphone is easily connected via the Electronic Communication Port (ECP)
- Additional external communication systems can be attached via this ECP using available leads



FILTRATION

- Filter canisters are side mounted on either left or right side minimizing interference and allowing improved capability for shoulder mounted devices
 - Standard STANAG round thread 40 x 1/7 mm
- Allows for PAPR devices for improved protection

	C50 Mask Specifications						
	Filter	Part Number	Classification	Application			
/	CSCF50	72601/71/4	Riot Control	All particulate hazards including dust, fume, bacteria and virus, plus riot agent CS (meets 8 hour NIOSH test standards) and CN (<1 hour NIOSH test standards).			
/	CTCF50	72606/3	Riot Control	Removal of aerosols, particulate matter, smoke, fumes and vapours. Specifically designed for removal of tear gases including CS, CN and OC pepper spray.			
	MILCF50	72604/3	NATO CBRN	CBRN filter canister designed to meet the relevant criteria specified in the NIOSH CBRN APR standard at the 15-minute classification level (CAP 1). The EUROPEAN STANDARD, EN 14387 (A1B2E1K1P3), and chemical and biological warefare agents in aerosols, liquid and vapour form.			
	CBRNFI2B	71510/1	NIOSH Approved CBRN CAP 1	Dual classification for industrial and CBRN applications. All particulate hazards including dust, mist, fume, bacteria and virus plus all NIOSH specified CBRN gases and vapors including nerve, blood, choking and blister agents and toxic industrial materials.			
	CBRNFI2CE	70010/23/1	CE Approved EN14387:04 A1 B2 E1 K1 P3	Dual classification for indstrial and CBRN applications. All particulate hazards including dust, mist, fume, bacteria and virus plus all vapours including nerve, blood, choking and blister agents and toxic industrial materials.			

100	C50 Technical Data					
	CBRN Agent Resistance	Requirement	C50 performance			
	Mustard (H) / Sarin (GB) Soman (GD) / VX	36 hours	Greater than 36 hours			
	Laboratory protection factor performance (sodium chloride)	2,000	Greater than 10,000			
i	Re-breathed CO ₂	Less than 1%	0.8%			
	Inhalation resistance at:					
	30 l/min	5 mm WG	3 mm WG			
	95 l/min	15 mm WG	13 mm WG			
	160 l/min	25 mm WG	23 mm WG			
	Exhalation resistance at 160 l/min	30 mm WG	15 mm WG			
	Mask weight	N/A	490 grams			
	NIOSH Visual Field Score (VFS)	90	96			

NIOSH C50 Twin Filter Port Mask					
Description	Part Number				
C50 Mask Assembly Twinport RH LGE	70501/187				
C50 Mask Assembly Twinport RH MED	70501/188				
C50 Mask Assembly Twinport RH SML	70501/189				
C50 Single Filter Port Mask					
C50 Mask Assembly RH LGE	70501/193				
C50 Mask Assembly RH MED	70501/194				
C50 Mask Assembly RH SML	70501/195				
C50 Mask Assembly LH LGE	70501/199				
C50 Mask Assembly LH MED	70501/200				
C50 Mask Assembly LH SML	70501/201				
(C50 Twin Filter Port Mask	C C C C C C C C C C				
C50 CE Mask Assembly Twinport LGE	70501/562				
C50 CE Mask Assembly Twinport MED	70501/563				
C50 CE Mask Assembly Twinport SML	70501/564				

The Americas

t: +1 888 286 6440

e: customerservice@avon-protection.com

Europe, Middle East, Asia, Africa & Australasia

t: +44 (0) 1225 896705

e: protection@avon-protection.com

GR13188 - EMEA/C50/BR/UK/191015



Industry Certified Protection Factors NATO standard protection factors give reassurance that the mask has been rigorously tested to optimum levels. NIOSH CBRN approved TC-14G-0285. NIOSH approved 42 CFR 84 CS/CN/P100 TC-149-0278.



C50 single & twin filter port masks are CE certified for use in a CBRN environment (Article 10 certificate number C11-6401-1)

Avon products and associated technical information are controlled under U.S. export laws and regulations and are subject to the Export Administration Regulations (EAR) under the U.S. Department of Commerce (DOC), Bureau of Industry and Security (22 CFR 730-774). Prior authorization from the U.S. Government may be required for any export, re-export, diversion, or transfer.



