



Fittings & Accessories

AKRON BRASS COMPANY | P.H. 800.228.1161 (330.264.5678) | akronbrass.com



630 Angle Elbow SWIVEL FEMALE x MALE
• 2 1/2" & 3" sizes in 30° (64 & 76 mm)
• 4" size 45° (102 mm)
† 2 1/2" x 2 1/2" (65 x 65 mm)
† 3" x 2 1/2" (75 x 65 mm)
3" x 3" (76 x 76 mm)
◊ 4" x 4" (100 x 100 mm)

632 90° Suction Elbow FEMALE x MALE
† ◊ 2 1/2" x 2 1/2" (65 x 65 mm)
† ◊ 5" x 5" (125 x 125 mm)

KEY

- ✓ Optional with strainer
- * Pyrolite
- † Cast or chrome
- ◊ Chrome Ends with Red Paint
- # Cast brass

NOTE: All items are chrome, unless noted otherwise.

655 90° Front Suction Elbow with Strainer FEMALE NPT x MALE NH
4" x 4" (100 x 100 mm)
4" x 4 1/2" (100 x 114 mm)
† 5" x 5" (125 x 125 mm)
† ◊ 5" x 6" (125 x 150 mm)

635 90° Continuous Swiveling Elbow FEMALE NPT x MALE NH or NPSH
• Full 2" (51 mm) waterway with cast-in turning vane
1 1/2" or 2" female x 1 1/2" male (38 or 50 x 38 mm)
2 7/16" or 4 5/8" length
2 1/2" female x 2 1/2" male (65 mm x 65mm)
5" length

347 Hose Plug
• Available with rocker lug
• Chain optional through 4" (102 mm)
† 1 1/2" (38 mm)
2" (50 mm)
† 2 1/2" (65 mm)
* † 3" (75 mm)
3 1/2" (89 mm)
4" (100 mm)
4 1/2" (114 mm)
† 5" (125 mm)
6" (150 mm)



326 British Instantaneous Adapter MALE x BIM
*# 1 1/2" x 2 1/2" (38 x 38 mm)
*# 2 1/2" x 2 1/2" (65 x 65 mm)

335 Double Female Swivel Adapter
* † 1 1/2" (38 mm)
† 2" (50 mm)
* † 2 1/2" (65 mm)
† 2 1/2" x 1 1/2" (65 x 38 mm)
† 3" x 2 1/2" (75 x 38 mm)
† 3" (75 mm)

336 Double Male Adapter
* † 1 1/2" (38 mm)
† 2" (50 mm)
† 2" x 1 1/2" (50 x 38 mm)
2" x 2 1/2" (50 x 65 mm)
† 2 1/2" x 1 1/2" (65 x 38 mm)
* † 2 1/2" (65 mm)
† 3" x 2 1/2" (75 x 65 mm)
† 3" (75 mm)
3 1/2" (89mm)
4" (100 mm) Pyrolite only

354 Female Swivel to Male Adapter
• Long handle or rocker lug
† 2 1/2" x 2 1/2" (65 x 65 mm)
2 1/2" x 3" (65 x 75 mm)
2 1/2" x 3 1/2" (65 x 89 mm)
† 2 1/2" x 4" (65 x 100 mm)
2 1/2" x 4 1/2" (65 x 114 mm)
2 1/2" x 5" (65 x 125 mm)
2 1/2" x 6" (65 x 150 mm)
† 3" x 2 1/2" (75 x 65 mm)
3" x 3" (76 x 76 mm)
3" x 3 1/2" (75 x 89 mm)
3" x 4" (75 x 100 mm)
3" x 4 1/2" (75 x 114 mm)
3" x 5" (76 x 127 mm)
3 1/2" x 2 1/2" (89 x 89 mm)
3 1/2" x 3" (89 x 75 mm)
3 1/2" x 4 1/2" (89 x 114 mm)
† 4" x 2 1/2" (100 x 64 mm)
4" x 3" (100 x 75 mm)
4" x 4" (100 x 100 mm)
4" x 4 1/2" (100 x 114 mm)
4" x 5" (100 x 125 mm)
4" x 6" (100 x 153 mm)
4 1/2" x 2 1/2" (114 x 65 mm)
4 1/2" x 4" (114 x 100 mm)
4 1/2" x 4 1/2" (114 x 114 mm)
4 1/2" x 5" (114 x 125 mm)
4 1/2" x 6" (114 x 150 mm)
5" x 4" (125 x 100 mm)
5" x 4 1/2" (125 x 114 mm)
5" x 6" (125 x 150 mm)
6" x 2 1/2" (150 x 65 mm)
6" x 4" (150 x 100 mm)
6" x 4 1/2" (150 x 114 mm)
6" x 5" (150 x 125 mm)
* 6" x 6" (150 x 150 mm)

357 Double Female Swivel Adapter
• Long handle or rocker lug
† 3" x 2 1/2" (76 x 65 mm)
3 1/2" x 3 1/2" (89 x 89 mm)
4" x 2 1/2" (100 x 65 mm)
4" x 3 1/2" (100 x 89 mm)
* 4" x 4" (100 x 100 mm)
* 4 1/2" x 2 1/2" (114 x 65 mm)
4 1/2" x 3" (114 x 75 mm)
4 1/2" x 4" (114 x 100 mm)
* 4 1/2" x 4 1/2" (114 x 65 mm)
* 5" x 2 1/2" (125 x 65 mm)
5" x 4" (125 x 100 mm)
* 5" x 4 1/2" (125 x 114 mm)
5" x 5" (125 x 125 mm)
* 6" x 2 1/2" (150 x 65 mm)
6" x 3 1/2" (150 x 89 mm)
6" x 4" (150 x 100 mm)
* 6" x 4 1/2" (150 x 114 mm)
* 6" x 5" (150 x 125 mm)
* 6" x 6" (150 x 150 mm)

1422

Rigid Direct Connect Base

- For adapting an 1 1/2" nozzle base to a 2 1/2" hose line
- Pyrolite® construction
- 2 1/2" female x 1 1/2" male
- Tapered waterway for reduced turbulence
- Weight: 12 oz. (340 g)



Style 1422

422

Rigid Direct Connect Base

- Same as Style 1422 except brass with cast or chrome finish
- Weight: 1 1/2 lbs. (.7 kg)



345 Hose Cap

- Available with
rocker lug
- Chain optional

† 3/4" GHT (19 mm)
† 1" (25 mm)
† 1 1/2" (38 mm)
† 2" (50 mm)
† 2 1/2" (65 mm)
† 3" (75 mm)
† 3 1/2" (89 mm)



KEY

- ✓ Optional with strainer
- * Pyrolite
- † Cast or chrome
- ◊ Chrome Ends with Red Paint
- # Cast brass

NOTE: All items are chrome, unless noted otherwise.



331 Long Internal Lug Adapter FEMALE NPT x MALE
† 2 1/2" only (65 mm)



330 Short Internal Lug Adapter FEMALE NPT x MALE
† 1 1/2" x 1 1/2" (38 x 38 mm)
2" x 1 1/2" (50 x 38 mm)
✓† 2 1/2" x 2 1/2" (65 x 65 mm)
† 3" x 2 1/2" (75 x 65 mm)
† 3" x 3" (75 x 75 mm)



337 Rigid Female to Male Adapter
† 3/4" GHT x 1" (19 x 25 mm)
† 1" x 3/4" GHT (25 x 19 mm)
† 1" x 1" (25 x 25 mm)
† 1" x 1 1/2" (25 x 38 mm)
† 1 1/4" x 1" (32 x 25 mm)
† 1 1/2" x 3/4" (38 x 19 mm)
† 1 1/2" x 1" (38 x 25 mm)
† 1 1/2" x 1 1/2" (38 x 38 mm)
† 1 1/2" x 2" (38 x 50 mm)
*† 1 1/2" x 2 1/2" (38 x 65 mm)
† 2" x 1" (50 x 25 mm)
† 2" x 1 1/2" (50 x 38 mm)
† 2" x 2" (50 x 50 mm)
† 2" x 2 1/2" (50 x 65 mm)
† 2 1/2" x 3/4" GHT (65 x 19 mm)
† 2 1/2" x 1 1/2" (65 x 38 mm)
† 1 1/2" x 1" (38 x 25 mm)
*† 2 1/2" x 1 1/2" (65 x 38 mm)
† 2 1/2" x 2" (65 x 50 mm)
*† 2 1/2" x 2 1/2" (65 x 65 mm)
† 2 1/2" x 3" (65 x 76 mm)
† 2 1/2" x 3 1/2" (65 x 89 mm)
† 3" x 1 1/2" (75 x 38 mm)
† 3" x 2 1/2" (75 x 65 mm)
† 3" x 3" (75 x 75 mm)
† 3" x 3 1/2" (75 x 89 mm)
† 3 1/2" x 2 1/2" (89 x 65 mm)
† 3 1/2" x 3" (89 x 75 mm)



356 Rigid Female to Male Adapter
† 2 1/2" x 4" (65 x 100 mm)
† 3 1/2" x 4" (89 x 100 mm)
† 4" x 2 1/2" (100 x 65 mm)
† 4" x 3" (100 x 75 mm)
† 4" x 3 1/2" (100 x 89 mm)
† 4" x 3" (100 x 75 mm)
† 4" x 3 1/2" (100 x 89 mm)
✓† 4" x 4" (100 x 100 mm)
† 4" x 4 1/2" (100 x 114 mm)
† 4" x 5" (100 x 125 mm)
† 4" x 6" (100 x 153 mm)
† 4 1/2" x 2 1/2" (114 x 65 mm)
† 4 1/2" x 3" (114 x 75 mm)
† 4 1/2" x 4" (114 x 100 mm)
† 4 1/2" x 4 1/2" (114 x 114 mm)
† 4 1/2" x 5" (114 x 125 mm)
† 4 1/2" x 6" (114 x 150 mm)
† 5" x 2 1/2" (125 x 65 mm)
† 5" x 3" (125 x 75 mm)
† 5" x 4" (125 x 100 mm)
✓† 5" x 4 1/2" (125 x 114 mm)
† 5" x 5" (125 x 125 mm)
† 5" x 6" (125 x 150 mm)
† 6" x 3" (150 x 75 mm)
† 6" x 4" (150 x 100 mm)
✓† 6" x 4 1/2" (150 x 114 mm)
✓† 6" x 5" (150 x 125 mm)
† 6" x 6" (150 x 150 mm)



338 Suction Lug Adapter with Strainer FEMALE NPT x FEMALE SWIVEL
† 1 1/2" x 1 1/2" (38 x 38 mm)
† 2 1/2" x 2 1/2" (65 x 65 mm)
† 3" x 2 1/2" (75 x 65 mm)
3" x 3" (75 x 75 mm)
3" x 3 1/2" (75 x 89 mm)
3 1/2" x 3 1/2" (89 x 89 mm)
3 1/2" x 4" (89 x 100 mm)
4" x 3 1/2" (100 x 89 mm)
† 4" x 4" (100 x 100 mm)
5" x 4" (125 x 100 mm)



361 Double Male Hex Nipple
3/4" x 3/4" GHT or NPSH (19 x 19 mm)
† 1" x 3/4" GHT (25 x 19 mm)
† 1" x 1" (25 x 25 mm)
1 1/2" x 1" NH (38 x 25 mm)
† 1 1/2" x 1 1/2" (38 x 38 mm)
† 2" x 1 1/2" NH (50 x 38 mm)
† 2" x 2" (50 x 50 mm)
† 2 1/2" x 2" (65 x 50 mm)
† 2 1/2" x 2 1/2" (65 x 65 mm)



362 Female to Male Hex Nipple
† 3/4" x 3/4" (19 x 19 mm)
† 1" x 3/4" GHT (25 x 19 mm)
† 1" x 1" (25 x 25 mm)
† 1 1/2" x 3/4" GHT (38 x 19 mm)
† 1 1/2" x 1 1/2" (38 x 38 mm)
† 2" x 1 1/2" (50 x 38 mm)
† 2" x 2 1/2" (50 x 65 mm)
† 2 1/2" x 2 1/2" (65 x 65 mm)
† 3" x 2 1/2" (75 x 65 mm)

- 631 60° Angle Elbow**
- For high-rise stand pipes
 - Pyrolite® finish
 - 2 1/2" female x 2 1/2" male
 - Weight: 1 7/8 lbs. (.9 kg)

- 633 30° Discharge Elbow**
- For use on the pumper discharge
 - Chrome finish
 - 2 1/2" NPT X 2 1/2" NH weight: 3 lbs. (1.4 kg)

- 650 Swiveling Elbow**
- For aerial applications
 - Pyrolite finish
 - Full flow waterway with cast-in turning vanes for reduced friction loss
 - Available in 4", 5" and 6" sizes
 - Weight: 8 3/4 lbs. (4 kg)



Style 631



Style 650



Style 633



Hose Equipment

AKRON BRASS COMPANY | P.H. 800.228.1161 (330.264.5678) | akronbrass.com

Suction Strainers

339 Basket Suction Strainer

An economical, high capacity suction strainer with galvanized plated mesh for longer life.

- Available in 2 1/2" (65 mm) and 5" (127 mm) size NH and other selected threads
- 2 1/2" (65 mm) barrel strainer length: 4 7/8" (124 mm), weight: 2 lbs. (.9 kg)



Style 339

340 Barrel Suction Strainer

Heavy-duty barrel suction strainer with rope eye. Capable of flowing large volumes of water to match today's high capacity pumpers.

- Pyrolite® finish
- Available in 4" (102 mm) through 6" (152 mm) NH; 5" (127 mm) weight: 4 1/4 lbs. (1.9 kg)
- 5" (127 mm) barrel strainer length: 10" (254 mm), weight: 4 1/4 lbs. (1.9 kg)



Style 340

Hose Jackets

772 2 1/2" (64 mm) Hose Jacket

For emergency repair of burst or leaky hose - or as an emergency adapter for the connection of two hose lines with different threads in situations where pressures do not exceed 150 psi (10.34 bar).

- Akrolite® construction and molded neoprene liner
- Fits all 2 1/2" (64 mm) hose from 2 3/4" (70 mm) to 3 5/16" (84 mm) O.D.
- Length: 13" (330 mm), weight: 16 1/2 lbs. (7.5 kg)

773 3" (76 mm) Hose Jacket

- Same as Style 772, except: Fits 3" (76 mm) hose from 3 1/2" (89 mm) to 3 3/4" (95 mm) O.D.
- Length: 15" (381 mm), weight: 26 3/4 lbs. (12.1 kg)

352 2 1/2" (64 mm) Hose Jacket Mounting Peg

- For mounting 2 1/2" (64 mm) hose jacket on a running board or in a compartment
- Length: 13 3/8" (340 mm), weight: 2 1/4 lbs. (1 kg)

353 3" (76 mm) Hose Jacket Mounting Peg

- Same as Style 352, except for 3" (76 mm) hose jacket
- Length: 15 1/2" (394 mm), weight: 3 3/4 lbs. (1.7 kg)



Style 772

Hose Clamp

588 Hose Clamp

- For use on double-jacketed woven hose up to 3" (76 mm)
- Rubber jaws and lock
- Lightweight for easy handling
- Supplied with Style 589 mounting bracket
- Length: 30" (762 mm), weight: 16 lbs. (7.3 kg)

589 Hose Clamp Mounting Bracket

- For Style 588 Hose Clamp



Style 588



Tool Kit

9200 Nozzle Repair Tool Kit

Self-contained kit includes the tools needed to repair standard Akron® Nozzles. All tools packaged in a carrying case.

- Tools include:
 - Hammer
 - Pliers
 - Open Face Spanner
 - Strap Wrench
 - O-Ring Lubricant
 - 2 O-Ring Tools
 - 2 Screw Drivers
 - 2 Punches
 - 3 Swivel Adapter Tools
 - 8 Hex Wrenches
 - 1 Retaining Pin Removal Tool
- Size: 12" x 8 1/2" x 2 3/4" (305 mm x 216 mm x 70 mm)
- Weight: 8 1/2 lbs. (3.9 kg)



Style 9200

Equipment Holders

350 Mounting Plate

- Chrome plated
- Available in 1" (25 mm) to 6" (152 mm) sizes
- For securing equipment with female threads
- Screw type mount with bolt holes in the center for neat appearance
- 2 1/2" (64 mm) weight: 12 oz. (340 g)



Style 350

373 E-Z - Lok Nozzle Holder

- Available in 1 1/2" (38 mm) and 2 1/2" (64 mm) sizes - Must specify
- For securing equipment with female threads
- Quick release for fast and easy mounting and removal
- Weight: 1 5/8 lbs. (.7 kg)



Style 373

Sprinkler Shutoff

1078 Quickfit Sprinkler Shutoff

Simple, quick, positive shutoff for many types of sprinkler heads with openings of approximately 7/8" (22 mm) wide by 1" (25 mm) high or 3/4" (19 mm) wide by 1 1/16" (43 mm) high. Allows sprinkler heads out of fire area to be shut off. Weight: 6 oz. (170 g)



Style 1078



Specialized Tools

AKRON BRASS COMPANY | PH. 800.228.1161 (330.264.5678) | akronbrass.com

Lubricants

Repair instructions for Akron® products often call for lubricants to ensure proper repair and long term service.

- 9201 Parker® O-Lube**
 - 4 oz. (113 g) tube
- 9202 Low-Temp Lubriplate®**
 - 10 oz. (284 g) tube
- 9203 Low-Temp Lubriplate**
 - 14 1/2 oz. (411 g) cartridge
- 9210 Mobilith SHC 460 Synthetic Grease**
 - 13.7 oz. (390g) tube



Style 9201



Style 9202



Style 9203



Style 9210

Heat Sensors

- 9011 Heat Sensor with Laser Sight**
 - Only 11 oz.
 - Backlit 7/16" (11.1 mm) LCD display
 - Detects surface temperature of -25° to 999°F (-32° to 535°C)
 - Includes 9V battery and compact storage case
 - D:S-12:1

Mini Heat Sensor with Laser Sight

- Only 8 oz. (227 g)
- Backlit LCD display
- Detects surface temperature of 0° to 525°F (-18° to 275°C)
- Includes 9V battery
- D:S-8:1



Style 9011
Mini

Style 9011

Hose Accessories

- 583 Hose Hoist**
 - Akrolite™ construction
 - For raising or lowering hose, ladders, etc. to and from the roof or through windows
 - Weight: 7 1/8 lbs. (3.4 kg)
- 78 Hose & Ladder Strap**
 - Secures hose up to 3" (76 mm) on ladders, fire escapes, etc. and aids in the handling of hose
 - Anodized aluminum fittings with 1" (25 mm) wide, flat, water-resistant nylon webbing
 - Fits ladder rungs up to 2" (51 mm) O.D.
 - Weight: 1 lbs. (.5 kg)



Style 583

Style 78

