HILLYARD

Ready-To-Use

#807

Clean Action® II

Carpet Extraction Cleaner

CAUTION/CUIDADO

EYE IRRITANT

MAY CAUSE NOSE AND THROAT IRRITATION

KEEP OUT OF REACH OF CHILDREN

(See Manufacturer's Label for Additional Information)

Customer Affixed Label

7

HILLYARD ARSENAL®

HILLYARD INDUSTRIES
St. Joseph, MO 64502 U.S.A.
Telephone: 816-233-1321
www.hillyard.com

DIRECTIONS FOR USE:
1, Place Wet Floor signs in area to be cleaned. 2. Test for colorfastness and effect on texture in an inconspicuous area. 3. Vacuum carpet thoroughly and spray assigned area. Allow to set for 5 minutes, but do not allow to dry. 4. Extract carpeting with hot water, not to exceed 150ºF. Move the self-contained extractor or wand over the carpet pile very slowly. Hillyard's Arsenal Neutralizer/Carpet Rinse (#18) may be used in the extractor during this process to neutralize previously used high alkaline cleaners or tracked in ice melt compounds. 5. Allow carpeting to thoroughly dry before replacing furniture and opening to traffic. Air blowers will aid in this drying process. When replacing furniture, use leg pads or aluminum foil to prevent rust and furniture stains.
NOTICE: For use only with Hillyard Arsenal Dilution System.

VOC of concentrate is 5% at dilution of 1 ounce per gallon less than 1%
HMIS Rating: Health = 1, Flammability = 0, Reactivity = 0

CONTAINS: WATER (CAS #7732-18-5); PROPYLENE GLYCOL N-PROPYL ETHER (CAS #1569-01-3); SODIUM LAURYL SULFONATE (CAS #151-21-3); ALCOHOLS (C_{12}-C_{15}) ETHOXYLATE (CAS #68131-39-5).
See Material Safety Data Sheet for additional information.

INSTRUCCIONES:
1. Coloque letreros de Piso Mojado en las áreas que se vayan a limpiar. 2. Pruebe, en un área poco visible, la inalterabilidad del color y el efecto sobre la textura. 3. Pásele la aspiradora a fondo a la alfombra y rocíe el área que se quiere limpiar. Deje que se impregne por cinco minutos, pero no deje que se seque. 4. Extraiga el producto de la alfombra con agua caliente que no exceda de 150ºF. Mueva el extractor o vara del extractor muy lentamente sobre el pelo de la alfombra. Se puede utilizar el Neutralizador/Enjuague de Alfombras Arsenal de Hillyard (#18) en el extractor durante este proceso, para neutralizar los limpiadores alcalinos anteriormente utilizados o los compuestos para derretir hielo que hayan sido traídos con los zapatos desde el exterior. 5. Deje que la alfombra se seque completamente antes de colocar en su lugar los muebles y permitir el paso de las personas. Los sopladores de aire ayudarán en este proceso de secado. Cuando reemplace el mobiliario, utilice protectores para las patas o papel de aluminio para evitar el óxido y las manchas causadas por los muebles.
AVISO: Use solo con Hillyard Arsenal Dilution System.

VOC de concentrado es de 5% a la dilución de 1 onza por galón menos de 1%
Clasificación HMIS: Salud = 1, Inflamabilidad = 0, Reactividad = 0

CUIDADO

IRRITANTE DE LOS OJOS

PUEDE CAUSAR IRRITACION DE LA NARIZ Y LA GARGANTA

CONTIENE: AGUA (CAS #7732-18-5); ETER N-PROPIL DE PROPILEN GLICOL (CAS #1569-01-3); SULFONATO LAURIL DE SODIO (CAS #151-21-3); ALCOHOLES (C_{12}-C_{15}) ETOXILATO (CAS #68131-39-5).
Consulte con la hoja de datos de seguridad del material para obtener información adicional.

MANTENGASE FUERA DEL ALCANCE DE LOS NIÑOS
(Consulte la etiqueta del fabricante para obtener información adicional.)

Label Reorder #HIL31602

0510