HILLYARD

HIL0053904

Restorer

A Zinc-free High Gloss Restorer/Cleaner Specially Formulated For Ultra-high Speed And High Speed Floor Machines

Restaurador De Alto Brillo/Limpiador, Libre De Zinc, Especialmente Formulado Para Maquinas Para Pisos De Ultra Alta Velocidad Y Alta Velocidad

WARNING/ADVERTENCIA

COMBUSTIBLE LIQUID
CAUSES SERIOUS EYE IRRITATION
KEEP OUT OF REACH OF CHILDREN
(See back panel for additional precautions)

HILLYARD FLOOR CARE

HILLYARD INDUSTRIES
PO Box 909 St. Joseph, MO 64502
Telephone: 816-233-1321
www.hillyard.com

NET CONTENTS: 32 FL. OZ. (1QT.) OR 0.946 LITER

HIL0053904

WARNING

HAZARD STATEMENTS: Combustible liquid. Causes serious eye irritation. Harmful to aquatic life. May cause long lasting harmful effects to aquatic life.

PRECAUTIONARY STATEMENTS: Prevention: Keep away from heat/sparks/open flames/hot surfaces. No smoking. Wash thoroughly after handling. Avoid release to the environment. Wear protective gloves/eye protection/face protection. Use with Adequate ventilation.

RESPONSE: First Aid: If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. **If eye irritation persists:** Get medical advice/attention. **If on skin:** Wash off with soap and water. Get medical attention if irritation develops and persists. **In case of fire:** Use appropriate media to extinguish.

STORAGE: Store in a well-ventilated place. Keep cool.

DISPOSAL: Buyer assumes all risk and liability associated with disposal of this product (original concentration or dilution) in violation of applicable law.

CONTAINER DISPOSAL: Triple rinse (or equivalent). Then offer clean, dry container for recycling or reconditioning.

CONTAINS: Dipropylene Glycol Methyl Ether (CAS #34590-94-8); Isopropyl Alcohol (CAS #67-63-0); Water (CAS #7732-18-5); Acrylic Copolymer Emulsion (CAS # Unknown to Hillyard).

See Safety Data Sheet for additional information.

KEEP OUT OF REACH OF CHILDREN

Instrucciones y precauciones en español están dentro de la caja.

HMIS Rating: Health = 2, Flammability = 2, Reactivity = 0

AUTO-BURNISH APPLICATION: 1) Dust mop all flooring and remove gum and stickers. 2) Dilute Restorer 4 oz. per gallon of cool water in the solution tank of the autoscrubber. 3) Autoscrub all assigned flooring using overlapping passes while dispensing, agitating, and picking up the solution. 4) Pick up any squeegee trails or puddles with a damp mop. 5) Allow floor to dry. 6) Burnish all flooring. NOTE: Do not allow Restorer solution to remain in the autoscrubber tank. Drain and rinse.

MOP ON APPLICATION: 1) Dust mop all flooring and remove gum and stickers. 2) Damp mop or autoscrub assigned flooring with Assurance® or Top Clean® following label directions. 3) Dilute 1 part Restorer to 4 parts cool water in a mop bucket. 4) Using a synthetic mop apply a thin, even coat to the floor. 5) When dry, burnish all flooring. NOTE: Do not apply more than one coat of Restorer when mop-on restoring. This process should not be used more than 3 times per week.

SPRAY METHOD FOR 175-1500 RPM MACHINES: Perform 1) and 2) under the Mop On Application above. 3) Dilute 1 part Restorer to 4 parts water and apply with a quart spray bottle or pump-up sprayer. 4) Spray a light mist to a small area and immediately buff. For 175 RPM machines, use a red pad followed by a white pad. For 1000-1500 RPM machines use a Hillyard 100-D Polythermal or Hillyard Beige Polythermal.

MAINTENANCE: Dust mop often with a treated mop. Damp mop or autoscrub with a solution of Assurance or Top Clean as scheduled.

NOTICE: Keep container closed when not in use. Do not pour unused product back into container. Best results are obtained with adequate ventilation and floor temperatures above 60°F (16°C). Do not use on buffable waxes.

CLASSIFIED UL FLOOR COATING AND FINISHING MATERIAL AS TO SLIP RESISTANCE ONLY. 186S

PROTECT FROM FREEZING

DISCLAIMER OF WARRANTY: Seller makes no warranty of any kind, express or implied, except that this product shall be of seller's standard quality.

0114