HILLYARD

Ready-To-Use

#814

Carpet Pre-Spray

For Carpets and Area Rugs
Concentrated Carpet Cleaner - Phosphate Free - Fragrance Free

GREEN SEAL CERTIFIED®

This bottle contains a work solution of a concentrate that meets the Green Seal™ environmental standard for industrial and institutional cleaners based on its reduced human and environmental toxicity and reduced volatile organic compound content.

CAUTION/CUIDADO

PROLONGED CONTACT MAY CAUSE EYE IRRITATION
KEEP OUT OF REACH OF CHILDREN
(See Manufacturer's Label for Additional Information)
Customer Affixed Label

14

HILLYARD ARSENAL®

HILLYARD INDUSTRIES
St. Joseph, MO 64502 U.S.A.
Telephone: 816-233-1321
www.hillyard.com

CAUTION

CONTAINS: Water (CAS # 7732-18-5); Sodium Xylene Sulfonate (CAS #1300-72-7). Do not get concentrate into eye. Safety goggles are suggested where splash of concentrate is a concern. Wash thoroughly after handling. Use only as directed: Improper dilution can lead to adverse health effects. Rinse container before reusing.

DISPOSAL: Waste from normal use may be sewered to a public-owned treatment works in compliance with applicable federal, state and local requirements.

FIRST AID: In case of contact, immediately flush eyes with plenty of water for 15 minutes. If eye irritation persists, get medical attention. If inhaled, remove to fresh air. If breathing is difficult, get medical attention.

See Safety Data Sheet for additional information.

HMIS Rating: Health = 1, Flammability = 0, Reactivity = 0

Directions for use as a Pre-Spray

Use of hot tap water is recommended. 1. For use with Hillyard Arsenal Push Button Dispensers. Remove shipping cap and attach adapter cap to the one gallon of concentrate. Place into either a wire rack or cabinet. 2. Dispense diluted product into a pump-up pressure sprayer. 3. Vacuum the floor thoroughly. 4. Pre-spray carpet with diluted product from a pump-up pressure sprayer or trigger sprayer. Light agitation of carpet with a carpet brush will increase cleaning efficiency. Let product dwell for 5 minutes before extracting.

5. Wait overnight for the carpet to dry before walking on it. To dry thoroughly, open windows and use fans. 6. Once the carpet is completely dry, vacuum the carpet thoroughly.

NOTICE: Over-wetting of carpet may cause shrinkage and browning.

Label Reorder #HIL31614

CUIDADO

EL CONTACTO PROLONGADO PUEDE CAUSAR LA IRRITACION DEL OJO

CONTIENE: Agua (Nr. CAS #7732-18-5); Sulfonato De Xileno De Sodio (CAS #1300-72-7). No consiga el concentrado en ojo. Anteojos de protección contra sustancias químicas. Lávese después de manipular el producto. Utilizar sólo siguiendo las instrucciones: Dilución inadecuada puede dar lugar a efectos adversos para la salud. Enjuagar el contenedor antes de la reutilización.

ELIMINACION DEL PRODUCTO: Los desechos de uso normal puede verterse al desagüe de acuerdo con los requisitos federales, estatales y locales.

PRIMEROS AUXILIOS: En caso de contacto, lavar los ojos inmediatamente con agua abundante durante 15 minutos. Si persiste la irritación de la ojos, obtenga asistencia médica. Si se inhala, salga al aire fresco. Si la respiración es difícil, obtenga asistencia médica.

Ver la Hoja de Datos de Seguridad para obtener información adicional.

MANTENGASE FUERA DEL ALCANCE DE LOS NIÑOS

Clasificacion HMIS: Salud = 1, Inflamabilidad = 0, Reactividad = 0

Instrucciones para su uso como un Pre-Spray

El uso de agua caliente se recomienda. 1. Para uso con Dosificadores con Botones de Contacto Arsenal de Hillyard. Retirar la tapa de transporte y poner la tapa del adaptador en el galón de concentrado. Colocar dentro de una rejilla de alambre o caja. 2. Dispensar diluye el producto en un pulverizador de presión de la bomba en marcha.

3. Aspire el suelo cuidadosamente. 4. Pre-spray alfombra de producto diluido a partir de un pulverizador de presión de la bomba en marcha o rociador de gatillo. Agitación luz de la alfombra con un cepillo de limpieza de alfombras aumentará la eficiencia. Vamos a vivir del producto durante 5 minutos antes de la extracción. 5. Espere un día para otro para la alfombra se seque antes de caminar sobre él. Para secar bien, abra las ventanas y use ventiladores. 6. Una vez que la alfombra esté completamente seca, aspire la alfombra a fondo.

AVISO: El empapar excesivamente la alfombra puede encogerla y darle un color marrón.

(Consulte la etiqueta del fabricante para obtener información adicional.)

0215