

Diversey

Vectra® Floor Finish



A floor finish that saves time, while giving floors diamond-like brilliance, clarity and durability.

Excellent Performance

- Diamond-like clarity and gloss
- Cures on the floor faster than traditional floor coatings
- Resists dirt embedment, black heel marks, scratching and scuffing
- Versatile finish responds well to 175–1500 rpm and
- UHS equipment

Improved Formulation

- Provides better buff response
- Reduced VOCs of 54.4% and significantly decreased odors
- Now compliant with California 2010 VOC requirements

Easy-to-Use

- Less mop drag for more consistent results
- Can be used in a variety of settings and climate conditions

Designed For

- Health Care
- Education
- Retail
- Government
- BSC

Use Overview



Vectra® Floor Finish provides diamond-like brilliance, clarity and long-lasting performance, saving you time and labor, while giving the brilliant appearance you demand on your floors.

- Blockade areas to be stripped or finished. Position wet-floor signs around area to be cleaned.
- Strip floor using recommended Diversey brand stripper according to label directions.
- Apply 2–3 uniform coats using a clean mop. If higher gloss is desired, apply additional coats.
- Allow 30 minutes drying time between coats.

Maintenance

- Dust mop or sweep.
- Clean the floor with a mop or an automatic scrubber using the recommended Diversey brand cleaner following label directions.
- If desired, spray buff using recommended Diversey brand floor maintainer to enhance gloss.

Before Recoating

- Dust mop or sweep.
- Deep scrub floor using Diversey cleaner according to label directions.



Removal

- Remove using recommended Diversey brand stripper according to label directions.

Best Results

- Do not dilute.
- Do not use on surfaces colder than 50° F (10° C).
- To avoid contamination, do not return unused product to original container.
- **Note:** Floors will be slippery when wet or contaminated with foreign materials. Promptly clean-up spills and foreign materials. Meets ASTM D2047 requirements for slip resistance.

Product Specifications

Description	
Color/Form	Off-white, liquid
Flash Point	> 200°F (> 93.4°C)
pH	8.6
Scent	Ammonia
Shelf Life	2 years
Slip Resistance	0.5 minimum (ASTM D2047)
Solids %	19
Solubility	Dispersible
Specific Gravity	1.03

Hazard Rating

HMIS		NFPA
1	Health	1
0	Flammability	0
0	Reactivity	0

4=Very High; 3=High; 2=Moderate; 1=Slight; 0=Insignificant.

Available Items

Product Code	Description/Package Size	Dilution
5105047	1 x 5 gallon / 18.9 L Envirobox™/MC	Ready-to-Use
4971921	6 x 2.5 L / 2.64 Qt. ProSpeed™/MC BIB (Bag-in-Box)	Ready-to-Use
04078	4 x 1 gallon / 3.78 L Containers	Ready-to-Use

Safety Reminder

Please make sure your employees read and understand the product label and Safety Data Sheet before using this product. The label contains directions for use, and both the label and SDS contain hazard warnings, precautionary statements and first aid procedures. SDSs are available on-line at www.sealedair.com or by calling 888 352 2249. Improper use or dilution may result in damage to surfaces and may result in health and physical hazards that match those of the concentrate. Please refer to the Diversey HazMat Library, only available through Internet Explorer, <http://naextranet.diversey.com/dot/>, for up to date shipping information.