

HIGH AFFINITY



**For Unsurpassed Durability and Long-Lasting Shine
Will respond well to burnishing up to 1 time per week**



Product Order # 16



Product Specifications

| | |
|------------------|-------|
| % Solids | 22 |
| pH | 8.5 |
| Specific Gravity | 1.024 |
| Viscosity, cps | 15 |
| Color | White |

| | |
|------------------------------|--|
| Coverage per gallon, sq. ft. | 1,500 – 2,500 |
| Floor Types | All finishable floor types, including VCT, terrazzo, vinyl |

The premium high solids durable floor finish designed to deliver an exceptional high depth of gloss.

- Durable high gloss finish that is designed to be extremely resistant to soil, scratching, scuffing and marking.
- Outstanding application among a broad range of environmental conditions and application techniques
- Formulated with special acrylic copolymer technology to withstand heavy traffic & maintain high shine
- Holds up & responds to both propane or electric burnishing
- Exceeds UL slip resistance classification.
- Compliant with California Air Resources Board VOC (Volatile Organic Compound) limit.
- Low odor for healthcare & 24/7 facilities.

Recommended For

- Healthcare
- Government
- Commercial facilities
- Building service contractors
- Education

Hazard Rating

| HMIS | | NFPA |
|------|--------------|------|
| 1 | Health | 1 |
| 0 | Flammability | 0 |
| 0 | Reactivity | 0 |

Another similar P&G Pro Line finish to consider: *Dexterity* is a versatile finish for moderate burnishing up to 1 to 3 times per week.

| SIZE | DESCRIPTION |
|------------------|--------------|
| 4 - 1 gal./3.78L | Ready-to-use |
| 1 - 5 gal./18.9L | Ready-to-use |

HIGH AFFINITY



For Unsurpassed Durability and Long-Lasting Shine
Will respond well to burnishing up to 1 time per week

DIRECTIONS FOR USE

Initial Application:



1. Remove all old wax and floor finish with appropriate PGPL Floor Finish Stripper.



2. Rinse floor thoroughly with clear water and allow to dry.

3. Using a clean, dry rayon or microfiber flat mop, apply a uniform coat of finish. Allow to dry thoroughly (typically 30-40 minutes). Apply additional coats in the same manner and let dry. For very porous or highly worn floors, one initial coat of floor sealer is recommended.

Day-to-Day Maintenance:



1. Sweep or dust mop as necessary.



2. Auto-scrubbing is recommended or damp mopping with PGPL Finish Floor Cleaner.



3. Will respond well to burnishing up to 1 time per week



4. Periodic deep scrub and recoat will be required to replenish the base film for best burnish results.

| | YES | NO |
|-------------------------------------|-----|----|
| Acrylic Copolymer Base | X | |
| Metal Interlock | X | |
| UHS Repairable | X | |
| UL Classified as to Slip Resistance | X | |
| Strips Easily | X | |
| DOT Regulated | | X |